

REMS


www.rems.de




Innovative
manufacturer of
machines and tools
for pipe working




2024
Catalogue




Product information



Operating instructions



Parts lists



Product films

REMS App – All product information available any time, anywhere – quickly and easily.

On the building site or at your dealer: All operating instructions, parts lists, product information, product films and more can be called upon immediately*. Many other functions are also available to you.



Scan product logo

Are you standing in front of a REMS product? Just scan the product logo and you will get all the product details.



Scan product illustration

You can scan the product illustrations in our offer brochures and get all the details about the product.



Scan QR code

You can scan the REMS QR code and get all the details about the product.



REMS App

Free application software from the Apple App Store or Android App at Google Play.



* Only with an existing data link via network operator or wifi.

Contents

	Threading Roll Grooving	20
	Sawing	54
	Cutting, chamfering, deburring, calibrating	72
	Assembling	102
	Testing, cleaning, disinfecting, preserving, flushing, filling	112
	Bending	126
	Radial Press Jointing	144
	Axial Press Jointing	242
	Expanding, Extracting	250
	Soldering	262
	Freezing	268
	Pipe and Drain Inspection / Pipe and Drain Cleaning	272
	Plastic Pipe Welding	290
	Diamond Core Drilling Diamond chasing saws	300
	Drying, dehumidifying, aeration and deaeration	326

We deliver exclusively on the basis of our general conditions of sale and delivery.

The prices stated in this catalogue are valid for one piece respectively for one set (e.g. dies) or one pack (e.g. saw blades). Prices do not include any value added tax (VAT) and are subject to change without notice. We reserve the right to increase prices. These prices supersede all previous prices.

Drawings, illustrations, dimensions, weights, standards and other data stated in this catalogue are not binding and are subject to alteration. All power data stated to be understood as the rated power input. Subject to alteration. All rights reserved, particularly for translations, reproductions, illustrations, radio transmission, photomechanic reproductions or similar and storage of data in computers, including utilization in extracts.

© Copyright 2024
REMS GmbH & Co KG, Waiblingen.

Sale through specialist dealers.




They are creative and have plenty of practical experience, they continuously find possibilities for improvement of the work of the installation professional: REMS development engineers are innovative and therefore important factors in the success of the company.

REMS – heading technical progress for more than 110 years. Development is never finished.

Since its foundation in 1909 REMS has been developing products for the pipe working, especially for sanitary and heating installers. At first, hand tools and then subsequently machines and electric power tools. The stipulation of the company founder Christian Föll "REMS must be superior" has always been the benchmark for our actions. Today REMS is a leading manufacturer of machines and tools for the pipe working.

REMS development engineers have persuasive, groundbreaking ideas which ease the daily routines of the installations professional. They have all the significant requirements in their focus and use all their comprehensive practical experience. Experts from all areas of industry ensure that every possibility for improvement is integrated in the new development. In this way the perfect tools for the tough demands of the building site are created. The REMS products are highly valued because of their innovative technology as well as their high standards of quality and are being used everywhere in the world. Both trade and user profit in this way.

Again and again REMS is able to maintain its position at the forefront of technical progress as a result of its innovative products. Many valid national and international patents prove this.



Through the application of modern construction and development techniques, the quality of REMS products has been to the fore from the beginning: Safe use, robust design, simple operation, durability.



New ideas, technical progress and REMS belong together: e.g. REMS Amigo, REMS Tiger, REMS Curvo, REMS Akku-Press 22V Connected, REMS Multi-Push – products, which have revolutionised the application technology.



Fully automatic 3D measuring machines are a part of the comprehensive quality control system at REMS. The accuracy of measurements at 0.001 mm guarantees the highest precision.

Highly modern production – guarantor for REMS quality products.


Made in Germany. Our own production plant is located in Waiblingen near Stuttgart, in the centre of Germany's high-tech industrial region. There highly modern equipment and facilities are available for research and development, for production and quality control. In addition to this there is a permanent staff of highly-qualified employees, who in part represent the 4th generation of service at REMS. They have the special level of knowledge and experience that is essential for the manufacture of quality products.

Quality means much more to REMS than simply dimensional accuracy and function. It is backed up by a comprehensive quality control system, which begins as early as the assessment of market needs and which is ever present during the product development and manufacture and continues with systematic quality analysis in the market. Furthermore the quality of the production processes is regularly monitored and affirmed by the testing agency that awards the GS safety sign.

All REMS products correspond with safety and accident prevention regulations and fulfil the respective appropriate European standards according to the terms of the EU directives. Additionally, with the exception of a few hand tools which are not safety relevant, all REMS products are checked and approved by independent testing agencies. All REMS products thereby meet an especially high standard with regard to work safety, functional safety and operational safety.



Permanent innovations in processes as well as investments in efficient CNC manufacturing systems engineering ensure that REMS products are amongst the best in the world.



Flexible assembly lines allow adjustment to the requirements of the customer at any time.

REMS is evaluated as having the largest number of training staff in the region. So it is able to maintain its own know-how at a high level.



Tightly defined test intervals during the whole manufacturing process as well as comprehensive function and safety checks after completion of the assembly ensure that no faulty product leaves the plant.



Reliable staff with many years experience are responsible for ensuring that the optimum progression of the hardening process in the material for each component is realised exactly.

Nobody hardens metal better than us. Therefore, we do it ourselves.

Highly durable, safe in application and extremely resilient – a tool can only meet such demands if the components are perfectly hardened.



An important cornerstone for the quality of REMS tools is laid in our own heat treatment shop. The decades of experience has provided important know-how and is the secret of REMS quality tools. The special heat treatment leads to an ideal combination of solidity and robustness and to an especially long durability, as, for example for threading dies, cutter wheels and pressing tongs. The heat treatment process is automatically monitored and permanently recorded by efficient computer technology. This allows a uniformly high product quality.

Our own heat treatment shop – an important aspect of the know-how and the secret of REMS quality tools.



The proven, indestructible REMS quality threading dies. Of robust, especially hardened special steel.



REMS cutter wheels complement the special demands of the various materials. In particular the special hardening process determines the durability of the REMS cutter wheels.



The art of hardening:
It creates extremely resilient components for the highest demands.

REMS
for Professionals

REMS
for Professionals

REMS
for Professionals



Only two from every 45 employees in the logistics industry know that time is money. Speed and absolute reliability are the most important factors for delivery and service.

REMS – for professionals.

Excellent service. On location everywhere.

REMS produces machines and tools for professionals – the demands required are high. REMS fulfils its tasks with competence, responsibility and a first-rate service. This also includes the swift delivery as well as maintenance and repair work. A high degree of flexibility and absolute reliability are the basis for the excellent service.

The whole logistics organisation is oriented towards the needs of our customers. In order to be able to deliver promptly REMS keeps more than 10,000 items ready in the central storage facility. All wear and replacement parts are always available. A service that keeps down-times to a minimum.

In the case of a repair the area-wide network of contracted customer service workshops is available for a rapid and professional repair. Highly-qualified and well-trained staff repair and maintain the machines and tools for our customers. After completion of the repair or inspection the products are returned again to the customer by the fastest means.



Speed is a question of logistics. REMS keeps wear and replacement parts in stock in a 14,000 m² storage facility.



The demands at the building site are extreme – wear parts are worn, the need for repairs arises. The REMS customer services department is ready and flexible. There is an extensive service organisation in more than 25 countries.



Service is extremely important for REMS: All demonstration vehicles for the more than 200 REMS specialist advisors are fitted with testing equipment with which the function test and force of pressure measurement for REMS radial presses can be carried out on location everywhere.



Product training in the
REMS training centre:
Become familiar with,
compare, evaluate.



REMS – business partner to the trade. Excellent advice for contented customers.

Only those who receive competent advice when purchasing find the individually best, economic solution for the tasks ahead. For this reason REMS assigns great significance to the product training of its own REMS specialist advisors and also the staff in the specialist stores.

In the REMS training centre, modern and fully-fitted demonstration, training and conference rooms are available in an area of 1,600 m². The practical-oriented training gives the staff of the specialist stores, in an understandable form, a broad basis and high specialist competence for product advice and successful sale. The detailed sales documentation with information relating to all necessary product specifications facilitate a swift product selection and are the basis for the simple and time-saving generation of offers.

This partnership with the specialist store also guarantees the user qualified, comprehensive product advice and excellent service.



REMS training centre in Waiblingen near Stuttgart.



Modern and fully-fitted demonstration rooms:
REMS creates many opportunities for the specialist-store staff
to become familiar with the products.



Dennis Maaß, Christian Heipert, Ralf Bähler and Florian Zorn, four of more than 200 qualified REMS specialist advisors are flexible and, when needed, swiftly on location for training courses and presentations.

REMS – Market strength through a consistent product and sales philosophy.

REMS' basis for market strength is technically-advanced and high-quality products as well as a product range tightly concentrated on high turnover units and highly competitive prices thanks to the rational, economical in-house production.

At the centre of the sales philosophy the principle has always been that REMS products are sold exclusively via specialist dealers. These are supported by REMS in many ways. REMS specialist advisors equipped with demonstration vehicles carry out product training on location and demonstrate the REMS products at on-site visits, counter demonstrations and at in-house exhibitions. They advise in the selection of the tools and find the most comfortable, reliable and economical solution in each individual situation.



The consistent sales philosophy is designed for long-term results, trust and predictability.



This is how installation professionals become familiar with the product range in practice: The REMS specialist advisors are on the road with demonstration vehicles and demonstrate the machines and tools in real situations, directly on the building site.

The REMS product presentation system – the ideal opportunity for the specialist stores to optimally present the REMS products: touch – compare – select.



Touch. Compare. Select. Promoting the mutual sale.


The participation at many national and international trade fairs, the advertising in trade magazines and the direct mail marketing to the user is highly valued by trade outlets as sales-promotion measures.

The attractive REMS product presentation system provides the trade outlet with an optimal presentation of the REMS products: Touch, compare, select. The individual stocking with REMS products is carried out with close cooperation between the REMS specialist advisors and the trade outlet.

The online information system at www.rems.de offers extensive opportunities to find out information about the REMS group, the REMS products and their application possibilities and operation. Furthermore, the user has access to the complete online catalogue and detailed technical documentation, information about current trade fair appearances and addresses of REMS contracted customer service workshops, download opportunities of sales documentation, operating instructions, parts lists, product illustrations and product films, opportunities to order sales documentation in various languages for postal dispatch, e-mail addresses for REMS contacts and much more.



The REMS products are exhibited and demonstrated at many national and international trade fairs.



Practical for the trade, clear for the customers – the REMS product presentation system.




The online information system at www.rems.de




REMS App





REMS products are highly valued and used across the world because of their innovative technology and high standards of quality. REMS products are available in all locations where perfection in installation work is demanded.



More than 20,000 trade partners in Europe: REMS products are available locally everywhere.

Innovative products and a high standard of quality open new markets for REMS.

In the last years the market area has been continuously build-up and extended.

Reliable trade partners throughout Europe and beyond guarantee that ever more customers can be persuaded of the quality of REMS.



REMS sets benchmarks for quality throughout Europe – the sales are carried out through the tight network of reliable trade partners in the whole of Europe which are in turn supported by more than 200 well trained REMS specialist advisors.



Sales subsidiaries in many countries deliver optimum conditions for users and trade outlets.

6



Threading Roll Grooving

	Hand die stocks	22
	Quick-change die heads S	23
	Electric die stocks	24
	Cordless die stock	28
	Threading machines	32
	Semi-automatic threading machines	42
	Pipe nipple chucks	46
	Thread-cutting oil	47
	Roll grooving attachments	48
	Roll grooving machine	49
	Cordless roll grooving machine	50
	Roll grooving machines	52

REMS eva

Hand die stock with
quick-change die heads

Proven quality die stock with excellent threading
capabilities.

Pipe threads	1/8 – 2", 16 – 50 mm
Bolt threads	6 – 30 mm, 1/4 – 1"

Thread types see page 30, 31.

REMS eva – the plumber's die stock.

Excellent start-cutting and threading.

Steel ratchet lever, thickly plastic coated.

Only one type of quick-change die heads.

Indestructible quality dies.

System advantage

Large working range up to 1 1/4" and up to 2" with only **one** ratchet lever. Only **one** type of small, compact quick-change die heads and only **one** type of dies. The same quick-change die heads fit all REMS die stocks and other suitable makes of die stocks. Efficient and easy stocking. No confusion possible.

Ratchet lever

Robust. Ratchet lever in steel, thickly plastic coated, for convenient operation. Serrated plastic handle for secure grip. Easy adjustment of ratchet rotation. Perfect, secure seating of quick-change die heads, fast and easy change.

Quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads. Quick-change die heads S for cutting pipe threads in hard-to-reach areas (page 23).

Dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with REMS Nippelspanner 3/8 – 2" (page 46).

Supply format

REMS eva Set. Hand die stock with quick-change die heads. For pipe threads 1/8 – 2", 16 – 50 mm, bolt threads 6 – 30 mm, 1/4 – 1". For right and left-hand threads. 1 ratchet lever for the complete work range. Quick-change die heads with dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to EN 60423 M. In sturdy steel case or in a cardboard box.

Description/Size	Art.-No.	€
REMS eva Set in steel case		
R 1/2 + 3/4 + 1	520014	415,20
R 1/2 + 3/4 + 1 + 1 1/4	520015	493,05
R 3/8 + 1/2 + 3/4 + 1 + 1 1/4	520013	560,52
R 1/2 + 3/4 + 1 + 1 1/4 + 1 1/2 + 2	520017	685,08
R 3/8 + 1/2 + 3/4 + 1 + 1 1/4 + 1 1/2 + 2	520016	757,74
M 16 + 20 + 25 + 32 (M x 1,5)	520010	581,28
M 20 + 25 + 32 + 40 (M x 1,5)	520009	622,80
REMS eva Set in cardboard box		
R 1/2 + 3/4	520008	259,50
R 1/2 + 3/4 + 1	520004	332,16
R 3/8 + 1/2 + 3/4 + 1 + 1 1/4	520003	477,48

REMS eva sets available for left-handed threads and NPT threads.

Accessories

Description	Art.-No.	€
Ratchet lever for complete work range	522000	168,16
Quick-change die heads S see page 23.		
Quick-change die heads, dies, attachment heads for button dies, see page 30 – 31.		
Steel case with inlay, for REMS eva 3/8 – 2"	526050	110,03
Thread-cutting oil see page 47.		
REMS Nippelspanner 3/8 – 2" see page 46.		
REMS Aquila 3B , pipe workstation with chain pipe vice on folding tripod stand, see page 105.		
REMS Aquila WB , chain pipe vice for workbench, see page 105.		



German Quality Product



Info



REMS quick-change die heads S

Accessories for REMS eva and other makes

For cutting pipe threads in hard-to-reach areas,
e.g. caved wall, lay bare pipes, trench.
Ideal for repair and renovation.

Pipe threads

3/8 – 1 1/4"

REMS quick-change die heads S – the trouble shooter for hard-to-reach areas.

Quick-change die heads S with specially mounted dies.

Additional, precise pipe guidance at the cover side ensure perfect pipe centering and easy start-cutting.

Extension of ratchet drive REMS eva for threading in caved areas.

Quick-change die heads S and extension fit into the ratchet lever REMS eva and other suitable die stocks.



German Quality Product



Supply format

Die heads S Set. choice of quick-change die heads S for pipe threads tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT) respectively Taper Pipe Thread ASME B1.20.1, Extension 300 mm. In sturdy steel case.

Description	Art.-No.	€
Set R 3/8 + 1/2 + 3/4	520025R	560,52
Set R 1/2 + 3/4 + 1	520026R	570,90
Set NPT 1/2 + 3/4 + 1	520056R	570,90



Accessories

Description	Size	Art.-No.	€
Ratchet lever for complete work range		522000	168,16
Quick-change die heads S			
Pipe threads tapered, right ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 3/8 R 1/2 R 3/4 R 1 R 1 1/4	521026 521036 521046 521056 521066	155,70 161,93 169,19 175,42 182,69
Extension 300 mm		522051	168,16
Steel case with inlay for ratchet lever, 4 quick-change die heads S and extension.		526052R	110,03



REMS Amigo E

Electric die stock with quick-change die heads

Powerful, super handy electric tools for threading with unique support bracket. Ready to use anywhere, without vice. Ideal for repair, renovation, job site.

Pipe threads	1/8 – 1", 16 – 32 mm
Bolt threads	6 – 30 mm, 1/4 – 1"

Thread types see page 30, 31.

REMS Amigo E – the fastest, strongest and lightest up to 1".

System advantage

Only one type of small, compact quick-change die heads and only one type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket

Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design

Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Drive unit only 3.4 kg, without die head. No heavy top, therefore single-hand operation possible. Perfect, secure seating of quick-change die heads.

Drive

Solid, compact, maintenance-free gear. Robust, powerful 950 W universal motor with 30 % power increase thanks to automatic carbon brush adjustment while changing the direction of rotation. Peak power input up to 1500 W. Fast threading time 35–27 rpm. Safety tip switch.

Quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with REMS Nippelspanner 3/8 – 1" (2") (page 46).

Supply format

REMS Amigo E Set. Electric die stock with quick-change die heads. For pipe threads 1/8 – 1", 16 – 32 mm, bolt threads 6 – 30 mm, 1/4 – 1". For right and left-hand threads. Drive unit with maintenance-free gear, powerful universal motor 230 V or 110 V, 50 – 60 Hz, 950 W, safety tip switch, power increase thanks to automatic carbon brush adjustment. Peak power input up to 1500 W. Right and left-hand rotation. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to EN 60423 M. In sturdy steel case.

Description	Art.-No.	€
Set R 1/2 + 3/4 + 1	530013R220	913,44
Set M 20 + 25 + 32	530014R220	975,72

REMS Amigo E Set for NPT threads available.

Accessories

Description	Art.-No.	€
Quick-change die heads, dies, attachment heads for button dies, see page 30 – 31.		
REMS Amigo E drive unit	530003R220	517,96
Support bracket	533000R	165,04
REMS REG St 1/4 – 2", pipe deburrer, see page 97.	731700	150,51
Dual purpose holder for threading and sawing with REMS Amigo E, Amigo, Amigo 2 and REMS Tiger	543100	264,69
Ratchet lever see page 22.	522000	168,16
Thread-cutting oil see page 47.		
REMS Nippelspanner 3/8 – 2" see page 46.		
Steel case with inlay	536000	110,03



German Quality Product



Info



REMS Amigo

Electric die stock with quick-change die heads

Powerful, easy-to-operate electric tool for threading with unique support bracket. Ready for use anywhere, without vice. Ideal for repair, renovation, job site.

Pipe threads	1/8 – 1 1/4", 16–40 mm
Bolt threads	6–30 mm, 1/4–1"

Thread types see page 30, 31.

REMS Amigo – the smallest, lightest, strongest and fastest up to 1 1/4".

System advantage

Only one type of small, compact quick-change die heads and only one type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket

Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design

Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Drive unit only 3.5 kg, without die head. No heavy top, therefore single-hand operation possible. Perfect, secure seating of quick-change die heads.

Drive

Solid, compact, maintenance-free gear. Robust, powerful 1200 W universal motor with 30 % power increase thanks to automatic carbon brush adjustment while changing the direction of rotation. Peak power input up to 1800 W. Fast threading time 35–27 rpm. Safety tip switch.

Quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with REMS Nippelspanner 3/8–1 1/4" (2") (page 46).

Supply format

REMS Amigo Set. Electric die stock with quick-change die heads. For pipe threads 1/8 – 1 1/4", 16–40 mm, bolt threads 6–30 mm, 1/4–1". For right and left-hand threads. Drive unit with maintenance-free gear, powerful universal motor 230 V or 110 V, 50–60 Hz, 1200 W, safety tip switch, power increase thanks to automatic carbon brush adjustment. Peak power input up to 1800 W. Right and left-hand rotation, overload protection switch. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to EN 60423 M. In sturdy steel case.

Description	Art.-No.	€
Set R 1/8 + 3/8 + 1 + 1 1/4	530020R220	1 100,28
Set M 16 + 20 + 25 + 32 (M x 1,5)	530022R220	1 162,56
Set M 20 + 25 + 32 + 40 (M x 1,5)	530023R220	1 245,60

REMS Amigo Set for NPT threads available.

Accessories

Description	Art.-No.	€
Quick-change die heads, dies, attachment heads for button dies, see page 30–31.		
REMS Amigo drive unit	530000R220	621,76
Support bracket	533000R	165,04
REMS REG St 1/4 – 2", pipe deburrer, see page 97.	731700	150,51
Dual purpose holder for threading and sawing with REMS Amigo E, Amigo, Amigo 2 and REMS Tiger	543100	264,69
Ratchet lever see page 22.	522000	168,16
Thread-cutting oil see page 47.		
REMS Nippelspanner 3/8 – 2" see page 46.		
Steel case with inlay	536000	110,03

All prices excl. VAT



German Quality Product



Info



REMS Amigo 2

Electric die stock with quick-change die heads

Powerful, easy-to-operate electric tool for threading with unique support bracket. Ready for use anywhere, without vice. Ideal for repair, renovation, job site.

Pipe threads	1/8 – 2", 16 – 50 mm
Bolt threads	6 – 30 mm, 1/4 – 1"

Thread types see page 30, 31.

REMS Amigo 2 – extremely strong up to 2".

System advantage

Only one type of small, compact quick-change die heads and only one type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket

Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design

Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Drive unit only 6.5 kg, without die head. Perfect seating of quick-change die heads.

Drive

Solid, maintenance-free gear. Robust 1700 W universal motor with 30 % power increase thanks to automatic carbon brush adjustment while changing the direction of rotation. Fast threading time 30 – 18 rpm. Safety tip switch.

Quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with REMS Nippelspanner 3/8 – 1" (2") (page 46).



German Quality Product



Info



Supply format

REMS Amigo 2 Set. Electric die stock with quick-change die heads. For pipe threads 1/8 – 2", 16 – 50 mm, bolt threads 6 – 30 mm, 1/4 – 1". For right and left-hand threads. Drive unit with maintenance-free gear, powerful universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W, safety tip switch, power increase thanks to automatic carbon brush adjustment, right and left-hand rotation. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to EN 60423 M. In sturdy steel case.

Description	Art.-No.	€
Set R 1/2 + 3/4 + 1 + 1 1/4 + 1 1/2 + 2	540020R220	1 743,84
Set M 20 + 25 + 32 + 40 + 50 (M x 1,5)	540022R220	1 889,16

REMS Amigo 2 Set for NPT threads available.

Other voltages on request.

Accessories

Description	Art.-No.	€
Quick-change die heads, dies, attachment heads for button dies, see page 30 – 31.		
REMS Amigo 2 drive unit	540000R220	1 100,28
Support bracket Amigo 2	543000	227,32
REMS REG St 1/4 – 2", pipe deburrer, see page 97.	731700	150,51
Dual purpose holder for threading and sawing with REMS Amigo E, Amigo, Amigo 2 and REMS Tiger	543100	264,69
Ratchet lever see page 22.	522000	168,16
Thread-cutting oil see page 47.		
REMS Nippelspanner 3/8 – 2" see page 46.		
Steel case with inlay	546000	128,71



REMS Amigo 2 Compact

Electric die stock with quick-change die heads

Powerful, easy-to-operate electric tool for threading with unique support bracket. Ready for use anywhere, without vice. Ideal for repair, renovation, job site.

Pipe threads	1/8 – 2", 16 – 50 mm
Bolt threads	6 – 30 mm, 1/4 – 1"

Thread types see page 30, 31.

REMS Amigo 2 Compact – The smallest and lightest up to 2".

System advantage

Only one type of small, compact quick-change die heads and only one type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket

Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design

Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Drive unit only 4.9 kg, without die head. Perfect seating of quick-change die heads.

Drive

Solid, maintenance-free gear. Robust 1200 W universal motor with 30% power increase thanks to automatic carbon brush adjustment while changing the direction of rotation. Peak power input up to 1800 W. Fast threading time 30 – 18 rpm. Safety tip switch.

Quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with REMS Nippelspanner 3/8 – 1" (2") (page 46).



German Quality Product



Info



Supply format

REMS Amigo 2 Compact Set. Electric die stock with quick-change die heads.

For pipe threads 1/8 – 2", 16 – 50 mm, bolt threads 6 – 30 mm, 1/4 – 1". For right and left-hand threads. Drive unit with maintenance-free gear, powerful universal motor 230 V or 110 V, 50 – 60 Hz, 1200 W, safety tip switch, power increase thanks to automatic carbon brush adjustment. Peak power input up to 1800 W. Right and left-hand rotation. Overload protection. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to DIN DN 60423 M. In sturdy steel case.

Description	Art.-No.	€
Set R 1/2 + 3/4 + 1 + 1 1/2	540023R220	1 598,52
Set R 1/2 + 3/4 + 1 + 1 1/4 + 1 1/2 + 2	540024R220	1 743,84
Set M 20 + 25 + 32 + 40 + 50 (M x 1,5)	540025R220	1 889,16

REMS Amigo 2 Compact Set for NPT threads available.

Other voltages on request.

Accessories

Description	Art.-No.	€
Quick-change die heads, dies, attachment heads for button dies, see page 30 – 31.		
REMS Amigo 2 Compact drive unit	54001R220	1 100,28
Support bracket Amigo 2 Compact	543010	227,32
REMS REG St 1/4 – 2", pipe deburrer, see page 97.	731700	150,51
Ratchet lever see page 22.	522000	168,16
Thread-cutting oil see page 47.		
REMS Nippelspanner 3/8 – 2" see page 46.		
Steel case with inlay	546000	128,71



REMS Amigo 22 V

Cordless die stock with quick-change die heads

Powerful, mobile, handy electric tool for threading with unique support bracket. Ready for use anywhere, without vice. Ideal for repair, renovation, job site. Li-Ion 22V Technology. For battery and corded operation.

Pipe threads	1/8 – 1", 16 – 32 mm
Bolt threads	6 – 30 mm, 1/4 – 1"

Thread types see page 30, 31.

REMS Amigo 22V – mobile, handy, light.

Li-Ion 21.6 V, 9.0 Ah battery, for approx. 52 ¾" threads with one battery charge*.

System advantage

Only one type of small, compact quick-change die heads and only one type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket

Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design

Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Mobile, handy, light. Drive unit with battery pack weighs only 5.6 kg. Practical D-shaped handle with soft grip. Perfect seating of quick-change die heads. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check by a 2-coloured green/red LED.

Drive

Solid, maintenance-free gear. Powerful battery motor 21.6V, with large power reserve, 500W output. High cutting speed 27–20 rpm. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V batteries with 9.0 Ah capacity for long service life. Light and powerful, for 52 ¾" threads with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range -10 to +60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 40A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies

The proven, indistructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with REMS Nippelspanner ¾ – 1" (2") (page 46).



German Quality Product



Info



REMS Amigo 22V

Cordless die stock with quick-change die heads

Supply format

REMS Amigo 22V Set. Cordless die stock with quick-change die heads. For pipe threads $\frac{1}{8}$ – $1\frac{1}{4}$ ", 16–32 mm, bolt threads 6–30 mm, $\frac{1}{4}$ – $1\frac{1}{4}$ ". For right and left-hand threads. Drive unit with maintenance-free gear, powerful battery motor 21.6V, 500 W. Safety switch. Right and left-hand rotation, machine status check with overload protection, temperature monitoring, battery charging status check. Li-Ion 21.6V, 9.0 Ah battery, 100–240V, 50–60 Hz, 90W rapid charger. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to DIN DN 60423 M. In sturdy steel case.

Description	Art.-No.	€
Set R $\frac{1}{8}$ + $\frac{3}{8}$ + 1	530015R220	1 920,30
Set M 20 + 25 + 32	530016R220	1 992,96

REMS Amigo 22V Set for NPT threads available.

Other voltages on request.

Accessories

Description	Art.-No.	€
Quick-change die heads, dies, attachment heads for button dies, see page 30–31.		
REMS Akku-Amigo 22V drive unit, without battery	530004R22	1 162,56
Support bracket Amigo 2 Compact	543010	227,32
Battery Li-Ion 21.6V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 40A, for mains operation instead of battery Li-Ion 21.6V	571578R220	517,96
REMS REG St $\frac{1}{4}$ – 2", pipe deburrer, see page 97.	731700	150,51
Ratchet lever see page 22.	522000	168,16
Thread-cutting oil see page 47.		
REMS Nippelspanner $\frac{3}{8}$ – 2" see page 46.		
Steel case with inlay	566030R	128,71
REMS Lumen 2800 22V, cordless LED flood light, see page 111		



REMS quick-change die heads

Accessories for REMS die stocks
and other makes

REMS quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521000	202,41
	R 1/4	521010	176,46
	R 3/8	521020	119,37
	R 1/2	521030	124,56
	R 5/8	521040	129,75
	R 1	521050	134,94
	R 1 1/4	521060	140,13
	R 1 1/2	521070	166,08
	R 2	521080	176,46
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521100	242,89
	R 1/4 LH	521110	211,75
	R 3/8 LH	521120	143,24
	R 1/2 LH	521130	149,47
	R 5/8 LH	521140	155,70
	R 1 LH	521150	161,93
	R 1 1/4 LH	521160	168,16
	R 1 1/2 LH	521170	199,30
	R 2 LH	521180	211,75
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521200	202,41
	NPT 1/4	521210	176,46
	NPT 3/8	521220	119,37
	NPT 1/2	521230	124,56
	NPT 5/8	521240	129,75
	NPT 1	521250	134,94
	NPT 1 1/4	521260	140,13
	NPT 1 1/2	521270	166,08
	NPT 2	521280	176,46
Threads M for electric conduit EN 60423	M 16 x 1.5	521300	155,70
	M 20 x 1.5	521310	155,70
	M 25 x 1.5	521320	161,93
	M 32 x 1.5	521330	168,16
	M 40 x 1.5	521340	199,30
	M 50 x 1.5	521350	211,75



Right-hand
pipe thread



Left-hand
pipe thread

German Quality Product

REMS dies

Accessories for REMS die stocks

REMS dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.


Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521002RWS	92,38
	R 1/4	521012RWS	87,19
	R 3/8	521022RWS	87,19
	R 1/2	521032RWS	87,19
	R 5/8	521042RWS	95,50
	R 1	521052RWS	95,50
	R 1 1/4	521062RWS	95,50
	R 1 1/2	521072RWS	95,50
	R 2	521082RWS	95,50
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521102RWS	111,07
	R 1/4 LH	521112RWS	104,84
	R 3/8 LH	521122RWS	104,84
	R 1/2 LH	521132RWS	104,84
	R 5/8 LH	521142RWS	115,22
	R 1 LH	521152RWS	115,22
	R 1 1/4 LH	521162RWS	115,22
	R 1 1/2 LH	521172RWS	115,22
	R 2 LH	521182RWS	114,18
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521202RWS	92,38
	NPT 1/4	521212RWS	87,19
	NPT 3/8	521222RWS	87,19
	NPT 1/2	521232RWS	87,19
	NPT 5/8	521242RWS	95,50
	NPT 1	521252RWS	95,50
	NPT 1 1/4	521262RWS	95,50
	NPT 1 1/2	521272RWS	95,50
	NPT 2	521282RWS	95,50
Threads M for electric conduit EN 60423	M 16 x 1.5	521302RWS	115,22
	M 20 x 1.5	521312RWS	115,22
	M 25 x 1.5	521322RWS	115,22
	M 32 x 1.5	521332RWS	115,22
	M 40 x 1.5	521342RWS	115,22
	M 50 x 1.5	521352RWS	114,60



German Quality Product

Attachment heads for button dies / intermediate rings / guide bushings

Accessories for REMS die stocks
and other makes



Attachment heads

Attachment heads for incorporating standard, round button dies of all thread types. Locking of button dies to the attachment head with stud bolt.

Description	Size	Art.-No.	€
Attachment head for button dies	Ø 65 mm	731200	152,59
Attachment head for button dies	G 1¼	731250	158,81
Attachment head for button dies	Ø 105 mm	541401	196,18



Intermediate rings

Intermediate rings for different outside diameters of button dies.

Description	Size	I.D. mm	Art.-No.	€
Intermediate rings to attachment head 731200	M 6–9	20/25	731205	85,12
	M 10–11	30	731210	85,12
	M 12–14 (Pg 7–9)	38	731220	85,12
	M 16–20 (Pg 11–13,5)	45	731230	85,12
	M 22–24 (Pg 16)	55	731240	85,12
without intermediate ring	M 27–30 (Pg 21–29)	65		
Intermediate rings to attachment head 541401	Ø 65/105 (Pg 21–29)	65	541404	96,53
	Ø 75/105	75	541406	96,53
	Ø 90/105 (Pg 36)	90	541410	96,53
without intermediate ring	Pg 42–48	105		



Guide bushings

Guide bushings for easy and concentric start-cutting.

Description	Size	Art.-No.	€
Guide bushings to attachment head 731200	Ø 6	731301	26,99
	Ø 8	731302	26,99
	Ø 10	731303	26,99
	Ø 12	731304	26,99
	Ø 14	731305	26,99
	Ø 16	731306	26,99
	Ø 18	731307	26,99
	Ø 20	731308	26,99
	Ø 22	731309	26,99
	Ø 24	731310	26,99
	Ø 27	731311	26,99
	Ø 30	731312	26,99
	Ø 12,8 (Pg 7)	731320	26,99
	Ø 15,5 (Pg 9)	731321	26,99
	Ø 18,9 (Pg 11)	731322	26,99
	Ø 20,7 (Pg 13,5)	731323	26,99
	Ø 22,8 (Pg 16)	731324	26,99
	Ø 28,6 (Pg 21)	731325	26,99
	Ø 37,3 (Pg 29)	731326	26,99
Guide bushings to attachment head 541401	Ø 28,6 (Pg 21)	541413	31,14
	Ø 37,3 (Pg 29)	541414	31,14
	Ø 47,3 (Pg 36)	541415	31,14
	Ø 54,3 (Pg 42)	541416	31,14



German Quality Product

REMS Tornado

Proven high performance machine for threading, cutting, deburring, threading of nipples, roll grooving.
For installation, metalworking, industry.
For job site and workshop.

Pipe threads	(1/16) 1/8 – 2", 16 – 63 mm
Bolt threads	(6) 10 – 60 mm, 1/4 – 2"

Thread types see page 40.

Pipe grooving with REMS roll grooving attachment	DN 25 – 200 1 – 8"
---	-----------------------

REMS Tornado – a class of its own.

Automatic chuck. Universal automatic die head.

Automatic lubrication and cooling.

Operating principle

Rotating material - stationary tools.

Design

Robust, job site-proven. Favourable size and weight, e.g. REMS Tornado 2000 complete only 50 kg. Large work and chip compartment. Easy handling of chip tray. Adjustable height material support.

2 versions:

- Portable version with 3 tubular legs, with removable large oil basin and chip tray.
- Version T with integrated, even larger oil basin and chip tray.
For workbench. Stand, collapsible wheel stand or wheel stand with material shelf, as an accessory, for easy transport, optimum working height and stable positioning.

Drive

Extremely powerful and fast, e.g. R 2" thread in only 15 s.
Completely maintenance-free gear which runs in a sealed oil bath.

Choice of 3 powerful motors:

- Strong universal motor, 1700 W.
Overload protection. Spindle speed 53 rpm.
- Pole-reversible capacitor motor, 2100 W.
Overload protection. 2 spindle speeds 52 and 26 rpm,
also under full load. **Extremely quiet running.**
- Pole-reversible 3~induction motor, 2000 W.
Overload protection. 2 spindle speeds 52 and 26 rpm,
also under full load. **Extremely quiet running.**

Operator-friendly safety foot switch with emergency-stop, 2-step. Foot switch, can be loaded with the full body weight during operation.

Automatic chuck

2 automatic chucks with self-centering clamping jaws for easy and fast clamping and release of the material. Self-tightening, hence maximum clamping force. No slipping of pipes. Collets are available for clamping pipes < Ø 1 1/8" and bolts < Ø 10 mm.

Automatic lubrication and cooling

Robust, proven oil pump with high pumping volume. Optimized oil distribution directly onto the threading point through the die head ensures clean threads and long service life of dies, gear and motor.

Universal automatic die head

Only one universal automatic die head for all threads, including long threads;
automatic opening with automatic thread-length-stop for tapered threads.
Fast and easy adjustment of thread size. Easy-to-read thread-size scale. Simple and fast change of dies through lock-in positioning in die holder.

Dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Pipe cutter

Self centering. Robust body made of forged steel. Ergonomic, wide handle for powerful infeed of spindle. Specially hardened cutter wheel in tough-hard REMS die-steel ensures long service life.

Inner pipe deburrer

Robust, easy-to-handle deburring device with adjustable deburring positioning. Specially hardened and designed deburring blade ensures easy deburring and extremely long service life. Two cutting edges for optimum chip flow, specially for small diameters.

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with the automatic internal clamping REMS Nippelfix 1/2 – 2" (4") or with the manual internal clamping REMS Nippelspanner 3/8 – 2" (page 46).

Threading machine



German Quality Product



Info



Choice of 3 powerful motors.



REMS Tornado

Threading machine

REMS roll grooving attachment

Robust, compact roll grooving attachment with oil hydraulic in-feed for pipe grooving of grooved coupling systems DN 25–300, 1–12" (page 48). Roll grooving with REMS Tornado up to DN 200, 8".



Supply format

REMS Tornado. Threading machine for pipe threads ($\frac{1}{16}$) $\frac{1}{8}$ –2", 16–63 mm, bolt threads (6) 10–60 mm, $\frac{1}{4}$ –2". With maintenance-free gear, safety foot switch with emergency-stop, 2 automatic chucks, automatic lubrication and cooling. With tool set consisting of one universal automatic die head for all threads, also long threads, automatic opening, with automatic thread-length-stop for tapered threads. Dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R $\frac{1}{2}$ – $\frac{3}{4}$ " and R 1–2" right-hand, pipe cutter, inner pipe deburrer, pressing lever, adjustable height material support. Choice of 3 motors. Portable version with 3 tubular legs, with removable, large oil and chip tray. Version T with integrated, even bigger oil tray and chip tray, for workbench, stand, collapsible wheel stand or wheel stand with material shelf. In a carton.

Description	Version	Art.-No.	€
2000	Universal motor 230 V or 110 V, 50–60 Hz, 1700 W. 53 rpm. Portable, 3 legs.	340200R220	4 660,62
2010	Pole-reversible capacitor, motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running. Portable, 3 legs.	340201R220	4 795,56
2020	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running. Portable, 3 legs.	340202R380	5 023,92
2000 T	Universal motor 230 V or 110 V, 50–60 Hz, 1700 W. 53 rpm For work bench, stand or wheel stand.	340206R220	5 646,72
2010 T	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running. For work bench, stand or wheel stand.	340207R220	5 781,66
2020 T	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running. For work bench, stand or wheel stand.	340208R380	6 010,02

Other voltages and NPT versions on request.

Accessories

Description	Art.-No.	€
Stand	344105R	290,64
Wheel stand with material shelf	344100R	493,05
Collapsible wheel stand	344150R	705,84
Dies see page 40.		
Universal automatic die head $\frac{1}{16}$–2" quick-change die head instead of changing the dies	341000RR	778,50
REMS cutter wheel St $\frac{1}{8}$–4", s 8	341614R	15,47
Thread-cutting oil see page 47.		
Nipple holder see page 46.		
REMS Hercules material supports, see page 107.		
REMS roll grooving attachment for pipe grooving, see page 48.	347000R	2 242,08

Version T



Wheel stand (accessory)



Version T

Collapsible wheel stand (Accessory)



REMS Magnum (up to 2")

Robust, compact high performance machine for threading, cutting, deburring, threading of nipples, roll grooving. For installation, metalworking, industry. For job site and workshop.

Pipe threads	(1/16) 1/8 – 2", 16 – 63 mm
Bolt threads	(6) 8 – 60 mm, 1/4 – 2"

Thread types see page 40.

Grooving of pipes with REMS roll grooving attachment	DN 25 – 300 1 – 12"
---	------------------------

REMS Magnum – the compact up to 2".

Operating principle

Rotating material – stationary tools.

Design

Robust, compact, job site-proven design. Favorable size and weight, e.g. REMS Magnum 2000 L-T only 62 kg. Large work and chip compartment. Tool support. 2 versions:

- Light version L-T with removable large oil basin and chip tray.
 - Version T with integrated, even larger oil basin and chip tray.
- For workbench. Stand, collapsible wheel stand or wheel stand with material shelf, as an accessory, for easy transport, optimum working height and stable positioning.

Drive

Extremely powerful and fast, e.g. thread R 2" in only 15 s.

Completely maintenance-free gear which runs in a sealed oil bath.

Choice of 3 powerful motors:

- Strong universal motor, 1700 W.
Overload protection. Spindle speed 53 rpm.
- Pole-reversible capacitor motor, 2100 W.
Overload protection. 2 spindle speeds 52 and 26 rpm,
also under full load. **Extremely quiet running.**
- Pole-reversible 3~ induction motor, 2000 W.
Overload protection. 2 spindle speeds 52 and 26 rpm,
also under full load. **Extremely quiet running.**

Operator-friendly safety foot switch with emergency-stop, 2-step. Foot switch, can be loaded with the full body weight during operation.

Chuck

Proven quick-action hammer chuck, self-tightening. No slipping of pipes.

Large space between chuck and centering device ensures secure clamping of long pipes. Rear centering device for alignment of the material. Collets are available for clamping pipes < Ø 1/8" and bolts < Ø 8 mm.

Automatic lubrication and cooling

Robust, proven oil pump with high pumping volume. Optimized oil distribution directly onto the threading point through the die head ensures clean threads and long service life of dies, gear and motor.

Universal automatic die head

Only one universal automatic die head for all threads, including long threads; automatic opening with automatic thread-length-stop for tapered threads.

Fast and easy adjustment of thread size. Simple and fast change of dies through lock-in positioning in die holder.

Dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Pipe cutter

Self centering. Robust body made of forged steel. Ergonomic, wide handle for powerful infeed of spindle. Specially hardened cutter wheel in tough-hard REMS die-steel ensures long service life.

Inner pipe deburrer

Robust, easy-to-handle deburring device for adjustable deburring positioning. Specially hardened and designed deburring blade ensures easy deburring and extremely long service life. Two cutting edges for optimum chip flow, specially for small diameters.

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with automatic internal clamping REMS Nippelfix 1/2 – 2" (4") or with manual internal clamping REMS Nippelspanner 3/8 – 2" (page 46).

REMS roll grooving attachment

Robust, compact roll grooving attachment with oil hydraulic in-feed for pipe grooving of grooved coupling systems DN 25 – 300, 1 – 12" (page 48).

Threading machine



German Quality Product



Info



Choice of 3 powerful motors.



REMS Magnum (up to 2")

Threading machine



Version L-T

Stand
(Accessory)



Version T

Wheel stand
(accessory)



Version L-T

Collapsible wheel stand
(Accessory)

Supply format

REMS Magnum. Threading machine for pipe threads ($\frac{1}{16}$) $\frac{1}{8}$ – 2", 16 – 63 mm, bolt thread (6) 8 – 60 mm, $\frac{1}{4}$ – 2". With maintenance-free gear, safety foot switch with emergency-stop, self-tightening quick-action hammer chuck, rear centering device, automatic lubrication and cooling. With complete tool set consisting of one universal automatic die head for all threads, also long threads; automatic opening, with automatic thread-length-stop for tapered threads, dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R $\frac{1}{2}$ – $\frac{3}{4}$ " and R 1 – 2" right-hand, pipe cutter, inner pipe deburrer, pressing lever. Tool support. Choice of 3 motors. Version L-T with removable large oil basin and chip tray. Version T with integrated, even bigger oil tray and chip tray. For workbench, stand, collapsible wheel stand or wheel stand with material shelf. In a carton.

Description	Version	Art.-No.	€
2000 L-T	Universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W. 53 rpm.	340226R220	4 712,52
2010 L-T	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running.	340227R220	5 117,34
2020 L-T	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running.	340228R380	5 273,04
2000 T*	Universal motor 230 V or 110 V, 50 – 60 Hz, 1700 W. 53 rpm.	340220R220	5 646,72
2010 T*	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running.	340221R220	6 051,54
2020 T*	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running.	340222R380	6 207,24

Other voltages and NPT versions on request.

*T versions with REMS roll grooving device for roll grooving can only be used up to DN 200, 8".

Accessories

Description	Art.-No.	€
Stand	344105R	290,64
Wheel stand with material shelf	344100R	493,05
Collapsible wheel stand	344150R	705,84
Dies see page 40.		
Universal automatic die head $\frac{1}{16}$ – 2" quick-change die head instead of changing the dies	341000RR	778,50
Changeover valve , for reversing flow direction of the coolant-lubricant pump for cutting left-handed threads with REMS Magnum 2010, 2020, 3010, 3020, 4010 and 4020	342080RX	143,24
REMS cutter wheel St $\frac{1}{8}$ – 4", s 8	341614R	15,47
Thread-cutting oil see page 47.		
Nipple holder see page 46.		
REMS Herkules material supports, see page 107.		
REMS roll grooving attachment for pipe grooving, see page 48.	347000R	2 242,08



REMS Magnum (up to 3")

Robust, compact high performance machine for threading, cutting, deburring, threading of nipples, roll grooving. For installation, metalworking, industry. For job site and workshop.

Pipe threads	(1/16) 1/2 – 3", 16 – 63 mm
Bolt threads	(6) 18 – 60 mm, 1/2 – 2"

Thread types see page 40.

Pipe grooving with REMS roll grooving attachment	DN 25 – 300 1 – 12"
---	------------------------

REMS Magnum – the super machine up to 3".

Exceptionally round and clean threads up to 3"
by using 5 threading dies.

Operating principle

Rotating material – stationary tools.

Design

Robust, compact, job site-proven design. Favorable size and weight, e.g. REMS Magnum 3000 L-T only 79 kg. Large work and chip compartment. Tool support. 2 versions:

- Light version L-T with removable large oil basin and chip tray.
 - Version T with integrated, even larger oil basin and chip tray.
- For workbench. Stand, collapsible wheel stand or wheel stand with material shelf, as an accessory, for easy transport, optimum working height and stable positioning.

Drive

Extremely powerful and fast. Completely maintenance-free gear which runs in a sealed oil bath.

Choice of 3 powerful motors:

- Strong universal motor, 1700 W.
Overload protection. Spindle speed 23 rpm.
- Pole-reversible capacitor motor, 2100 W.
Overload protection. 2 spindle speeds 20 and 10 rpm, also under full load. **Extremely quiet running.**
- Pole-reversible 3~ induction motor, 2000 W.
Overload protection. 2 spindle speeds 20 and 10 rpm, also under full load. **Extremely quiet running.**

Operator-friendly safety foot switch with emergency-stop, 2-step.

Foot switch, can be loaded with the full body weight during operation.

Chuck

Proven quick-action hammer chuck, self-tightening. No slipping of pipes. Large space between chuck and centering device ensures secure clamping of long pipes. Rear centering device for alignment of the material. Collets are available for clamping pipes < Ø 1/2" and bolts < Ø 18 mm.

Automatic lubrication and cooling

Robust, proven oil pump with high pumping volume. Optimized oil distribution directly onto the threading point through the die head ensures clean threads and long service life of dies, gear and motor.

Universal automatic die head

Only 1 universal automatic die head each for the sizes 1/16 – 2" and 2 1/2 – 3" for all threads, including long threads; automatic opening with automatic thread-length-stop for tapered threads. 5 dies 2 1/2 – 3" ensure a favourable distribution of the cutting force onto the pipe, hence round and clean threads. Fast and easy adjustment of thread size. Simple and fast change of dies through lock-in positioning in die holder.

Dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Pipe cutter

Self centering. Robust body made of forged steel. Ergonomic, wide handle for powerful infeed of spindle. Specially hardened cutter wheel in tough-hard REMS die-steel ensures long service life.

Inner pipe deburrer

Robust, easy-to-handle deburring device for adjustable deburring positioning. Specially hardened and designed deburring blade ensures easy deburring and extremely long service life. Two cutting edges for optimum chip flow, specially for small diameters.

Tool sets

For 2 1/2 – 3" and 1/2 – 2" one complete tool set each adapted to the work range with universal die head, pipe cutter, inner-pipe-deburring device, pressing lever, dies.

Threading machine



German Quality Product



Choice of 3 powerful motors.



REMS Magnum (up to 3")

Threading machine

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with automatic internal clamping REMS Nippelfix ½–3" (4") or with manual internal clamping REMS Nippelspanner (page 46).

REMS roll grooving attachment

Robust, compact roll grooving attachment with oil hydraulic in-feed for pipe grooving of grooved coupling systems DN 25–300, 1–12" (page 48).

Supply format

REMS Magnum. Threading machine for pipe threads (1/16) ½–3", 16–63 mm, bolt threads (6) 18–60 mm, ½–2". With maintenance-free gear, safety foot switch with emergency-stop, self-tightening quick-action hammer chuck, rear centering device, automatic lubrication and cooling. With tool sets 1/16–2" and/or 2 1/2–3", each consisting of universal automatic die head for all threads, also long threads; automatic opening, with automatic thread-length-stop for tapered threads, dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand, pipe cutter, inner pipe deburrer, pressing lever. Tool support. Choice of 3 motors. Version L-T with removable large oil basin and chip tray. Version T with integrated, even larger oil basin and chip tray. For workbench, stand, collapsible wheel stand or wheel stand with material shelf. In a carton.


Description	Version/Equipment	Art.-No.	€
3000 L-T	Universal motor 230 V or 110 V, 50–60 Hz, 1700 W. 23 rpm. Equipment R 2 1/2–3 Equipment R ½–3	380303R220 380309R220	5 625,96 6 923,46
3010 L-T	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 20/10 rpm, also under full load. Extremely quiet running. Equipment R 2 1/2–3 Equipment R ½–3	380304R220 380310R220	5 926,98 7 224,48
3020 L-T	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 20/10 rpm, also under full load. Extremely quiet running. Equipment R 2 1/2–3 Equipment R ½–3	380305R380 380311R380	6 144,96 7 442,46
3000 T*	Universal motor 230 V or 110 V, 50–60 Hz, 1700 W. 23 rpm. Equipment R 2 1/2–3 Equipment R ½–3	380306R220 380312R220	6 560,16 7 857,66
3010 T*	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 20/10 rpm, also under full load. Extremely quiet running. Equipment R 2 1/2–3 Equipment R ½–3	380307R220 380313R220	6 861,18 8 158,68
3020 T*	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 20/10 rpm, also under full load. Extremely quiet running. Equipment R 2 1/2–3 Equipment R ½–3	380308R380 380314R380	7 079,16 8 376,66

Other voltages and NPT versions on request.

*T versions with REMS roll grooving device for roll grooving can only be used up to DN 200, 8".

Accessories

Description	Art.-No.	€
Stand	344105R	290,64
Wheel stand with material shelf	344100R	493,05
Collapsible wheel stand	344150R	705,84
Dies see page 40.		
Tool set R ½–2" complete with universal automatic die head 1/16–2", dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R ½–¾" and R 1–2" right-hand, pipe cutter, inner pipe deburrer, pressing lever.	340100RR	1 297,50
Universal automatic die head 1/16–2" and others	341000RR	778,50
Universal automatic die head 2 1/2–3"	381050R	1 027,62
Universal automatic die head 2 1/2–4"	381000R	1 816,50
Changeover valve, for reversing flow direction of the coolant-lubricant pump for cutting left-handed threads with REMS Magnum 2010, 2020, 3010, 3020, 4010 and 4020	342080RX	143,24
REMS cutter wheel St ½–4", s 8	341614R	15,47
REMS cutter wheel St 1–4", s 12	381622R	35,60
Thread-cutting oil see page 47.		
Nipple holder see page 46.		
REMS Herkules material supports, see page 107.		
REMS roll grooving attachment for pipe grooving, see page 48.	347000R	2 242,08



REMS Magnum (up to 4")

Robust, compact high performance machine for threading, cutting, deburring, threading of nipples, roll grooving. For installation, metalworking, industry. For job site and workshop.

Pipe threads	(1/16) 1/2 – 4", 18 – 63 mm
Bolt threads	(6) 20 – 60 mm, 1/2 – 2"

Thread types see page 40.

Pipe grooving with REMS roll grooving attachment	DN 25 – 300 1 – 12"
---	------------------------

REMS Magnum – the super machine up to 4".

Exceptionally round and clean threads up to 4"
by using 6 threading dies.

Operating principle

Rotating material - stationary tools.

Design

Robust, compact, job site-proven design. Favorable size and weight, e.g. REMS Magnum 4000 L-T only 81 kg. Large work and chip compartment. Tool support. 2 versions:

- Light version L-T with removable large oil basin and chip tray.
 - Version T with integrated, even larger oil basin and chip tray.
- For workbench. Stand, collapsible wheel stand or wheel stand with material shelf, as an accessory, for easy transport, optimum working height and stable positioning.

Drive

Extremely powerful and fast. Completely maintenance-free gear which runs in a sealed oil bath.

Choice of 3 powerful motors:

- Strong universal motor, 1700 W.
Overload protection. Spindle speed 23 rpm.
- Pole-reversible capacitor motor, 2100 W.
Overload protection. 2 spindle speeds 20 and 10 rpm,
also under full load. **Extremely quiet running.**
- Pole-reversible 3~ induction motor, 2000 W.
Overload protection. 2 spindle speeds 20 and 10 rpm,
also under full load. **Extremely quiet running.**

Operator-friendly safety foot switch with emergency-stop, 2-step. Foot switch, can be loaded with the full body weight during operation.

Chuck

Proven quick-action hammer chuck, self-tightening. No slipping of pipes. Large space between chuck and centering device ensures secure clamping of long pipes. Rear centering device for alignment of the material. Collets are available for clamping pipes < Ø 1/2" and bolts < Ø 18 mm.

Automatic lubrication and cooling

Robust, proven oil pump with high pumping volume. Optimized oil distribution directly onto the threading point through the die head ensures clean threads and long service life of dies, gear and motor.

Universal automatic die head

Only 1 universal automatic die head each for the sizes 1/16 – 2" and 2 1/2 – 4" for all threads, including long threads; automatic opening with automatic thread-length-stop for tapered threads. 6 dies 2 1/2 – 4" ensure a favourable distribution of the cutting force onto the pipe, hence round and clean threads. Fast and easy adjustment of thread size. Simple and fast change of dies through lock-in positioning in die holder.

Dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Pipe cutter

Self centering. Robust body made of forged steel. Ergonomic, wide handle for powerful infeed of spindle. Specially hardened cutter wheel in tough-hard REMS die-steel ensures long service life.

Inner pipe deburrer

Robust, easy-to-handle deburring device for adjustable deburring positioning. Specially hardened and designed deburring blade ensures easy deburring and extremely long service life. Two cutting edges for optimum chip flow, specially for small diameters.

Tool sets

For 2 1/2 – 4" and 1/2 – 2" one complete tool set each adapted to the work range with universal die head, pipe cutter, inner-pipe-deburring device, pressing lever, dies.

Threading machine



German Quality Product



Choice of 3 powerful motors.



REMS Magnum (up to 4")

Threading machine

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with automatic internal clamping REMS Nippelfix ½–4" or with manual internal clamping REMS Nippelspanner ¾–2" (page 46).

REMS roll grooving attachment

Robust, compact roll grooving attachment with oil hydraulic in-feed for pipe grooving of grooved coupling systems DN 25–300, 1–12" (page 48).

Supply format

REMS Magnum. Threading machine for pipe threads (1/16) ½–4", 16–63 mm, bolt threads (6) 18–60 mm, ½–2". With maintenance-free gear, safety foot switch with emergency-stop, self-tightening quick-action hammer chuck, rear centering device, automatic lubrication and cooling. With tool sets 1/16–2" and/or 2½–4", each consisting of universal automatic die head for all threads, also long threads; automatic opening, with automatic thread-length-stop for tapered threads, dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand, pipe cutter, inner pipe deburrer, pressing lever. Tool support. Choice of 3 motors. Version L-T with removable large oil basin and chip tray. Version T with integrated, even larger oil basin and chip tray. For workbench, stand, collapsible wheel stand or wheel stand with material shelf. In a carton.

Description	Version/Equipment	Art.-No.	€
4000 L-T	Universal motor 230 V or 110 V, 50–60 Hz, 1700 W. 23 rpm. Equipment R ½–2 Equipment R 2½–4 Equipment R ½–4	380447R220 380441R220 380444R220	5 397,60 6 466,74 7 764,24
4010 L-T	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 20/10 rpm, also under full load. Extremely quiet running. Equipment R ½–2 Equipment R 2½–4 Equipment R ½–4	380448R220 380442R220 380445R220	5 698,62 6 767,76 8 065,26
4020 L-T	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 20/10 rpm, also under full load. Extremely quiet running. Equipment R 2½–4 Equipment R ½–4	380443R380 380446R380	6 985,74 8 283,24
4000 T*	Universal motor 230 V or 110 V, 50–60 Hz, 1700 W. 23 rpm. Equipment R 2½–4 Equipment R ½–4	380426R220 380429R220	7 400,94 8 698,44
4010 T*	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 20/10 rpm, also under full load. Extremely quiet running. Equipment R 2½–4 Equipment R ½–4	380427R220 380430R220	7 701,96 8 999,46
4020 T*	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 20/10 rpm, also under full load. Extremely quiet running. Equipment R 2½–4 Equipment R ½–4	380428R380 380431R380	7 919,94 9 217,44

Other voltages and NPT versions on request.

*T versions with REMS roll grooving device for roll grooving can only be used up to DN 200, 8".

Accessories

Description	Art.-No.	€
Stand	344105R	290,64
Wheel stand with material shelf	344100R	493,05
Collapsible wheel stand	344150R	705,84
Dies see page 40.		
Tool set R ½–2" complete with universal automatic die head 1/16–2", dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R ½–¾" and R 1–2" right-hand, pipe cutter, inner pipe deburrer, pressing lever.	340100RR	1 297,50
Universal automatic die head 1/16–2" and others	341000RR	778,50
Universal automatic die head 2½–4"	381000R	1 816,50
Changeover valve , for reversing flow direction of the coolant-lubricant pump for cutting left-handed threads with REMS Magnum 2010, 2020, 3010, 3020, 4010 and 4020	342080RX	143,24
REMS cutter wheel St ½–4", s 8	341614R	15,47
REMS cutter wheel St 1–4", s 12	381622R	35,60
Thread-cutting oil see page 47.		
Nipple holder see page 46.		
REMS Herkules material supports , see page 107.		
REMS roll grooving attachment for pipe grooving, see page 48.	347000R	2 242,08




Version L-T



Version T



Version L-T



REMS dies


For REMS Tornado, REMS Magnum

REMS dies (set)

The proven REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for materials < 500 N/mm² (MPa) for extremely long die life.

Dies for other threads (e.g. BSW) on request. HSS dies for materials that are difficult to cut ≥ 500 N/mm² (MPa) 50 % surcharge.

¹⁾ Some dies only available in HSS.



For universal automatic die head 1/16 – 2"

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/16 – 1/8 HSS ¹⁾	341401RHSS	492,01
	R 1/4 – 3/8	341402RWS	328,01
	R 1/2 – 3/4	341403RWS	328,01
	R 1 – 2	341404RWS	328,01
Pipe threads G parallel, right-hand ISO 228-1 (DIN 259, BSPP)	G 1/16 – 1/8	341406RWS	373,68
	G 1/4 – 3/8	341407RWS	373,68
	G 1/2 – 3/4	341408RWS	373,68
	G 1 – 2	341409RWS	373,68
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/16 – 1/8 HSS ¹⁾	341411RHSS	492,01
	NPT 1/4 – 3/8	341412RWS	328,01
	NPT 1/2 – 3/4	341413RWS	328,01
	NPT 1 – 2	341414RWS	328,01
Pipe threads NPSM parallel, right-hand Straight Pipe Thread ASME B1.20.1	NPSM 1/8	341416RWS	373,68
	NPSM 1/4 – 3/8	341417RWS	373,68
	NPSM 1/2 – 3/4 HSS ¹⁾	341418RHSS	560,52
	NPSM 1 – 2 HSS ¹⁾	341419RHSS	560,52
Conduit threads Pg DIN 40430	Pg 7	341466RWS	373,68
	Pg 9	341467RWS	373,68
	Pg 11	341468RWS	373,68
	Pg 13.5	341469RWS	373,68
	Pg 16	341470RWS	373,68
	Pg 21	341471RWS	373,68
	Pg 29	341472RWS	373,68
	Pg 36	341473RWS	373,68
	Pg 42	341474RWS	373,68
Conduit threads M EN 60423	Pg 48	341475RWS	373,68
	M 16 × 1.5	341493RWS	373,68
	M 20 × 1.5	341494RWS	373,68
	M 25 × 1.5	341495RWS	373,68
	M 32 × 1.5	341496RWS	373,68
	M 40 × 1.5	341497RWS	373,68
	M 50 × 1.5	341498RWS	373,68
Metric bolt threads M ISO 261 (DIN 13)	M 63 × 1.5	341499RWS	373,68
	M 6	341426RWS	373,68
	M 8	341427RWS	373,68
	M 10	341428RWS	373,68
	M 12	341429RWS	373,68
	M 14	341430RWS	373,68
	M 16	341431RWS	373,68
	M 18	341432RWS	373,68
	M 20	341433RWS	373,68
	M 22	341434RWS	373,68
	M 24	341435RWS	373,68
	M 27	341436RWS	373,68
	M 30	341437RWS	373,68
	M 33	341438RWS	404,82
	M 36	341439RWS	404,82
	M 39	341440RWS	404,82
	M 42	341441RWS	404,82
Bolt threads UNC Unified Inch Screw Thread ASME B1.1	M 45	341442RWS	404,82
	M 48	341443RWS	404,82
	M 52	341444RWS	404,82
	M 56 HSS ¹⁾	341445RHSS	607,23
	M 60 HSS ¹⁾	341446RHSS	607,23
	UNC 1/4 – 20 HSS ¹⁾	341476RHSS	560,52
	UNC 5/16 – 18	341477RWS	373,68
	UNC 3/8 – 16 HSS ¹⁾	341478RHSS	560,52
	UNC 7/16 – 14	341479RHSS	373,68
	UNC 1/2 – 13 HSS ¹⁾	341480RHSS	560,52



German Quality Product



For universal automatic die head 2 1/2 – 3"

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 2 1/2 – 3	381430RWS	456,72
Pipe threads G parallel, right-hand ISO 228-1 (DIN 259, BSPP)	G 2 1/2 – 3 HSS ¹⁾	381431RHSS	739,06
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 2 1/2 – 3 HSS ¹⁾	381432RHSS	685,08
Pipe threads NPSM parallel, right-hand Straight Pipe Thread ASME B1.20.1	NPSM 2 1/2 – 3 HSS ¹⁾	381433RHSS	739,06



For universal automatic die head 2 1/2 – 4"

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 2 1/2 – 4	381401RWS	689,23
Pipe threads G parallel, right-hand ISO 228-1 (DIN 259, BSPP)	G 2 1/2 – 4 HSS ¹⁾	381405RHSS	1 098,20
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 2 1/2 – 4 HSS ¹⁾	381410RHSS	1 033,85
Pipe threads NPSM parallel, right-hand Straight Pipe Thread ASME B1.20.1	NPSM 2 1/2 – 4 HSS ¹⁾	381415RHSS	1 098,20



REMS Unimat 75

Semi-automatic high-performance machine
for efficient cutting of bolt and pipe threads.
For industry, metalworking, installation.

Bolt threads		6–72 mm ¼–2¾"
Pipe threads		1/16–2½", 16–63 mm
Tolerance class corresponding to ISO 261 (DIN 13)		"medium" (6 g)
Thread length	≤ Ø 30 mm ≤ Ø 72 mm	unlimited ≤ 200 mm
Chamfering	Range Chamfered Ø Maximum chamfer Chamfer angle	7–62 mm ≥ 7 mm 7 mm 45°
Peeling	Range Peeled Ø	7–62 mm ≥ 7 mm
Thread types see page 44.		

REMS Unimat 75 – high efficiency.

Tangential-chaser-threading-system. Large threading range. Fast working, short resetting time. For single and series production. Low hourly rate for the machine. Simple operation. Relieves expensive turning machines and specialists.

Operating principle

Operating principle Stationary material – rotating die head.

Design

Die Head
Compact, rugged design for continuous use. Die head with regrindable tangential chasers in self centering holder system. After start-cutting with feed lever and rack mechanism self feeding action of die head (no guide thread). Welded, sturdy machine stand with large oil compartment and removable chip drawer.

Drive

Drive
Indestructible planetary gear with annulus gear for long threads up to Ø 30 mm. Proven and powerful pole-reversible three-phase motor, specially designed for threading, with hollow shaft, 2000/2300 W. Overload protection. Reverse switch for cutting right and left-hand threads. High operating speed, 2 spindle speeds 70 and 35 rpm.

Clamping device

Clamping device
Self-centering universal vice for the complete range with specially toothed and hardened clamping jaws. Choice of manual or hydraulic clamping with operation by foot switch (working pressure 6 bar).

Special clamping jaws

Special clamping jaws
For drawn material, stud bolts, hex screws and pipe nipples, as accessory.

Automatic lubrication and cooling

Automatic lubrication and cooling
Robust, proven oil pump with high pumping volume. Ample oil volume ensures longer service life of chasers, gear and motor.

Universal automatic die head

Only one universal automatic die head for all threads. Fine adjustment of thread diameter with spindle and scale. Die head closes automatically and opens automatically when the required thread length is reached. After starting the thread via feed lever and rack the chaser-system initiates an automatic feed-forward of the die head. All threads can be cut in a single pass. Copying unit for tapered threads. Instead of changing the dies, additional quick-change die heads ensure shorter resetting time.

Chasers

The proven regrindable REMS tangential chasers with precise cutting geometry ensure an excellent start-cutting performance and clean threads. Tool steel chasers made of special hardened steel for material < 500 N/mm² (MPa). HSS chasers for hard-to-machine material ≥ 500 N/mm² (MPa). The chasers sit in a special holder system. Chasers and holders together form a threading set.

Thread cutting on rebar

Special chaser dies M with additional, ground cut for cutting threads on rebar in a single pass. Driven by REMS Unimat 75 with oil-hydraulic/pneumatic vice, for high clamping pressure.

Threading machine



German Quality Product

Machining examples



REMS Unimat 75

Threading machine

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with special clamping jaws $\frac{1}{16}$ – $1\frac{1}{4}$ " or with the automatic internal clamping REMS Nippelfix $\frac{1}{2}$ – $2\frac{1}{2}$ " or with the manual internal clamping REMS Nippelspanner $\frac{3}{8}$ – 2 " (page 46).

Supply format

REMS Unimat 75 Basic. Semi-automatic threading machine for bolt threads 6–72 mm, $\frac{1}{4}$ – $2\frac{3}{4}$ ", pipe threads $\frac{1}{16}$ – $2\frac{1}{2}$ ", 16–63 mm. Machine on stand. Pole-reversible 3~ induction motor with hollow shaft, 400 V, 50 Hz, 2000/2300 W, right and left-hand rotation. Die head speed 70 and 35 rpm. Self-centering universal chuck for the complete clamping range, choice of manual or oil-hydraulic/pneumatic operation. Automatic lubrication and cooling. 1 universal automatic die head for all threads, opens and closes automatically. Without threading sets, without closing lever. Electric locking system of safety cover. Adjustment gauge. Wrench. In transport case.

Description	Version	Art.-No.	€
REMS Unimat 75 Basic mS	manual clamping device	750003R380	21 964,08
REMS Unimat 75 Basic pS	oil-hydraulic/pneumatic vice clamping device	750004R380	25 794,30

Other voltages on request.



Accessories

Description	Art.-No.	€
Chasers and holders (threading sets) and chasers see page 44.		
Universal automatic die head, without threading sets, without closing lever	751000	1 348,36
Closing lever for closing and opening the chasers		
R for taper pipe threads, right-hand	751040R90	176,46
R-L for taper pipe threads, left-hand	751050R90	176,46
G for cylindrical pipe threads, right-hand	751060R90	176,46
G-L for cylindrical pipe threads, left-hand	751070R90	176,46
M for all bolt threads, right-hand	751080R90	176,46
M-L for all bolt threads, left-hand	751090R90	176,46
Chamfering/peeling die head 45°, Ø 7–62 mm, with chamfering/peeling chasers 45°, Ø 7–62 mm, HSS, with holder	751100	3 316,41
Chamfering/peeling die head 45°, Ø 7–62 mm, without threading sets	751102	1 404,41
Chamfering/peeling chasers 45°, Ø 7–46 mm, HSS, with holder	751096	956,00
Chamfering/peeling chasers 45°, Ø 40–62 mm, HSS, with holder	751098	956,00
Chamfering/peeling chasers 45°, Ø 7–62 mm, pack of 4, with holder	751097	552,63
Special clamping jaws, pair, for drawn material, stud bolts and hex screws. Workpiece length protrude from vice without thread, minimum 15 mm, Ø 6–42 mm		
	753240	1 432,44
Thread-cutting oil see page 47.		
Nipple holder see page 46.		
REMS Herkules material supports , see page 107.		



Chasers and Holders

Chasers



German Quality Product

For REMS Unimat 75



German Quality Product

Chasers and holders (threading set)

The proven regridable REMS tangential chasers with precise cutting geometry ensure an excellent start-cutting performance and clean threads. Tool steel chasers made of special hardened steel for material < 500 N/mm² (MPa). HSS chasers for hard-to-machine material ≥ 500 N/mm² (MPa). The chasers sit in a special holder system. Chasers and holders together form a threading set.

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/16 – 1/8	759250RWS	817,94
	R 1/4 – 3/8	759251RWS	817,94
	R 1/2 – 3/4	759252RWS	817,94
	R 1 – 2	759253RWS	817,94
	R 2 1/2	759254RWS	817,94
Pipe threads G parallel, right-hand ISO 228-1 (DIN 259, BSPP)	G 1/16 – 1/8	759255RWS	817,94
	G 1/4 – 3/8 HSS ¹⁾	759256RHSS	1 004,78
	G 1/2 – 3/4 HSS ¹⁾	759257RHSS	1 004,78
	G 1 – 2 HSS ¹⁾	759258RHSS	1 004,78
	G 2 1/2 HSS ¹⁾	759259RHSS	1 004,78
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1. 20.1	NPT 1/16 – 1/8	759360RWS	817,94
	NPT 1/4 – 3/8 HSS ¹⁾	759361RHSS	1 004,78
	NPT 1/2 – 3/4 HSS ¹⁾	759362RHSS	1 004,78
	NPT 1 – 2 HSS ¹⁾	759363RHSS	1 004,78
	NPT 2 1/2 HSS ¹⁾	759364RHSS	1 004,78
Pipe threads NPSM parallel, right-hand Straight Pipe Thread ASME B1. 20.1	NPSM 1/16 – 1/8	759365RWS	817,94
	NPSM 1/4 – 3/8	759366RWS	817,94
	NPSM 1/2 – 3/4 HSS ¹⁾	759367RHSS	1 004,78
	NPSM 1 – 2 HSS ¹⁾	759368RHSS	1 004,78
Conduit threads Pg DIN 40430	Pg 7	759260RWS	817,94
	Pg 9 – 16	759261RWS	817,94
	Pg 21 – 48	759262RWS	817,94
Conduit threads M EN 60423	M 16 – 20 × 1.5	759263RWS	817,94
	M 25 – 32 × 1.5	759264RWS	817,94
	M 40 – 50 × 1.5	759265RWS	817,94
	M 63 × 1.5 HSS ¹⁾	759330RHSS	1 004,78
	M 14 – 16 HSS	759274RHSSZ	1 004,78
Threads M for rebar ISO 261 (DIN 13)	M 18 – 22 HSS	759275RHSSZ	1 004,78
	M 24 – 27 HSS	759276RHSSZ	1 004,78
	M 30 – 33 HSS	759277RHSSZ	1 004,78
	M 36 – 39 HSS	759278RHSSZ	1 126,23
	M 42 – 45 HSS	759279RHSSZ	1 126,23
	M 48 – 52 HSS ¹⁾	759280RHSS	1 126,23
	M 56 – 60 HSS ¹⁾	759281RHSS	1 126,23
Metric bolt threads M ISO 261 (DIN 13)	M 6 HSS ¹⁾	759270RHSS	1 004,78
	M 8	759271RWS	817,94
	M 10	759272RWS	817,94
	M 12	759273RWS	817,94
	M 14 – 16	759274RWS	817,94
	M 18 – 22	759275RWS	817,94
	M 24 – 27	759276RWS	817,94
	M 30 – 33	759277RWS	817,94
Bolt threads UNC Unified Inch Screw Thread ASME B1.1	M 36 – 39	759278RWS	903,06
	M 42 – 45	759279RWS	903,06
	M 48 – 52 HSS ¹⁾	759280RHSS	1 126,23
	M 56 – 60 HSS ¹⁾	759281RHSS	1 126,23
	M 64 – 72 HSS ¹⁾	759282RHSS	1 126,23
	UNC 1/4 – 20	759370RWS	817,94
	UNC 5/16 – 18	759371RWS	817,94
	UNC 3/8 – 16	759372RWS	817,94
Dies for other threads (e.g. bicycle threads, fine threads, BSW) and HSS chaser dies for materials above 500 N/mm ² (MPa) that are difficult to cut on request. Dies with HSS chaser dies with 50% surcharge on chaser dies. ¹⁾ Some chasers only available in HSS. Threading sets for left-hand threads 50% extra charge on chasers.	UNC 7/16 – 14	759373RWS	817,94
	UNC 1/2 – 13	759374RWS	817,94
	UNC 5/16 – 12	759375RWS	817,94
	UNC 5/8 – 11	759376RWS	817,94
	UNC 3/4 – 10	759377RWS	817,94
	UNC 7/8 – 9	759378RWS	817,94
	UNC 1 – 8 HSS ¹⁾	759379RHSS	1 004,78
	UNC 1 1/8 – 1 1/4 – 7	759380RWS	817,94
	UNC 1 3/8 – 1 1/2 – 6	759381RWS	903,06
	UNC 1 1/4 – 5	759382RWS	903,06
	UNC 2 – 2 1/4 – 4,5	759383RWS	903,06
	UNC 2 1/2 – 2 3/4 – 4	759384RWS	903,06

Dies for other threads (e.g. bicycle threads, fine threads, BSW) and HSS chaser dies for materials above 500 N/mm² (MPa) that are difficult to cut on request. Dies with HSS chaser dies with 50% surcharge on chaser dies. ¹⁾Some chasers only available in HSS. Threading sets for left-hand threads 50% extra charge on chasers.

Chasers (set)

The proven regridable REMS tangential chasers with precise cutting geometry ensure an excellent start-cutting performance and clean threads. Tool steel chasers made of special hardened steel for material < 500 N/mm² (MPa). HSS chasers for hard-to-machine material ≥ 500 N/mm² (MPa).

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/16 – 1/8	751501RWS	373,68
	R 1/4 – 3/8	751502RWS	373,68
	R 1/2 – 3/4	751503RWS	373,68
	R 1 – 2 1/2	751504RWS	373,68
Pipe threads G parallel, right-hand ISO 228-1 (DIN 259, BSPP)	G 1/16 – 1/8 HSS ¹⁾	751505RHSS	560,52
	G 1/4 – 3/8	751506RHSS	560,52
	G 1/2 – 3/4 HSS ¹⁾	751507RHSS	560,52
	G 1 1/2 – 2 HSS ¹⁾	751508RHSS	560,52
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1. 20.1	NPT 1/16 – 1/8	751544RWS	373,68
	NPT 1/4 – 3/8 HSS ¹⁾	751545RHSS	560,52
	NPT 1/2 – 3/4 HSS ¹⁾	751546RHSS	560,52
	NPT 1 – 2 HSS ¹⁾	751547RHSS	560,52
Pipe threads NPSM parallel, right-hand Straight Pipe Thread ASME B1. 20.1	NPSM 1/16 – 1/8	751549RWS	373,68
	NPSM 1/4 – 3/8	751550RWS	373,68
	NPSM 1/2 – 3/4 HSS ¹⁾	751551RHSS	560,52
	NPSM 1 – 2	751552RWS	373,68
Conduit threads Pg DIN 40430	Pg 7	751509RWS	373,68
	Pg 9 – 16	751510RWS	373,68
	Pg 21 – 48	751511RWS	373,68
Conduit threads M EN 60423	M 16 – 63 × 1.5 (M 10)	751518RWS	373,68
	M 14 – 16 HSS	751520RHSSZ	560,52
Threads M for rebar ISO 261 (DIN 13)	M 18 – 22 HSS	751521RHSSZ	560,52
	M 24 – 27 HSS	751522RHSSZ	560,52
	M 30 – 33 HSS	751523RHSSZ	560,52
	M 36 – 39 HSS	751524RHSSZ	669,51
	M 42 – 45 HSS	751525RHSSZ	669,51
Metric bolt threads M ISO 261 (DIN 13)	M 6	751516RHSS	560,52
	M 8	751517RWS	373,68
	M 10 (M 16 – 63 × 1.5)	751518RWS	373,68
	M 12	751519RWS	373,68
	M 14 – 16	751520RWS	373,68
	M 18 – 22	751521RWS	373,68
	M 24 – 27	751522RWS	373,68
	M 30 – 33	751523RWS	373,68
	M 36 – 39	751524RWS	446,34
	M 42 – 45	751525RWS	446,34
Bolt threads UNC Unified Inch Screw Thread ASME B1.1	M 48 – 52	751526RWS	446,34
	M 56 – 60	751527RWS	446,34
	M 64 – 72	751528RWS	446,34
	UNC 1/4 – 20	751557RWS	373,68
	UNC 5/16 – 18	751558RWS	373,68
	UNC 3/8 – 16	751559RWS	373,68
	UNC 7/16 – 14	751560RWS	373,68
	UNC 1/2 – 13	751561RWS	373,68
	UNC 5/16 – 12	751562RWS	373,68
	UNC 7/8 – 11	751563RWS	373,68
Chaser dies for other threads (e.g. bicycle threads, fine threads, BSW) and HSS chaser dies for materials above 500 N/mm ² (MPa) that are difficult to cut on request. HSS chaser dies with 50% surcharge. ¹⁾ Some chasers only available in HSS. Chasers for left-hand threads 50% extra charge.	UNC 3/4 – 10	751564RWS	373,68
	UNC 7/8 – 9	751565RWS	373,68
	UNC 1 – 8 HSS ¹⁾	751566RHSSZ	560,52
	UNC 1 1/8 – 1 1/4 – 7	751567RWS	373,68
	UNC 1 3/8 – 1 1/2 – 6	751568RWS	446,34
	UNC 1 1/4 – 5	751569RWS	446,34
	UNC 2 – 2 1/4 – 4,5	751570RWS	446,34
	UNC 2 1/2 – 2 3/4 – 4	751571RWS	446,34

Dies for other threads (e.g. bicycle threads, fine threads, BSW) and HSS chaser dies for materials above 500 N/mm² (MPa) that are difficult to cut on request. HSS chaser dies with 50% surcharge. ¹⁾Some chasers only available in HSS. Chasers for left-hand threads 50% extra charge.

Thread tables

Taper Pipe Threads

Whitworth Pipe Thread ISO 7-1, EN 10226 (DIN 2999, BSPT) External thread taper 1:16 Flank angle 55°		
Nominal Size R BSPT	Outside Ø of thread mm	T.P.I.
1/16	7.723	28
1/8	9.728	28
1/4	13.157	19
3/8	16.662	19
1/2	20.955	14
5/8	26.441	14
1	33.249	11
1 1/4	41.910	11
1 1/2	47.803	11
2	59.614	11
2 1/2	75.184	11
3	87.884	11
4	113.030	11

Standard Taper Pipe Thread NPT, ASME B 1.20.1 External thread taper 1:16 Flank angle 60°		
Nominal Size NPT	Outside Ø of thread mm	T.P.I.
1/16	7.938	27
1/8	10.287	27
1/4	13.716	18
3/8	17.145	18
1/2	21.336	14
5/8	26.670	14
1	33.401	11.5
1 1/4	42.164	11.5
1 1/2	48.260	11.5
2	60.325	11.5
2 1/2	73.025	8
3	88.900	8
3 1/2	101.600	8
4	114.300	8

Whitworth Pipe Thread ISO 228-1 (DIN 259, BSPP) External thread parallel Flank angle 55°		
Nominal Size G BSPP	Outside Ø of thread mm	T.P.I.
1/16	7.723	28
1/8	9.728	28
1/4	13.157	19
3/8	16.662	19
1/2	20.955	14
5/8	26.441	14
1	33.249	11
1 1/4	41.910	11
1 1/2	47.803	11
2	59.614	11
2 1/2	75.184	11
3	87.884	11
3 1/2	100.330	11
4	113.030	11

Parallel Pipe Threads

Straight Pipe Thread for Fixtures NPSM, ASME B 1.20.1 External thread parallel Flank angle 60°		
Nominal Size NPSM	Outside Ø of thread mm	T.P.I.
1/8	10.083	27
1/4	13.360	18
3/8	16.815	18
1/2	20.904	14
5/8	26.264	14
1	32.842	11.5
1 1/4	41.605	11.5
1 1/2	47.676	11.5
2	59.715	11.5
2 1/2	72.161	8
3	88.062	8
3 1/2	100.787	8
4	113.436	8

Metric Bolt Thread

Metric ISO Thread ISO 261 (DIN 13) External thread Flank angle 60°		
Nominal Size M	Outside Ø of thread mm	Pitch mm
6	5.974	1
8	7.972	1.25
10	9.968	1.5
12	11.966	1.75
14	13.962	2
16	15.962	2
18	17.958	2.5
20	19.958	2.5
22	21.958	2.5
24	23.952	3
27	26.952	3
30	29.947	3.5
33	32.947	3.5
36	35.940	4
39	38.940	4
42	41.937	4.5
45	44.937	4.5
48	47.929	5
52	51.929	5
56	55.925	5.5
60	59.925	5.5
64	63.920	6
68	67.920	6
72	71.920	6

American and British Bolt Threads

Unified Inch Screw Thread UNC, ASME B 1.1 External thread Flank angle 60°		
Nominal Size UNC	Outside Ø of thread mm	T.P.I.
1/4	6.322	20
5/16	7.907	18
3/8	9.491	16
7/16	11.076	14
1/2	12.661	13
9/16	14.246	12
5/8	15.834	11
3/4	19.004	10
7/8	22.176	9
1	25.349	8
1 1/8	28.519	7
1 1/4	31.694	7
1 3/8	34.864	6
1 1/2	38.039	6
1 5/8	44.381	5
2	50.726	4.5
2 1/4	57.076	4.5
2 1/2	63.421	4
2 3/4	69.768	4

British Standard Parallel Screw Thread of Whitworth Form B.S.W. BS 84 (obsolete): External thread Flank angle 55°		
Nominal Size BSW	Outside Ø of thread mm	T.P.I.
1/4	6.350	20
5/16	7.937	18
3/8	9.525	16
7/16	11.112	14
1/2	12.700	12
5/8	15.875	11
3/4	19.050	10
7/8	22.225	9
1	25.400	8
1 1/8	28.575	7
1 1/4	31.750	7
1 3/8	38.100	6
1 1/2	44.450	5

Threads for Electric Conduit

Conduit Thread DIN 40 430 External thread parallel Flank angle 80°		
Nominal Size Pg	Outside Ø of thread mm	T.P.I.
7	12.5	20
9	15.2	18
11	18.6	18
13.5	20.4	18
16	22.5	18
21	28.3	16
29	37	16
36	47	16
42	54	16
48	59.3	16

Conduit Thread EN 60423 External thread parallel Flank angle 60°		
Nominal Size M	Outside Ø of thread mm	Pitch mm
16	15.968	1.5
20	19.968	1.5
25	24.968	1.5
32	31.968	1.5
40	39.968	1.5
50	49.968	1.5
63	62.968	1.5

Outside diameter of thread is always the maximum diameter, for taper pipe threads this is measured at the scale line.

REMS Nippelspanner

Manual pipe nipple chuck for internal clamping of short pipe pieces. For universal use.

Nipples and double nipples in standard and special lengths $\frac{3}{8}$ – 2"

REMS Nippelspanner – efficient nipple-threading. Any length. Anywhere.

To be used universally for threading machines and for hand die stocks of all types and makes. For opening and non-opening die heads. Ideal accessory for REMS Amigo E, REMS Amigo, REMS Amigo 2, REMS Amigo 2 Compact, REMS Amigo 22V, REMS eva and other makes.

Ideal tool for using up short pipe pieces. Saves time and money.

Chucking and centering of pipe pieces by expanding of specially hardened spring steel segments.

Internal clamping, so no thread required for clamping.

Supply format

REMS Nippelspanner. Manual pipe nipple chuck for internal clamping of short pipe pieces.

Description	Size	Art.-No.	€
REMS Nippelspanner	$\frac{3}{8}$ "	11000R	126,64
	$\frac{1}{2}$ "	11010R	146,36
	$\frac{3}{4}$ "	11020R	167,12
	1"	11030R	229,40
	$1\frac{1}{4}$ "	11040R	271,96
	$1\frac{1}{2}$ "	11050R	323,86
	2"	11060R	396,52

Supply format

REMS Nippelspanner Set. Manual pipe nipple chuck for internal clamping of short pieces of pipe. In sturdy steel case.

Description	Art.-No.	€
Set $\frac{1}{2} + \frac{3}{4} + 1 + 1\frac{1}{4}$"	110620R	761,89
Set $\frac{1}{2} + \frac{3}{4} + 1 + 1\frac{1}{4} + 1\frac{1}{2} + 2"$	110621R	1 375,35

REMS Nippelfix

Automatic pipe nipple chuck for internal clamping of short pipe pieces.

Nipples and double nipples in standard and special lengths $\frac{1}{2}$ – 4"

REMS Nippelfix – efficient nipple-threading up to 4". Any length. Anywhere. Automatic internal clamping. Super fast and simple.

For threading machines with opening die head: Pipe turning machines, machines with rotating die head, threading devices.

Ideal tool for using up short pipe pieces. Saves time and money.

Automatic quick-chuck and centering of pipe piece. No tools.

Automatic release after completion of nipple. Production of nipples possible without taking the Nippelfix out of the clamping device.

Internal clamping, so no thread required for clamping.

Specially hardened and ground clamping jaws for fast and safe clamping.

Supply format

REMS Nippelfix. Automatic pipe nipple chuck for internal clamping of short pipe pieces.

Description	Size	Art.-No.	€
REMS Nippelfix	$\frac{1}{2}$ "	11100R	106,91
	$\frac{3}{4}$ "	11110R	127,67
	1"	11120R	165,04
	$1\frac{1}{4}$ "	11130R	200,33
	$1\frac{1}{2}$ "	11140R	231,47
	2"	11150R	270,92
	$2\frac{1}{2}$ "	11170R	373,68
	3"	11180R	482,67
	4"	11190R	517,96

Supply format

REMS Nippelfix Set. Automatic pipe nipple chuck for internal clamping of short pieces of pipe. In sturdy steel case.

Description	Art.-No.	€
Set $\frac{1}{2} + \frac{3}{4} + 1 + 1\frac{1}{4}$"	111620R	666,40
Set $\frac{1}{2} + \frac{3}{4} + 1 + 1\frac{1}{4} + 1\frac{1}{2} + 2"$	111621R	1 094,05

Accessories for threading machines and hand die stocks of all types and makes



German Quality Product



Accessories for threading machines with opening die head



German Quality Product



REMS Spezial

Thread-cutting oil

High-alloyed mineral oil based thread-cutting oil.
For all materials.

For drinking water supplies, comply with local regulations! Mineral oil based thread cutting materials are not permitted for drinking water pipes in AUT, CHE, DEU, DNK and FRA for example.

REMS Spezial – high-alloyed mineral based thread-cutting oil, can be washed out with water. High lubricating and cooling effect.

Specially developed for threading. High lubricating and cooling effect. Essential for clean threads, long service life of dies, tools and machines.

Can be washed out with water, approved by experts.

Also well suited as a cooling lubricant for sawing metals.

REMS Spezial spray without CFC's, so ozone-harmless.

REMS Spezial squirt bottle without propellants. Refillable.



German Quality Product

Supply format

REMS Spezial. High-alloyed mineral based thread-cutting oil.

Description	Packing	Art.-No.	€
REMS Spezial	5l can	140100R	74,74
	10l can	140101R	149,47
	50l barrel	140103R	724,52
	600ml spray	140105R	23,36
	500ml squirt bottle	140106R	25,74

REMS Sanitol

Thread-cutting oil

Synthetic, mineral oil-free thread-cutting oil.
Specially for drinking water supplies. For all materials.

REMS Sanitol – mineral oil-free, ethanol-free.

Completely water soluble.

High lubricating and cooling effect.

Developed especially for drinking water pipes but also excellently suitable for universal thread cutting. High lubricating and cooling effect. Essential for clean threads, long service life of dies, tools and machines.

Completely water soluble. Mineral oil-free, ethanol-free. Therefore no negative influence on the drinking water in terms of appearance, smell and taste.

Red in colour for flushing control. Perfect corrosion protector.

Viscosity at -10°C: ≤ 250 mPa s (cP). Pumpable to -28°C.

Also well suited as a cooling lubricant for sawing metals.

REMS Sanitol spray without CFC's, so ozone-harmless.

REMS Sanitol squirt bottle without propellants. Refillable.



German Quality Product

Supply format

REMS Sanitol. Synthetic, mineral oil free thread-cutting oil specially for drinking water supplies and for universal use.

Description	Packing	Art.-No.	€
REMS Sanitol	5l can	140110R	174,38
	50l barrel	140113R	1 656,65
	600ml spray	140115R	33,94
	500ml squirt bottle	140116R	37,37



W1.303



7808-649

REMS roll grooving attachment

Roll grooving attachment

Robust, compact roll grooving attachment with oil hydraulic forward feed for grooving pipes of pipe coupling systems. For installation, sprinkler lines, commercial heating, industry and mining.

For job site and workshop.

Steel pipes	DN 25 – 300 1 – 12" $s \leq 7.2 \text{ mm}$
-------------	---

Stainless steel pipes, copper, aluminium, PVC pipes

REMS roll grooving attachment – compact – universal. Oil hydraulic pressure cylinder for powerful in-feed of pressure roller.

Design

Compact, job site-proven. Robust metal housing for tough use. Handy, easy to transport, only 26 kg. Oil hydraulic pressure cylinder for powerful in-feed of pressure roller. Pressure build-up with hydraulic hand pump. Individually adjustable groove-depth-stop with fine adjustment, for automatic limitation of groove depth. Built-in ring gauge for automatic groove-depth-stop.

Grooving rollers

The proven REMS grooving rollers with perfectly size-adjusted pressure rollers and counterpressure rollers with well gripping axial knurls guarantee a secure rotation of the pipe and precise grooving. Grooving rollers machined from hardened special steel ensure extremely long service life. 3 pairs of groove rollers (pressure roller, counter-pressure roller) for the whole working range DN 25–300, 1–12", easy change. Grooving rollers Cu (pressure roller, counterpressure roller) for copper pipe 54–159 mm. Groove rollers INOX (pressure roller made of stainless steel, counter-pressure roller made of toughened, specially hardened steel, nickel-plated) for stainless steel pipes 1–1½", 2–6" and 8–12". Grooving rollers for aluminium, PVC pipes on request.

Drive

Only one roll grooving device for REMS Amigo, REMS Amigo 2, REMS Amigo 2 Compact, REMS Tornado and REMS Magnum. Fast, simple assembly. 3-face drive shaft of roll grooving attachment for secure clamping and optimum power transmission. Roll grooving attachments for threading machines of other makes, adjusted to support arm distance, diameter of support arm and spindle axis of the corresponding drive machine, on request.

Supply format

REMS roll grooving attachment. Roll grooving attachment for grooving pipes of pipe coupling systems DN 25–300, 1–12". Roll grooving attachment, hydraulic hand pump, built-in ring gauge for automatic groove-depth-stop, 1 pair of groove rollers (pressure roller, counter-pressure roller) 2–6", Allen key. For REMS Amigo, REMS Amigo 2, REMS Amigo 2 Compact, REMS Tornado and REMS Magnum or for other thread cutting machine makes. In a carton.

Description	fit onto	Art.-No.	€
REMS roll grooving attachment	REMS Amigo/ Amigo 2 Compact ¹⁾ REMS Amigo 2 ¹⁾ REMS Tornado ²⁾ REMS Magnum ²⁾	347000R	2 242,08
Roll grooving attachment R 300	Ridgid 300	347001R	2 242,08

¹⁾ Conversion kit Amigo/Amigo 2/Amigo 2 Compact (Art. No. 347007) required.

Can be used for roll grooving devices manufactured from 2014 onwards.

²⁾ Can only be used for roll grooving up to DN 200, 8" on T versions.

Roll grooving attachments for other makes on request.

Accessories

Description	Art.-No.	€
Grooving rollers 1–1½" (pair), for steel pipes	347030	310,36
Grooving rollers INOX 1–1½" (pair), for stainless steel pipes	347053	747,36
Grooving rollers 2–6" (pair), for steel pipes	347035	310,36
Grooving rollers INOX 2–6" (pair), for stainless steel pipes	347046	840,78
Grooving rollers 8–12" (set), for steel pipes	347040	507,58
Grooving rollers INOX 8–12" (pair), for stainless steel pipes	347047	851,16
Grooving rollers Cu 54–159 (pair) for Cu pipes	347034	310,36
Conversion kit Amigo / Amigo 2 / Amigo 2 Compact / Amigo 22V	347007R	153,62

REMS Herkules material supports, see page 107.



German Quality Product



Info



Powerful roll grooving machine for fast, economical grooving of pipes for pipe coupling systems. For installation, sprinkler lines, commercial heating, industry and mining. For job site and workshop.

Steel pipes	DN 25 – 300 1 – 12" $s \leq 7.2 \text{ mm}$
-------------	---

Stainless steel pipes, copper, aluminium, PVC pipes

REMS Collum – electrical roll grooving up to 12".

Fast and economical feed of the pressure roller with oil-hydraulic pressure cylinder.

Design

Robust, compact construction suitable for building sites. Favourable dimensions, favourable weight, roll grooving device with drive machine only 31 kg. For work bench. Stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning.

Drive

Fast and powerful, e.g. roll grooving of 6" steel pipe with REMS Collum in just 52 s. Sturdy, compact gear, maintenance-free. Robust, powerful 1200 W universal motor (REMS Collum and REMS Collum 2 Compact) or 1700 W universal motor (REMS Collum 2) for intensive use at large dimensions. Safety switch. Foot switch with coupling for ergonomic working as an accessory.

Roll grooving attachment

Compact, job site-proven. Robust metal housing for tough use. Handy, easy to transport, only 26 kg. Oil hydraulic pressure cylinder for powerful in-feed of pressure roller. Pressure build-up with hydraulic hand pump. Built-in ring gauge for automatic groove-depth-stop.

Grooving rollers

The proven REMS grooving rollers with perfectly size-adjusted pressure rollers and counterpressure rollers with well gripping axial knurls guarantee a secure rotation of the pipe and precise grooving. Grooving rollers machined from hardened special steel ensure extremely long service life. 3 pairs of groove rollers (pressure roller, counter-pressure roller) for the whole working range DN 25–300, 1–12", easy change. Grooving rollers Cu (pressure roller, counterpressure roller) for copper pipe 54–159 mm. Groove rollers INOX (pressure roller made of stainless steel, counter-pressure roller made of toughened, specially hardened steel, nickel-plated) for stainless steel pipes 1–1½", 2–6" and 8–12". Grooving rollers for aluminium, PVC pipes on request.

Material support


Extra sturdy REMS Herkules XL 12" material support for roll grooving of pipes up to 12" (page 107).



German Quality Product



Info



Wheel stand (Accessory)

Herkules 3B (Accessory)

Supply format

REMS Collum. Roll grooving attachment for grooving pipes of pipe coupling systems DN 25–300, 1–12". Roll grooving attachment, hydraulic hand pump, built-in ring gauge for automatic groove-depth-stop, 1 pair of groove rollers (pressure roller, counter-pressure roller) 2–6", Allen key. Choice of 3 drive units, with maintenance-free gear, powerful universal motor, safety switch. For workbench, stand or wheel stand. In a carton.

Description	Version	Art.-No.	€
Collum	Universal motor 230 V, 50–60 Hz, 1200 W, overload protection. 29 min ⁻¹	347006R220	2 761,08
Collum 2	Universal motor 230 V, 50–60 Hz, 1700 W. 28 min ⁻¹	347008R220	3 093,24
Collum 2 Compact	Universal motor 230 V, 50–60 Hz, 1200 W, overload protection. 26 min ⁻¹	347009R220	3 093,24

Other voltages on request.

Accessories

Description	Art.-No.	€
Stand	849315R	216,94
Wheel stand	849310R	351,88
Foot switch with coupling	347010R220	249,12

REMS Herkules material supports, see page 107.

Grooving rollers and other accessories, see page 48.



REMS Collum 22 V

Cordless roll grooving machine

Powerful, mobile, cordless roll grooving machine for fast, economical grooving of pipes for pipe coupling systems. For installation, sprinkler lines, commercial heating, industry and mining. For job site and workshop. Li-Ion 22 V Technology. For battery and corded operation.

Steel pipes	DN 25–300
	1–12"
	s ≤ 7.2 mm

Stainless steel pipes, copper, aluminium, PVC pipes

**REMS Collum 22 V – electrical roll grooving up to 12".
Mobile, fast, economical. Feed of the pressure roller
with oil-hydraulic pressure cylinder. Li-Ion 21.6 V, 9.0 Ah
battery, for approx. 23 DN 100/4" grooves with one
battery charge*.**

Design

Compact, robust, building site-compatible, mobile. Convenient dimensions, comfortable weight, cordless roll grooving machine with drive unit just 34 kg. Practical D-shaped handle with soft grip. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check by a 2-coloured green/red LED. For work bench. Stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning.

Drive

Powerful and fast, e.g. roll grooving of 4" steel pipe in just 77 s. Solid, maintenance-free gear. Powerful battery motor 21.6 V, with high power reserve, 500 W output, for intensive use with large dimensions. High grooving speed 27–20 rpm. Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V batteries with 9.0 Ah capacity for long service life. Light and powerful, for approx. 23 DN 100/4" grooves with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range -10 to +60 °C. No memory effect for maximum battery power. Rapid charger 100–240 V, 90 W. Rapid charger 100–240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220–240 V/21.6 V, 40 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Roll grooving attachment

Compact, job site-proven. Robust metal housing for tough use. Handy, easy to transport, only 26 kg. Oil hydraulic pressure cylinder for powerful in-feed of pressure roller. Pressure build-up with hydraulic hand pump. Built-in ring gauge for automatic groove-depth-stop.

Grooving rollers

The proven REMS grooving rollers with perfectly size-adjusted pressure rollers and counterpressure rollers with well gripping axial knurls guarantee a secure rotation of the pipe and precise grooving. Grooving rollers machined from hardened special steel ensure extremely long service life. 3 pairs of groove rollers (pressure roller, counter-pressure roller) for the whole working range DN 25–300, 1–12", easy change. Grooving rollers Cu (pressure roller, counterpressure roller) for copper pipe 54–159 mm. Groove rollers INOX (pressure roller made of stainless steel, counter-pressure roller made of toughened, specially hardened steel, nickel-plated) for stainless steel pipes 1–1½", 2–6" and 8–12". Grooving rollers for aluminium, PVC pipes on request.

Material support

Extra sturdy REMS Herkules XL 12" material support for roll grooving of pipes up to 12" (page 107).



German Quality Product



Info



REMS Collum 22V

Cordless roll grooving machine



Wheel stand (Accessory)

Herkules 3B (Accessory)



Stand (Accessory)

Herkules XL 12" (Accessory)

Supply format

REMS Collum 22V. Cordless roll grooving machine for grooving pipes for DN 25–300, 1–12" pipe coupling systems. Roll grooving attachment, hydraulic hand pump, built-in ring gauge for automatic groove-depth-stop, 1 pair of groove rollers (pressure roller, counter-pressure roller) 2–6", Allen key. Drive unit with maintenance-free gear, powerful battery motor 21.6V, 500 W. Safety switch. Right and left-hand rotation, machine status check with overload protection, temperature monitoring, battery charging status check. Universal support. Li-Ion 21.6 V, 9.0 Ah battery, 100–240V, 50–60 Hz, 90W rapid charger. For workbench, stand or wheel stand. In a carton.

	Art.-No.	€
	347005R220	3 736,80

Other voltages on request.



Accessories

Description	Art.-No.	€
REMS Amigo 22 V drive unit, without battery	530004R22	1 162,56
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 40 A, for mains operation instead of battery Li-Ion 21.6V	571578R220	517,96
Stand	849315R	216,94
Wheel stand	849310R	351,88
REMS Herkules material supports, see page 107.		
Grooving rollers and other accessories, see page 48.		
REMS Lumen 2800 22V , cordless LED flood light, see page 111		



REMS Magnum RG

Roll grooving machine

Robust, compact high performance machine with roll grooving attachment for pipe grooving of pipe coupling systems. For installation, sprinkler lines, commercial heating lines, industry and mining.

For job site and workshop.

Steel pipes	DN 25 – 300 1 – 12" $s \leq 7.2 \text{ mm}$
-------------	---

Stainless steel pipes, copper, aluminium,
PVC pipes

Pipe threads $\frac{1}{16}$ – 2", 16 – 63 mm, bolt threads
6 – 60 mm, $\frac{1}{4}$ – 2", with conversion kit.

REMS Magnum RG – the compact up to 12".

Immensely powerful and extremely fast. Feed of the pressure roller with oil-hydraulic pressure cylinder.

Design

Robust, compact, job site-proven design. Favorable size and weight, e.g. REMS Magnum 2000 RG-T only 68 kg. Tool support. For workbench. Stand, collapsible wheel stand or wheel stand with material shelf, as an accessory, for easy transport, optimum working height and stable positioning.

Drive

Immensely powerful and fast, e.g. roll grooving of 6" steel pipe with REMS Magnum 2010 RG-T in just 40 s. Completely maintenance-free gear which runs in a sealed oil bath. Choice of 3 powerful motors (see REMS Magnum page 34). Operator-friendly safety foot switch with emergency-stop, 2-step, can be loaded with the full body weight during operation.

Roll grooving attachment

Compact, job site-proven. Robust metal housing for tough use. Handy, easy to transport, only 26 kg. Oil hydraulic pressure cylinder for powerful in-feed of pressure roller. Pressure build-up with hydraulic hand pump. Built-in ring gauge for automatic groove-depth-stop.

Grooving rollers

The proven REMS grooving rollers with perfectly size-adjusted pressure rollers and counterpressure rollers with well gripping axial knurls guarantee a secure rotation of the pipe and precise grooving. Grooving rollers machined from hardened special steel ensure extremely long service life. 3 pairs of groove rollers (pressure roller, counter-pressure roller) for the whole working range DN 25 – 300, 1 – 12", easy change. Grooving rollers Cu (pressure roller, counterpressure roller) for copper pipe 54 – 159 mm. Groove rollers INOX (pressure roller made of stainless steel, counter-pressure roller made of toughened, specially hardened steel, nickel-plated) for stainless steel pipes 1 – 1½", 2 – 6" and 8 – 12". Grooving rollers for aluminium, PVC pipes on request.

Conversion kit for threading

Tool set $\frac{1}{4}$ – 2" complete with universal automatic die head, dies for pipe threads, tapered, ISO 7-1 (DIN 2999, BSPT) R $\frac{1}{2}$ – $\frac{3}{4}$ and R 1 – 2" right-hand, pipe cutter, inner pipe deburrer, pressing lever, pump for automatic oiling, oil basin, chip tray.

Material support


Extra sturdy REMS Herkules XL 12" material support for roll grooving of pipes up to 12" (page 107).



German Quality Product



Info



Stand
(Accessory)



Wheel stand (Accessory)

Herkules 3B
(Accessory)



Collapsible wheel stand
(Accessory)

Supply format

REMS Magnum RG. Roll grooving machine for pipe grooving of pipe coupling systems DN 25–300, 1–12". With maintenance-free gear, safety foot switch with emergency-stop, self-tightening quick-action hammer chuck, rear centering device, automatic lubrication and cooling, tool support. Choice of 3 motors. Roll grooving attachment, hydraulic hand pump, built-in ring gauge with automatic groove-depth-stop, 1 set of grooving rollers (pressure roller, counterpressure roller) 2–6", hexagon key. For workbench, stand, collapsible wheel stand or wheel stand with material shelf. In a carton.

Description	Version	Art.-No.	€
2000 RG-T	Universal motor 230 V or 110 V, 50–60 Hz, 1700 W, 53 rpm.	340230R220	5 646,72
2010 RG-T	Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W, 52/26 rpm, also under full load. Extremely quiet running.	340231R220	5 999,64
2020 RG-T	Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W, 52/26 rpm, also under full load. Extremely quiet running.	340232R380	6 279,90

Other voltages on request.

Accessories


Description	Art.-No.	€
Stand	344105R	290,64
Wheel stand with material support	344100R	493,05
Collapsible wheel stand	344150R	705,84

REMS Herkules material supports, see page 107.

Grooving rollers and other accessories, see page 48.

Conversion kit Magnum RG-T to L-T for threading.	340110RR	1 453,20
--	----------	-----------------





Sawing

	Universal electric reciprocating saws	58
	Cordless universal reciprocating saw	60
	Electric reciprocating pipe saws	62
	Pneumatic reciprocating pipe saw	64
	Cordless pipe reciprocating saw	66
	Saw blades for reciprocating saws	68
	Circular pipe sawing machine	70
	Universal circular metal sawing machine	71

REMS reciprocating saws


Legend



Aggressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades.

Fixed orbital action, running in needle


bearings, ensures long-lasting and forceful sawing also during extreme load conditions, e.g. sawing of steel pipe. Adjustable mechanisms with a great variety of parts and a reduced system stability do not withstand the high in-feed pressure and the heavy-duty requirements of forceful cutting of steel pipes, particularly when a guide support with leverage is being used.




Sturdy, square lift rod in special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use and by applying multiple sawing force, e.g. using a guide support with leverage. For extremely long service life.



ANC



Super stable, water and dust resistant, maintenance-free oscillating gear enables a simultaneous generation of saw and orbital stroke of lift rod and saw blade. Allround needle bearing mounted crank drive (**ANC**) reduces friction, heat generation, wear. Thus long service life also at extreme sawing.



Universal saw blade clamp for mounting all saw blades – with universal or double tang – without changing or turning the saw blade thrust piece.



Guide support for 400 % additional sawing force for fast, effortless sawing. Also for effortless demolition work.



V/bar
Drive motors
230 V, 110 V, 48 V,
22 V, 6 bar

Ergonomically shaped front housing grip with slip resistant protection cover, for forceful feed forward while sawing free-hand.

REMS reciprocating saws

Legend



Vario-Electronic

Electronic stepless speed control of drive unit for sensitive start-sawing and for stroke selection during sawing according to the material. The stroke speed is controlled continuously by variable pressure on the touch switch from 0 to 2,800 rpm (REMS Puma VE), 0 to 2,400 rpm (REMS Cat VE, REMS Tiger VE) or 0 to 1,900 rpm (REMS Cat 22V VE, REMS Tiger 22V VE) (accelerator switch).



Ideal speed

Deliberately fixed speed. Therefore optimum cutting speed for maximum protection of motor and gear and maximum service life of saw blades. The ideal cutting speed of 2,400 rpm has been determined by extensive sawing tests with steel pipe which lead to optimum performance in combination with the aggressive, fixed orbital action, guide support and REMS special saw blade.



Power-transferring guide support

400 % more sawing power for effortless, ultra-fast sawing of pipes and profiles, e.g., 2" steel pipe in just 8 s. For assembly and disassembly. Guide support with 5-fold power-transferring leverage allows effortless, fast, right-angled sawing everywhere on site, also free-hand without a pipe vice. Ideal handling, very quick and easy operation, only one handle for clamping and sawing. No free-swinging chain. No danger of jamming by limitation of swing angle. Straight machine handle for optimum forward feed.



Power-transferring chain guide support 6"

400 % more sawing power for effortless, ultra-fast sawing of Ø 1/8 – 6" pipes and other profiles, e.g., 2" steel pipe in just 8 s. For assembly and disassembly. Guide support with 5-fold power-transferring leverage allows effortless, fast, right-angled sawing everywhere on site, even in very confined spaces. Clamping chain with strong chain links, easy clamping by quick closure and threaded spindle. Straight machine handle for optimum forward feed.



Speed-Regulation

Stepless electronic speed control of drive unit for selecting the speed according to the material. Ideal for sawing stainless steel pipe, cast pipe and for sawing boilers, tanks, bath tubs etc. The speed is continuously adjustable between 700 and 2,200 rpm on the dial. The electronic speed control which is being used keeps the selected speed constant, also under load, including speed generator, control electronics, residual current limitation for sensitive start-sawing, motor temperature control of field wires with PTC resistance (Positive Temperature Coefficient) and stall protection of gear and motor.



Weight

High sawing efficiency at low weight by innovative, proven technology and perfect tuning of all components. For effortless, fatigue-free sawing and easy handling.



Power

All power data stated to be understood as the rated power input. The drive motors of REMS reciprocating saws have a very high efficiency of approx. 65% thanks to an outstanding technology and quality. Therefore the user has a high power output available which is useful particularly for sawing difficult-to-cut materials, e.g. steel pipe. High power output can only be used fully by levered sawing, e.g. with the REMS guide support.



Drive Motors

Depending on model universal motors of voltages of 230 V, 110 V, 48 V, battery motors 22 V or pneumatic motors for 6 bar operating pressures are used. All drive motors are extremely powerful, fulfill highest quality demands and come with large power reserves, for long service life.



Saw blade holder with quick-change system

Practical saw blade holder with quick-change system for fast saw blade changing without tools. For holding single tang saw blades.



Continuously adjustable support shoe

Swivel support shoe for safe guiding of the saw on the material to be sawn. Support shoe continuously adjustable in longitudinal direction by 40 mm for better utilisation of partially blunted saw blades and for setting the plunge-in depth of the saw blade in the material.



Anti-vibration system

Special drive technology with mass compensation and vibration damping handles. For low vibration, effortless sawing.



Saw blade can be inserted turned 180°.

Saw blade can be inserted with the teeth facing down or turned 180° facing up for cuts in confined spaces with difficult access.

REMS Puma VE

Universal electric reciprocating saw

Powerful power tool for universal free-hand sawing. Only 3.8 kg. Ideal for assembly, disassembly, repair.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

REMS Puma VE – the powerful universal saw with anti-vibration system. Quick saw blade change without tools. Adjustable support shoe.

Universal use

Can be used anywhere, free hand, over head, in tight corners, flush with the wall. Extremely versatile and powerful. For all sawing work on the building site and for rescue and emergency operations. Also for plunge-cut sawing.

Design

Powerful, suitable for building sites. Handy, easy grip shape. Only 3.8 kg. Ergonomically designed front housing grip with non-slip, heat insulating protective jacket with soft grip, for powerful sawing thrust. Practical D-shaped handle with vibration damping soft grip. Drive rod runs in an enclosed drive housing for safe work. Large saw blade stroke, 30 mm, for better cut clearance. Fast stroke speed up to 2,800 rpm for fast sawing thrust and effective sawing. Robust crank drive, maintenance-free. High sliding special seal. Powerful, high capacity universal motor with large power reserve, 1,300 W, safety switch. 4 m long connecting lead. Safety switch.

Anti-vibration system

Special drive technology with mass compensation and vibration damping handles. For low vibration, effortless sawing.

Vario-Electronic

Continuous electronic stroke speed control for gentle start of sawing and selection of a stroke speed suitable for the material. The stroke speed can be continuously controlled by variable pressure on the safety switch from 0 to 2,800 rpm (accelerator switch).

Saw blade holder with quick-change system


Practical saw blade holder with quick-change system for fast saw blade changing without tools. For holding single tang saw blades. Saw blade can be inserted with the teeth facing down or turned 180° facing up for cuts in confined spaces with difficult access.

REMS saw blades

Full range of REMS saw blades for free-hand sawing of different materials (page 69).

Continuously adjustable support shoe

Swivel support shoe for safe guiding of the saw on the material to be sawn. Support shoe continuously adjustable in longitudinal direction by 40 mm for better utilisation of partially blunted saw blades and for setting the plunge-in depth of the saw blade in the material. For economical working.



Supply format

REMS Puma VE Set. Electric universal reciprocating saw with Vario-Electronic (VE) for free-hand sawing, with anti-vibration system. Drive machine with D-shaped handle with soft grip, maintenance-free crank drive, powerful 230 V, 50–60 Hz, 1,300 W universal motor, safety switch, connecting cable 4 m. Continuous electronic stroke speed control (accelerator switch) 0 to 2,800 rpm. 30 mm stroke. Saw blade holder with quick-change system Adjustable support shoe. Hexagon key. 1 REMS saw blade 210-1.8/2.5. In sturdy steel case.

	Art.-No.	€
560023R220	369,53	


Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Puma VE drive unit	560003R220	331,12
REMS saw blades see page 69.		
Steel case	566051R	82,73



Info



REMS Cat VE

Universal electric reciprocating saw

Powerful, robust, handy power tool for universal free-hand sawing. Only 3.0 kg. Ideal for assembly, dismantling, repair.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

Especially also for steel pipes

REMS Cat VE – saws anything, anywhere.

Extremely versatile and powerful.

Robust and handy.

Universal use

Ready for use anywhere, free-hand, overhead, in confined areas, flush to wall. Extremely versatile and efficient. Especially also for sawing metal pipes, sawing up boilers, tanks, bath tubs. For rescue and emergency operations. Also for plunge-cut sawing.

Design

Robust, job site-proven. Slender, handy design. Super light, only 3.0 kg. Ergonomically shaped front housing grip with slip resistant, heat insulating protection cover with soft grip, for forceful feed forward. Proven D-shaped handle. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful universal motor with ample reserve capacity, 1050 W. Safety tip switch.

Sturdy, square lift rod

In special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use. For extremely long service life. Drive rod runs in an enclosed housing for safe work.

Oscillating drive with ANC

Super stable, water and dust resistant, maintenance-free oscillating drive for simultaneous generation of sawing stroke and orbital action of lift rod and saw blade. Allround needle bearing mounted crank drive (ANC) reduces friction, heat generation, wear. For long service life of drive also at extreme sawing.

Aggressive orbital action

Aggressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades. Fixed orbital action, running in needle bearings, ensures long-lasting and forceful sawing also during extreme load conditions, e.g. sawing of steel pipe.

Vario-Electronic

Electronic stepless speed control of drive unit for sensitive start sawing and for speed selection during sawing. The speed is controlled by pressing the tip switch steplessly from 0 to 2,400 rpm (acceleration switch).

Universal saw blade clamp

All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

REMS universal saw blade

Only 1 REMS universal saw blade (page 68) for all sawing work instead of many different saw blades. Double tang for free-hand sawing and sawing with guide holder.


REMS saw blades

Full range of REMS saw blades for free-hand sawing of different materials (page 69).



ANC

- reduced friction and wear
- substantially reduced heat generation
- for extremely long service life, also during tough use



German Quality Product



Info



Supply format

REMS Cat VE Set. Electric universal reciprocating saw with Vario-Electronic (VE) for free-hand sawing. Drive unit with D-shaped handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful universal motor 230 V or 110 V, 50–60 Hz, 1050 W, safety tip switch. Electronic stepless speed control (acceleration switch) 0 to 2,400 rpm. Universal saw blade clamp. Hexagon key. 1 REMS universal saw blade 150-1.8/2.5. In sturdy steel case.

	Art.-No.	€
	560040R220	580,24

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Cat VE drive unit	560004R220	580,24
REMS saw blades see page 68–69.		
Steel case	566005R	82,73

REMS



REMS Cat 22V VE

Cordless universal reciprocating saw

Powerful, mobile, handy power tool for universal free-hand sawing. Only 3.1 kg. Ideal for assembly, dismantling, repair. Li-Ion 22V Technology. For battery and corded operation.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

Especially also for steel pipes

REMS Cat 22V VE – saws anything, anywhere.

Mobile, handy, light. Li-Ion 21.6 V, 5.0 Ah battery, for approx. 75 1" steel pipe cuts with one battery charge*.

Universal use

Ready for use anywhere, free-hand, overhead, in confined areas, flush to wall. Mains independent. Extremely versatile and efficient, particularly for metal. Saws metal pipes, boilers, tanks, bath tubs, window frames, etc., for rescue and disaster service operations. Also for plunge-cut sawing.

Design

Robust, job site-proven. Mobile, handy, light. Drive unit with battery pack weighs only 3.1 kg. Slim form. Ergonomically shaped front housing grip with slip resistant, heat insulating protection cover with soft grip, for forceful feed forward. Practical D-shaped handle with soft grip. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful 21.6 V battery motor with ample reserve capacity, 500 W output. Safety tip switch. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check with charging level indication by a 2-coloured green/red LED.

Sturdy, square lift rod

In special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use. For extremely long service life.

Oscillating drive with ANC

Super stable, water and dust resistant, maintenance-free oscillating drive for simultaneous generation of sawing stroke and orbital action of lift rod and saw blade. Allround needle bearing mounted crank drive (ANC) reduces friction, heat generation, wear. For long service life of drive also at extreme sawing.

Vario-Electronic

Electronic stepless speed control of drive unit for sensitive start sawing and for speed selection during sawing. The speed is controlled by pressing the tip switch steplessly from 0 to 1,900 rpm (acceleration switch).

Aggressive orbital action

Aggressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades. Fixed orbital action, running in needle bearings, ensures long-lasting and forceful sawing also during extreme load conditions, e.g. sawing of steel pipe.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 4.4 Ah battery, for approx. 66 1" steel pipe cuts, 5.0 Ah battery, for approx. 75 1" steel pipe cuts, 9.0 Ah for approx. 140 1" steel pipe cuts with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6 V, 40 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Universal saw blade clamp

All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

REMS universal saw blade

Only 1 REMS universal saw blade (page 68) for all sawing work instead of many different saw blades. Double tang for free-hand sawing and sawing with guide holder.


REMS saw blades

Full range of REMS saw blades for free-hand sawing of different materials (page 69).



ANC

- reduced friction and wear
- substantially reduced heat generation
- for extremely long service life, also during tough use



German Quality Product



Info

Supply format

REMS Cat 22V VE Set. Battery driven universal reciprocating saw with Vario-Electronic (VE) for free-hand sawing. Drive unit with D-shaped handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful 21.6 V battery motor, safety tip switch. Electronic stepless speed control (acceleration switch) 0 to 1,900 rpm. Machine status check with overload protection, temperature monitoring, battery charging status check. Li-Ion 21.6 V, 5.0 Ah battery, 100–240V, 50–60 Hz, 90W rapid charger. Universal saw blade clamp. Hexagon key. 1 pcs REMS universal saw blade 150-1.8/2.5. In sturdy steel case.

	Art.-No.	€
	560052R220	1 230,03

Other voltages on request.



Accessories

Description	Art.-No.	€
REMS saw blades see page 68 – 69.		
REMS Cat 22V VE drive unit, without battery	560010R22	704,80
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 40A, for mains operation instead of battery Li-Ion 21.6 V	571578R220	517,96
Steel case with inlay	566030R	128,71
REMS Lumen 2800 22V , cordless LED flood light, see page 111		

Powerful, robust, handy power tool with force-transmitting guide holder for effortless, fast, right-angled sawing everywhere on site, without a vice. Also for universal free-hand sawing. Only 3.0 kg. Ideal for assembly, dismantling, repair.

Ideal for steel pipes and others.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

For materials that are difficult to cut, e.g. stainless steel pipes, hard cast iron, use the REMS Tiger SR with electronic stroke speed control.

REMS Tiger – the saw for the pipe fitter.

Saws effortless, fast, right angle.

Robust and handy.

Power-transferring guide support

400 % more sawing power for effortless, ultra-fast sawing of pipes and profiles, e.g., 2" steel pipe in just 8 s. For assembly and disassembly. Guide support with 5-fold power-transferring leverage allows effortless, fast, right-angled sawing everywhere on site, also free-hand without a pipe vice. Ideal handling, very quick and easy operation, only one handle for clamping and sawing. No free-swinging chain. No danger of jamming by limitation of swing angle. For optimum in-feed with guide support a straight machine handle is advantageous.

Power-transferring chain guide support 6"

400 % more sawing power for effortless, ultra-fast sawing of Ø ¼" - 6" pipes and other profiles, e.g., 2" steel pipe in just 8 s. For assembly and disassembly. Guide support with 5-fold power-transferring leverage allows effortless, fast, right-angled sawing everywhere on site, even in very confined spaces. Clamping chain with strong chain links, easy clamping by quick closure and threaded spindle. For optimum in-feed with guide support a straight machine handle is advantageous.

Right angle sawing

Right angle cut thanks to REMS guide support and REMS special saw blade. Essential for subsequent operations in pipe installation.

REMS special saw blade

REMS special saw blade (page 68), extra thick, rigid and unbendable, double tang, absolutely essential for right-angled sawing and fast disassembly of steel pipes with force-transmitting guide holder.

REMS universal saw blade

Only 1 REMS universal saw blade (page 68) for all sawing work instead of many different saw blades. Double tang for free-hand sawing and sawing with guide holder.

REMS saw blades

Full range of REMS saw blades for free-hand sawing of different materials (page 69).

Universal saw blade clamp

All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

Design

Robust, job site-proven. Slender, handy design. Super light, only 3.0 kg. Can be used anywhere. Ergonomically shaped front housing grip with slip resistant protection cover for forceful feed forward during free-hand sawing. Choice of practical D-shaped handle, advantageous during free-hand sawing, or straight machine handle, advantageous during sawing with guide support. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful universal motor with ample reserve capacity, 1050 W respectively 1400 W (REMS Tiger SR). Safety tip switch. Choice of drive unit with fixed, ideal speed, electronic speed control (Vario-Electronic) or electronic speed regulation. Overload protection (REMS Tiger) protects motor, gear and saw blade. The electronic tachometer speed controller (REMS Tiger SR) used for control keeps the preselected number of strokes constant even under load and includes tachogenerator, electronic control, start-up current limiter for soft start-up, overheating protection by temperature monitoring of the field winding of the motor with PTC resistance (Positive Temperature Coefficient) and blocking protection for gearbox and motor.

Sturdy, square lift rod

In special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use. For extremely long service life. Drive rod runs in an enclosed housing for safe work.

Oscillating drive with ANC

Super stable, water and dust resistant, maintenance-free oscillating drive for simultaneous generation of sawing stroke and orbital action of lift rod and saw blade. Allround needle bearing mounted crank drive (ANC) reduces friction, heat generation, wear. For long service life of drive also at extreme sawing.


Aggressive orbital action

Aggressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades. Fixed orbital action, running in needle bearings, ensures long-lasting and forceful



German Quality Product

- reduced friction and wear
- substantially reduced heat generation
- for extremely long service life, also during tough use



REMS Tiger/VE/SR

sawing also during extreme load conditions, e.g. sawing of steel pipe. Adjustable mechanisms with a great variety of parts and a reduced system stability do not withstand the high feed forward pressure and the heavy-duty requirements of forceful cutting of steel pipes, particularly when a guide support with leverage is being used.

Ideal speed (REMS Tiger)

Deliberately fixed speed. Therefore optimum cutting speed for maximum protection of motor and gear and maximum service life of saw blades. The ideal cutting speed of 2,400 rpm has been determined by extensive sawing tests with steel pipe which lead to optimum performance in combination with the aggressive, fixed orbital action, guide support and REMS special saw blade.

Vario-Electronic (REMS Tiger VE)

Electronic stepless speed control of drive unit for sensitive start-sawing and for speed selection during sawing according to the material. Also for plunge-cut sawing. The stroke speed can be continuously controlled by variable pressure on the safety switch from 0 to 2,400 rpm (accelerator switch).

Speed Regulation (REMS Tiger SR)

Stepless electronic speed control of drive unit for selecting the stroke according to the material. Ideal for sawing stainless steel pipe, cast pipe and for sawing boilers, tanks, bath tubs etc. Also for plunge-cut sawing. The number of strokes is steplessly adjustable on the dial from 700 to 2,200 rpm.

Electric reciprocating pipe saws



Anywhere,
without vice!



German Quality Product



Supply format

REMS Tiger Set. Electric reciprocating pipe saw for effortless, fast, right angle sawing with guide support and for free-hand sawing. Drive unit with straight machine handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful universal motor 230 V or 110 V, 50–60 Hz, 1050 W, safety tip switch. Fixed stroke 2,400 rpm. Overload protection. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

	Art.-No.	€
	560020R220	725,56

Other voltages, also 48 V on request.

Supply format

REMS Tiger VE Set. Electric reciprocating pipe saw with Vario-Electronic for effortless, fast, right angle sawing with guide support and for free-hand sawing. Drive unit with D-shape handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful universal motor 230 V or 110 V, 50–60 Hz, 1050 W, safety tip switch. Electronic stepless speed control (acceleration switch) 0 to 2,400 rpm. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

	Art.-No.	€
	560027R220	746,32

Other voltages on request.

Supply format

REMS Tiger SR Set. Electric reciprocating pipe saw with speed regulation (SR) for effortless, fast, right angle sawing with guide support and for free-hand sawing. Drive unit with straight machine handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful universal motor 230 V or 110 V, 50–60 Hz, 1400 W, safety tip switch. Stepless electronic speed control 700 to 2,200 rpm with sensitive start-sawing, speed generator, temperature control and stall protection. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

	Art.-No.	€
	560026R220	818,98

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Tiger drive unit	560000R220	621,76
REMS Tiger VE drive unit	560008R220	642,52
REMS Tiger ANC SR drive unit	560001R220	715,18
REMS saw blades see page 68–69.		
Guide support 2", for pipes Ø 1/2 – 2"	563000R	165,04
Guide support 4", for pipes Ø 2 1/2 – 4"	563100R	227,32
Guide support 6", for pipes Ø 5 – 6"	563200R	258,46
Chain guide support 6", for Ø 1/2 – 6" pipes and other profiles	563203R	205,52
Dual purpose holder for sawing and threading, with REMS Tiger and REMS Amigo E, Amigo, Amigo 2	543100	264,69
Protective cap for guide support 2", 4" and 6", for clamping of thin-walled material	563008R	20,14
Steel case	566051R	82,73

REMS Tiger pneumatic

Pneumatic reciprocating pipe saw

Powerful, robust, handy compressed air tool with force-transmitting guide holder for effortless, fast, right-angled sawing everywhere on site, without a vice. Also for universal free-hand sawing. Ideal for use in dangerous, e.g. in wet environment. For assembly, dismantling, repair.

Ideal for steel pipes and others.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

For materials that are difficult to cut, e.g. stainless steel pipes, hard cast iron, use the REMS Tiger SR with electronic stroke speed control.

REMS Tiger pneumatic – for sawing in dangerous environment.

Saws effortless, fast, right-angle. Force transmitting guide support for 400 % more sawing power.

Sturdy, square lift rod. Oscillating drive with ANC.

Aggressive orbital action for fast feed
forward sawing and long service life of saw
blades. Universal saw blade clamp.

Design

Robust, job site-proven. Slender, handy design. Super light, only 3.8 kg. Can be used anywhere. Ergonomically shaped front housing grip with slip resistant, heat insulating protection cover with soft grip, for forceful feed forward during free-hand sawing. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful pneumatic motor with ample reserve capacity, 1000 W. Stroke speed control (accelerator switch) 0 to 1,700 rpm. Operating pressure 6 bar, air consumption ≤ 1.6 m³/min. Safety switch with lock.

Additional description see REMS Tiger, page 62–63.



German Quality Product



Info



Supply format

REMS Tiger pneumatic Set. Pneumatic reciprocating pipe saw for effortless, fast, right angle sawing with guide support and for free-hand sawing. Drive unit with straight machine handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful pneumatic 1000 W, operating pressure 6 bar, safety switch with lock. Stroke speed control (accelerator switch) 0 to 1,700 rpm. Air inlet hose, air outlet hose. Universal saw blade clamp. Hexagon key. Guide support 2".
2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

Art.-No.	€
560022	2 176,69

Accessories

Description	Art.-No.	€
REMS saw blades see page 68–69.		
REMS Tiger pneumatic drive unit	560002R	1 865,29
Guide support 2", for pipes Ø 1/8–2"	563000R	165,04
Guide support 4", for pipes Ø 2 1/2–4"	563100R	227,32
Guide support 6", for pipes Ø 5–6"	563200R	258,46
Chain guide support 6", for Ø 1/8–6" pipes and other profiles	563203R	205,52
Dual purpose holder for sawing and threading, with REMS Tiger and REMS Amigo E, Amigo, Amigo 2	543100	264,69
Protective cap for guide support 2", 4" and 6", for clamping of thin-walled material	563008R	20,14
Steel case	566051R	82,73





REMS 
Spitz 2"140-3.2 HSS-Bi Made in Germany
Art.-Nr. 581001

REMS
22V

REMS 22V 9,0

REMS 22V 9,0

REMS Tiger 22 V VE

Cordless pipe reciprocating saw

Powerful, mobile, handy power tool with force-transmitting guide holder for effortless, fast, right-angled sawing everywhere on site, without a vice. Also for universal free-hand sawing. Only 3.4 kg. Ideal for assembly, dismantling, repair. Li-Ion 22V Technology. For battery and corded operation.

Ideal for steel pipes and others.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

REMS Tiger 22 V VE – the saw for the pipe fitter.
Saws effortless, fast, right angle. Mobile, handy, light.
Li-Ion 21.6 V, 9.0 Ah battery, for approx. 80 1" steel pipe cuts with guide holder for approx. 140 1" steel pipe cuts without guide holder with one battery charge*.

Power-transferring guide support

400% more sawing power for effortless, ultra-fast sawing of pipes and profiles, e.g., 2" steel pipe in just 8 s. For assembly and disassembly. Guide support with 5-fold power-transferring leverage allows effortless, fast, right-angled sawing everywhere on site, also free-hand without a pipe vice. Ideal handling, very quick and easy operation, only one handle for clamping and sawing. No free-swinging chain. No danger of jamming by limitation of swing angle. For optimum in-feed with guide support a straight machine handle is advantageous.

Right angle sawing

Right angle cut thanks to REMS guide support and REMS special saw blade. Essential for subsequent operations in pipe installation.

REMS special saw blade

REMS special saw blade (page 68), extra thick, rigid and unbendable, double tang, absolutely essential for right-angled sawing and fast disassembly of steel pipes with force-transmitting guide holder.

REMS universal saw blade

Only 1 REMS universal saw blade (page 68) for all sawing work instead of many different saw blades. Double tang for free-hand sawing and sawing with guide holder.

REMS saw blades

Full range of REMS saw blades for free-hand sawing of different materials (page 69).

Universal saw blade clamp

All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

Design

Robust, job site-proven. Mobile, handy, light. Drive unit with battery pack weighs only 3.4 kg. Slim form. Can be used anywhere. Ergonomically shaped front housing grip with slip resistant protection cover for forceful feed forward during free-hand sawing. Practical D-shaped handle with soft grip. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful 21.6 V battery motor with ample reserve capacity, 500 W output. Safety tip switch. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check with charging level indication by a 2-coloured green/red LED.

Sturdy, square lift rod

In special solid steel, mounted precisely in needle bearings towards the force direction and along the complete stroke length, for distortion-free, precise cutting also during tough use. For extremely long service life. Drive rod runs in an enclosed housing for safe work.

Oscillating drive with ANC

Super stable, water and dust resistant, maintenance-free oscillating drive for simultaneous generation of sawing stroke and orbital action of lift rod and saw blade. Allround needle bearing mounted crank drive (ANC) reduces friction, heat generation, wear. For long service life of drive also at extreme sawing.

Vario-Electronic

Electronic stepless speed control of drive unit for sensitive start sawing and for speed selection during sawing. The speed is controlled by pressing the tip switch steplessly from 0 to 1,900 rpm (acceleration switch).

Aggressive orbital action

Aggressive orbital action by vertical hacking motion of saw blade provides forceful, fast forward feed, excellent chip flow and long service life of saw blades. Fixed orbital action, running in needle bearings, ensures long-lasting and forceful sawing also during extreme load conditions, e.g. sawing of steel pipe.



German Quality Product



Info

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 9.0 Ah capacity, for long service life. Light and powerful, for approx. 80 1" steel pipe cuts with guide holder or approx. 135 1" steel pipe cuts without guide holder with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 40A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Universal saw blade clamp

All saw blades – with universal or double tang – can be clamped without changing or turning the saw blade thrust piece.

Supply format

REMS Tiger 22V VE Set. Cordless pipe reciprocating saw with Vario Electronics (VE) for effortless, fast, right-angled sawing with guide holder and for free-hand sawing. Drive unit with spade handle, maintenance-free, water and dust proof oscillation drive with all-round needle bearing crank drive (ANC), aggressive orbital stroke, powerful 21.6 V, 500 W battery motor, safety switch. Continuous, electronic stroke speed control (accelerator switch) 0 to 1900 rpm. Machine status check with overload protection, temperature monitoring, battery charging status check. Li-Ion 21.6 V, 9.0 Ah battery, 100–240V, 50–60 Hz, 90W rapid charger. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

	Art.-No.	€
	560053R220	1 347,32

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Tiger 22V VE drive unit, without battery	560011R22	808,60
REMS saw blades see page 68–69.		
Guide support 2", for pipes Ø 1/8 – 2"	563000R	165,04
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 40A, for mains operation instead of battery Li-Ion 21.6 V	571578R220	517,96
Steel case with inlay	566030R	128,71
REMS Lumen 2800 22V , cordless LED flood light, see page 111		



REMS special saw blades

For REMS Tiger/VE/SR, Tiger pneumatic, Tiger 22V VE and other makes

Special saw blades for right angle sawing and for fast dismantling of steel pipes with power transmitting guide support.

Steel pipes

REMS special saw blades – for right-angled sawing with force-transmitting guide holder, for 400% more sawing power.


Specially developed for REMS Tiger.

Absolutely essential for right angle sawing and for fast dismantling with power transmitting guide support. This produces multiple thrust pressure by a five-fold force-transmitting leverage, for 400% more sawing power. Normal saw blades with single tang do not withstand the high feed pressure during sawing with guide support, they break at the mounting point.

For this reason, extra thick REMS special saw blade, resistant to bending and distortion.

Double tang mounting with exceptionally wide clamping face ensures accurate seating and high stability.

Coarse, corrugated tooth pattern for rapid sawing. Long service life.



German Quality Product



REMS special saw blades → REMS Tiger, etc.	Ø inches/ Length mm	Tooth pitch mm	Material*	Teeth	Colour		Art.-No.	€
REMS special saw blade 2"/140-2.5 steel pipes ≤ 2"	2"/140	2.5	HSS-Bi	—	yellow	5	REMS	62,18
REMS special saw blade 2"/140-3.2 steel pipes ≤ 2"	2"/140	3.2	HSS-Bi	—	yellow	5	REMS	58,02
REMS special saw blade 4"/200-3.2 steel pipes ≤ 4"	4"/200	3.2	HSS-Bi	—	yellow	5	REMS	76,92
REMS special saw blade 6"/260-3.2 steel pipes ≤ 6"	6"/260	3.2	HSS-Bi	—	yellow	5	REMS	99,54

For hard-to-machine materials, e.g. stainless steel pipes, hard cast iron pipes, use the finer toothed REMS universal saw blade instead of the REMS special saw blade in combination with REMS Tiger SR with electronic speed regulation (page 63).

REMS universal saw blades

For REMS Cat VE, Tiger/VE/SR, Cat 22V VE and other makes

Universal saw blade for free-hand sawing and for sawing with power transmitting guide support. Instead of many different saw blades.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

Highly flexible, also ideal for sawing flush with the wall.

REMS universal saw blades – for all sawing jobs.

Only 1 universal saw blade instead of many different saw blades for all sawing jobs.


Resilient material, highly flexible, also for flush-to-wall sawing.

Double tang mounting with exceptionally wide clamping face for accurate seating and high stability. Also for sawing with power transmitting guide support.

Single tang saw blades are unable to cope with the high thrust pressure when sawing with a guide holder, they break at the clamping point.

Alternating tooth pitch (combi-teeth) for fast, smooth cut, very highly hardened in the teeth area. Straight-set teeth.

Thus outstanding cutting performance and prolonged service life.



German Quality Product



REMS universal saw blades → REMS Tiger, REMS Cat, etc.	Length mm	Tooth pitch mm	Material*	Teeth	Colour		Art.-No.	€
REMS universal saw blade 100-1.8/2.5 for all sawing work	100	Combo 1.8/2.5	HSS-Bi flexible	—	red	5	REMS	39,96
REMS universal saw blade 150-1.8/2.5 for all sawing work	150	Combo 1.8/2.5	HSS-Bi flexible	—	red	5	REMS	57,19
REMS universal saw blade 200-1.8/2.5 for all sawing work	200	Combo 1.8/2.5	HSS-Bi flexible	—	red	5	REMS	75,67
REMS universal saw blade 300-1.8/2.5 for all sawing work	300	Combo 1.8/2.5	HSS-Bi flexible	—	red	5	REMS	111,79

Also for nail-embedded wood, pallets. For hard-to-machine materials, e.g. stainless steel pipes, hard cast iron pipes, lower speed required, e.g. by using REMS Tiger SR with electronic speed regulation (page 63).

REMS saw blades

For REMS Puma VE, Cat VE, Tiger/VE/SR, Cat 22V VE, Tiger 22V VE and other makes

Saw blades for free-hand sawing for different materials.

Alternating tooth pitch (combi-teeth) for fast, smooth cut, also when sawing mixed materials (wood/metal).

Flexible saw blades, also for sawing flush with wall.

German Quality Product



REMS saw blades for metal → REMS Puma, REMS Cat, REMS Tiger, etc.	Length mm	Tooth pitch mm	Material*	Teeth	Colour			Art.-No.	€
REMS saw blade 150-1 sheet metal, metal, also stainless steel, ≥ 1.2 mm	150	1	HSS-Bi flexible		red			561105R05	25,74
REMS saw blade 200-1 sheet metal, metal, also stainless steel, ≥ 1.2 mm	200	1	HSS-Bi flexible		red			561106R05	33,74
REMS saw blade 90-1.4, curved blade metal, also stainless steel, ≥ 1.5 mm	90	1.4	HSS-Bi		red			561107R05	23,87
REMS saw blade 150-1.4 metal, also stainless steel, ≥ 1.5 mm	150	1.4	HSS-Bi flexible		red			561104R05	26,88
REMS saw blade 200-1.4 metal, also stainless steel, ≥ 1.5 mm	200	1.4	HSS-Bi flexible		red			561108R05	33,94
REMS saw blade 100-1.8 metal, also stainless steel, ≥ 2 mm	100	1.8	HSS-Bi flexible		red			561101R05	23,04
REMS saw blade 150-1.8 metal, also stainless steel, ≥ 2 mm	150	1.8	HSS-Bi flexible		red			561103R05	26,88
REMS saw blade 200-1.8 metal, also stainless steel, ≥ 2 mm	200	1.8	HSS-Bi flexible		red			561102R05	33,74
REMS saw blade 200-2.5 metal, also stainless steel, ≥ 3 mm	200	2.5	HSS-Bi flexible		red			561109R05	33,74
REMS saw blade 280-2.5 metal, also stainless steel, ≥ 3 mm	280	2.5	HSS-Bi flexible		red			561112R05	42,77

German Quality Product



REMS saw blades for wood and metal → REMS Puma, REMS Cat, REMS Tiger, etc.	Length mm	Tooth pitch mm	Material*	Teeth	Colour			Art.-No.	€
REMS saw blade 210-1.8/2.5 round tip, no sticking pallets, wood, wood with nails, metal ≥ 2.5 mm	210	Combo 1.8/2.5	HSS-Bi flexible		black			561113R05	34,77
REMS saw blade 150-2.5 wood, wood with nails, pallets, metal ≥ 3 mm	150	2.5	HSS-Bi flexible		black			561110R05	25,74
REMS saw blade 225-2.5, extra thick, for disassembly wood, wood with nails, metal ≥ 3 mm	225	2.5	HSS-Bi		black			561114R03	33,11
REMS saw blade 300-2.5, extra thick, for disassembly wood, wood with nails, metal ≥ 3 mm	300	2.5	HSS-Bi		black			561116R03	44,12
REMS saw blade 300-4.2 wood	300	4.2	WS		black			561111R05	31,45
REMS saw blade 225-3.2/5.0 wood, wood with nails	225	Combo 3.2/5.0	HSS-Bi flexible		black			561117R05	39,24
REMS saw blade 290-5.0/6.35 green wood	290	Combo 5.0/6.35	WS		black			561118R05	42,77
REMS saw blade 150-6.35 wood	150	6.35	WS		black			561119R05	18,17

REMS saw blades for different purposes → REMS Puma, REMS Cat, REMS Tiger, etc.	Length mm	Tooth pitch mm	Material*	Teeth	Colour			Art.-No.	€
REMS saw blade 150-4.2 breeze blocks, plasterboard	150	4.2	WS		white			561115R05	22,52
REMS saw blade 225-8.5 breeze blocks, hard wood	225	8.5	HM		white			561120R01	58,54
REMS saw blade 300-8.5 breeze blocks, hard wood	300	8.5	HM		white			561121R01	70,17
REMS saw blade 400-8.5 breeze blocks, hard wood	400	8.5	HM		white			561122R01	100,69
REMS saw blade 235-12 breeze blocks, pumice, brick	235	12	HM		white			561123R01	81,48
REMS saw blade 300-12 breeze blocks, pumice, brick	300	12	HM		white			561124R01	94,35
REMS saw blade 300-12, extra high blade breeze blocks, pumice, brick	300	12	HM		white			561125R01	111,79
REMS saw blade 200 cast iron etc.	200		HM-G		white			561126R02	33,63



REMS Turbo Cu-INOX

Circular pipe sawing machine

Compact, portable circular pipe sawing machine for burr-reduced, right angle and rapid sawing. For stainless steel pipes, carbon steel pipes and copper pipes of the press fitting systems etc. Also for cutting thin-walled sections for front-wall installation. For job site and workshop.

Stainless steel pipes, carbon steel pipes, copper pipes and other materials	$\leq \varnothing 76\text{ mm}$
REMS saw blade	$\varnothing 225\text{ mm}$

REMS Turbo Cu-INOX – burr-reduced, right angle, rapid. Burr-reduced sawing through double clamping vice. Powerful, e.g. $\varnothing 22\text{ mm}$ in only 4 s. Easy to transport.

Ideal for pressfitting systems

In accordance with requirements:

Dry sawing, so no damage to O-rings from lubricants.

Burr-reduced through double clamping vice.

Optimum cutting speed prevents degradation of pipe material through overheating.

Design

Compact, robust, job site-proven. Small in size, handy, portable, only 17 kg. Easy sawing through favourable leverage effect. Fast saw blade change. Precise sawing. Mark on the saw blade protection cover showing the saw blade cutting line. Connection for driving outer/inner pipe deburrer REMS REG 10–54 E. For workbench, stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning.

Universal double clamping vice

Robust, easy-running universal double clamping vice for burr-reduced sawing. Both pipe ends remain securely clamped during sawing. Easy, secure clamping also of thin-walled pipes through inclined jaw. Only one strong clamping spindle for both clamping sides ensures even, effortless and secure clamping of the material.

Drive

Robust gear, precisely mounted in roller and needle bearings, maintenance-free. Proven universal motor, 500 W. Powerful, e.g. stainless steel pipe $\varnothing 22\text{ mm}$ in only 4 s. Ideal speed 60 rpm for optimum cutting speed and smooth sawing.

REMS saw blades

Top German quality. REMS circular saw blade HSS $225 \times 2 \times 32\text{ mm}$, 220 teeth, for metal, adjusted to the efficiency of REMS Turbo Cu-INOX for sawing stainless steel tubes. Specially fine-toothed, hardened and ground. For easy and exact sawing. Prolonged durability. REMS circular saw blade HSS-E (cobalt alloyed) $225 \times 2 \times 32\text{ mm}$, 220 teeth, for metal, for even better durability. Specially fine-toothed, hardened and ground.

Outer/inner pipe deburrer

Outer/inner pipe deburrer REMS REG 10–54 E for pipes $\varnothing 10\text{--}54\text{ mm}$, $0\frac{1}{2}\text{--}2\frac{1}{8}\text{ in}$, for electric drive with the REMS Turbo Cu-INOX pipe circular sawing machine and others, see page 99.

Supply format


REMS Turbo Cu-INOX Basic. Circular pipe saw with universal double clamping vice for burr-reduced, right angle, rapid sawing. For stainless steel pipes, carbon steel pipes and copper pipes of the press fitting systems etc. Also for cutting thin-walled sections for front-wall installation. For REMS saw blade $\varnothing 225\text{ mm}$. With maintenance-free gear, proven universal motor 230 V or 110 V, 50–60 Hz, 500 W. Safety tip switch, saw blade protection cover. Speed 60 rpm. Ring spanner. Hexagon key. Without saw blade. For workbench, stand or wheel stand. In a carton.

Art.-No.	€
849006R220	1 287,12

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS circular saw blade HSS for metal, specially for stainless steel pipes, fine-toothed, $225 \times 2 \times 32\text{ mm}$, 220 teeth.	849703R	222,13
REMS circular saw blade HSS-E (cobalt alloyed) circular saw blade HSS-E (cobalt alloyed) toothed, $225 \times 2 \times 32\text{ mm}$, 220 teeth. Very long service life.	849706R	309,32
REMS REG 10–54 E outer/inner pipe deburrer, see page 99		
Stand	849315R	216,94
Wheel stand	849310R	351,88
REMS Jumbo, folding workbenches, see page 106.		
REMS Herkules, material supports, see page 107.		



German Quality Product



Info



REMS Turbo K

Universal circular metal sawing machine
with automatic cooling lubricant unit

Compact, mobile, universal circular metal sawing
machine for installation, metal working and
industry. For job site and workshop.

→	○	□	■	L	●	■	■
90° ↗	78	55	70 × 50	50 × 50	40	40	50 × 30
45° ↗	60	55	60 × 40	50 × 50	40	40	50 × 30

REMS saw blade

Ø 225 mm

REMS Turbo K – the most powerful in its class.

Progressive drive, e.g. 2" steel pipe in only 5 s.

Easy to transport.

Design

Compact, robust, job site-proven. Small in size, handy, portable, complete only 22 kg. Automatic cooling lubricant unit. Easy sawing through favourable leverage effect. Fast saw blade change. Precise sawing. For workbench, stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning.

Universal vice

Robust, easy-running universal vice with strong clamping spindle and large clamping lever for effortless, secure clamping of the material. Standard with clamp insert for thin-walled pipes. Quick setting of bevel angle thanks to clearly laid out scale and clamping lever. Simple, sturdy length stop.

Drive


Robust, maintenance-free gear, precisely mounted in roller and needle bearings. Proven universal motor, 1200 W. Extremely strong and powerful, e.g. 2" steel pipe in only 5 s. Ideal speed 115 rpm for fast and smooth sawing.

REMS saw blades

Top German quality. REMS universal circular saw blade HSS 225 × 2 × 32 mm for metal, 120 teeth, adjusted to the efficiency of REMS Turbo K. Specially toothed, hardened and ground. For easy and exact sawing. REMS universal circular saw blade HSS 225 × 2 × 32 mm, 220 teeth, adjusted for sawing stainless steel. Specially fine-toothed, hardened and ground. For an even better durability, REMS universal circular saw blade HSS-E (cobalt alloyed) 225 × 2 × 32 mm, 220 teeth. Specially fine-toothed, hardened and ground.

Kühlsmierstoffe

REMS Sanitol and REMS Spezial (page 47). High lubricating and cooling effect. Essential for clean cuts, long service life of saw blades and machine.



German Quality Product



Supply format

REMS Turbo K Basic. Universal circular metal sawing machine with automatic cooling lubricant unit. For straight cuts and bevel cuts up to 45°. For REMS saw blade Ø 225 mm. Maintenance-free gear. Proven, powerful universal motor 230 V or 110 V, 50–60 Hz, 1200 W. Safety tip switch, saw blade protection cover, length stop. Clamp insert for thin-walled pipes. Speed 115 rpm. Ring spanner. Hexagon key. 1 filling of cooling lubricant REMS Spezial. Without saw blade. For workbench, stand or wheel stand. In a carton.

	Art.-No.	€
	849007R220	1 614,09

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS universal circular saw blade HSS for metal, 225 × 2 × 32 mm, 120 teeth	849700R	192,03
REMS circular saw blade HSS for metal, fine-toothed, 225 × 2 × 32 mm, 220 teeth	849703R	222,13
REMS circular saw blade HSS-E (cobalt alloyed) for metal, fine-toothed, 225 × 2 × 32 mm, 220 teeth. Very long service life.	849706R	309,32
Electronic speed regulator for hard-to-machine materials, e.g. stainless steel pipes, hard cast iron pipes. Fixed, optimum speed.	565051R220	279,22
Cooling lubricants see page 47.		
Stand	849315R	216,94
Wheel stand	849310R	351,88
REMS Jumbo , folding workbenches, see page 106.		
REMS Herkules , material supports, see page 107.		



Made
in Germany

REMS

Cutting

Chamfering

Deburring

Calibrating

	Pipe cutters	74
	Cutter wheels	81
	Electric pipe cutter/ Cordless pipe cutter	82
	Pipe cutting machines	84
	Pipe shears	90
	Pipe cutting and pipe chamfering tools	94
	Pipe deburrers	97
	Calibrating tools and outer-inner pipe deburrer	100

Robust quality tools for cutting pipes.

Meets high demands and long service life.

Steel pipes

$\varnothing \frac{1}{8}$ –4", Ø 10–115 mm

REMS RAS St – quality pipe cutters.

Solid body in forged steel.

Robust spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the pipe and a long service life.

Ergonomic, wide handle provides a powerful in-feed of spindle.

Broad, precise cutter wheel bearing on a hardened, non rotating wheel shaft guarantees a right angle cut.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Only 1 cutter wheel for pipes Ø $\frac{1}{8}$ –4" (10–115 mm), wall thickness s ≤ 8 mm, suitable for both pipe cutters. Cutter wheel for pipes Ø 1–4" to wall thickness s ≤ 12.5 mm available as accessory.



German Quality Products



Info

Supply format

REMS RAS St. Pipe cutter for steel pipes. With cutter wheel. In a carton.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	€
St $\frac{1}{8}$–2"	$\frac{1}{8}$ –2" 10–60	8	113000R	227,32
St 1$\frac{1}{4}$–4"	1 $\frac{1}{4}$ –4" 30–115	8	113100R	414,16

Accessories

Description	s ≤ mm	Art.-No.	€
REMS cutter wheel St 1/8–4", s 8 for REMS RAS St $\frac{1}{8}$ –2" and St 1 $\frac{1}{4}$ –4"	8	341614R	15,47
REMS cutter wheel St 1–4", s 12 for REMS RAS St 1 $\frac{1}{4}$ –4"	12.5	381622R	35,60



REMS RAS Cu-INOX

Pipe cutters

Robust quality tools for cutting tubes.

Particularly suited for cutting stainless steel tubes.

Copper tubes, thin-walled
stainless steel tubes, thin-walled
steel, aluminium, brass tubes

\varnothing 3 – 120 mm
 \varnothing 1/8 – 4"

REMS RAS Cu-INOX – for places with difficult access.

Small, handy, specially for use in restricted spaces.

Robust design and hardened back pressure rollers provide exact alignment to the tube and a long service life.

Large operating knob in metal for easy in-feed and cutting.

Broad, precise cutter wheel bearing on a hardened, non rotating wheel shaft guarantees a right angle cut.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

REMS RAS Cu-INOX 3–28 S Mini with needle bearing cutter wheel and needle bearing counter-pressure rollers for very easy cutting.



Supply format

REMS RAS Cu-INOX. Pipe cutter for copper tubes, thin-walled stainless steel tubes, thin-walled steel, aluminium, brass tubes. With cutter wheel.

In blister pack.

Description	Pipes \varnothing mm/inch	Wall thickness $s \leq$ mm	Art.-No.	€
Cu-INOX 3–16	3–16 1/8 – 5/8"	4	113200R	28,55
Cu-INOX 3–25	3–25 1/8 – 1"	4	113230R	34,57
Cu-INOX 3–28 Mini	3–28 1/8 – 1 1/8"	4	113240R	39,55
Cu-INOX 3–28 S Mini on needle bearings	3–28 1/8 – 1 1/8"	4	113241R	55,74



Info



REMS RAS Cu-INOX – the compact version

with telescopic spindle.

Telescopic spindle. Easy, quick adjustment in both directions.

Compact design for tough use.

Sturdy telescopic spindle, long spindle guidance and 4 specially hardened back pressure rollers ensure exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.


Ergonomic, handy operating knob in metal for easy work and long service life. Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

REMS RAS Cu-INOX 3–35 S with needle bearing cutting wheel and needle bearing counter-pressure rollers for very easy cutting.

Integrated pipe deburring device, on rotating bearing, adapts to the workpiece edge to be deburred.

Specially hardened and ground universal deburring blade guarantees easy deburring and extremely long life.

Fast, simple blade change.



Supply format

REMS RAS Cu-INOX. Pipe cutting machine for copper pipes, thin-walled stainless steel pipes, thin-walled steel-aluminium pipes, brass pipes, with integrated pipe deburring device. With cutter wheel. In blister pack.

Description	Pipes \varnothing mm/inch	Wall thickness $s \leq$ mm	Art.-No.	€
Cu-INOX 3–35	3–35 1/8 – 1 1/8"	4	113350R	61,14
Cu-INOX 3–35 S on needle bearings	3–35 1/8 – 1 1/8"	4	113351R	81,90
Cu-INOX 3–42	3–42 1/8 – 1 3/4"	4	113330R	76,71



REMS RAS Cu-INOX

Pipe cutters

REMS RAS Cu-INOX – quality pipe cutter.

Robust, solid design for heavy-duty application.

Sturdy spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

REMS RAS Cu-INOX 8–64 S and REMS RAS Cu-INOX 8–42 S with needle bearing cutting wheel and needle bearing counter-pressure rollers for very easy cutting. Quick adjustment of the engagement spindle in both directions.

Only 1 cutter wheel for the complete working capacity Ø 3–120 mm.



Info



International
Design Award



German Quality Products

Supply format

REMS RAS Cu-INOX. Pipe cutter for copper tubes, thin-walled stainless steel tubes, thin-walled steel, aluminium, brass tubes. With cutter wheel. In blister pack/in box.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	€
Cu-INOX 3–28	3–28 $\frac{1}{8}$ – $2\frac{1}{8}$ "	4	113300R	33,63
Cu-INOX 6–42	6–42 $\frac{1}{4}$ – $1\frac{1}{8}$ "	4	113380R	158,81
Cu-INOX 8–42 S on needle bearings, with quick adjustment	8–42 $\frac{3}{8}$ – $1\frac{1}{8}$ "	4	113385R	163,49
Cu-INOX 6–64	6–64 $\frac{1}{4}$ – $2\frac{1}{2}$ "	4	113400R	185,80
Cu-INOX 8–64 S on needle bearings, with quick adjustment	8–64 $\frac{3}{8}$ – $2\frac{1}{2}$ "	4	113401R	206,56
Cu-INOX 64–120	64–120 $2\frac{1}{2}$ –4"	4	113500R	268,84

Accessories

Description	Wall thick- ness s ≤ mm	Art.-No.	€
REMS cutter wheel Cu-INOX 3–120, s 4	4	113210R	12,04
REMS cutter wheel Cu-INOX 3–120 S, s 4, on needle bearings	4	113213R	21,07
Universal deburring blade, ground		113360	7,89



REMS RAS Cu

Pipe cutters

Robust quality tools for cutting tubes.

Copper tubes	$\varnothing 3 - 64 \text{ mm}$ $\varnothing \frac{1}{8} - 2\frac{1}{2} \text{"}$
--------------	--

REMS RAS Cu – for places with difficult access.

Small, handy, specially for use in restricted spaces.

Robust design and hardened back pressure rollers provide exact alignment to the tube and a long service life.

Large operating knob in metal for easy in-feed and cutting.

Broad, precise cutter wheel bearing on a hardened, non rotating wheel shaft guarantees a right angle cut.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.



Info



Supply format

REMS RAS Cu. Pipe cutter for copper tubes. With cutter wheel. In blister pack.

Description	Pipes $\varnothing \text{ mm/inch}$	Wall thickness $s \leq \text{mm}$	Art.-No.	€
Cu 3-16	3-16 $\frac{1}{8}-\frac{5}{8} \text{"}$	3	113250R	28,55
Cu 3-25	3-25 $\frac{1}{8}-1 \text{"}$	3	113255R	34,57
Cu 3-28	3-28 $\frac{1}{8}-1\frac{1}{8} \text{"}$	3	113260R	39,55

REMS RAS Cu – the compact version

with telescopic spindle.

Telescopic spindle. Easy, quick adjustment in both directions.

Compact design for tough use.

Sturdy telescopic spindle, long spindle guidance and 4 specially hardened back pressure rollers ensure exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.


Ergonomic, handy operating knob in metal for easy work and long service life.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Integrated pipe deburring device, on rotating bearing, adapts to the workpiece edge to be deburred.

Specially hardened and ground universal deburring blade guarantees easy deburring and extremely long life.

Fast, simple blade change.



Supply format

REMS RAS Cu. Pipe cutter for copper tubes, with integrated pipe deburring device. With cutter wheel. In blister pack.

Description	Pipes $\varnothing \text{ mm/inch}$	Wall thickness $s \leq \text{mm}$	Art.-No.	€
Cu 3-35	3-35 $\frac{1}{8}-1\frac{3}{8} \text{"}$	3	113340R	58,02
Cu 3-42	3-42 $\frac{1}{8}-1\frac{3}{4} \text{"}$	3	113320R	69,65



REMS RAS Cu

Pipe cutters

REMS RAS Cu – quality pipe cutter.

With quick adjustment.

Solid, handy, U-shaped design.

Sturdy spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the pipe, easy in-feed, easy cutting and precise, right angle cut.


Ergonomic, handy operating knob in metal for easy work and long service life.

Ratchet for quick adjustment in both directions.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Only 1 cutter wheel for the complete working capacity Ø 3–120 mm.



German Quality Products

Supply format

REMS RAS Cu. Pipe cutter for copper tubes. With cutter wheel. In blister pack/in box.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	€
Cu 8–42 with quick adjustment	8–42 ¾–1½"	3	113370R	154,66
Cu 8–64 with quick adjustment	8–64 ¾–2½"	3	113410R	185,80

International
Design Award



Accessories

Description	Wall thickness s ≤ mm	Art.-No.	€
REMS cutter wheel Cu 3–120, s 3	3	113225R	12,04
Universal deburring blade, ground		113360	7,89

REMS RAS P

Pipe cutters

REMS RAS P – the compact version with telescopic spindle.

Telescopic spindle. Easy, quick adjustment in both directions.

Compact design for tough use.

Sturdy telescopic spindle, long spindle guidance and 4 specially hardened back pressure rollers ensure exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Integrated pipe deburring device, on rotating bearing, adapts to the workpiece edge to be deburred.

Specially hardened and ground universal deburring blade guarantees easy deburring and extremely long life.

Fast, simple blade change.



Supply format

REMS RAS P. Pipe cutter for plastic pipes and multi-layer composite tubes, with integrated pipe deburring device. With cutter wheel. In blister pack.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.	€
P 10–32 T	10–32 ½–1½"	4,5	290001R	58,02
P 10–40 T	10–40 ½–1½"	4,5	290002R	69,65



REMS RAS P

Pipe cutters

High performance quality tools for cutting pipes.
With quick adjustment.

Plastic pipes,
multi-layer composite tubes

$\varnothing 10 - 315 \text{ mm}$
 $\varnothing 1/2 - 12"$

REMS RAS P – quality pipe cutter.

With quick adjustment.

Solid, handy, U-shaped design.

Sturdy spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the pipe, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Ratchet for quick adjustment in both directions.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Cutter wheels for different wall thicknesses (s).

REMS RAS P 50–125 with integrated pipe deburrer, on rotating bearing, adapts to the workpiece edge to be deburred. Specially hardened and ground universal deburring blade guarantees easy deburring and extremely long life. Fast, simple blade change. Additional guide roller, adjustable, for cutting $\varnothing 110 \text{ mm}$ or $\varnothing 125 \text{ mm}$ pipes. Fast cutting wheel change without tools by cutting wheel axle with ball catch.

Supply format

REMS RAS P. Pipe cutter for plastic pipes and multi-layer composite tubes.
With cutter wheel. In blister pack/in box.

Description	Pipes $\varnothing \text{ mm/inch}$	Wall thickness $s \leq \text{mm}$	Art.-No.	€
P 10–40* with quick adjustment	10–40 $1/2 - 1\frac{1}{8}"$	7	290050R	154,66
P 10–63* with quick adjustment	10–63 $1/2 - 2"$	7	290000R	196,18
P 50–110*, s11 with quick adjustment	50–110 $2 - 4"$	11	290100R	234,59
P 50–110*, s16 with quick adjustment	50–110 $2 - 4"$	16	290100R	234,59
P 50–110*, s19 with quick adjustment	50–90 $2 - 3"$	19	290100R	234,59
P 50–125, s16 with quick adjustment	50–125 $2 - 5"$	16	290500R-S16	241,85
P 110–160* with quick adjustment	110–160 $4 - 6"$	16	290200R	289,60

REMS RAS P – cutting up to $\varnothing 315 \text{ mm}$, $s \leq 19 \text{ mm}$.

Fast and inexpensive cutting of large pipes. Quick adjustment.

Separate pipe centering for right angle cutting.

Solid design, double-T-shaped body.

Cutter wheels for different wall thicknesses (s).


Supply format

REMS RAS P. Pipe cutter for plastic pipes and multi-layer composite tubes.
With cutter wheel and spare cutter wheel. In sturdy steel case.

Description	Pipes $\varnothing \text{ mm/inch}$	Wall thickness $s \leq \text{mm}$	Art.-No.	€
P 180–315 with quick adjustment	180–315 $7 - 12"$	16	290300	1 717,89

Accessories

Description	$s \leq \text{mm}$	Art.-No.	€
REMS cutter wheel P 10–40, s 4,5 for REMS RAS P 10–32 T, 10–40 T	4,5	290023R	19,51
REMS cutter wheel P 10–63, s 7 for REMS RAS P 10–40, 10–63	7	290016R	19,51
REMS cutter wheel P 50–315, s 11 for REMS RAS P 50–110, 50–125, 110–160, 180–315	11	290116R	23,67
REMS cutter wheel P 50–315, s 16 for REMS RAS P 50–110, 50–125, 110–160, 180–315	16	290216R	28,23
REMS cutter wheel P 50–315, s 19 for REMS RAS P 50–110, 110–160, 180–315	19	290316R	45,57



*German Quality Products



Info

International
Design Award



P 50–110, s11
P 50–110, s16
P 50–110, s19



REMS RAS P/SW 45/L

Robust quality tool with two cutting systems for cutting and slitting plastic corrugated protective pipes.

Cutting	$\varnothing \leq 45 \text{ mm}$ $\varnothing \leq 1\frac{3}{4} "$
Slitting (lengthwise cutting)	ID $\geq \varnothing 14 \text{ mm}$

REMS RAS P/SW 45/L – Cutting and slitting of plastic corrugated protective pipes.

Stable magnesium version, extremely light.

Specially hardened and specially ground blades for cutting and slitting.
German quality product.

Four-edged, wedge-shaped blades with a cutting angle of 90°, rotatable 4 times by 90° for four times longer life. Right-angled, burr-free cutting by pipe rest with shaft guide.

Automatic contact pressure when cutting.

Cutting depth limiting of the cutting tools during cutting prevents damage to the inside of the pipe.

Supply format

REMS RAS P/SW 45/L. Pipe cutter/pipe slitter for plastic corrugated protective pipes. With 3 blades. In blister pack.

Pipes Ø mm/inch	Art.-No.	€
$\leq 45 \text{ mm} / \leq 1\frac{3}{4} "$	113480R	56,99

Accessories

Description	Art.-No.	€
Blade P/SW 45/L (pack of 3) for REMS RAS P/SW 45/L	113481R	28,49

REMS RAS W INOX

Highly resistant quality tool for cutting pipes.

Corrugated metal hoses (corrugated pipes)
of stainless steel, also jacketed DN 10 – 32 (40)
 $\frac{3}{8} – 1\frac{1}{2} " (2")$

REMS RAS W INOX 10 – 32/40 S – Quality pipe cutter especially for cutting corrugated metal hoses (corrugated pipes) made of stainless steel.

Compact design for tough use.

Easy in-feed, easy cutting and precise, right angle cut.

Sturdy telescopic spindle, long spindle guide, cutting wheel on needle bearing and 2 specially hardened counter pressure rollers on needle bearings. Three high-molecular plastic guide rollers each on both sides, arranged triangularly for straight guidance of the corrugated metal hose (corrugated pipe) during the cutting process.

Ergonomically designed, comfortable rotary handle.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Supply format


REMS RAS W INOX 10 – 32/40 S. Pipe cutter for corrugated metal hoses (corrugated pipes) of stainless steel, also jacketed. Counter pressure rollers on needle bearings. With cutting wheel, on needle bearing. In blister pack.

Pipes	Art.-No.	€
DN 10 – 32 (40) / $\frac{3}{8} – 1\frac{1}{2} " (2")$	113450R	216,94

Accessories

Description	Art.-No.	€
REMS cutter wheel W INOX 10 – 32/40 S on needle bearings	113461R	11,83

Pipe cutter/pipe slitter



Info



Pipe cutter



e.g.
Armaflex,
BANIDES,
Boagaz,
Chchu Decayeux,
Clesse,
Eurotis,
FlexiPipe,
Gastite,
Gurtner

German Quality Products



Info



REMS cutter wheels


German Quality Products
For REMS pipe cutters and other makes

Specially hardened cutter wheels in approved, tough-hard REMS die steel, ensure a long service life. German Quality Products.

REMS cutter wheels also fit in suitable pipe cutters of other makes, see table with dimensional data.


REMS cutter wheel	Material	Wall thickness	to fit following pipe cutters	Capacity Ø	Art.-No.	€
St 1/8" - 4", s 8	Steel pipes	s ≤ 8 mm	REMS RAS St 1/8" - 2"	1/8" - 2"	341614 R	15,47
St 1 - 4", s 12			REMS RAS St 1 1/4" - 4"	1 1/4" - 4"		
Cu-INOX 3 - 120, s 4	Copper tubes, stainless steel tubes	s ≤ 4 mm	REMS RAS Cu-INOX 3 - 16	3 - 16 mm	113210 R	12,04
			REMS RAS Cu-INOX 3 - 28	3 - 28 mm		
			REMS RAS Cu-INOX 3 - 35	3 - 35 mm		
			REMS RAS Cu-INOX 3 - 42	3 - 42 mm		
			REMS RAS Cu-INOX 6 - 42	6 - 42 mm		
			REMS RAS Cu-INOX 6 - 64	6 - 64 mm		
			REMS RAS Cu-INOX 64 - 120	64 - 120 mm		
			REMS RAS Cu 3 - 35	3 - 35 mm		
			REMS RAS Cu 3 - 42	3 - 42 mm		
Cu-INOX 3 - 120 S, s 4, on needle bearings			REMS RAS Cu-INOX 3 - 28 S	3 - 28 mm		
			REMS RAS Cu-INOX 3 - 35 S	3 - 35 mm		
			REMS RAS Cu-INOX 8 - 42 S	8 - 42 mm		
			REMS RAS Cu-INOX 8 - 64 S	8 - 64 mm		
Cu-INOX b 3, s 4	Copper tubes, stainless steel tubes	s ≤ 4 mm	See table "Dimensional data for REMS cutter wheels"		113220 R	12,04
Cu 3 - 120, s 3			REMS RAS Cu-INOX 3 - 16	3 - 16 mm	113225 R	12,04
			REMS RAS Cu-INOX 3 - 25	3 - 25 mm		
			REMS RAS Cu-INOX 3 - 28	3 - 28 mm		
			REMS RAS Cu-INOX 3 - 35	3 - 35 mm		
			REMS RAS Cu-INOX 3 - 42	3 - 42 mm		
			REMS RAS Cu-INOX 6 - 42	6 - 42 mm		
			REMS RAS Cu-INOX 6 - 64	6 - 64 mm		
			REMS RAS Cu-INOX 64 - 120	64 - 120 mm		
			REMS RAS Cu 3 - 16	3 - 16 mm		
			REMS RAS Cu 3 - 25	3 - 25 mm		
			REMS RAS Cu 3 - 28	3 - 28 mm		
			REMS RAS Cu 3 - 35	3 - 35 mm		
			REMS RAS Cu 3 - 42	3 - 42 mm		
P 10 - 40, s 4,5	Plastic pipes, composite tubes	s ≤ 4,5 mm	REMS RAS P 10 - 32 T	10 - 32 mm	290023 R	19,51
P 10 - 63, s 7			REMS RAS P 10 - 40 T	10 - 40 mm		
P 50 - 315, s 11	Plastic pipes, composite tubes	s ≤ 11 mm	REMS RAS P 10 - 40	10 - 40 mm	290016 R	19,51
			REMS RAS P 10 - 63	10 - 63 mm		
			REMS RAS P 50 - 110	50 - 110 mm		
			REMS RAS P 50 - 125	50 - 125 mm		
			REMS RAS P 110 - 160	110 - 160 mm		
			REMS RAS P 180 - 315	180 - 315 mm		
P 50 - 315, s 16	Plastic pipes, composite tubes	s ≤ 16 mm	REMS RAS P 50 - 110	50 - 110 mm	290216 R	28,23
			REMS RAS P 50 - 125	50 - 125 mm		
			REMS RAS P 110 - 160	110 - 160 mm		
			REMS RAS P 180 - 315	180 - 315 mm		
P 50 - 315, s 19	Plastic pipes, composite tubes	s ≤ 19 mm	REMS RAS P 50 - 110	50 - 110 mm	290316 R	45,57
			REMS RAS P 50 - 125	50 - 125 mm		
			REMS RAS P 110 - 160	110 - 160 mm		
			REMS RAS P 180 - 315	180 - 315 mm		
W INOX 10 - 32/40 S, on needle bearings	Corrugated metal hoses (corrugated pipes) of stainless steel		REMS RAS W INOX 10 - 32/40 S	DN 10 - 32 (40)	113461 R	11,83

Dimensional data for REMS cutter wheels



REMS cutter wheel	Art.-No.	OD mm	W mm	ID mm
St 1/8" - 4", s 8	341614 R	32.30	18.94	9.04
St 1 - 4", s 12	381622 R	41.30	18.94	9.04
Cu-INOX 3 - 120, s 4	113210 R	19.70	4.93	5.00
Cu-INOX 3 - 120 S, s 4	113213 R	19.70	4.93	5.00
Cu-INOX b 3, s 4	113220 R	18.70	3.07	4.80
Cu 3 - 120, s 3	113225 R	18.70	4.93	5.00
P 10 - 40, s 4,5	290023 R	20.50	4.93	5.00
P 10 - 63, s 7	290016 R	25.20	5.97	6.00
P 50 - 315, s 11	290116 R	35.30	10.95	8.00
P 50 - 315, s 16	290216 R	45.30	10.95	8.00
P 50 - 315, s 19	290316 R	51.30	10.95	8.00
W INOX 10 - 32/40 S	113461 R	26.60	4.93	5.00

German Quality Products



Powerful, handy electric tool for cutting pipe and tubing. For trade and industry. For the building site and the workshop.

Stainless steel pipes of pressfitting systems, carbon steel, copper	\varnothing 12–28 mm \varnothing 10–35 mm
Multilayer composite pipes	\varnothing 10–40 mm

REMS Nano – cutting up to \varnothing 40 mm.

**Ultra-light. Fast. Right angled. Chip-free.
Without outer burr. Dry.**

Ideal for pressfitting systems

Right angled cutting, according to requirements

Chip-free, no chips in piping system

No outer burr, no damage to O-ring by outer burr

Dry cutting, no damage to O-rings from lubricants

Fast, prevents degradation of pipe material through overheating.

Design

Mobile, electric pipe cutting machine for fast, right angled cutting without outer burr. Handy and light, only 1.9 kg. Also for fixing to the workbench or in the vice. Strong, torsion-free aluminium structure for right angled cutting. Easy cutting of the pipes by specially designed cutter wheel. Powered cutter wheel for fast cutting. Energy-saving in-feed due to ergonomically designed pressing lever. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Pipe support

3 sturdy, specially arranged counter-pressure rollers made of hardened precision steel for low-friction turning and safe guidance of the pipes to be cut in the whole working range \varnothing 10–40 mm and for optimisation of the contact points of the cutting wheel on the pipe to be cut (**Patent EP 2 077 175**). No setting.

Drive

Robust gear precisely mounted in ball and needle bearings, maintenance-free. Proven DC motor 230 V, 130 W. Powerful. e.g. copper pipe \varnothing 22 mm in only 3 s. Ideal speed 130 rpm for optimum cutting speed of the pipes. Safety switch.

REMS cutter wheels

Top German quality. Cutter wheels specially designed to the performance capability of the REMS Nano and for numerous pipe materials with variable cutting geometries for fast cutting with no outer burr. Specially hardened, from proven, through-hardened REMS die-steel, ensuring long service life.

Patent EP 2 077 175



German Quality Product



Info




Supply format

REMS Nano Basic-Pack. Electric pipe cutting machine for fast, right angled cutting of pipes \varnothing 10–40 mm, without outer burr. For pipes of the press fitting systems made of stainless steel, carbon steel, \varnothing 12–28 mm, copper \varnothing 10–35 mm. Multilayer composite tubes \varnothing 10–40 mm. With maintenance-free gear, proven DC motor 130 V, 50–60 Hz, 200 W. Speed 130 rpm. Back pressure rollers made of hardened precision steel. Safety switch. Single open ended wrench size 8. Without cutter wheel. In carrying bag.

	Art.-No.	€
	844010R220	529,38

Accessories

Description	Art.-No.	€
REMS cutter wheel Cu-INOX for stainless steel pipes of pressfitting systems, copper, carbon steel	844050R	38,20
REMS cutter wheel V for multilayer composite pipes	844051R	38,20
Carrying bag	574436R	38,41
L-Boxx system case with inlay for REMS Nano/ Nano 12V, rapid charger, battery, REMS REG 8–35, 2x REMS cutter wheels, metre rule	844045R	146,36
REMS Jumbo , folding workbenches, see page 106.		
REMS Herkules , material supports, see page 107.		



REMS Nano 12V

Cordless pipe cutter

Powerful, mobile, handy electric tool for cutting pipe and tubing. For trade and industry. For the building site and the workshop.

Stainless steel pipes of pressfitting systems, carbon steel, copper	Ø 12–28 mm Ø 10–35 mm
Multilayer composite pipes	Ø 10–40 mm

REMS Nano 12V – cutting up to Ø 40 mm. Mobile, handy, ultra-light. Fast. Right angled. Chip-free.

Without outer burr. Dry.

Ideal for pressfitting systems

Right angled cutting, according to requirements

Chip-free, no chips in piping system

No outer burr, no damage to O-ring by outer burr

Dry cutting, no damage to O-rings from lubricants

Fast, prevents degradation of pipe material through overheating.

Design

Mobile, battery-powered pipe cutting machine for fast, right angled cutting without outer burr. Handy and light, only 2.1 kg. Also for fixing to the workbench or in the vice. Strong, torsion-free aluminium structure for right angled cutting. Easy cutting of the pipes by specially designed cutter wheel. Powered cutter wheel for fast cutting. Energy-saving in-feed due to ergonomically designed pressing lever. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Pipe support

3 sturdy, specially arranged counter-pressure rollers made of hardened precision steel for low-friction turning and safe guidance of the pipes to be cut in the whole working range Ø 10–40 mm and for optimisation of the contact points of the cutting wheel on the pipe to be cut (**Patent EP 2 077 175**). No setting.

Drive

Robust, precision ball and needle bearing gears, maintenance-free. Powerful battery motor 12V, with large power reserve, 270 W output. Super fast, e.g. copper pipe Ø 22 mm in just 3 s. Ideal speed 130 rpm for optimum cutting speed of the pipes. Safety switch.

Li-Ion technology

Battery Li-Ion 12V with 2.5 Ah capacity. Light and powerful. High energy density for many cuts. Overheating and overloading protection by temperature monitor (NTC). Rapid charger 220–240V, 10.8–18V, 65W, for short charging times. No memory effect for maximum battery performance.

REMS cutter wheels

Top German quality. Cutter wheels specially designed to the performance capability of the REMS Nano 12V and for numerous pipe materials with variable cutting geometries for fast cutting with no outer burr. Specially hardened, from proven, through-hardened REMS die-steel, ensuring long service life.

Supply format

REMS Nano 12V Basic-Pack. Electric pipe cutting machine for fast, right angled cutting of pipes Ø 10–40 mm, without outer burr. For pipes of the press fitting systems made of stainless steel, carbon steel, Ø 12–28 mm, copper Ø 10–35 mm. Multilayer composite tubes Ø 10–40 mm. With maintenance-free gear, powerful battery motor 12V, 270 W. Speed 130 rpm. Safety switch. Battery Li-Ion 12V, 2.5 Ah, rapid charger 220–240V, 50–60 Hz, 10.8–18V, 65W. Counter pressures rollers made of hardened precision steel. Single open ended wrench size 8. Without cutting wheel. In carrying bag.

	Art.-No.	€
	844011R220	705,84


Accessories

Description	Art.-No.	€
REMS cutter wheel Cu-INOX for stainless steel pipes of pressfitting systems, copper, carbon steel	844050R	38,20
REMS cutter wheel V for multilayer composite pipes	844051R	38,20
Battery Li-Ion 12V, 2.5 Ah	844510R12	139,09
Rapid charger 220–240V, 50–60Hz, 10.8–18V, 65W	571560R220	154,66
Carrying bag	574436R	38,41
L-Boxx system case with inlay for REMS Nano/ Nano 12V, rapid charger, battery, REMS REG 8–35, 2 x REMS cutter wheels, metre rule	844045R	146,36

REMS Jumbo, folding workbenches, see page 106.

REMS Herkules, material supports, see page 107.

Patent EP 2 077 175



German Quality Product



Info



Light, portable compact machine. Universal for cutting and deburring pipes. For trade and industry.

For the building site and the workshop.

Stainless steel pipes of pressfitting systems, carbon steel, copper Ø 8–108 mm

Steel pipes EN 10255 (DIN 2440) DN 6–100
Ø 1/8–4", Ø 10–115 mm

Cast iron pipes (SML) EN 877 (DIN 19522) DN 50–100

Plastic pipes SDR 11
Wall thickness s ≤ 10 mm Ø 10–110 mm
Ø 1/8–4"

Multilayer composite pipes Ø 10–110 mm

REMS Cento RF Set

Welded drain pipe/down pipe made of stainless steel (EN 1124) Ø 40–110 mm

REMS Cento – Cutting and deburring up to Ø 115 mm. Super fast. Right angled. Chip-free. No outer burr. Dry cutting.

Universal for many pipe types.

Ideal for pressfitting systems

Right angled cutting, according to requirements

Chip-free, no chips in piping system

No outer burr, no damage to O-ring by outer burr

Dry, no damage to the O-ring by coolants-lubricants.

Fast, prevents degradation of pipe material through overheating.

Design

Compact, mobile pipe cutting machine for fast, right angled, cutting with no outer burr. Handy and light, only 16.8 kg. Stable, distortion-free cast construction for right angled cutting. Easy pipe-cutting through specially designed cutter wheel. Powered cutter wheel and linear advance for fast cutting (**Patent EP 1 782 904**). Power saving feed-in through easy to grip, proven advance-lever and needle bearing mounted machine screw spindle. Cutter wheel protected – as movement restricted to before any contact with the rollers. Connection for driving outer/inner pipe deburrer REMS REG 10–54 E. For workbench, stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning. An alternative feed lever is available for operating the drive unit on the floor, see accessories.

Running rollers

4 strong hardened precision tubular steel running rollers on ball bearings for low-friction turning of the pipes Ø 22–115 mm, Ø 3/4–4" to be cut, trapezoidally arranged, replaceable. No setting work required in the whole working range Ø 22–115 mm. Stainless tubular steel rollers as accessory. Cutting of pipes Ø 8–22 mm by placing two pipe sections Ø 28×220 mm on the running rollers. REMS Cento RF with 4 sturdy polyamide rollers mounted on ball bearings, to avoid damage to the pipe surfaces, for low-friction rotation of the welded drain pipes/downpipes of stainless steel (EN 1124) Ø 40–110 mm to be cut; pipe guides Ø 75 and 110 mm prevent the pipe from becoming oval shaped.

Drive

Robust gear, precisely mounted in roller and needle bearings, maintenance-free. Proven universal motor, 1200 W. Powerful, e.g. stainless steel pipe Ø 54 mm in just 4 s. Ideal speed 115 rpm for optimum cutting speed of the pipes. Safety foot-switch with emergency stop.

REMS cutter wheels

Top German quality. Cutter wheels specially designed to the performance capability of the REMS Cento and for numerous pipe materials with variable cutting geometries for fast cutting with no outer burr. Specially hardened, from proven, through-hardened REMS die-steel, ensuring long service life.

Pipe support

Pipe support, height adjustable, for pipes Ø 40–110 mm, Ø 1 1/2–4", with operation of the drive unit with feed lever on the floor. Easy moving of the material in all directions when turning, pulling and pushing by four stainless steel balls mounted in a rust-protected housing. Safe guiding of long pipes by use of several pipe supports.



REMS pipe deburrer

Inner pipe deburrer REMS REG 28–108 for pipes Ø 28–108 mm, Ø 3/4–4", with circulating friction element on the deburrer housing (**Patent EP 2 500 122**) for electrical rotary drive by the cutting wheel of the REMS Cento, REMS Cento 22V pipe cutting machine, as an accessory. Outer/inner pipe deburrer REMS REG 10–54 E for pipes Ø 10–54 mm, Ø 1/2–2 1/8", for electric drive with the REMS Cento, REMS Cento 22V pipe cutting machines, see page 99.

Marking device

Marking device for marking the insertion depth for fittings on pipes, as an accessory.

Patent EP 1 782 904



German Quality Product



Supply format

REMS Cento Basic. Pipe cutting machine for fast, right angled, cutting of pipes with no outer burr Ø 8–115 mm. For pipes of the press fitting systems made from stainless steel, carbon steel, copper, Ø 8–108 mm. For steel pipes EN 10255 (DIN 2440) DN 6–100, Ø ½–4", Ø 10–115 mm, cast pipes (SML) EN 877 (DIN 19522) DN 50–100, plastic tubes SDR 11, wall thickness s ≤ 10 mm, Ø 10–110 mm, Ø ½–4", composite tubes Ø 10–110 mm. With maintenance-free gear, proven universal motor 230 V or 110 V, 50–60 Hz, 1200 W. Speed 115 rpm. Rollers in hardened precision steel pipe for pipes Ø 22–115 mm, Ø ¾–4". Safety foot-switch. Ring spanner. Without cutter wheel. For workbench, stand or wheel stand. In a carton.

	Art.-No.	€
	845001R220	1 463,58

Other voltages on request.



Supply format

REMS Cento RF Set. Pipe cutting machine especially for fast, right-angled cutting of welded drain pipes/down pipes made of stainless steel (EN 1124) Ø 40–110 mm. As Art. No. 845001, but with rollers made of polyamide and pipe guides Ø 75 and 110 mm. Safety foot switch. Ring spanner. With cutting wheel RF. For workbench, stand or wheel stand. In a carton.

	Art.-No.	€
	845003R220	2 324,08

Other voltages on request.



Accessories

Description	Art.-No.	€
Feed lever with spring plug for operating the drive unit on the floor (for drive units manufactured from 2014 onwards).	845218R	91,66
REMS cutter wheel Cu-INOX for stainless steel pipes of pressfitting systems, copper, carbon steel	845050R	111,07
REMS cutter wheel Cu specially for pipes of copper pressfitting systems	845053R	111,07
REMS cutter wheel St for steel pipes, cast iron pipes (SML)	845052R	111,07
REMS cutter wheel V for plastic and multilayer composite pipes, wall thickness s ≤ 10 mm	845051R	111,07
REMS cutting wheel C-SF especially for pipes of the pressfitting systems and push fitting systems made from carbon steel, simultaneously produces a chamfer.	845055R	111,07
REMS cutting wheel RF for cutting welded drain pipes/down pipes made of stainless steel (EN 1124) with REMS Cento RF.	845054R	111,07
Pipe support 1 , height adjustable, for pipes Ø 40–110 mm, Ø 1 ½–4", with operation of the drive unit with feed lever on the floor	845220R	152,59
Hardened, precision tubular steel rollers (pack of 4)	845118R	214,87
Stainless tubular steel INOX rollers (pack of 4)	845110RINOX	303,10
Polyamide roller (pack of 4)	845131RPA	355,00
Marking device for marking the insertion depth for fittings on pipes. For REMS Cento, REMS Cento 22V.	845530R	129,75

REMS REG 10–54 E, outer/inner pipe deburrer, see page 99

REMS REG 28–108 , inner pipe deburrer for pipes Ø 28–108 mm, Ø ½–4", for electric rotary drive by the cutting wheel of the REMS Cento, REMS Cento 22V pipe cutting machine (with REMS cutting wheel Art. No. 845050 or 845053).	113840R	333,20
Stand	849315R	216,94
Wheel stand	849310R	351,88
REMS Jumbo , folding workbenches, see page 106.		
REMS Herkules , material supports, see page 107.		
L-Boxx H system case for REMS Cento/Cento RF	845085R	142,73



REMS Cento 22 V

Cordless pipe cutting machine

Light, mobile compact machine. Universal for cutting and deburring pipes. For trade and industry. For the building site and the workshop. Li-Ion 22V Technology. For battery and corded operation.

Stainless steel pipes of pressfitting systems, carbon steel, copper	Ø 8 – 108 mm
Steel pipes EN 10255 (DIN 2440)	DN 6 – 100
	Ø 1 1/8 – 4", Ø 10 – 115 mm
Cast iron pipes (SML) EN 877 (DIN 19522)	DN 50 – 100
Plastic pipes SDR 11	
Wall thickness s ≤ 10 mm	Ø 10 – 110 mm
	Ø 1 1/8 – 4"
Multilayer composite pipes	Ø 10 – 110 mm

REMS Cento 22 V – Mobile cutting and deburring up to Ø 115 mm. Super fast. Right angled. Chip-free. No outer burr. Dry cutting. Li-Ion 22 V Technology. Li-Ion 21.6 V, 5.0 Ah battery, for approx. 280 stainless steel pipe sections of the Ø 22 mm press fitting systems with one battery charge*.

Universal for many pipe types.

Ideal for pressfitting systems

Right angled cutting, according to requirements
Chip-free, no chips in piping system
No outer burr, no damage to O-ring by outer burr
Dry, no damage to the O-ring by coolants-lubricants.
Fast, prevents degradation of pipe material through overheating.

Design

Compact, mobile cordless pipe cutting machine for fast, right angled, cutting with no outer burr. Handy and light, drive unit with battery only 17.6 kg. Stable, distortion-free cast construction for right angled cutting. Easy pipe-cutting through specially designed cutter wheel. Powered cutter wheel and linear advance for fast cutting (**Patent EP 1 782 904**). Power saving feed-in through easy to grip, proven advance-lever and needle bearing mounted machine screw spindle. Cutter wheel protected – as movement restricted to before any contact with the rollers. Practical handle for easy transport. Connection for driving outer/inner pipe deburrer REMS REG 10 – 54 E. For workbench, stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning. An alternative feed lever is available for operating the drive unit on the floor, see accessories.

Running rollers

4 strong hardened precision tubular steel running rollers on ball bearings for low-friction turning of the pipes Ø 22–115 mm, Ø 3/8–4" to be cut, trapezoidally arranged, replaceable. No setting work required in the whole working range Ø 22–115 mm. Stainless tubular steel rollers as accessory. Cutting of pipes Ø 8–22 mm by placing two pipe sections Ø 28 × 220 mm on the running rollers.

Drive

Robust gear, precisely mounted in roller and needle bearings, maintenance-free. Powerful 21.6 V battery motor, e.g. stainless steel pipe Ø 54 mm in just 7 s. Ideal speed 84 rpm for optimum cutting speed of the pipes. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check with charging level indication by a 2-coloured green/red LED. Safety foot-switch with emergency stop.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 4.4 Ah battery for approx. 246 stainless steel pipe sections, 5.0 Ah battery for approx. 280 stainless steel pipe sections, 9.0 Ah for approx. 520 stainless steel pipe sections of the Ø 22 mm press fitting systems with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 40A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.


REMS cutter wheels

Top German quality. Cutter wheels specially designed to the performance capability of the REMS Cento 22V and for numerous pipe materials with variable cutting geometries for fast cutting with no outer burr. Specially hardened, from proven, through-hardened REMS die-steel, ensuring long service life.

Pipe support

Pipe support, height adjustable, for pipes Ø 40–110 mm, Ø 1 1/8–4", with operation of the drive unit with feed lever on the floor. Easy moving of the material in all directions when turning, pulling and pushing by four stainless steel balls mounted in a rust-protected housing. Safe guiding of long pipes by use of several pipe supports.

Patent EP 1 782 904



German Quality Product



REMS pipe deburrer

Inner pipe deburrer REMS REG 28–108 for pipes Ø 28–108 mm, Ø $\frac{3}{4}$ –4", with circulating friction element on the deburrer housing (**Patent EP 2 500 122**) for electrical rotary drive by the cutting wheel of the REMS Cento, REMS Cento 22V pipe cutting machine, as an accessory. Outer/inner pipe deburrer REMS REG 10–54 E for pipes Ø 10–54 mm, Ø $\frac{1}{2}$ – $\frac{1}{4}$ ", for electric drive with the REMS Cento, REMS Cento 22V pipe cutting machines, see page 99.

Marking device

Marking device for marking the insertion depth for fittings on pipes, as an accessory.

Supply format

REMS Cento 22 V Basic. Cordless pipe cutting machine for fast, right angled, cutting of pipes with no outer burr Ø 8–115 mm. For pipes of the press fitting systems made from stainless steel, carbon steel, copper, Ø 8–108 mm. For steel pipes EN 10255 (DIN 2440) DN 6–100, Ø $\frac{1}{8}$ –4", Ø 10–115 mm, cast pipes (SML) EN 877 (DIN 19522) DN 50–100, plastic tubes SDR 11, wall thickness s ≤ 10 mm, Ø 10–110 mm, Ø $\frac{1}{8}$ –4", composite tubes Ø 10–110 mm. With maintenance-free gear, powerful 21.6 V battery motor. Speed 84 rpm. Machine status check with overload protection, temperature monitoring, battery charging status check. Rollers in hardened precision steel pipe for pipes Ø 22–115 mm, Ø $\frac{3}{4}$ –4". Safety foot-switch. Li-Ion 21.6 V, 5.0 Ah battery, 100–240V, 50–60 Hz, 90W rapid charger. Ring spanner. Without cutter wheel. For workbench, stand or wheel stand. In a carton.

	Art.-No.	€
	845002R220	2 055,24

Other voltages on request.

Accessories

Description	Art.-No.	€
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 40 A, for mains operation instead of battery Li-Ion 21.6 V	571578R220	517,96
Feed lever with spring plug for operating the drive unit on the floor.	845218R	91,66
REMS cutter wheel Cu-INOX for stainless steel pipes of pressfitting systems, copper, carbon steel	845050R	111,07
REMS cutter wheel Cu specially for pipes of copper pressfitting systems	845053R	111,07
REMS cutter wheel St for steel pipes, cast iron pipes (SML)	845052R	111,07
REMS cutter wheel V for plastic and multilayer composite pipes, wall thickness s ≤ 10 mm	845051R	111,07
REMS cutting wheel C-SF especially for pipes of the pressfitting systems and push fitting systems made from carbon steel, simultaneously produces a chamfer.	845055R	111,07
Pipe support 1 , height adjustable, for pipes Ø 40–110 mm, Ø $\frac{1}{2}$ –4", with operation of the drive unit with feed lever on the floor	845220R	152,59

Hardened, precision tubular steel rollers (pack of 4)	845118R	214,87
--	---------	---------------

Stainless tubular steel INOX rollers (pack of 4)	845110RINOX	303,10
---	-------------	---------------

Marking device for marking the insertion depth for fittings on pipes. For REMS Cento, REMS Cento 22 V.	845530R	129,75
---	---------	---------------

REMS REG 10–54 E , outer/inner pipe deburrer, see page 99		
--	--	--

REMS REG 28–108 , inner pipe deburrer for pipes Ø 28–108 mm, Ø $\frac{3}{4}$ –4", for electric rotary drive by the cutting wheel of the REMS Cento, REMS Cento 22V pipe cutting machine (with REMS cutting wheel Art. No. 845050 or 845053).	113840R	333,20
---	---------	---------------

Stand	849315R	216,94
--------------	---------	---------------

Wheel stand	849310R	351,88
--------------------	---------	---------------

REMS Jumbo, folding workbenches, see page 106.

REMS Herkules, material supports, see page 107.

REMS Lumen 2800 22V, cordless LED flood light, see page 111



Robust, mobile compact machine. Universal for cutting pipes. For trade and industry. For the building site and the workshop.

Stainless steel pipes of pressfitting systems, carbon steel, copper	\varnothing 54–225 mm
Steel pipes EN 10255 (DIN 2440)	DN 40–150 \varnothing 1½–6"
Cast iron pipes (SML) EN 877 (DIN 19522)	DN 50–200
Plastic pipes SDR 11	
Wall thickness s \leq 21 mm	\varnothing 40–225 mm
Multilayer composite pipes	\varnothing 40–110 mm

REMS DueCento – Cutting up to \varnothing 225 mm.

Right angled. Chip-free. Ready for welding. Fast.

No outer burr. Dry cutting.

Universal for many pipe types.

Right angled cutting, according to requirements

Chip-free, no chips in the pipe system, no dust

Weldable, for muff and butt welds

Fast, without impairment of the pipe material by overheating

Without outside burr, easy insertion into connecting muffs

Dry cutting, without impairment by coolant lubricants

Design

Compact, mobile pipe cutting machine for fast, right angled, cutting with no outer burr. Handy and easily transportable, only 37 kg. Stable, distortion-free cast construction for right angled cutting. Easy pipe-cutting through specially designed cutter wheel. Powered cutter wheel and linear advance for fast cutting (**Patent EP 1 782 904**). Power saving feed-in through easy to grip, proven advance-lever and needle bearing mounted machine screw spindle. Cutter wheel protected – as movement restricted to before any contact with the rollers. Practical chassis with two rubber tyred wheels for easy transport.

Running rollers

4 strong hardened precision tubular steel running rollers on ball bearings for low-friction turning of the pipes to be cut, arranged in convex square for centred thrust pressure of the cutting wheel in the working range \varnothing 100–225 mm, \varnothing 4–6", without setting work (**Patent EP 2 740 556**). Roller insert for cutting pipes \varnothing 40–110 mm, \varnothing 1½–4", as an accessory.

Drive

Robust gear, precisely mounted in roller and needle bearings, maintenance-free. Proven universal motor, 1200 W. Powerful, e.g. plastic tube PE \varnothing 225 mm in just 15 s. Ideal speed 115 rpm for optimum cutting speed of the pipes. Safety foot-switch with emergency stop.


REMS cutter wheels

Top German quality. Cutter wheels specially designed to the performance capability of the REMS DueCento and for numerous pipe materials with variable cutting geometries for fast cutting with no outer burr. Specially hardened, from proven, through-hardened REMS die-steel, ensuring long service life.

Pipe supports

Pipe supports, height adjustable, for pipes \varnothing 40–110 mm, \varnothing 1½–4" and \varnothing 100–225 mm, \varnothing 4–8". Easy moving of the material in all directions when turning, pulling and pushing by four stainless steel balls mounted in a rust-protected housing. Safe guiding of long pipes by use of several pipe supports.

Patent EP 1 782 904
Patent EP 2 740 556



German Quality Product



Info



Supply format

REMS DueCento Basic. Pipe cutting machine for fast, right angled cutting of pipes Ø 40–225 mm, without outside burr. For pipes of the press fitting systems made from stainless steel, carbon steel, copper, Ø 54–225 mm. For steel pipes EN 10255 (DIN 2440) DN 40–150, Ø 1½–6", cast pipes (SML) EN 877 (DIN 19522) DN 50–200, plastic tubes SDR 11, wall thickness s ≤ 21 mm, Ø 40–225 mm, Ø 1¼–8", composite tubes Ø 40–110 mm. With maintenance-free gears, proven universal motor 110 / 230 V, 50–60 Hz, 1,200 W. Speed 115 rpm. Hardened, precision tubular steel rollers for pipes Ø 100–225 mm, Ø 4–6". Safety foot switch. Ring spanner. Without cutter wheel. 2 height adjustable pipe supports 1 for pipes Ø 100–225 mm, Ø 4–8". In a carton.

	Art.-No.	€
	845004R220	2 896,02

Other voltages on request.



Accessories

Description	Art.-No.	€
REMS cutter wheel Cu-INOX for stainless steel pipes of pressfitting systems, copper, carbon steel	845050R	111,07
REMS cutter wheel Cu specially for pipes of copper pressfitting systems	845053R	111,07
REMS cutter wheel St for steel pipes, cast iron pipes (SML)	845052R	111,07
REMS cutting wheel C-SF especially for pipes of the pressfitting systems and push fitting systems made from carbon steel, simultaneously produces a chamfer.	845055R	111,07
REMS cutter wheel V, s 10 for plastic and multilayer composite pipes, wall thickness s ≤ 10 mm	845051R	111,07
REMS cutter wheel P, s 21 for plastic and multilayer composite tubes, wall thickness s ≤ 21 mm	845057R	140,13
Pipe support 1 , height adjustable for pipes Ø 100–225 mm, Ø 4–8"	845220R	152,59
Pipe support 2 , height adjustable, for pipes Ø 40–110 mm, Ø 1½–4" (roller insert required)	845230R	152,59
Roller insert for cutting pipes Ø 40–110 mm, Ø 1½–4"	845060R	242,89



Robust quality tool for clean, fast cutting of pipes in one cut. Stable magnesium version. For one-hand operation.	
Flexible plastic hoses, soft plastic pipes	$\leq \varnothing 28\text{ mm}$ $\leq \varnothing 1\frac{1}{8}\text{"}$

REMS ROS P flex – Fast cutting in one cut. Ideal for cutting flexible plastic hoses and soft plastic pipes.

Stable magnesium version, extremely light.

Ergonomically designed handles for fast cutting in one cut.
For one-hand operation.

Blade drawback by spring-loaded articulated lever.

Specially hardened and specially ground, wedge-shaped blade with cutting angle of 110°, PTFE-coated. Ideal for cutting hoses and soft plastic pipes.

Right-angled, burr-free cutting by pipe rests on both sides and bilaterally clamped blade.

One-hand locking for safe transport and protection of the blade.

Chip-free cutting – no chips left in the pipe.

REMS ROS P flex 28 S with softgrip. Needle bearing-mounted articulated lever for easy cutting in one step.



Supply format

REMS ROS P flex. One-hand pipe shears for flexible plastic hoses and soft plastic pipes. With blade. In blister pack.

Description	Pipes $\leq \varnothing$ mm/inch	Art.-No.	€
P flex 14	14 $\frac{9}{16}\text{"}$	291400R	53,46
P flex 22	22 $\frac{7}{8}\text{"}$	291410R	59,79
P flex 28 S on needle bearings	28 $1\frac{1}{8}\text{"}$	291430R	84,08

Accessories

Description	Art.-No.	€
Blade P flex 14 for REMS ROS P flex 14	291401R	26,73
Blade P flex 22 for REMS ROS P flex 22	291411R	29,84
Blade P flex 28 for REMS ROS P flex 28 S	291431R	33,58



REMS ROS P 26/SW 35 S

One-hand pipe shears

Robust quality tool for clean, fast cutting of pipes in one cut. With integrated pipe cutter for protective corrugated tubes. Stable magnesium version. For one-hand operation.

Plastic tubes, composite tubes $\leq \varnothing 26 \text{ mm}$
 $\leq \varnothing 1"$

Protective corrugated plastic tubes $\varnothing 18-35 \text{ mm}$
 $\varnothing \frac{3}{4}-\frac{13}{8}"$

REMS ROS P 26/SW 35 S – Universal for many materials. Ideal for cutting composite pipes and PEX pipes. Fast cutting in one cut. With integrated pipe cutter for protective plastic corrugated tube.

Stable magnesium version, extremely light.

Ergonomically designed handles with softgrip for fast cutting in one cut. For one-hand operation.

Needle bearing-mounted articulated lever for easy cutting in one step.

Blade drawback by spring-loaded articulated lever.

One-hand locking for safe transport and protection of the blade.

Specially hardened and specially ground, rounded blade for low-wear working, PTFE-coated. 4 counter pressure rollers on needle bearings. For easy swivelling of the pipe shears during the cutting process. Ideal for cutting composite pipes, PEX pipes and similar.




Right-angled, burr-free cutting by extra-wide pipe rests on both sides and bilaterally clamped blade.

Cutting of protective corrugated pipes by 4 cutting tools at the end of the handle.

Three-edged, wedge-shaped cutting tools with a cutting angle of 120°, rotatable 3 times by 120° for three times longer life.

Cutting depth limiting of the cutting tools during cutting of corrugated protective pipes prevents damage to the inside of the pipe.

Chip-free cutting – no chips left in the pipe.



Info

Supply format

REMS ROS P 26/SW 35 S. One-hand pipe shears for plastic and composite pipes with integrated pipe cutter for plastic corrugated protective pipes. 4 counter pressure rollers on needle bearings. With blade and 4 cutting tools. In blister pack.

	Pipes $\leq \varnothing \text{ mm/inch}$	Art.-No.	€
	P 26/1" SW 35/1½"	291242R	116,26

Accessories

Description	Art.-No.	€
Blade P 26/SW 35 for REMS ROS P 26/SW 35 S	291243R	46,50
Cutting tool P26/SW 35, pack of 4 for REMS ROS P 26/SW 35 S	291244R	46,50



REMS ROS P/PEX

One-hand pipe shears

Robust quality tool for clean, fast cutting of pipes in one cut. Stable magnesium version. For one-hand operation.
Plastic pipes, multilayer composite pipes $\leq \varnothing 26\text{ mm}$
 $\leq \varnothing 1"$

REMS ROS P 26 – fast cutting in one cut.

Stable magnesium version, extremely light.
Ergonomically designed handles for fast cutting in one cut.
For one-hand operation.
Blade drawback by spring-loaded articulated lever.
One-hand locking for safe transport and protection of the blade.
Specially hardened and specially ground blade, PTFE-coated.
Right-angled, burr-free cut by pipe rest on both sides and blade guided on both sides.
Chipless cutting – no chips remaining in pipe.



Supply format

REMS ROS P 26. One-hand pipe shears for plastic and multilayer composite tubes. With blade. In blister pack.

	Pipes $\leq \varnothing$ mm/inch	Art.-No.	€
	26 1"	291240R	57,30

Robust quality tool for clean, fast cutting of pipes in one cut. Stable magnesium version. For one-hand operation.

PEX pipes and similar $\leq \varnothing 28\text{ mm}$
 $\leq \varnothing 1\frac{1}{8}"$

REMS ROS PEX 28 S – fast cutting in one cut.

Ideal for cutting PEX pipes.

Stable magnesium version, extremely light.
Ergonomically designed handles with softgrip for fast cutting in one cut.
For one-hand operation.
Needle bearing-mounted articulated lever for easy cutting in one step.
Blade drawback by spring-loaded articulated lever.
One-hand locking for safe transport and protection of the blade.
Specially hardened and specially ground, wedge-shaped blade with cutting angle of 150° for low-wear working, PTFE-coated. Ideal for cutting PEX pipes.
Right-angled, burr-free cut by pipe rest on both sides and blade guided on both sides.
Chipless cutting – no chips remaining in pipe.



Supply format

REMS ROS PEX 28 S. One-hand pipe shears for PEX pipes, on needle bearing. With blade. In blister pack.

	Pipes $\leq \varnothing$ mm/inch	Art.-No.	€
	28 / 1 $\frac{1}{8}"$	291420R	87,30

Accessories

Description	Art.-No.	€
Blade P 26 for REMS ROS P 26	291241R	22,94
Blade PEX 28 for REMS ROS PEX 28 S	291421R	34,82



REMS ROS P

One-hand pipe shears with ratchet feed/
pipe shears with ratchet feed

Handy quality tools for clean, fast pipe cuts. For thin-walled pipes also. Sturdy aluminium/ magnesium version. For single-hand operation.	
Plastic pipes, multi-layer composite tubes	≤ Ø 63 mm ≤ Ø 2"

REMS ROS P 35 / ROS P 35 A / ROS P 42 / ROS P 42 PS / ROS P 42 S / ROS P 63 P / ROS P 63 S

Sturdy aluminium version, REMS ROS P 42 S and magnesium (Mg) version P 63 S, ultra light.

Specially hardened, wedge-shaped blade, also for thin-walled pipes.
For single-hand operation. Effortless working through power transmitting ratchet feed.

Quick reverse saves time and effort. REMS ROS P 35 A with automatic quick reverse after completion of cutting.

Right angle, burr-free cut through exact pipe support and guided blade on both sides.


Chipless cutting – no chips remaining in pipe.



Supply format

REMS ROS P. One-hand pipe shears for plastic pipes and multi-layer composite tubes. With blade. In blister pack/in box.

Description	Pipes ≤ Ø mm/inch	Art.-No.	€
P 35 with quick reverse	35 1 1/8"	291200R	62,07
P 35 A with automatic quick reverse	35 1 1/8"	291220	79,10
P 42 with quick reverse	42 1 1/8"	291250R	135,98
P 42 PS with quick reverse	42 1 1/8"	291000RPS	83,87
P 42 S with quick reverse	42 1 1/8"	291010R	94,46
P 63 P with quick reverse	63 2"	291270R	165,04
P 63 S with quick reverse	63 2"	291290R	180,61



Robust quality tools for clean, fast pipe cuts.

Robust steel version.

Plastic pipes

≤ Ø 75 mm, ≤ Ø 2 1/2"

REMS ROS P 75 P

Robust steel version for rugged conditions and long life, with end stop for powerful engagement, also ideal for thick-walled plastic pipes.

Rough, non-slip handle for good grip.

Specially hardened and specially ground, wedge-shaped blade with cutting angle of 150° for low-wear working.

Fast, easy operation through guided ratchet on both sides and fine-toothed ratchet gear, specially hardened.

Right angle, burr-free cut through two-point pipe support and guided blade on both sides.

Chipless cutting – no chips remaining in pipe.



Supply format


REMS ROS P 75 P. Pipe shear for plastic pipes. With blade. In a carton.

Description	Pipes ≤ Ø mm/inch	Art.-No.	€
	75 / 2 1/2"	291101R	360,19



Accessories

Description	Art.-No.	€
Blade P 35 for REMS ROS P 35	291201	24,91
Blade P 35 A for REMS ROS P 35 A	291221	31,66
Blade P 42 for REMS ROS P 42	291251	54,39
Blade P 42 PS for REMS ROS P 42 PS	291023	33,63
Blade P 42 S for REMS ROS P 42 S	291036R	41,94
Blade P 63 P for REMS ROS P 63 P	291271	66,02
Blade P 63 S for REMS ROS P 63 S	291037R	66,02
Blade P 75 P for REMS ROS P 75 P	291112	144,28



REMS Cut 110 P

Pipe cutting and pipe chamfering tool

Robust quality tool for right-angle, plain cutting and chamfering (15°) in one operation. Can be used anywhere, free-hand, on parallel vice or work bench.

Plastic pipes in
ABS, PB, PE, PE-HD, PE-X,
PP, PVC, PVDF

\varnothing 40 – 110 mm

REMS Cut 110 P – cutting and chamfering at the same time.

Robust metal design for tough use.

Cutting and chamfering in one operation. While turning the tool shaft, also cutting only possible.

Fast and easy to use, ergonomic clamping grip.

Spring loaded clamp inserts in plastic for concentric clamping of different pipe sizes. Easy to change without tools.

Steplessly adjustable clamping pressure accommodates pipe tolerances.

Cutting and chamfering tool in hard metal with optimum cutter geometry ensures precise cutting and chamfering. Long service life.

Holder for workbench for effortless operation.

Tool set Cu-INOX and clamp inserts for cutting welded rain gutter pipes in copper, titanium zinc, stainless steel, as accessory.



Supply format


REMS Cut 110 P Set. Pipe cutting and pipe chamfering tool for plastic pipes in ABS, PB, PE, PE-HD, PE-X, PP, PVC, PVDF, \varnothing 40–110 mm. Quick clamping device \varnothing 110 mm with 2 each of clamping inserts \varnothing 50 and 75 mm. Tool set P with cutting and chamfering blade P, s 11. In sturdy case.

Description	Art.-No.	€
Set 50 + 75 + 110	290400R	490,97



Accessories

Description	Pipes \varnothing mm	Art.-No.	€
Clamping inserts (pack of 2)			
40	290420	81,90	
50	290421	81,90	
52	290422	81,90	
56	290444	81,90	
58	290423	81,90	
60	290445	81,90	
63	290427	81,90	
75	290424	81,90	
76	290446	81,90	
78	290425	81,90	
80	290447	81,90	
87	290448	81,90	
90	290426	81,90	
100	290449	81,90	
Tool set P with cutting and chamfering blade P, s 11		290432R	86,36
Cutting and chamfering blade P, s 11		290430	34,98
Cutting and chamfering blade P, s 15,5		290431	56,05
Tool set Cu-INOX with cutter wheel Cu-INOX 3–120, s 4		290433R	86,36
REMS cutter wheel Cu-INOX 3–120, s 4		113210R	12,04
Holder for work bench		290440R	92,80
Case		290437	64,36



REMS Cut 110 Cu-INOX

Pipe cutting tool

Robust quality tool for right-angle cutting of welded pipe. Can be used anywhere, free-hand, on parallel vice or work bench.

Welded copper drainpipe/downpipe,
Titanium zinc, stainless steel (EN 1124) Ø 50 – 110 mm

REMS Cut 110 Cu-INOX – Easy cutting of downpipes.

Robust metal design for tough use.

Fast and easy to use, ergonomic clamping grip.

Spring loaded clamp inserts in plastic for concentric clamping of different pipe sizes. Easy to change without tools.

Steplessly adjustable clamping pressure accommodates pipe tolerances.

Cutting and chamfering tool in hard metal with optimum cutter geometry ensures precise cutting and chamfering. Long service life.

Holder for workbench for effortless operation.

Tool set P and clamp inserts for right-angle, plain cutting and chamfering (15°) of plastic pipe, as accessory, see page 94.



Supply format

REMS Cut 110 Cu-INOX Set. Pipe cutter for welded drainpipes/downpipes made of copper, titanium zinc, stainless steel (EN 1124), Ø 50 – 110 mm. Quick action clamp Ø 110 mm with clamp inserts. Tool set Cu-INOX with cutter wheel Cu-INOX 3 – 120, s 4. In sturdy case.

Description	Art.-No.	€
Set 50 + 75 + 110	290412R	533,53
Set 60 + 80 + 100 + 110	290410R	643,56
Set 76 + 87 + 100 + 110	290411R	670,55



Accessories

Description	Art.-No.	€
Clamp inserts, see page 94.		
Tool set Cu-INOX with cutter wheel Cu-INOX 3 – 120, s 4	290433R	86,36
REMS cutter wheel Cu-INOX 3 – 120, s 4	113210R	12,04
Holder for work bench	290440R	92,80



Handy quality tools for simple and fast external chamfering (15°) of pipes.

Plastic pipes	$\varnothing 16 - 250 \text{ mm}, \varnothing \frac{3}{4} - 10"$
---------------	--

Wall thickness	$\leq \text{PN } 16$
----------------	----------------------

REMS RAG – chamfering at 15° .

Chamfering at 15° on commonly used plastic pipes.


Also suited for deburring plastic pipes. Ensures easy joining of sleeves to be welded.

Easily adjusted for pipe diameter and wall thickness.

Very fast and easy chamfering due to a particularly favourable cutting geometry of the chamfering blades.

Two adjacent, identical chamfering blades, one of which cuts the chamfer and the other one serves as a support for the pipe during chamfering. If the cutting chamfering blade is worn, it can be exchanged with the support part, for double the service life.

Easy-to-slide V-block with two different bevel angles for good guidance of small pipe sizes. In high-grade, glass-fibre reinforced polyamide.



German Quality Product



Supply format

REMS RAG. Pipe chamfering tool for plastic pipes. With blades. In a carton.

Description	Pipes $\leq \varnothing$ mm/inch	Art.-No.	€
P 16–110	16–110 / $\frac{3}{4}$ –4"	292110R	213,83
P 32–250	32–250 / 1 $\frac{1}{4}$ –10"	292210R	250,16



Accessories

Description	Art.-No.	€
Chamfering blades (pack of 2) for REMS RAG P 16–250	292011	85,53

REMS REG Universal

Universal deburrer

Universal quality tool for deburring tubes and edges of different materials.

Copper, steel, brass, aluminium, plastic.

REMS REG Universal – the all-purpose deburrer.


Robust metal design for tough use.

Easy handling and good grip thanks to ergonomically designed hexagon handle.

Rotating universal deburrer blade in handle accommodates to the work piece edge to be deburred.

Specially hardened and specially ground universal deburrer blade guarantees easy deburring and long service life.

Fast, simple blade replacement by pulling back the front sliding sleeve.



Supply format

REMS REG Universal. Universal deburrer. For copper, steel, brass, aluminium, plastic. On cardboard.

	Art.-No.	€
	113910R	26,78

Accessories

Description	Art.-No.	€
Universal deburring blade, ground	113360	7,89



REMS REG St ¼ – 2"

Inner pipe deburrer

Robust quality tool for inner pipe deburring.

For electric operation.

Steel pipes and other pipes

Ø ¼ – 2"

REMS REG St ¼ – 2": effortless electric deburring.

Inner pipe deburrer with octagonal attachment head for operating by means of electric die stocks with octagonal seat, e.g. REMS Amigo E, REMS Amigo, REMS Amigo 2, REMS Amigo 2 Compact.

Specially hardened and designed deburring blade ensures easy deburring and extremely long life. Double edges for optimum chip flow, specially for small sizes.



German Quality Product



Supply format

REMS REG St ¼ – 2". Inner pipe deburrer for electric operation.

For steel pipes and other pipes, Ø ¼ – 2". In a carton.

	Art.-No.	€
	731700	150,51

REMS REG 3 – 35

Outer-inner tube deburrer

Sturdy manual tool for outer-inner tube deburring.

Copper, brass, aluminium, steel, plastic tubes

Ø 3 – 35 mm
Ø 1/8 – 1 3/8"

REMS REG 3 – 35 – the sharp edge.

Fast, effortless deburring through 3 specially hardened and ground deburring blades.

Robust housing in shock-proof, resistant plastic.



German Quality Product

Supply format

REMS REG 3 – 35. Outer-inner tube deburrer. For copper, brass, aluminium, steel, plastic tubes, Ø 3 – 35 mm, Ø 1/8 – 1 3/8". In blister pack.

	Art.-No.	€
	113900R	20,03

REMS REG 8 – 35

Outer-inner pipe deburrer

Robust quality tool for removing outer and inner burr from pipes.

Stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes Ø 8 – 35 mm
Ø $\frac{5}{16}$ – $1\frac{3}{8}$ "

REMS REG 8 – 35 – the multiple edge up to Ø 35 mm.

Easy, effortless deburring through multiple blades which are specially hardened and ground.

Robust metal design for tough use.



Supply format

REMS REG 8 – 35. Outer-inner pipe and tube deburrer. For stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes, Ø 8 – 35 mm, Ø $\frac{5}{16}$ – $1\frac{3}{8}$ ". In blister pack.

	Art.-No.	€
113825R	66,95	



REMS REG 10 – 42

Outer-inner pipe deburrer

Robust, solid all-metal tool for outer-inner pipe and tube deburring. For manual or electric operation.

Stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes Ø 10 – 42 mm
Ø $\frac{1}{2}$ – $1\frac{5}{8}$ "

REMS REG 10 – 42 – by hand or electric.

Specially for stainless steel pipes.

Ideal for pipes of all types. Specially for stainless steel tubes of pressfitting systems.

Easy and fast deburring through an appropriate, solid all-metal tool, equipped with 4 specially hardened and ground deburring blades

Driver for electrical drive by REMS Helix 22V VE cordless drill/screwdriver (page 108) and other power drills/screwdrivers (speed ≤ 300 rpm), as an accessory.



German Quality Product



Supply format

REMS REG 10 – 42. Outer-inner pipe and tube deburrer for manual or electric operation. For stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes, Ø 10 – 42 mm, Ø $\frac{1}{2}$ – $1\frac{5}{8}$ ". Without adapter for electric drive. In blister pack.

	Art.-No.	€
113810R	121,45	



Accessories

Description	Art.-No.	€
Adapter for REMS REG 10 – 42	113815R	52,11
REMS Helix 22V VE, cordless drill/screwdriver, see page 108		



REMS REG 10–54

Outer-inner pipe deburrer

Robust quality tool for removing outer and inner burr from pipes.

Stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes Ø 10–54 mm
Ø ½–2⅛"

REMS REG 10–54 – the multiple edge up to Ø 54 mm.

Easy, effortless deburring through multiple blades which are specially hardened and ground.

Robust metal design for tough use.



Supply format

REMS REG 10–54. Outer-inner pipe and tube deburrer. For stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes, Ø 10–54 mm, Ø ½–2⅛". In blister pack.

Art.-No.	€
113830R	76,19



REMS REG 10–54 E

Outer-inner pipe deburrer

Robust quality tool for removing outer and inner burr from pipes. For manual operation or electric drive.

Stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes Ø 10–54 mm
Ø ½–2⅛"

REMS REG 10–54 E – by hand or electrically.

Especially for stainless steel pipes.

Easy, effortless deburring through multiple blades which are specially hardened and ground.

Integrated hexagonal driver for electrical drive by REMS Helix 22VVE cordless drill/screwdriver (page 108) and other power drills/screwdrivers with ¼" bit holders (speed ≤ 300 rpm), by the REMS Cento or REMS Cento 22V pipe cutting machine (page 84–87) and by the REMS Turbo Cu-INOX pipe circular sawing machine (page 70) (Patent EP 2 058 067).

Robust metal design for tough use.



Supply format

REMS REG 10–54 E. Outer-inner pipe and tube deburrer for manual or electric operation. For stainless steel pipes, other steel pipes, copper, brass, aluminium, plastic pipes, Ø 10–54 mm, Ø ½–2⅛". In blister pack.

Art.-No.	€
113835R	140,13

Accessories

Description

REMS Helix 22V VE, cordless drill/screwdriver, see page 108

REMS Cento, pipe cutting machine, see page 84

REMS Cento 22V, cordless pipe cutting machine, see page 86

REMS Turbo Cu-INOX, pipe circular sawing machine, see page 70

REMS KaliGrat E

Calibrating tool and outer-inner pipe deburrer

Robust, quality tool for calibration and outer-inner deburring of pipes. For manual operation or electric drive.

Multi-layer composite tubes Ø 14 – 63 mm

REMS KaliGrat E – simultaneous calibration and outer-inner deburring. Ratchet handle with changeable calibrating and deburring heads, with quick-change holder.


Universally usable for calibration after the cutting/cropping process, for inner deburring, to avoid damaging the fitting O-ring and for outer deburring.

Easy handling and fast feeding due to ergonomically designed plastic handle with ratchet function.

Robust steel version of the calibrating mandrel with integrated deburring blades for heavy-duty applications and long life. The calibrating mandrel and deburring blades are adapted to different pipe dimensions and wall thicknesses. Sturdy sleeve for protecting the calibrating mandrel and deburring blades from damage.

All calibrating and deburring heads with integrated hexagonal connection for manual operation with the REMS KaliGrat E ratchet handle or for electrical drive by the REMS Helix 22V VE cordless power drill/screwdriver (page 108) and other power drills/screwdrivers with $\frac{1}{4}$ " bit holders (speed $\leq 500 \text{ min}^{-1}$).

Quick calibrating and deburring head change by ratchet handle with quick-change holder with spring locking.



Supply format

REMS KaliGrat E Set. Calibrating tool and outer-inner pipe deburrer, for manual operation or electric drive. For Ø 14 – 63 mm composite tubes. Ratchet handle with quick-change holder with spring locking, calibrating and deburring heads. In sturdy case.

Version Ø mm x wall thickness mm	Art.-No.	€
Set 16x2 + 20x2 + 25x2.5/26x3	114000R	341,30
Set Allround 26 14x2 + 16x2 + 16x2.25 + 18x2 + 20x2 + 20x2.25 + 20x2.5 + 25x2.5/26x3	114001R	636,00

Accessories

Description	Art.-No.	€
REMS KaliGrat E ratchet handle, with quick-change holder, for easy driving of the REMS KaliGrat E calibrating and deburring heads	114044R	80,00
REMS KaliGrat E Ø 14x2 mm	114032R	50,70
REMS KaliGrat E Ø 16x2 mm	114033R	60,00
REMS KaliGrat E Ø 16x2.25 mm	114034R	60,00
REMS KaliGrat E Ø 18x2 mm	114035R	56,00
REMS KaliGrat E Ø 20x2 mm	114036R	64,00
REMS KaliGrat E Ø 20x2.25 mm	114037R	64,00
REMS KaliGrat E Ø 20x2.5 mm	114038R	64,00
REMS KaliGrat E Ø 25x2.5/26x3 mm	114039R	75,10
REMS KaliGrat E Ø 32x3 mm	114040R	92,00
REMS KaliGrat E Ø 40x3.5 mm	114041R	118,20
REMS KaliGrat E Ø 50x4 mm	114042R	168,00
REMS KaliGrat E Ø 63x4.5 mm	114043R	308,90
Case with inlay	114030R	62,20
REMS Helix 22V VE, cordless drill/screwdriver, see page 108		



REMS KaliGrat R

Calibrating tools and inner pipe deburrers

Robust, quality tools for calibration and inner deburring of pipes.

Multi-layer composite tubes Ø 16 – 63 mm

REMS KaliGrat R – simultaneous calibration and inner deburring. Ratchet handle with graduated calibrating mandrel with integrated deburring blades.

Universally usable for composite tubes for calibration after the cutting/cropping process and for inner deburring, to avoid damaging the fitting O-ring.

Easy handling and fast feeding due to ergonomically designed plastic handle with ratchet function.

Robust steel version of the calibrating mandrel with integrated deburring blades for heavy-duty applications and long life. The graduated calibrating mandrel and deburring blades are adapted to different pipe dimensions and wall thicknesses.



Supply format

REMS KaliGrat R. Calibrating tool and inner pipe deburrer. For Ø 16 – 63 mm composite tubes. Ratchet handle with calibrating mandrel for different diameters and wall thicknesses, with integrated deburring blades. In blister pack.

Version Ø mm x wall thickness mm	Art.-No.	€
R4 16x2 + 20x2 + 25x2.5/26x3 + 32x3	114045R	97,80
R4 16x2 + 20x2.25 + 25x2.5/26x3 + 32x3	114046R	97,80
R3 40x3.5 + 50x4 + 63x4.5	114047R	195,60
R3 40x4 + 50x4.5 + 63x6	114048R	195,60



REMS KaliGrat H

Calibrating tools and outer-inner pipe deburrers

Robust, quality tools for calibration and outer-inner deburring of pipes.

Multi-layer composite tubes Ø 16 – 26 mm

REMS KaliGrat H – simultaneous calibration and outer-inner deburring. Star handle with calibrating mandrels and deburring blades.

Universally usable for calibration after the cutting/cropping process, for inner deburring, to avoid damaging the fitting O-ring and for outer deburring. One product for several pipe sizes.

Easy handling and fast feeding due to ergonomically designed plastic housing with star handle.

Robust steel version of the calibrating mandrel with integrated deburring blades for heavy-duty applications and long life. The calibrating mandrel and deburring blades are adapted to different pipe dimensions and wall thicknesses. Sturdy sleeve for protecting the calibrating mandrel and deburring blades from damage.




Supply format

REMS KaliGrat H. Calibrating tool and outer-inner pipe deburrer.


For composite tubes. In blister pack.

Version Ø mm x wall thickness mm	Art.-No.	€
16x2 + 20x2 + 26x3	114060R	115,60
16x2 + 20x2 + 25x2.5	114061R	115,60





Assembling

	Water pump pliers	104
	Pipe workstation Chain pipe vices	105
	Folding workbenches	106
	Material supports	107
	Cordless power drill/screwdriver	108
	Electric LED flood light Cordless LED flood light	110

REMS Catch S

Swedish pattern wrench 'S'

Rugged quality tools for tough use and long service life.
All-steel, drop forged.

Swedish model according to DIN 5234 - Form C.

Pipes $\leq \varnothing 3"$
Nuts, bolts, flat material

REMS Catch S – for professional use.

Swedish model with S-shaped jaws for secure 3-point grip.
Self-locking thus secure gripping and holding even on smooth pipes.
Rugged design in chrome-vanadium steel, all steel, drop forged,
tempered, powder-coated. Hardened, highly wear resistant toothed.
Ergonomically shaped handle, slip-proof. Stop prevents jamming.
Adjusting nut cannot be lost. Reinforced sleeve.



Supply format

REMS Catch S. Swedish pattern wrench 'S'. DIN 5234 – Form C.

In plastic bag.

Description Pipes $\leq \varnothing$ inch	Width mm	Art.-No.	€
S ½"	36	116000R	51,80
S 1"	47	116005R	55,53
S 1½"	60	116010R	74,53
S 2"	78	116015R	99,44
S 3"	112	116020R	199,30



REMS Catch W

Water pump pliers

Rugged quality tools for tough use and long service life.
All-steel, drop forged.

According to ISO 8976 with box joint.

Pipes $\leq \varnothing 1\frac{1}{2}"$
Square, hexagonal joints, flat material

REMS Catch W – for professional use.

Gripping pliers with reinforced, ground, box joint. 7 grip positions.
Self-locking thus secure gripping and holding, even on smooth pipes.
Rugged design in chrome-vanadium steel, all-steel, drop forged,
tempered, powder-coated. Hardened, highly wear resistant toothed.
Ergonomically shaped handle, slip-proof. Stop prevents jamming.



Supply format

REMS Catch W. Water pump pliers, 7 grip positions. ISO 8976.

In plastic bag.

Description	Pipes $\leq \varnothing$ inch	Art.-No.	€
W 175	1"	116050R	25,43
W 240	1½"	116055R	29,27
W 300	1½"	116060R	43,08



REMS Aquila 3B

Sturdy, easy to carry pipe workstation with integrated chain pipe vice on folding tripod stand. With practical shelf plate. For trade and industry. For the building site and the workshop.

Clamping range	Ø 10 – 165 mm Ø 1 1/8 – 6"
Load capacity	≤ 450 kg

REMS Aquila 3B – portable pipe workstation. Safe clamping of pipes up to 6". Everywhere on site.

Sturdy, torsion-free die-cast structure of the work plate with integrated chain pipe vice, pipe rest, tool holders, 3 benders for bending pipes Ø 10 – 26 mm, Ø 3/8 – 3/4", clamping head.

Specially toothed double clamping jaws, easily changeable, prism-shaped, for safe clamping of the pipes in the whole working range. Specially hardened, for long life.

Clamping chain with strong chain links, easy clamping by quick closure and trapezoidal threaded spindle.

Well accessible working range in front of the chain pipe vice for free swing of even long tools.

Especially suitable for pipe installation, e.g. for cutting, thread cutting, bending, assembly.

Adjustable clamping head for clamping the pipe workstation between the ceiling and the floor, for especially secure standing.

Proven tripod stand for secure standing, folding, for easy erection and transport.

Practical shelf plate for tools and work material.

REMS Herkules height adjustable material supports (see page 107).

Portable pipe workstation with chain pipe vice



Info



Supply format

REMS Aquila 3B. Pipe workstation with chain pipe vice for clamping pipes, solid material Ø 10 – 165 mm, Ø 1 1/8 – 6". Work plate with integrated chain pipe vice with double clamping jaws, pipe rest, tool holders, 3 benders for bending pipes Ø 10 – 26 mm, Ø 3/8 – 3/4", clamping head. Folding tripod stand with shelf plate. Load capacity ≤ 450 kg. In a carton.

	Art.-No.	€
	120270R	529,38

REMS Aquila WB

Chain pipe vice for workbench

High quality, robust chain pipe vice for fixing to a workbench. Excellent quality for long life. For trade and industry. For the building site and the workshop.

Clamping range	Ø 10 – 165 mm Ø 1 1/8 – 6"
----------------	-------------------------------

REMS Aquila WB – safe clamping of pipes up to 6".

Sturdy, torsion-free die-cast structure of the base plate with integrated chain pipe vice, pipe rest, bender.

Specially toothed double clamping jaws, easily changeable, prism-shaped, for safe clamping of the pipes in the whole working range. Specially hardened, for long life.

Clamping chain with strong chain links, easy clamping by quick closure and trapezoidal threaded spindle.

Well accessible working range in front of the chain pipe vice for free swing of even long tools.

Especially suitable for pipe installation, e.g. for cutting, thread cutting, bending, assembly.

For fixing to the workbench. Pay attention to load capacity of the workbench.

REMS Herkules height adjustable material supports (see page 107).



German Quality Product



Info



Supply format

REMS Aquila WB. High quality chain pipe vice for clamping pipes, solid material Ø 10 – 165 mm, Ø 1 1/8 – 6". Base plate with integrated chain pipe vice with double clamping jaws, pipe rest, bending device. For work bench. In a carton.

	Art.-No.	€
	120250R	310,36

Sturdy, easy to carry folding workbenches for universal use. Worktop in accordance with DIN 68 705. For trade and industry. For the building site and the workshop.

REMS Jumbo E – handy and light.

Work top	Birch-Multiplex, 800 × 600 × 22 mm
Height	800 mm
Weight	23 kg
Load capacity	≤ 300 kg

REMS Jumbo – the indestructible folding workbench.

Handy and light. German quality product.

Work top	Beech-Multiplex, 1100 × 700 × 26 mm
Height	800 mm
Weight	28 kg
Load capacity	≤ 300 kg

REMS Jumbo – assembled and disassembled

at lightning speed. With toggle catch. Worktops

in accordance with DIN 68 705. Highly resistant

up to 300 kg.

Handy and light. REMS Jumbo E only 23 kg, REMS Jumbo only 28 kg.

Worktop made of special Birch-Multiplex plywood (REMS Jumbo E) or Beech-Multiplex plywood (REMS Jumbo), in accordance with DIN 68 705 weather-proof glued, impregnated, vice-proof and tear-proof, flat and torsion-free.

Impact and splinter resistant thanks to steel edge protection. Screws and nuts galvanised,

Especially safe standing by strong tubular steel frame with toggle catch, assembled and disassembled at lightning speed. Easy to carry.

Highly resistant, max. load capacity 300 kg.



German Quality Product



Info



Supply format

REMS Jumbo. Folding workbench with toggle catch. Worktop in accordance with DIN 68 705. Load capacity ≤ 300 kg. In a carton.

Description	Work top	Size mm	Art.-No.	€
REMS Jumbo E	Birch-Multiplex	800 × 600	120240R	289,60
REMS Jumbo	Beech-Multiplex	1100 × 700	120200R	445,30

REMS Herkules

Material supports

Vertically adjustable material support with roller guidance for rotating and stationary pipe and solid material.
For trade and industry. For the building site and the workshop.

Pipes, solid material \varnothing (1/8) 3/4 – 6", \varnothing (6) 26 – 168 mm
Load capacity \leq 150 kg

REMS Herkules – the sturdy support.

Easy moving of the material in all directions when turning, pulling and pushing by two stainless steel balls mounted in a rust-protected housing in the range \varnothing 3/4 – 6", \varnothing 26 – 168 mm.

Especially suitable for pipe installation, e.g. for cutting, thread cutting, roll grooving, welding, soldering.

Robust, job site-proven design. Dismantles for transport and stocking.

Optionally on safe standing tripod or with clamping device for workbench.


Height adjustable, REMS Herkules 3B from 690 to 1,180 mm from the floor, REMS Herkules Y from 35 to 580 mm from the workbench surface.



German Quality Product



Info



Supply format

REMS Herkules. Vertically adjustable material support for pipes, solid material \varnothing (1/8) 3/4 – 6", \varnothing (6) 26 – 168 mm. Optionally on tripod or with clamping device for workbench. Load capacity \leq 150 kg. In a carton.

Description	Version	Art.-No.	€
REMS Herkules 3B	Tripod with protection caps	120120R	334,24
REMS Herkules Y	Clamping fixture for workbench	120130R	201,37

Height adjustable material support with ball guide for rotating and standing tubular and solid material.
For trade and industry. For the building site and the workshop.

Pipes, solid material \varnothing (1/8) 1 1/4 – 12", \varnothing (6) 42 – 324 mm
Load capacity \leq 450 kg

REMS Herkules XL 12" – extra stable for pipes up to 12".

Especially suitable for pipe installation, e.g. for roll grooving, cutting, thread cutting, welding, soldering.


Easy moving of the material in all directions when turning, pulling and pushing by two stainless steel balls mounted in a rust-protected housing in the range \varnothing 1 1/4 – 12", \varnothing 42 – 324 mm.

Robust, job site-proven design. Securely standing tripod, folds up for transport and storage.

Height adjustable from 505 to 915 mm from the floor.

Threaded spindle for simple alignment of the pipe, with fixing device.

Practical handle for easy transport.



Supply format

REMS Herkules XL 12". Height adjustable, fold-up for pipes, solid material \varnothing 1 1/4 – 12", \varnothing 42 – 324 mm. Load capacity \leq 450 kg. In a carton.

	Art.-No.	€
	120125R	362,26

REMS Helix 22V VE

Cordless power drill/screwdriver

Powerful, mobile, handy power tool for drilling, driving in/loosening screws and deburring pipes. For assembly, disassembly, repair. Li-Ion 22V Technology. For battery and corded operation.

Drilling in steel, stone	≤ Ø 13 mm
Drilling in wood	≤ Ø 32 mm
Drilling with tile drills, e.g. in ceramic, fine clay, granite, marble	≤ Ø 14 mm
Driving in/loosening of screws	≤ Ø 8 mm

REMS Helix 22V VE – drilling, screw driving and deburring. With powerful, brushless battery motor.

Design

Ultra light, ultra small, ultra handy. Drive machine with battery pack weighs only 1.6 kg. Can therefore be used everywhere, free hand, over head, also in very confined spaces. Optimum weight distribution for one-hand operation. Ergonomically designed housing. Drive machine with keyless quick chuck, clamping range 1.5–13 mm, right and left hand rotation. 2 continuously adjustable speed ranges from 0 to 560 rpm and 0 to 1,900 rpm, 15 torque stages plus drilling stage, hard torque of 50 Nm in both speed ranges, soft torque of 12 Nm in the fast and 30 Nm in the slow speed range for powerful screwdriving. Integrated LED work light for illuminating the work place. Belt clip. For cordless and mains operation. 1 bit with double blade slot/cross-head, 50 mm long. Bit set as accessory.

Drive

Powerful electro-mechanical drive with powerful, brushless battery motor 21.6 V, 500W output, robust, 2-step, precision, ball bearing-mounted gear, maintenance-free. Safety switch.

Vario-Electronic

Continuous electronic speed control for gentle start drilling, driving in/loosening of screws and selection of the speed suitable for the material when drilling and driving in/loosening screws. The speed can be continuously controlled by variable pressure on the safety switch from 0 to 560 rpm or 0 to 1,900 rpm (accelerator switch (VE)).

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 1.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240 V, 90 W. Rapid charger 100–240 V, 290 W, for shorter charging times, as accessory. 220–240 V/21.6 V, 15 A output, voltage supply for mains operation instead of Li-Ion battery 21.6 V, as accessory.



Info

Supply format

REMS Helix 22 V VE Set. Cordless power drill/screwdriver with Vario-Electronics (VE) for drilling in steel, stone, $\leq \varnothing 13$ mm, wood $\leq \varnothing 32$ mm and other materials and for driving in/loosening screws $\leq \varnothing 8$ mm. Drive machine with keyless quick chuck, clamping range 1.5–13 mm, right and left hand rotation. Electromechanical drive with powerful, brushless battery motor 21.6 V, 500 W, 2-step robust gear. 2 continuously adjustable speed ranges from 0 to 560 rpm and 0 to 1,900 rpm, 15 torque stages plus drilling stage, hard torque of 50 Nm in both speed ranges. Safety switch. Integrated LED work light. Belt clip. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240 V or 110 V, 50–60 Hz, 70 W. 1 bit with double blade slot/cross-head, 50 mm long. In carrying bag.

	Art.-No.	€
	190110R220	499,00

Other voltages on request.



Accessories

Description	Art.-No.	€
REMS REG 10–42. Outer/inner pipe deburrer for pipes $\varnothing 10$ –42 mm, $\varnothing 1\frac{1}{2}$ – $1\frac{1}{8}$ ", see page 98		
REMS REG 10–54 E. Outer/inner pipe deburrer for pipes $\varnothing 10$ –54 mm, $\varnothing 1\frac{1}{2}$ – $2\frac{1}{8}$ ", see page 99		
REMS KaliGrat E. Calibrating tool and outer-inner pipe deburrer for multi-layer composite tubes $\varnothing 14$ –63 mm, see page 100		
REMS tile drilling, $\varnothing 5$ –14 mm, see page 320		
REMS Helix 22 V VE drive unit, without battery	190100R22	239,00
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240 V, 50–60 Hz, 90 W	571585R220	175,42
Rapid charger 100–240 V, 50–60 Hz, 290 W	571587R220	414,16
Voltage supply 220–240 V/21.6 V, 50–60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	414,16
Carrying bag	190053R	46,71
Bit set, comprising quick-change bit holder, magnetic, with automatic bit lock, 12 bits (4 Torx, 3 cross-head PH, 3 cross-head PZ, 2 slotted), in practical magazine with elastic band for fixing to wrist or to the power tool.	190051R	15,88
REMS Lumen 2800 22V, cordless LED flood light, see page 111		



REMS Lumen 5000/7000/10000

Electric LED flood light

Powerful, electric LED flood light with high light intensity. For the building site and the workshop.

REMS Lumen 5000

Light flux	5000 lm
------------	---------

REMS Lumen 7000

Light flux	7000 lm
------------	---------

REMS Lumen 10000

Light flux brightness stage 1	5000 lm
-------------------------------	---------

Light flux brightness stage 2	10000 lm
-------------------------------	----------

REMS Lumen 5000/7000/10000 – electric lighting.

With high light intensity. Handy, light.

Continuous swivel.

Universal use

Powerful, mobile, electric LED flood light with high light intensity for universal use on the building site or in the workshop. REMS Lumen 10000 with 2 selectable brightness stages for any application purpose.

Design

Handy, light, electric LED flood light. REMS Lumen 5000 only 1.8 kg, REMS Lumen 7000 only 2.2 kg, REMS Lumen 10000 only 3.0 kg. Impact-resistant aluminium housing, dust-proof, protected against water jets from all directions. LEDs protected by impact-resistant, unbreakable acrylic glass. Flood light housing swivels through 360°, fixable by star grips, for optimum alignment of the light. On/Off switch. Tubular steel frame with rubber feet for a firm stand. Practical, non-slip handle. Practical, sturdy, telescopic tripod stand, only 1.9 kg, for accurate positioning of the LED flood light, adjustable height from 615 to 1,590 mm above floor level, collapsible for easy transport, as an accessory.

LED flood light

Modern, energy-saving LED flood light with high light intensity. Lights immediately without switch-on delay. Brightness of the LEDs in REMS Lumen 10000 selectable in 2 stages. 120° radiation angle for good illumination. Colour temperature 5,000 K. Efficient heat dissipation by high-quality, aluminium, ribbed heat sinks. Overheating regulates the power supply automatically, for continuous operation.



Info



Supply format

REMS Lumen. Electric LED flood light with high light intensity. 230V, 50–60 Hz. 5 m connecting lead. In a carton.

Description	Light flux ≤ lm	Power ≤ W	Art.-No.	€
Lumen 5000	5000	50	175220R220	82,00
Lumen 7000	7000	70	175221R220	98,61
Lumen 10000	10000	100	175222R220	123,52

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS 3B telescopic stand, on a tripod, height-adjustable, collapsible	175230R	31,04



REMS Lumen 2800 22V

Cordless LED flood light

Powerful, mobile cordless LED flood light with high light intensity. Li-Ion 22V Technology. For battery and corded operation. For the building site and the workshop.

Light flux brightness stage 1	1100 lm
Light flux brightness stage 2	2000 lm
Light flux brightness stage 3	2800 lm

REMS Lumen 2800 22V – lights everywhere. With high light intensity. Mobile, handy, light. For battery and corded operation. Continuous swivel.

Universal use

Powerful, mobile, cordless LED flood light with high light intensity for universal use on the building site or in the workshop. 3 selectable brightness stages, ideal for any application purpose.

Design

Handy, lightweight, cordless LED flood light, only 1.7 kg, with battery only 2.1 kg. Impact-resistant plastic housing. LEDs protected by impact-resistant, unbreakable acrylic glass. Flood light housing swivels through 360°, fixable by wing nuts, for optimum alignment of the light. On/Off switch. Tubular steel frame with plastic plate and pluggable hook, for fastening or hanging the flood light. Practical, non-slip handle. 220–240V, 50–60 Hz, 138 W power supply, for mains operation included. Holder for REMS Li-Ion 21.6 V integrated into the housing for cordless instead of mains operation. In cordless operation with Li-Ion 21.6V, 2.5 Ah, 54Wh (output). Practical, sturdy, telescopic tripod stand, only 1.9 kg, for accurate positioning of the LED flood light, adjustable height from 615 to 1,590 mm above floor level, collapsible for easy transport, as an accessory.

LED flood light

Modern, energy-saving LED flood light with high light intensity. Lights immediately without switch-on delay. LED brightness selectable in 3 stages. 120° radiation angle for high illumination. Colour temperature 6,500 K. Efficient heat dissipation by high-quality, aluminium, ribbed heat sinks prevents overheating. For continuous operation.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Graduated charging status check by coloured LEDs. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory.

Description	Operating hours h*		
	Stage 1	Stage 2	Stage 3
Battery Li-Ion 21.6V, 2.5 Ah	5.4	2.4	1.6
Battery Li-Ion 21.6V, 4.4 Ah	9.6	4.2	2.8
Battery Li-Ion 21.6V, 5.0 Ah	10.9	4.8	3.2
Battery Li-Ion 21.6V, 9.0Ah	19.6	8.6	5.7



Info



Supply format

REMS Lumen 2800 22V Set Power-Edition. Cordless LED flood light with high light intensity. For battery and corded operation. Light flux ≤ 2800 lm. Voltage supply 220–240V, 50–60Hz, 138W. Without battery, without rapid charger. In a carton.

	Art.-No.	€
	175210R220	144,28

Other voltages on request.

Supply format

REMS Lumen 2800 22V Set. Cordless LED flood light with high light intensity. For battery and corded operation. Light flux ≤ 2800 lm. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240V or 110 V, 50–60 Hz, 70 W. Voltage supply 220–240V, 50–60 Hz, 138 W. In a carton.

	Art.-No.	€
	175211R220	455,68

Other voltages on request.

Accessories

Description	Art.-No.	€
Battery Li-Ion 21.6V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
REMS 3B telescopic stand, on a tripod, height-adjustable, collapsible	175230R	31,04





Pressure testing

Cleaning

Disinfecting

Preserving

Flushing

Filling

	Hand pressure testing pump	114
	Electric pressure testing pump	115
	Electric decalcifying pump	116
	Electronic flushing unit with compressor	117
	Electronic flushing and pressure testing unit with compressor	120
	Disinfection unit TW, cleaning and preservation unit H	123
	Machine cleaner	123
	Electric filling and flushing unit	124

REMS Push

Hand pressure testing pump

Proven, reliable testing pump for pressure and tightness tests of piping systems and receptacles.	
Testing and pressure range	≤ 6 MPa/60 bar/870 psi
Water, oil, glycol	
pH-value of liquids	7–12
Temperature of liquids	≤ 60°C
Viscosity of liquids	≤ 1.5 mPa s

REMS Push – reliable pressure hold.

Universal use

For plumbing, heating, solar system and sprinkler installations, for compressed air, steam and cooling systems, oil installations, for boiler and pressure vessel building.

Design

Robust, job-site proven metal design for tough use. REMS Push with corrosion-resistant, powder-coated 12 ltr steel tank. Distortion resistant lever with ergonomic handle, doubles as carrying handle when locked. Wear resistant pressure piston in brass, Ø 30 mm. High-pressure hose with $\frac{1}{2}$ "-connection. Fine scale pressure gauge (accessory), p ≤ 1.6 MPa/16 bar/232 psi, for reading a pressure change of 0.01 MPa/0.1 bar/1.45 psi for tightness testing according to DIN 1988, as accessory.

Stainless steel tank

REMS Push INOX with 12 ltr stainless steel tank. For extremely long life.

Functioning

Pressure and tightness test with water or oil. Double valve system for reliable pressure built-up, with rust-proof steel balls. High pumping capacity with long stroke, fine pressure adjustment at short pushes. High pressure hose with fabric ply prevents measurement errors.



Info

Supply format

REMS Push. Hand pressure testing pump with pressure gauge, p ≤ 6 MPa/60 bar/870 psi, for pressure and tightness testing of piping systems and receptacles up to 6 MPa/60 bar/870 psi. Corrosion-resistant, powder-coated 12 ltr steel tank. 1.5 m high-pressure hose with $\frac{1}{2}$ "-connection. In a carton.

	Art.-No.	€
	115000R	278,18



Supply format

REMS Push INOX. Hand pressure testing pump with pressure gauge, p ≤ 6 MPa/60 bar/870 psi, for pressure and tightness testing of piping systems and receptacles up to 6 MPa/60 bar/870 psi. 12 ltr stainless steel tank. 1.5 m high-pressure hose with $\frac{1}{2}$ "-connection. In a carton.

	Art.-No.	€
	115001R	358,11



Accessories

Description	Pressure p ≤ MPa/bar/psi	Art.-No.	€
Connecting piece with pressure gauge and shut off valve	6/60/870	115110R	123,52
Fine scale pressure gauge	1.6/16/232	115045	79,61



REMS E-Push 2

Electric pressure testing pump

Powerful, electric pressure testing pump for pressure and tightness tests of piping systems and receptacles.

Testing and pressure range $\leq 6 \text{ MPa}/60 \text{ bar}/870 \text{ psi}$

Pumping capacity 6.5 l/min

Water, hydrous solutions, emulsions

pH-value of liquids $7 - 10$

Temperature of liquids $\leq 60^\circ\text{C}$

Viscosity of liquids $\leq 1.5 \text{ mPa s}$

REMS E-Push 2 – electric charging and testing.

Up to 60 bar. With adjustable pressure limiting.

1300 W. Self sucking.

Universal use

In sanitary, heating, solar and sprinkler installation, for compressed air, steam and cooling systems, oil installations, in boiler and pressurised vessel construction.

Design

Robust, compact, light. Weighs only 10 kg. Easy to carry. Wear reduced high power piston pump. Pressure gauge, damped by filling with glycerine, $p \leq 6 \text{ MPa}/60 \text{ bar}/870 \text{ psi}$. High-pressure hose with fabric ply prevents measurement errors. Suction hose with suction filter. Non-return valve in the suction hose prevents the suction hose from running empty in standstill times; therefore shorter suction times. Suction hose and high pressure hose with $\frac{1}{2}''$ -connection. Connecting piece with pressure gauge, $p \leq 6 \text{ MPa}/60 \text{ bar}/870 \text{ psi}$, and shut off valve for pressure and tightness testing also after removal of the high pressure pump, e.g. theft protection or for use at several testing points, as accessory. Fine scale pressure gauge, $p \leq 1.6 \text{ MPa}/16 \text{ bar}/232 \text{ psi}$, for reading a pressure change of 0.01 MPa/0.1 bar/1.45 psi for tightness testing according to DIN 1988, as accessory.

High power piston pump

Self-sucking high power piston pump running in a sealed oil bath with wear reduced pressure piston in stainless steel. Proven, powerful capacitor motor, 1300 W, very powerful and fast. High pumping capacity of 6.5 l/min. Pressure and tightness testing up to 6 MPa/60 bar/870 psi.

Adjustable pressure limiting

Pressure limiting in 6 stages, 1–6 MPa/10–60 bar/145–870 psi, adjustable to the necessary pressure in the pipe system/tank.



Info



Supply format

REMS E-Push 2. Electric pressure testing pump with pressure gauge, $p \leq 6 \text{ MPa}/60 \text{ bar}/870 \text{ psi}$, for pressure and leak testing of pipe systems and tanks up to 6 MPa/60 bar/870 psi, with adjustable pressure limiting. Pump unit with capacitor motor 230 V, 50 Hz, 1300 W. 1.5 m suction hose with $\frac{1}{2}''$ connection and gaskets, suction filter with non-return valve. 1.5 m high-pressure hose with $\frac{1}{2}''$ connection and gaskets. In a carton.

	Art.-No.	€
	115500R220	943,54

Accessories

Description	Pressure $p \leq \text{MPa}/\text{bar}/\text{psi}$	Art.-No.	€
Connecting piece with pressure gauge and shut off valve	6/60/870	115110R	123,52
Fine scale pressure gauge	1.6/16/232	115045	79,61



REMS Calc-Push

Electric decalcifying pump

Powerful, electric decalcifying pump for effective decalcifying of pipes and containers, e.g. flow heaters, boilers, hot water tanks, cold water tanks, heat exchangers, heating and cooling systems.

Useful container volume	21 l
Displacement	≤ 30 l/min
Displacement pressure	≤ 0.1 MPa/1.0 bar/15 psi
Transport height	≤ 10 m
Temperature of decalcifying solution	≤ 50°C

**REMS Calc-Push – effective electric decalcifying.
High displacement. 3-way lever for reversal of flow direction, with zero setting.**

Universal use

For effective decalcifying of pipes and containers, e.g. flow heaters, boilers, hot water tanks, cold water tanks, heat exchangers, heating and cooling systems.

Design

Robust, compact, light, weights just 9.2 kg. Impact-proof plastic container for the decalcifying solution, useful container volume 21 l, with practical screw-on cap for closing the plastic container during transport. Flexible ½", 2.3 m long flexible PVC fabric hoses, with hose screw fittings with Rp ½" female thread and caps. 3-way lever for reversing the flow direction to remove even heavy lime deposits from both sides, with zero setting to interrupt the flow. Easy to carry due to centrally arranged handle with practical hose holders.

Unscrewable pump unit

Compact pump unit, consisting of a centrifugal pump and condenser motor, unscrewable, for easy cleaning of the pump unit and the plastic container after the decalcifying process. Self-sucking centrifugal pump, suitable for different decalcifying solutions of acetic acid, sulphuric acid, citric acid, formic acid, phosphoric acid, sulfamic acid. With proven, powerful condenser motor with quiet running, 165 W, on/off switch. High displacement ≤ 30 l/min for effective decalcifying.



Info

Supply format

REMS Calc-Push. Electric decalcifying pump for effective decalcifying of pipes and containers, e.g. flow heaters, boilers, hot water tanks, cold water tanks, heat exchangers, heating and cooling systems. Displacement ≤ 30 l/min, useful container volume 21 l. Pump unit with condenser motor 230V, 50 Hz, 165 W. Displacement pressure ≤ 0.1 MPa/1.0 bar/15 psi. Transport height ≤ 10 m. Flexible ½", 2.3 m long flexible PVC fabric hoses, with hose screw fittings with Rp ½" female thread and caps. 2 double nipples ⅜" - ½", 2 double nipples ½" - ¾". In a carton.

	Art.-No.	€
	115900R220	829,36

Other voltages on request.



REMS Multi-Push S

Electronic flushing unit with compressor

Powerful, compact, electronic flushing unit with oil-free compressor. For flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems and for operation of pneumatic tools.

Flushing and desilting

Water pressure pipe network $p \leq 1 \text{ MPa}/10 \text{ bar}/145 \text{ psi}$
Pipe diameter installation $\leq \text{DN } 50, 2"$

Disinfection of drinking water installations

Cleaning and preservation of radiators and area heating systems

Water temperature $5 - 35^\circ\text{C}$

Water flow $\leq 5 \text{ m}^3/\text{h}$

Operation of pneumatic tools

Operating pressure $p \leq 0.8 \text{ MPa}/8 \text{ bar}/116 \text{ psi}$

Suction rate $\leq 230 \text{ NL/min}$

REMS Multi-Push S – Flushing with water or a water/air mixture. Easy switching of the air supply during the flushing process when desilting. Permanent process monitoring. Logging. USB interface.

Universal use

Only one device for flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems, e.g. for desilting, cleaning and preservation of radiators and area heating systems, flushing and disinfection of drinking water installations in accordance with EN 806-4:2010 and for operating pneumatic tools.

Design

Powerful, compact, electronic flushing unit with oil-free compressor. Handy, easily portable, only 32 kg. Measuring and control devices for automatically running the flushing programs and for documenting the results. Safety devices for avoiding contamination of the pipe network by flow-back. Overpressure valve for pressure limiting. 5 µm condensation and particle filters. Large tubular steel frame as a compressed air tank. Two practical handles for easy carrying. Space-saving, folding handle grip for easy movement. Mobile tubular steel frame with two rubber-tyred wheels for easy transport and 2 rubber feet for firm standing. Connecting cable with integrated personal protection switch (PRCD). 2 hooks for winding up the power cable. Captive seals for input and output of the REMS Multi-Push S to avoid contamination during transport and storage. Practical hood for protecting the machine during transport and storage as an accessory.

Compressor

Proven, powerful, oil-free piston compressor with crank drive, with capacitor motor 230V, 1500W. Pressure gauge for displaying the air pressure in the compressed air tank. Emergency stop button.

Hoses

Transparent Ø 1" suction/pressure hose, with fabric inlay, 1.5 m long, with 1" hose screw fittings, with caps, for flushing, disinfection, cleaning, preservation. Captive caps for the inputs and outputs of the hoses to avoid contamination during transport and storage. Connecting hose compressor/water connections, 0.6 m long, with quick coupling DN 7.2 and 1" hose screw fitting, 1" double nipple, for blowing out water remains from REMS Multi-Push S and suction/pressure hoses at the end of work.

Input and control unit

Easy desilting operation by buttons to switch over the air supply during the flushing process. Menu-guided input and menu-guided control for flushing drinking water installations according to EN 806-4:2010 with the possibility for the user to change the factory-set default values for adaptation to the applicable national safety provisions, rules and regulations for the application site. Format selection for date and time and selection of the different units. Input and control unit with 3" display with modern LCD technology, 76 mm screen diagonal, 128 x 64 pixels. Permanent process monitoring during the program sequences. USB port for USB stick or printer. The respective latest version software for the input and control unit is available via USB stick as a download under www.rems.de > Downloads > Software.

Patent EP 2 954 960



German Quality Product



Info

REMS Multi-Push S

Electronic flushing unit with compressor

Desilting and flushing

Buttons for easy switching of the air supply during the flushing process when desilting radiator and flat heater systems with the following possibilities: (1) without compressed air, (2) intermittent compressed air, (3) constant compressed air.

Flushing according to EN 806-4

Flushing of drinking water installations with water or with a water/air mixture with intermittent compressed air in accordance with EN 806-4:2010 and information leaflet "Flushing, Disinfection and Commissioning of Drinking Water Installations" (August 2014) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK).

Disinfection

REMS V-Jet TW disinfection unit for disinfection of drinking water installations in accordance with EN 806-4:2010 and information leaflet "Flushing, Disinfection and Commissioning of Drinking Water Installations" (August 2014) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK) and other pipe systems, as an accessory. REMS Peroxi Color, consisting of a 1 l bottle of REMS Peroxi dosing solution for disinfection of approx. 100 l line volume and 20 ml bottle of red REMS Color dye for dyeing the dosing solution for filling and wash-out check, pipette for checking the effectiveness of the dosing solution, as an accessory. Feeding of the disinfectant solution without additional dosing pump (Patent EP 2 954 960).

Cleaning and preservation

REMS V-Jet H cleaning and preservation unit for cleaning and preserving radiators and area heating systems, as an accessory. Cleaner, dyed green for filling and wash-out check and corrosion protection, dyed blue for filling check, for approx. 100 l line volume respectively, as an accessory. Feeding of cleaner and corrosion protection without additional dosing pump (Patent EP 2 954 960).

Operation of pneumatic tools

Connection for pneumatic tools up to an air requirement $\leq 230 \text{ NL/min}$, adjustable, for adaptation to the pneumatic tool being used. Pressure gauge for controlling the air pressure supplied by the compressed air tank. Pneumatic hose with quick coupling DN 7.2, as an accessory.

Logging

Results of the flushing programs are saved with date, time and log number in the selected language and can be transferred to USB stick or printer for documentation. Printer as an accessory. Additions to saved data, e.g. customer name, project number, tester, are possible on external devices (e.g. PC, laptop, tablet-PC, Smartphone).



Supply format

REMS Multi-Push S Set. Electronic flushing unit with oil-free compressor. For flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems, e.g. for desilting, cleaning and preservation of radiators and area heating systems, flushing and disinfection of drinking water installations and for operation of pneumatic tools $\leq 230 \text{ NL/min}$. Input and control unit. Piston compressor with crank drive, capacitor motor 230V, 50Hz, 1,500 W, person circuit breaker (PRCD). Mobile tubular steel frame. Fastenings for water input and output of the REMS Multi-Push S. Two Ø 1" suction/pressure hoses, with fabric inlay, 1.5 m long, with 1" hose screw fittings, with caps. Connecting hose compressor/water connections, 0.6 m long, with quick coupling DN 7.2 and 1" hose screw fitting, 1" double nipple, for blowing out water remains from REMS Multi-Push S and suction/pressure hoses at the end of work. Without disinfection unit, without cleaning and preservation unit. In a carton

Art.-No.	€
115810R220	2 480,82

Other voltages on request.



REMS Multi-Push S

Electronic flushing unit with compressor

Description	Art.-No.	€
Fine filter with fine filter cartridge 90 µm , washable, with large dirt collection vessel	115609R	123,52
Fine filter cartridge 90 µm , for fine filter with fine filter cartridge 90 µm	043054	40,07
Compressed air hose Ø 14 mm , 1.5 m long, with quick couplings DN 7.2 (plug, socket), for connecting pneumatic tools	115621R	61,97
Ø 1" suction/pressure hose , with fabric inlay, 1.5 m long, with G 1" screw fittings for flushing, disinfection, cleaning, preservation and pressure testing with water.	115633R	59,27
Double nipple 1" , for connecting 2 suction/pressure hoses and blowing out the suction/pressure hoses	045159	10,38
Printer for printing the stored results of the flushing and test programs, 1 roll of paper, USB connecting cable, power supply/charger Ni-Mh 100–240 V, 50–60 Hz, 3 W	115604R	508,62
Paper roll , pack of 5 for printer	090015R	18,89
Case with inlays for printer, paper rolls and other accessories	115703R	70,58
REMS V-Jet TW , disinfection unit for drinking water installations, for feeding dosing solution for disinfection	115602R	304,13
REMS Peroxi Color , 1 l bottle of REMS Peroxi dosing solution for disinfection of approx. 100 l line volume, 20 ml bottle of red REMS Color dye for dyeing the dosing solution for filling and wash-out check, pipette for checking the effectiveness of the dosing solution.	115605R	82,00
Test strips H₂O₂ 0 – 1,000 mg/l, pack of 100 , for checking the concentration of the disinfection solution	091072	71,21
Test strips H₂O₂ 0 – 50 mg/l, pack of 100 , for checking the complete flushing out of the disinfection solution after disinfection	091073	71,21
REMS V-Jet H , cleaning and preservation unit for radiators and area heating systems, for feeding cleaner and corrosion protection.	115612R	304,13
REMS CleanH 1 l bottle of cleaner for radiators and area heating systems, dyed green for filling and wash-out check, for approx. 100 l line volume.	115607R	57,09
REMS NoCor 1 l bottle of corrosion protection for preservation of radiators and area heating systems, dyed blue for filling check, for approx. 100 l line volume.	115608R	61,24
Hood for protecting the machine during transport and storage	115677R	39,24
XL-Boxx system case for hoses	579600RMP	198,26



REMS Multi-Push SL/SLW

Powerful, compact, electronic flushing and pressure testing unit with oil-free compressor. For flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems, for pressure testing of pipe systems and vessels with compressed air or water, as a pneumatic pump for controlled filling of all types of vessels with compressed air and for operation of pneumatic tools.

Flushing and desilting

Water pressure pipe network $p \leq 1 \text{ MPa}/10 \text{ bar}/145 \text{ psi}$
Pipe diameter installation $\leq \text{DN } 50, 2"$

Disinfection of drinking water installations

Cleaning and preservation of radiators and area heating systems

Water temperature $5 - 35^\circ\text{C}$

Water flow $\leq 5 \text{ m}^3/\text{h}$

Pressure test

with compressed air $p \leq 0.4 \text{ MPa}/4 \text{ bar}/58 \text{ psi}$

Pressure test with water $p \leq 1.8 \text{ MPa}/18 \text{ bar}/261 \text{ psi}$

Pneumatic pump for controlled filling of all types of vessels with compressed air $p \leq 0.8 \text{ MPa}/8 \text{ bar}/116 \text{ psi}$

Operation of pneumatic tools

Operating pressure $p \leq 0.8 \text{ MPa}/8 \text{ bar}/116 \text{ psi}$

Suction rate $\leq 230 \text{ NL/min}$

REMS Multi-Push SL/SLW – just one device with more than 10 automatically running flushing and pressure testing programs. Permanent process monitoring.

Logging. USB interface.

Universal use

Only one device for flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems, for pressure testing of pipe systems and vessels with compressed air or water, e.g. drinking water installations, radiators or area heating systems, for pressure testing of gas installations with compressed air, as a pneumatic pump for controlled filling of all types of vessels with compressed air, e.g. for pumping up expansion vessels or tyres and for operating pneumatic tools. (Patent EP 2 816 231).

Design

Powerful, compact, electronic flushing and pressure testing unit with oil-free compressor. Handy, easily portable. REMS Multi-Push SL only 37 kg, REMS Multi-Push SLW only 39 kg. Measuring and control devices for automatically running the flushing and test programs and for documenting the results. Safety devices for avoiding contamination of the pipe network by flow-back. Overpressure valves for pressure limiting. 5 µm condensation and particle filters. Large tubular steel frame as a compressed air tank. Two practical handles for easy carrying. Space-saving, folding handle grip for easy movement. Mobile tubular steel frame with two rubber-tired wheels for easy transport and 2 rubber feet for firm standing. Connecting cable with integrated personal protection switch (PRCD). 2 hooks for winding up the power cable. Captive seals for inputs and outputs of the REMS Multi-Push SL/SLW to avoid contamination during transport and storage. Practical hood for protecting the machine during transport and storage as an accessory.

REMS Multi-Push SLW additionally with hydro-pneumatic water pump for generating the necessary water pressure for hydrostatic pressure testing of pipe systems and vessels with water.

Compressor



Proven, powerful, oil-free piston compressor with crank drive, with capacitor motor 230V, 1500W. Pressure gauge for displaying the air pressure in the compressed air tank. Emergency stop button.

Hoses

Transparent Ø 1" suction/pressure hose, with fabric inlay, 1.5 m long, with 1" hose screw fittings, with caps, for flushing, disinfection, cleaning, preservation and pressure testing with water. High-pressure hose Ø ½", with fabric inlay, 1.5 m long, with ½" hose screw fittings, with caps, for pressure testing with water with REMS Multi-Push SLW. Captive caps for the inputs and outputs of the hoses to avoid contamination during transport and storage. Compressed air hose Ø 8 mm, 1.5 m long, with quick coupling DN 5 and ½" hose screw fitting, for pressure testing with compressed air. Compressed air hose Ø 8 mm, 1.5 m long, with quick coupling DN 5 (plug, socket) for gas testing with compressed air. Connecting hose compressor/water connections, 0.6 m long, with quick coupling DN 7.2 and 1" hose screw fitting, 1" double nipple, for blowing out water remains from REMS Multi-Push SL/SLW and suction/pressure hoses at the end of work.

Electronic flushing and pressure testing unit with compressor

Patent EP 2 816 231
Patent EP 2 954 960



German Quality Product

REMS Multi-Push SL/SLW

Input and control unit

More than 10 flushing and test programs in 26 languages. Easy desilting operation by buttons to switch over the air supply during the flushing process. Menu-guided input and menu-guided control for flushing drinking water installations according to EN 806-4:2010 with the possibility for the user to change the factory-set default values for adaptation to the applicable national safety provisions, rules and regulations for the application site. Format selection for date and time and selection of the different units. Input and control unit with 3" display with modern LCD technology, 76 mm screen diagonal, 128 × 64 pixels. Permanent process monitoring during the program sequences. USB port for USB stick or printer. The respective latest version software for the input and control unit is available via USB stick as a download under www.rems.de > Downloads > Software.

Desilting and flushing

Buttons for easy switching of the air supply during the flushing process when desilting radiator and flat heater systems with the following possibilities: (1) without compressed air, (2) intermittent compressed air, (3) constant compressed air.

Flushing according to EN 806-4

Flushing of drinking water installations with water or with a water/air mixture with intermittent compressed air in accordance with EN 806-4:2010 and information leaflet "Flushing, Disinfection and Commissioning of Drinking Water Installations" (August 2014) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK).

Disinfection

REMS V-Jet TW disinfection unit for disinfection of drinking water installations in accordance with EN 806-4:2010 and information leaflet "Flushing, Disinfection and Commissioning of Drinking Water Installations" (August 2014) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK) and other pipe systems, as an accessory. REMS Peroxi Color, consisting of a 1 l bottle of REMS Peroxi dosing solution for disinfection of approx. 100 l line volume and 20 ml bottle of red REMS Color dye for dyeing the dosing solution for filling and wash-out check, pipette for checking the effectiveness of the dosing solution (page 123). Feeding of the disinfectant solution without additional dosing pump (**Patent EP 2 954 960**).

Cleaning and preservation

REMS V-Jet H cleaning and preservation unit for cleaning and preserving radiators and area heating systems, as an accessory. Cleaner, dyed green for filling and wash-out check and corrosion protection, dyed blue for filling check, for approx. 100 l line volume respectively (page 123). Feeding of cleaner and corrosion protection without additional dosing pump (**Patent EP 2 954 960 pending**).

Pressure testing with compressed air

Leak testing of drinking water installations with compressed air according to information leaflet "Leak Testing of Drinking Water Installations with Compressed Air, Inert Gas or Water" (January 2011) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK), leak testing of gas installations with compressed air according to the technical rule "DVGW-TRGI 2018, Technical Rules for Gas Installations - DVGW Worksheet G 600" of the German Gas and Water Association (DVGW) and leak testing of other pipe systems and vessels with compressed air.

Load testing of drinking water installations with compressed air according to information leaflet "Leak Testing of Drinking Water Installations with Compressed Air, Inert Gas or Water" (January 2011) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK), load testing of gas installations with compressed air according to the technical rule "DVGW-TRGI 2018, Technical Rules for Gas Installations - DVGW Worksheet G 600" of the German Gas and Water Association (DVGW) and load testing of other pipe systems and vessels with compressed air.

Pressure testing with water

REMS Multi-Push SLW with hydro-pneumatic water pump for hydrostatic pressure testing of drinking water installations with water in accordance with EN 806-4:2010, test method A, B or C or test method B, modified in accordance with information leaflet "Leak Testing of Drinking Water Installations with Compressed Air, Inert Gas or Water" (January 2011) of the German Central Association for Sanitary, Heating and Air Conditioning (ZVSHK) and for pressure testing of other pipe systems and vessels.

Pneumatic pump

Pneumatic pump for controlled filling of all types of vessels with compressed air ≤ 0.8 MPa/8 bar/116 psi, with automatic switch-off on reaching the preset air pressure, e.g. for pumping up expansion vessels or tyres.


Operation of pneumatic tools

Connection for pneumatic tools up to an air requirement ≤ 230 NL/min, adjustable, for adaptation to the pneumatic tool being used. Pressure gauge for controlling the air pressure supplied by the compressed air tank. Pneumatic hose with quick coupling DN 7.2, as an accessory.

Logging

Results of the flushing and test programs are saved with date, time and log number in the selected language and can be transferred to USB stick or printer for documentation. Printer as an accessory. Additions to saved data, e.g. customer name, project number, tester, are possible on external devices (e.g. PC, laptop, tablet-PC, Smartphone).

Electronic flushing and pressure testing unit with compressor



REMS Multi-Push SL/SLW

Supply format

REMS Multi-Push SL Set. Electronic flushing and pressure testing unit with oil-free compressor. For flushing with water or a water/air mixture, disinfection, cleaning, preservation of pipe systems, e.g. for desilting, cleaning and preservation of radiators and area heating systems, flushing and disinfection of drinking water installations, for pressure testing of pipe systems and vessels with compressed air, as a pneumatic pump for controlled filling of all types of vessels with compressed air $p \leq 0.8 \text{ MPa}/8 \text{ bar}/116 \text{ psi}$, and for operation of pneumatic tools $\leq 230 \text{ NL/min}$. Input and control unit. Piston compressor with crank drive, capacitor motor 230 V, 50 Hz, 1,500 W, person circuit breaker (PRCD). Mobile tubular steel frame. Fastenings for water inputs and outputs of the REMS Multi-Push. Two Ø 1" suction/pressure hoses, with fabric inlay, 1.5 m long, with 1" hose screw fittings, with caps. One Ø 8 mm compressed air hose, 1.5 m long, with quick coupling DN 5 and G 1/2" hose screw fitting, for pressure testing with compressed air. Connecting hose compressor/water connections, 0.6 m long, with quick coupling DN 7.2 and 1" hose screw fitting, 1" double nipple, for blowing out water remains from REMS Multi-Push and suction/pressure hoses at the end of work. Without disinfection unit, without cleaning and preservation unit. In a carton

	Art.-No.	€
	115610R220	3 108,81

Other voltages on request.

Electronic flushing and pressure testing unit with compressor



Supply format

REMS Multi-Push SLW Set. Same as REMS Multi-Push SL Set, Art. No. 115610, additionally with hydro-pneumatic water pump for hydrostatic pressure testing of drinking water installations with water in accordance with EN 806-4:2010, test method A, B or C or test method B and for pressure testing of other pipe systems and vessels. One high-pressure hose Ø 1/2", 1.5 m long, with 1/2" hose screw fittings, with caps. In a carton.

	Art.-No.	€
	115611R220	4 011,87

Other voltages on request.



Accessories

Description	Art.-No.	€
Fine filter with fine filter cartridge 90 µm , washable, with large dirt collection vessel	115609R	123,52
Fine filter cartridge 90 µm , for fine filter with fine filter cartridge 90 µm	043054	40,07
Pressure gauge, p ≤ 6 MPa/60 bar/870 psi , for pressure and leak testing of pipe systems and vessels up to 6 MPa/60 bar/870 psi.	115140	111,38
Fine scaled pressure gauge, p ≤ 1.6 MPa/16 bar/232 psi , for pressure and leak testing of pipe systems and vessels up to 1.6 MPa/16 bar/232 psi. CL 1.0.	115045	79,61
Fine scaled pressure gauge, p ≤ 250 hPa/250 mbar/3.6 psi , for pressure and leak testing of pipe systems and vessels up to 250 hPa/250 mbar/3.6 psi. CL 1.6.	047069	240,19
Compressed air hose Ø 14 mm , 1.5 m long, with quick couplings DN 7.2 (plug, socket), for connecting pneumatic tools	115621R	61,97
Compressed air hose Ø 8 mm , 7 m long, with quick coupling DN 5 (plug) and G 1/2" hose screw fitting, for pressure testing with compressed air.	115667R	64,88
Compressed air hose Ø 8 mm , 1.5 m long, with quick coupling DN 5 (plug, socket) for gas testing with compressed air.	115747R	67,26
High-pressure hose Ø 1/2" , 7 m long, with G 1/2" hose screw fittings, with caps, for pressure testing of pipe systems and vessels with water with REMS Multi-Push SLW.	115661R	128,71
Ø 1" suction/pressure hose , with fabric inlay, 1.5 m long, with G 1" screw fittings for flushing, disinfection, cleaning, preservation and pressure testing with water.	115633R	59,27
Double nipple 1" , for connecting 2 suction/pressure hoses and blowing out the suction/pressure hoses	045159	10,38



REMS Multi-Push SL/SLW

Electronic flushing and pressure testing unit
with compressor

Description	Art.-No.	€
Printer for printing the stored results of the flushing and test programs, 1 roll of paper, USB connecting cable, power supply/charger Ni-Mh 100–240 V, 50–60 Hz, 3 W	115604R	508,62
Paper roll , pack of 5 for printer	090015R	18,89
Case with inlays for printer, paper rolls and other accessories	115703R	70,58
REMS V-Jet TW , disinfection unit for drinking water installations, for feeding dosing solution for disinfection	115602R	304,13
REMS Peroxi Color , 1 l bottle of REMS Peroxi dosing solution for disinfection of approx. 100 l line volume, 20 ml bottle of red REMS Color dye for dyeing the dosing solution for filling and wash-out check, pipette for checking the effectiveness of the dosing solution.	115605R	82,00
Test strips H₂O₂ 0 – 1,000 mg/l, pack of 100 , for checking the concentration of the disinfection solution	091072	71,21
Test strips H₂O₂ 0 – 50 mg/l, pack of 100 , for checking the complete flushing out of the disinfection solution after disinfection	091073	71,21
REMS V-Jet H , cleaning and preservation unit for radiators and area heating systems, for feeding cleaner and corrosion protection.	115612R	304,13
REMS CleanH 1 l bottle of cleaner for radiators and area heating systems, dyed green for filling and wash-out check, for approx. 100 l line volume.	115607R	57,09
REMS NoCor 1 l bottle of corrosion protection for preservation of radiators and area heating systems, dyed blue for filling check, for approx. 100 l line volume.	115608R	61,24
Hood for protecting the machine during transport and storage	115677R	39,24
XL-Boxx system case for hoses	579600RMP	198,26



REMS CleanM

Machine cleaner

Highly effective machine cleaner for fast, reliable removal of oily and greasy soiling of all kinds.
For cleaning and degreasing machines, tools etc.
For trade and industry.

REMS CleanM – you can't get cleaner than that. Very high cleaning effect.

Especially for fast, reliable removal of oily and greasy soiling of all kinds.
Easily biodegradable according to OECD 302 B. Free from substances classified as harmful to the environment.

Universal cleaner for trade and industry. For cleaning and degreasing machines and tools.

Can also be used for removing lime scale.

REMS CleanM spray bottle without propellant.



German Quality Product



Info



Supply format

REMS CleanM. Highly effective machine cleaner for fast and reliable removal of oily and greasy soiling. For cleaning and degreasing machines, tools etc.

	Packing	Art.-No.	€
	500 ml spray bottle	140119R	19,41

REMS Solar-Push

Electric filling and flushing unit

Powerful electric filling and flushing unit for fast, easy filling, flushing and venting of closed systems. Ideal for solar power systems, ground heat systems and underfloor/wall heating.

Tank volume 30 litres

REMS Solar-Push K 60 with centrifugal pump

Transport capacity at 40 m pumping head 16 l/min

Transport volume \leq 36 l/min

Transport pressure \leq 0.55 MPa/5.5 bar/80 psi

Temperature of the transported media

(constant load) \leq 60°C

pH value of the transported media 6.5–9.5

REMS Solar-Push I 80 with impeller pump

Transport capacity at 40 m pumping head 18 l/min

Transport volume \leq 27 l/min

Transport pressure \leq 0.65 MPa/6.5 bar/94 psi

Temperature of the transported media

(constant load) \leq 80°C

pH value of the transported media 6.5–9.5

Media transported: heat transfer liquids, antifreeze, water, aqueous solutions, emulsions

REMS Solar-Push – filling, flushing and venting in one action. Self priming. High transport capacity.

System advantage

Filling, flushing and venting in one action. Ideal for solar power systems, ground heat systems and underfloor/wall heating. Also for filling tanks.

Design

Powerful, electric filling and flushing unit on stable, mobile tubular steel frame for secure standing. 2 large, air-filled tyres for easy transport in rugged building site conditions. Practical hose holder. Low weight, REMS Solar-Push I only 19 kg, REMS Solar-Push K only 20 kg. Sturdy plastic tank to hold 30 litres, made of UV-stabilised PE, with filling level indicator, removable, for easy cleaning, with large opening for easy filling. Practical screw cap for fast opening and closing. Return connection $\frac{3}{4}$ " with immersion pipe avoids foaming of the transport medium when it enters the plastic tank. Stop tap for easy cleaning and easy changing of the plastic tank when using different transport media. Two practical handles for easy carrying of the plastic tank. High temperature-resistant connecting hose between plastic tank and pump. Fine filter in the suction line with large viewing window for easy recognition of residue air in the circuit as well as emitted contamination, e.g. chips, solder and welding residue.

REMS Solar-Push K 60

Self-suction centrifugal pump, suitable for different transport media, e.g. heat transfer liquids, antifreeze, water, aqueous solutions, emulsions. With proven, powerful condenser motor with quiet running, 940 W, on/off switch. High transport volume 36 l/min for fast filling, efficient flushing and venting of closed systems and for filling tanks. Pressure relief valve for simple pressure relief in the pressure hose at the end of operation, as an accessory. For continuous load \leq 60°C. 2 pieces flexible, transparent PVC fabric hoses $\frac{1}{2}$ " T60, for pressure and return lines, each 3 m long, with $\frac{3}{4}$ " hose screw fittings, temperature-resistant \leq 60°C.

REMS Solar-Push I 80

Dry self-suction impeller pump with special impeller, suitable for different transport media, e.g. heat transfer liquids, antifreeze, water, aqueous solutions, emulsions. With proven, powerful condenser motor with quiet running, 1000 W, on/off switch. High transport volume 27 l/min for fast filling, efficient flushing and venting of closed systems and for filling tanks. Pressure relief valve for simple pressure relief in the pressure hose at the end of operation. For continuous load \leq 80°C. 2 flexible EPDM fabric hoses $\frac{1}{2}$ " T100 (synthetic rubber) for pressure and return lines, each 3 m long, with $\frac{3}{4}$ " hose screw fittings, high temperature-resistant \leq 100°C.

Extensive accessories

Shut-off valve for closing the pressure or return line, e.g. during transport. Fine filter with fine filter bag 70 µm, consisting of a screw cap with return line connection for return line with $\frac{3}{4}$ " union, adapter and fine filter bag 70 µm, or fine filter with fine filter cartridge 90 µm, washable, with large dirt collection vessel, for return line with $\frac{3}{4}$ " connection for flushing underfloor heating/wall radiators and clearing sludge. Flow direction changeover valve complete with EPDM fabric hose $\frac{1}{2}$ " T100, for flushing underfloor heating/wall radiators and effective clearance of sludge by pressure surges when flow direction changes. Changeover valve for alternative suction of the transport medium from another tank, e.g. for larger volumes.



German Quality Product



K 60



I 80



Supply format

REMS Solar-Push K 60. Electric filling and flushing unit for fast, easy filling, flushing and venting of closed systems. Transport volume $\leq 36 \text{ l/min}$, tank volume 30 l. With centrifugal pump, temperature-resistant for continuous load $\leq 60^\circ\text{C}$. Transport pressure $\leq 0.55 \text{ MPa}/5.5 \text{ bar}/80 \text{ psi}$. Condenser motor 230 V, 50 Hz, 940 W. 2 pieces flexible, transparent PVC fabric hoses $\frac{1}{2}'' \text{ T}60$, each 3 m long, temperature-resistant $\leq 60^\circ\text{C}$. On sturdy tubular steel frame with air-filled wheels. In box.

	Art.-No.	€
	115312R220	933,16

Other voltages on request.



Info



Supply format

REMS Solar-Push I 80. Electric filling and flushing unit for fast, easy filling, flushing and venting of closed systems. Transport volume $\leq 27 \text{ l/min}$, tank volume 30 l. With impeller pump, temperature-resistant for continuous load $\leq 80^\circ\text{C}$. Transport pressure $\leq 0.65 \text{ MPa}/6.5 \text{ bar}/94 \text{ psi}$. Transport capacity at 40 m transport height 10 l/min. Condenser motor 230 V, 50 Hz, 1000 W. Pressure relief valve. 2 pieces flexible, EPDM fabric hoses $\frac{1}{2}'' \text{ T}100$, each 3 m long, high temperature-resistant $\leq 100^\circ\text{C}$. On sturdy tubular steel frame with air-filled wheels. In box.

	Art.-No.	€
	115311R220	1 140,76

Other voltages on request.

Accessories

Description	Art.-No.	€
PVC fabric hose $\frac{1}{2}'' \text{ T}60$ for pressure or return line, 3 m long, with $\frac{3}{4}''$ hose screw fittings, temperature-resistant $\leq 60^\circ\text{C}$.	115314R	43,08
EPDM fabric hose $\frac{1}{2}'' \text{ T}100$ for pressure or return line, 3 m long, with $\frac{3}{4}''$ hose screw fittings, high temperature-resistant $\leq 100^\circ\text{C}$	115315R	57,61
EPDM fabric hose $\frac{1}{2}'' \text{ T}165$ for pressure or return line, 3 m long, with $\frac{3}{4}''$ hose screw fittings, high temperature-resistant $\leq 165^\circ\text{C}$	115319R	210,71
$\frac{3}{4}''$ shut-off valve for closing the pressure or return line, e.g. during transport.	115324R	52,11
30 l plastic tank made of UV-stabilised PE.	115375R	165,04
Pressure relief valve for Solar-Push K 60.	115217R	74,11
Fine filter with fine filter bag 70 μm , consisting of a screw cap with return line connection for return line with $\frac{3}{4}''$ union, adapter, 1 fine filter bag 70 μm , for flushing underfloor heating/wall radiators and clearing sludge	115220	104,84
Fine filter bag 70 μm (pack of 10), fine filter with fine filter bag 70 μm	115221R10	88,96
Fine filter with fine filter cartridge 90 μm , washable, with large dirt collection vessel, for return line with $\frac{3}{4}''$ union, for flushing underfloor heating/wall radiators and clearing sludge	115323R	220,06
Fine filter cartridge 90 μm , for fine filter with fine filter cartridge 90 μm	043054	40,07
Flow direction changeover valve complete with EPDM fabric hose $\frac{1}{2}'' \text{ T}100$, for flushing underfloor heating/wall radiators and effective clearance of sludge by pressure surges when flow direction changes	115326R	291,68
Changeover valve for alternative suction of the transport medium from another tank, e.g. for larger volumes.	115325R	86,98





Bending

	Single-hand tube bender	128
	Oil-hydraulic hand pipe bender	130
	Cordless electro-hydraulic tube bender	132
	Oil-hydraulic pipe bender	134
	Electric pipe and tube bender	136
	Cordless tube bender	140
	Hand tube bender	142

REMS Swing

Single-hand tube bender

Practical one-hand pipe bender for dimensionally accurate bending of pipes up to 90°. Ideal for on-site work. For trade and industry. For the building site and the workshop.

Soft copper pipes, also thin-walled	Ø 10 – 22 mm Ø $\frac{3}{8}$ – $\frac{7}{8}$ " $s \leq 1$ mm
Coated soft copper tubes	Ø 10 – 18 mm Ø $\frac{3}{8}$ – $\frac{5}{8}$ " $s \leq 1$ mm
Soft, coated carbon steel pipes of the pressfitting systems	Ø 12 – 18 mm $s \leq 1.2$ mm
Soft precision steel tubes	Ø 10 – 18 mm $s \leq 1$ mm
Multi-layer composite tubes	Ø 14 – 32 mm

REMS Swing – bending tubes where they are installed.
Ultra light, ultra small, ultra handy. Universally usable for many pipe types. Ultra fast operation by practical multifunction lever for fast in-feed and fast return.
Proven, reliable ratchet feed. Ideal also for coated tubes.

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Also for copper thin-walled heating tubes according to EN 1057 and for tubes of pressfitting systems.

Cost advantage

Bender recovered after a few bends through savings on fittings. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Compact, job site-proven. Handy and light, drive unit only 0.9 kg. Can be used anywhere, free-hand, in confined areas. Easy, quick working, e.g. Ø 22 mm copper pipe bend in just 9 s. Marked bending formers for exact bending. Overbend, tier bend possible. Easy and rapid changing of bending formers. Back former support S Ø 10–26 mm, rotatable according to the size of the pipe to be bent, with back formers for pipes Ø 10–26 mm, $\frac{3}{8}$ – $\frac{5}{8}$ ". Back former support Ø 32 mm with back formers for pipe Ø 32 mm. Device for reverse bending on laid pipes up to Ø 22 mm, $\frac{3}{8}$ ", as accessory.

Bending formers and sliding pieces

In high-strength, high-slide, glass-fibre reinforced polyamide. Angle scale on each bending former for dimensionally accurate bending. See table on page 129 for bending formers. UP bending formers with smaller bending radii for Uponor Uni Pipe PLUS composite pipes, see below.

Drive

Sturdy drive unit with proven, reliable ratchet feed for the complete work range up to Ø 32 mm. Practical multi-function lever for fast in-feed and fast return saves time and effort.



German Quality Product



Info



Supply format

REMS Swing UP Set. Single-hand tube bender Ø 16–32 mm, up to 90°, for Uponor Uni Pipe PLUS composite pipes Ø 16–32 mm. With UP drive unit, UP bending formers with smaller bending radii, UP back former supports Ø 16–32 mm with back formers, in a sturdy steel box/case.

Description mm	Art.-No.	€
Set 16 + 20 + 25 + 32	153030R	550,14

Accessories

Description	Art.-No.	€
REMS Swing UP drive unit	153300R	153,62
UP back former support Ø 16–32 mm with back formers for pipes Ø 16–32 mm	153307R	97,26
UP bending former Ø 16 mm, bending radius 32 mm	153303R	46,61
UP bending former UP Ø 20 mm, Biegeradius 40 mm	153304R	46,61
UP bending former UP Ø 25 mm, Biegeradius 62,5 mm	153305R	46,61
UP bending former UP Ø 32 mm, Biegeradius 80 mm	153306R	151,55
Steel case with inlay	153265R	55,01



Supply format

REMS Swing Set. Single-hand tube bender Ø 10–32 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", up to 90°. Soft copper pipes Ø 10–22 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", s ≤ 1mm, soft, coated copper pipes Ø 10–18 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", s ≤ 1 mm, soft, coated carbon steel pipes of the pressfitting systems Ø 12–18 mm, s ≤ 1.2 mm, soft precision steel pipes Ø 10–18 mm, s ≤ 1 mm, composite tubes Ø 14–32 mm. Up to Ø 26 mm with drive unit, bending formers, back former supports S Ø 10–26 mm with back formers, in a sturdy steel box/case. Up to Ø 32 mm with drive unit, bending formers, 2 back former supports Ø 10–26 mm and Ø 32 mm with back formers, in a sturdy steel case.

Description mm	inch	Art.-No.	€
Set 12+15+18+22	$\frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}"$	153025R	359,15
Set 10+12+15+18+22	$\frac{3}{8} + \frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}"$	153021R	375,76
Set 12+14+16+18+22	$\frac{1}{2} + \frac{3}{4} + \frac{7}{8}"$	153020R	375,76
Set 14+16+20+25/26		153026R	359,15
Set 14+16+18+20+25/26		153022R	375,76
Set 16+20+25/26+32		153029R	570,90
Set Allround 22			
10+12+14+15+16+17+18+20+22	$\frac{3}{8} + \frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}"$	153027R	482,67
Set 16+18+20+25/26+32		153023R	607,23
Set Allround 32			
10+12+14+15+16+17+18+20+22+			
25/26+32	$\frac{3}{8} + \frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}"$	153028R	679,89



Accessories

Description	Art.-No.	€
REMS Swing drive unit	153100R	153,62
Back former support S Ø 10–26 mm with back formers for pipes Ø 10–26 mm, $\frac{3}{8}$ – $\frac{7}{8}"$	153125RX	61,97
Back former support Ø 32 mm with back formers for pipe Ø 32 mm	153115RX2	133,38
Device for reverse bending on laid pipes up to Ø 26 mm, $\frac{7}{8}"$	153140	154,66
Steel case with inlay	153265R	55,01
Case with inlay	153270R	107,95



Bending former for tubes Ø mm/inch	Bending radius ¹⁾ mm	suitable for					
		C	Cu-U	St 10305-U	St 10305		
10, $\frac{3}{8}"$	30	●			●	153155R	32,07
12, 10 U, $\frac{1}{2}"$	36	●	●		●	153160R	32,07
14, 12 U	50	●	●	●	●	153170R	32,07
15, 12 U, $\frac{5}{8}"$	55	●	●		●	153175R	32,07
16, 14 U	55	●	●	●	●	153180R	32,07
17, 15 U	60			●	●	153185R	32,07
18, 14 U, 15 U, 16 U, $\frac{3}{4}"$	72	●	●	●	●	153190R	32,07
20, 18 U	79	●	●	●	●	153195R	32,07
22, 18 U, $\frac{7}{8}"$	86	●	●			153200R	32,07
25, 26	88				●	153205R	32,07
32	128				●	153210R	60,20



¹⁾ Bending radius mm at the neutral axis of the bend (DVGW GW 392)

Cu: soft copper tubes, also thin-wall

St 10305-U: soft, coated carbon steel pipes of the pressfitting systems
EN 10305-3

St 10305: soft precision steel pipes EN 10305-1, EN 10305-2,
EN 10305-3

U: coated

V: multi-layer composite tubes of pressfitting systems

REMS Hydro-Swing

Oil-hydraulic hand pipe bender

Effort-saving, oil-hydraulic hand pipe bender for dimensionally accurate bending of pipes up to 90°. Ideal for on-site work. For trade and industry. For the building site and the workshop.

Soft copper pipes, also thin-walled	\varnothing 10 – 22 mm \varnothing $\frac{3}{8}$ – $\frac{7}{8}$ " $s \leq 1$ mm
Coated soft copper tubes	\varnothing 10 – 18 mm \varnothing $\frac{3}{8}$ – $\frac{5}{8}$ " $s \leq 1$ mm
Pipes of press fitting systems made of: stainless steel, nickel steel	\varnothing 15 – 22 mm $s \leq 1.2$ mm
Soft, coated carbon steel	\varnothing 12 – 18 mm $s \leq 1.2$ mm
Soft precision steel tubes	\varnothing 10 – 22 mm $s \leq 1.5$ mm
Multi-layer composite tubes	\varnothing 14 – 32 mm

REMS Hydro-Swing – bending tubes where they are installed. Universally usable for many pipe types. Effortless working due to oil-hydraulic force transmission.

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Also for copper thin-walled heating tubes according to EN 1057 and for tubes of pressfitting systems.

Cost advantage

Bender recovered after a few bends through savings on fittings. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design


Robust, compact drive unit with closed, maintenance-free hydraulic system. Handy and light, only 2.4 kg. Can be used anywhere, even in confined spaces. Easy, quick working, e.g. Ø 22 mm copper pipe bend in just 18 s. Marked bending formers for exact bending. Overbend, tier bend possible. Easy and rapid changing of bending formers. Back former support H-S Ø 10 – 26 mm, rotatable according to the size of the pipe to be bent, with back formers for pipes Ø 10 – 26 mm, $\frac{3}{8}$ – $\frac{7}{8}$ ". Back former support Ø 32 mm with back formers for pipes Ø 32 mm. Device H-S for reverse bending on laid pipes up to Ø 26 mm, $\frac{7}{8}$ ", as accessory.

Bending formers and sliding pieces

Bending formers and back formers made of high strength, high sliding, glass fibre reinforced polyamide or aluminium bending formers. Angle scale on each bending former for dimensionally accurate bending. See table on page 131 for bending formers.

Drive

Oil-hydraulic drive unit with hydraulic cylinder made from high-quality, rolled hydraulic tube. Ergonomically designed thrust lever for strength saving pressure build-up with manual hydraulic pump. Reliable hydraulic thrust with overload protection in the foremost piston position and overpressure valves for safe working.



German Quality Product



Info

REMS Hydro-Swing

Oil-hydraulic hand pipe bender

Supply format

REMS Hydro-Swing Set. Oil-hydraulic hand pipe bender Ø 10–32 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", up to 90°. Soft copper pipes Ø 10–22 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", s ≤ 1 mm, soft, coated copper pipes Ø 10–18 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", s ≤ 1 mm, pipes of the press fitting systems made of soft, coated carbon steel Ø 12–18 mm, s ≤ 1.2 mm, soft precision steel pipes Ø 10–18 mm, s ≤ 1.5 mm, composite tubes Ø 14–32 mm. Up to Ø 26 mm with drive unit, polyamide bending formers, back former support H-S Ø 10–26 mm with back formers, in a sturdy case. Up to Ø 32 mm with drive unit, polyamide bending formers, 2 back former supports Ø 10–26 mm and Ø 32 mm with back formers, in a sturdy case.

Description mm	inch	Art.-No.	€
Set 12 + 15 + 18 + 22	$\frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}$ "	153525RX	699,61
Set 10 + 12 + 15 + 18 + 22	$\frac{3}{8} + \frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}$ "	153521RX	725,56
Set 12 + 14 + 16 + 18 + 22	$\frac{1}{2} + \frac{3}{4} + \frac{7}{8}$ "	153520RX	725,56
Set 14 + 16 + 20 + 25/26		153526R	699,61
Set 14 + 16 + 18 + 20 + 25/26		153522R	725,56
Set 16 + 20 + 25/26 + 32		153529R	777,46
Set Allround 22			
10 + 12 + 14 + 15 + 16 + 17 + 18 + 20 + 22	$\frac{3}{8} + \frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}$ "	153527RX	755,66
Set 16 + 18 + 20 + 25/26 + 32		153523R	801,34
Set Allround 32			
10 + 12 + 14 + 15 + 16 + 17 + 18 + 20 + 22 + 25/26 + 32	$\frac{3}{8} + \frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}$ "	153528RX	857,39



Supply format

REMS Hydro-Swing INOX Set. REMS Hydro-Swing with aluminium bending formers, especially also for
Geberit Mapress Stainless Steel (EN 10088, 1.4401),
Geberit Mapress Stainless Steel (EN 10088, 1.4521, nickel-free),
Geberit Mapress Carbon Steel (EN 10305-3, 1.0034 (E195)),
Viega Sanpress (EN 10088, 1.4401),
Viega Prestabo (EN 10305-3, 1.0308 (E235)).

Description mm	Art.-No.	€
Set 15 + 18 + 22	153510R	773,31

Accessories


Description	Art.-No.	€
REMS Hydro-Swing drive unit	153500R	569,86
Back former support H-S Ø 10–26 mm with back formers for pipe Ø 10–26 mm, $\frac{3}{8}$–$\frac{7}{8}$"	153501R	69,34
Back former support Ø 32 mm with back formers for pipe Ø 32 mm	153115RX2	133,38
Device H-S for reverse bending on laid pipes up to Ø 26 mm, $\frac{7}{8}$"	153450R	237,70
Case with inlay	153570R	107,95

Bending former for tubes Ø mm/inch	Bending radius ¹⁾ mm	suitable for				
		C	Cu-U	St 10217	St 10305	St 10305-U >
10, $\frac{3}{8}$ "	30	●		●		153155R 32,07
12, 10 U, $\frac{1}{2}$ "	36	●	●	●		153160R 32,07
14, 12 U	50	●		●	●	153170R 32,07
15, 12 U, $\frac{5}{8}$ " ²⁾	55	●	●	●	●	153531R 73,49
15, 12 U, $\frac{7}{8}$ "	55	●	●		●	153175R 32,07
16, 14 U	55	●	●	●		153180R 32,07
17, 15 U	60				●	153185R 32,07
18, 14 U, 15 U, 16 U, $\frac{3}{4}$ " ²⁾	72	●	●	●	●	153532R 73,49
18, 14 U, 15 U, 16 U, $\frac{7}{8}$ "	72	●	●		●	153190R 32,07
20, 18 U	79	●	●		●	153195R 32,07
22, 18 U, $\frac{5}{8}$ " ²⁾	86	●	●	●		153540R 73,49
22, 18 U, $\frac{7}{8}$ "	86	●	●			153200R 32,07
25, 26	88				●	153205R 32,07
32	128				●	153210R 60,20

¹⁾ Bending radius mm at the neutral axis of the bend (DVGW GW 392)

²⁾ Aluminium bending formers

- Cu: soft copper tubes, also thin-wall, EN 1057
- St 10217: stainless, nickel steel pipes of the press fitting systems EN 10217-7, EN 10312, series 2, material 1.4401
- St 10305: soft precision steel pipes EN 10305-1, EN 10305-2, EN 10305-3
- St 10305-U: soft, coated carbon steel pipes of the pressfitting systems EN 10305-3
- U: coated
- V: multi-layer composite tubes of pressfitting systems



REMS Hydro-Swing 22 V

Cordless tube bender

Universal, mobile, handy electric tool for dimensionally accurate bending of pipes up to 90°. Ideal for on-site work. For trade and industry. For the building site and the workshop. Li-Ion 22 V Technology. For battery and corded operation.

Soft copper pipes, also thin-walled	Ø 10 – 22 mm Ø 3/8 – 7/8" s ≤ 1 mm
Coated soft copper tubes	Ø 10 – 18 mm Ø 3/8 – 5/8" s ≤ 1 mm
Pipes of press fitting systems made of: stainless steel, nickel steel	Ø 15 – 22 mm s ≤ 1.2 mm
Soft, coated carbon steel	Ø 12 – 18 mm s ≤ 1.2 mm
Soft precision steel tubes	Ø 10 – 22 mm s ≤ 1.5 mm
Multi-layer composite tubes	Ø 14 – 32 mm

REMS Hydro-Swing 22 V – bending tubes where they are installed. Mobile, handy, light. Universally usable for many pipe types. Li-Ion 21.6 V, 2.5 Ah battery, for approx. 110 stainless steel pipe bends of the Ø 22 mm press fitting systems with one battery charge*.

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Also for copper thin-walled heating tubes according to EN 1057 and for tubes of pressfitting systems.

Cost advantage

Cordless tube bender recovered after a few bends through savings on fittings. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Robust, compact drive unit with closed, maintenance-free hydraulic system. Mobile, handy, light. Drive machine with battery pack weights only 3.0 kg. Can be used anywhere, even in confined spaces. Easy, quick working, e.g. Ø 22 mm stainless steel pipe bend in just 8 s. Marked bending formers for exact bending. Overbend, tier bend possible. Easy and rapid changing of bending formers. Back former support H-S Ø 10–26 mm, rotatable according to the size of the pipe to be bent, with back formers for pipes Ø 10–26 mm, 3/8 – 7/8". Back former support Ø 32 mm with back formers for pipes Ø 32 mm. LED work light for illuminating the work place. Device H-S for reverse bending on laid pipes up to Ø 26 mm, 7/8", as accessory.

Bending formers and sliding pieces

Bending formers and back formers made of high strength, high sliding, glass fibre reinforced polyamide or aluminium bending formers. Angle scale on each bending former for dimensionally accurate bending. See table on page 133 for bending formers.

Drive

Tons of thrust for crease-free bending within seconds. Thrust force 9 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah battery for approx. 110 pipe bends, 4.4 Ah for approx. 190 pipe bends, 5.0 Ah for approx. 220 pipe bends, 9.0 Ah for approx. 396 pipe bends of the stainless steel Ø 22 mm press fitting systems with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 15A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Supply format

REMS Hydro-Swing 22V INOX Set. REMS Hydro-Swing 22 V with aluminium bending formers, especially also for Geberit Mapress Stainless Steel (EN 10088, 1.4401), Geberit Mapress Stainless Steel (EN 10088, 1.4521, nickel-free), Geberit Mapress Carbon Steel (EN 10305-3, 1.0034 (E195)), Viega Sanpress (EN 10088, 1.4401), Viega Prestabo (EN 10305-3, 1.0308 (E235)).

Description	mm	Art.-No.	€
Set 15 + 18 + 22		153419R220	1 483,30

Other voltages on request.



German Quality Product



Info



REMS Hydro-Swing 22 V

Cordless tube bender

Supply format

REMS Hydro-Swing 22 V Set. Cordless tube bender Ø 10–32 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", up to 90°. Soft copper pipes Ø 10–22 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", s ≤ 1 mm, soft, coated copper pipes Ø 10–18 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", s ≤ 1 mm, pipes of the press fitting systems made of soft, coated carbon steel Ø 12–18 mm, s ≤ 1.2 mm, soft precision steel pipes Ø 10–18 mm, s ≤ 1.5 mm, composite tubes Ø 14–32 mm. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240V or 110 V, 50–60 Hz, 70 W. Up to Ø 26 mm with polyamide bending formers, back former support H-S Ø 10–26 mm with back formers. Up to Ø 32 mm with polyamide bending formers, 2 back former supports Ø 10–26 mm and Ø 32 mm with back formers. In XL-Boxx system case.

Description mm	inch	Art.-No.	€
Set 12+15+18+22	$\frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}$ "	153410RX220	1 389,88
Set 10+12+15+18+22	$\frac{3}{8} + \frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}$ "	153411RX220	1 431,40
Set 12+14+16+18+22	$\frac{1}{2} + \frac{3}{4} + \frac{7}{8}$ "	153412RX220	1 431,40
Set 14+16+20+25/26		153413R220	1 389,88
Set 14+16+18+20+25/26		153414R220	1 431,40
Set 16+20+25/26+32		153415R220	1 483,30
Set Allround 22			
10+12+14+15+16+17+18+20+22	$\frac{3}{8} + \frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}$ "	153416RX220	1 555,96
Set 16+18+20+25/26+32		153417R220	1 587,10
Set Allround 32			
10+12+14+15+16+17+18+20+22+	$\frac{3}{8} + \frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}$ "	153418RX220	1 784,32
25/26+32			
Basic-Pack (ohne Biegesegmente und Gleitstücke)		153401R220	1 203,04

Other voltages on request.



Accessories

Description	Art.-No.	€
REMS Hydro-Swing 22V drive unit, without battery	153400R22	544,95
Back former support H-S Ø 10–26 mm with back formers for pipe Ø 10–26 mm, $\frac{3}{8}$ – $\frac{7}{8}$ "	153501R	69,34
Back former support Ø 32 mm with back formers for pipe Ø 32 mm	153115RX2	133,38
Device H-S for reverse bending on laid pipes up to Ø 26 mm, $\frac{3}{8}$ "	153450R	237,70
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 15A, for mains operation instead of battery Li-Ion 21.6 V	571567R220	414,16
XL-Boxx system case with inserts	153455R	233,55

REMS Lumen 2800 22V, cordless LED flood light, see page 111

Bending former for tubes Ø mm/inch	Bending radius ¹⁾ mm	suitable for						
		$\text{\textcircled{C}}$	Cu-U	St 10217	St 10305	St 10305-U		
10, $\frac{3}{8}$ "	30	●		●			153155R	32,07
12, 10 U, $\frac{1}{2}$ "	36	●	●	●			153160R	32,07
14, 12 U	50	●			●	●	153170R	32,07
15, 12 U, $\frac{5}{8}$ " ²⁾	55	●	●	●	●		153531R	73,49
15, 12 U, $\frac{7}{8}$ "	55	●	●		●		153175R	32,07
16, 14 U	55	●	●		●	●	153180R	32,07
17, 15 U	60				●	●	153185R	32,07
18, 14 U, 15 U, 16 U, $\frac{3}{4}$ " ²⁾	72	●	●	●	●	●	153532R	73,49
18, 14 U, 15 U, 16 U, $\frac{7}{8}$ "	72	●	●		●	●	153190R	32,07
20, 18 U	79	●	●		●	●	153195R	32,07
22, 18 U, $\frac{7}{8}$ " ²⁾	86	●	●	●	●		153540R	73,49
22, 18 U, $\frac{7}{8}$ "	86	●	●				153200R	32,07
25, 26	88					●	153205R	32,07
32	128					●	153210R	60,20

¹⁾ Bending radius mm at the neutral axis of the bend (DVGW GW 392)

²⁾ Aluminium bending formers

- Cu: soft copper tubes, also thin-wall, EN 1057
 St 10217: stainless, nickel steel pipes of the press fitting systems
 EN 10217-7, EN 10312, series 2, material 1.4401
 St 10305: soft precision steel pipes EN 10305-1, EN 10305-2,
 EN 10305-3
 St 10305-U: soft, coated carbon steel pipes of the pressfitting systems
 EN 10305-3
 U: coated
 V: multi-layer composite tubes of pressfitting systems

* Ambient temperature approx. 20°C.

Robust, oil-hydraulic pipe bender for dimensionally accurate bending of pipes up to 90°. For trade and industry. For the building site and the workshop.

Steel pipes EN 10255	Ø 3/8 – 2"
Multilayer composite tubes	Ø 32 – 75 mm

REMS Python – extremely easy bending up to Ø 2", 75 mm. Ideal for steel pipes EN 10255 and for multilayer composite tubes of the pressfitting systems. Also for producing level bends in different planes.

Universal use

For locksmith work, sanitary and heating installation and machine and plant engineering. Excellently suitable for steel pipes EN 10255 and for multilayer composite tubes of the pressfitting systems.

System advantage

Only one bender drive for the whole working range up to Ø 2", Ø 75 mm. Thus simple, inexpensive stocking. No confusion possible.

Cost advantage

Pipe bender is amortised after just a few bends by saving on fittings. No costs for fittings, storage, procurement. Saving of welds, press connections and working time. Increased safety due to fewer pipe connections.

Design

Robust, oil-hydraulic drive unit with closed, maintenance-free hydraulic system. 2 slide roller supports and 2 slide rollers form a closed bending frame for high rigidity and precision when bending. Upper back former support tiltable for easy insertion and removal of the pipe, with marked plug positions for the back formers according to the pipe size to be bent, with angle scale 0 to 90°. Upper slide roller support with laterally adjustable slide roller bearing plate for producing over-bends and level bends according to requirements also in different planes. Can be used anywhere, any time. No setting. Easy, effortless, quick working, e.g. 90° bend Ø 63 mm only 60 s. Tripod as accessory.

Bending formers and back formers

Bending formers St for steel pipes, form and pressure stable, made of highly resistant spheroidal iron. Bending formers V for multilayer composite tubes, form and pressure stable, made of torsion-free shell-cast aluminium. See page 135. Marking on every bending former for dimensionally accurate bending. Angle gauge with angle scale 0 to 180° for dimensionally accurate bending, as an accessory. Optimum matching of bending formers and back formers guarantees material-compatible bending without cracks and creases. High strength back formers for low friction support of the thrust pressure. Fast changing of the bending formers and back formers by simple plug system.

Drive

Oil-hydraulic drive unit with hydraulic cylinder made from high-quality, rolled hydraulic tube. Overload protection of the hydraulic thrust in the foremost piston position and overpressure valves for safe working. Ergonomically designed thrust lever for strength saving pressure build-up with manual hydraulic pump. No danger of crushing due to end limiting of the thrust lever, for high work safety.



German Quality Product



Bridges.



Info



Doglegs on several levels.

Supply format

REMS Python Set. Oil-hydraulic pipe bender for dimensionally accurate bending of pipes up to 90°. Steel pipes EN 10255 Ø ¾"-2", multilayer composite tubes Ø 32-75 mm. Drive unit with back former supports, upper back former support with laterally adjustable back former support bearing plate, 2 back formers, bending formers St or V. In sturdy carrying case.

Description	Art.-No.	€
Set St $\frac{3}{8} + \frac{1}{2} + \frac{3}{4} + 1 + 1\frac{1}{4}$"	590020R	1 676,37
Set St $\frac{1}{2} + \frac{3}{4} + 1 + 1\frac{1}{4} + 1\frac{1}{2} + 2$"	590021R	1 806,12
Set V 40 + 50 + 63 mm	590022R	1 702,32



Accessories

Description			Art.-No.	€
Drive unit with back former supports and back formers			590000R	1 479,15
Slide piece Ø 75 mm (pack of 2)			590111R	370,57
Tripod			590150R	168,16
Carrying case with practical handles			590160R	247,04
Angle gauge for dimensionally accurate bending			590153R	43,18
			suitable for	
Bending former for pipes Ø mm/inch	Bending radius ¹⁾ mm	Bending radius ²⁾ mm	St 10255	>
St 3/8"	50		●	
St 1/2"	65		●	
St 3/4"	85		●	
St 1"	100		●	
St 1 1/4"	150		●	
St 1 1/2"	170		●	
St 2"	220		●	
V 32 mm	112	128	●	590061R
V 40 mm	140	160	●	590058R
V 50 mm	175	200	●	590059R
V 63 mm	220	252	●	590060R
V 75 mm	260	298	▲	590062R
				330,08



St 10255: Steel pipes (threaded pipes) EN 10255

St 10255: Steel pipes (threaded pipes) EN 10255
V: multilayer composite pipes of the pressfitting systems

▲ Multilayer composite pipes of the pressfitting system
2 slide pieces Ø 75 mm (Art. No. 590111) required

¹⁾ Bending radius mm on the inside of the bend (EN 10255)

²⁾ Bending radius mm at the neutral axis of the bend (DVGW VP 632)

Universal, compact electric tool for cold bending of pipes and tubes up to 180°. Can be used anywhere, without vice. For trade and industry. For the building site and the workshop.

Hard, half-hard, soft copper tubes also thin-wall	Ø 10 – 35 mm Ø 3/8 – 1 1/8"
Coated soft copper tubes, also thin-wall	Ø 10 – 18 mm
Thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1	Ø 3/8 – 1 1/8"
Pipes of press fitting systems made of stainless steel	Ø 12 – 28 mm
Carbon steel (coated)	Ø 12 – 28 mm
Soft precision steel tubes	Ø 10 – 28 mm
Steel pipes EN 10255	Ø 1/4 – 3/4"
Electric conduit EN 50086	Ø 16 – 32 mm
Multi-layer composite tubes	Ø 14 – 40 mm

REMS Curvo – wrinkle-free bending.

Universal for many pipe types. Instant use without setting. Fast and creep speed operation for precise bending. Rapid change of bending and back formers.

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Specially suited for tubes of pressfitting systems, for hard and half-hard copper tubes and for thin-walled copper heating tubes according to EN 1057.

System advantage

Only one type of bending and back formers for REMS Curvo 22V, REMS Curvo, REMS Curvo 50 and REMS Sinus. Therefore simple, inexpensive stocking. No confusion possible.

Cost advantage

Bender cost recovered after a small number of bends. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Compact, handy electric tool with integral absorbtion of torque during bending. Super light, drive unit only 8 kg. Can be used anywhere, anytime. No setting. Simple, effortless, fast working, e.g. 90° bends, Ø 22 mm in only 6 s. Fast and creep speed operation for precise bending. Overbend, double bend, tier bend, reversed bend possible. Height adjustable machine support as accessory.

Bending formers and back formers

Form and pressure resistant, in high-strength, high-slide, glass-fibre reinforced polyamide. Optimum matching of bending former and back former guarantees material-compatible gliding without cracks and creases. Angle scale 0 to 180° provided on each bending former and mark on the back former ensure precise bending. Rapid change of bending formers and back formers. Bending formers and back formers for different sizes, materials and bending radii (page 143).

Drive

Robust, maintenance-free gear. Final point safety in both directions through safety slipping clutch. Proven, powerful universal motor, 1000 W. Right and left-hand rotation. Stepless electronic safety switch for rapid and creep speed operation.

Bending lubricant

REMS bending spray ensures a permanent lubricating film for reducing energy expenditure and uniform bending. High-pressure-proof, acid-free. CFC-free, so ozone-harmless.



German Quality Product



Info



Supply format

REMS Curvo Set. Electric pipe and tube bender Ø 10–40 mm, Ø ¼–1½", up to 180°. Hard, semi-hard, soft copper pipes, also thin-walled, Ø 10–35 mm, Ø ¾–1½", soft coated copper pipes, also thin-walled, Ø 10–18 mm, thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1 Ø ¾–1½", pipes of the press fitting systems of stainless steel Ø 12–28 mm, carbon steel, also coated, Ø 12–28 mm, soft precision steel pipes Ø 10–28 mm, steel pipes EN 10255 Ø ¼–¾", electrical installation pipes EN 50086 Ø 16–32 mm, composite tubes Ø 14–40 mm, etc. Drive unit with maintenance-free gear and safety slipping clutch, universal motor 230 V or 110 V, 50–60 Hz, 1000 W, stepless electronic safety switch, right and left-hand rotation, insert bolt. Bending formers and back formers. In sturdy steel case.

Description	Art.-No.	€
Set 15+18+22	580026R220	1 743,84
Set 15+18+22+28¹⁾	580027R220	1 941,06
Set 15+18+22+28²⁾	580036R220	2 055,24
Set 15+18+22+28³⁾	580035R220	2 013,72
Set 12+15+18+22	580020R220	1 837,26
Set 12+15+18+22+28¹⁾	580033R220	2 107,14
Set 12+15+18+22+28²⁾	580037R220	2 148,66
Set 15+22+28¹⁾	580022R220	1 837,26
Set 15+22+28²⁾	580040R220	1 951,44
Set 17+20+24	580023R220	1 909,92
Set 12+14+16+18+22	580021R220	1 930,68
Set 12+14+16+18+22+28¹⁾	580031R220	2 138,28
Set 12+14+16+18+22+28²⁾	580038R220	2 242,08
Set 14+16+18+22+28¹⁾	580028R220	2 034,48
Set 14+16+18+22+28²⁾	580039R220	2 148,66
Set ¾ + ½ + ¾ + ¾ + ¾"	580024R220	2 345,88
Set 16+20+26+32	580025R220	2 231,70
Set 16+20+25+32	580034R220	2 148,66
Set 20+25+32	580029R220	2 117,52
Set 32+40	580030R220	2 148,66
Basic-Pack (without bending and back formers)	580010R220	1 328,64

REMS Curvo Set delivered with the smaller radius bending and back former (except Art.-No. 580029 and 580030), see page 143.

- ¹⁾ Bending former and back former 28, R102, Art. No. 581070, for hard, semi-hard copper pipes, also thin-walled. See page 143.
- ²⁾ Bending former and back former 28, ¾" (DN 20), R102, Art. No. 581260, for hard copper pipes Ø 28 mm, Ø 1½", pipes of the press fitting systems of stainless steel/carbon steel Ø 28 mm, steel pipes ¾". See page 143.
- ³⁾ Bending former and back former 28, ¾" (DN 20), R114, Art. No. 581310, for hard, semi-hard copper pipes Ø 28 mm, pipes of the press fitting systems of stainless steel/carbon steel Ø 28 mm, steel pipes ¾". According to DVGW work sheet GW 392 for hard and semi-hard copper pipes Ø 28 mm minimum bending radius 114 mm necessary. Wall thickness ≥ 0.9 mm. See page 143.

Accessories

Description	Art.-No.	€
Bending formers and back formers see page 143.		
REMS Curvo drive unit	580000R220	1 183,32
Insert bolt	582036	40,79
REMS bending spray, 400 ml	140120R	28,86
Steel case with insert	586000R	128,71
Machine support 3B, height adjustable, on tripod	586100R	243,93
Machine support WB, height adjustable, for mounting on work bench	586150R	171,27




Basic-Pack



Universal, compact electric tool for cold bending of pipes and tubes up to 90°. Can be used anywhere, without vice. For trade and industry. For the building site and the workshop.

Steel pipes EN 10255 (DIN 2440)	Ø 1/4 – 1 1/4"
Stainless steel pipes EN ISO 1127, EN 10217-1	Ø 1/2 – 1 1/4" s ≤ 2.6 mm
Hard, half-hard, soft copper tubes	Ø 10 – 42 mm
Thin-wall copper tubes	Ø 10 – 35 mm
Thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1	Ø 3/8 – 1 5/8"
Pipes of press fitting systems made of stainless steel	Ø 12 – 42 mm
Carbon steel, also coated	Ø 12 – 42 (28) mm
Multi-layer composite tubes	Ø 14 – 50 mm
Further materials, see REMS Curvo	



REMS Curvo 50 – wrinkle free bending of large pipes.

Universal use

For metalwork and in sanitary, heating, air conditioning, refrigeration and hydraulic applications. Specially suited for steel pipe EN 10255, pipe for press-fitting systems, for hard and half hard copper pipe and for thin-walled copper heating pipe according to EN 1057.

System advantage

Bending formers and back formers of REMS Curvo 22V, REMS Curvo and REMS Sinus (page 143) also fit in the REMS Curvo 50 drive machine with adaptor block 10–40, support 10–40. Therefore simple, inexpensive stocking. No confusion possible.

Cost advantage

Bender cost recovered after a small number of bends. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Compact, handy electric tool with integral absorption of torque during bending. Can be used anywhere, anytime. No setting. Simple, effortless, fast working, e.g. 90° bends of steel pipe Ø 1 1/4" in only 37 s. Fast and creep speed operation for precise bending. Overbend, tier bend, reversed bend possible.

Bending formers and back formers

Optimum matching of bending former and back former guarantees material-compatible gliding without cracks and creases. Angle scale provided on each bending former and mark on the back former ensure precise bending. Rapid change of bending formers and back formers. Bending formers and back formers for different sizes, materials and bending radii (page 143). Bending formers and back formers REMS Curvo 50 (Ø 35 R 100, Ø 42 R 140, Ø 50 R 135, Ø 1" R 100, Ø 1 1/4" R 140): Form and pressure resistant bending formers in ductile iron and back formers in high-strength, high-slide glass-fibre reinforced polyamide.

Drive

Robust, maintenance-free gear. Final point safety in both directions through safety slipping clutch. Proven, powerful universal motor, 1000 W. Right and left-hand rotation. Stepless electronic safety switch for rapid and creep speed operation.

Bending lubricant

REMS bending spray ensures a permanent lubricating film for reducing energy expenditure and uniform bending. High-pressure-proof, acid-free. CFC-free, so ozone-harmless.



German Quality Product



Info



Supply format

REMS Curvo 50 Basic-Pack. Electric pipe and tube bender Ø 10–50 mm, up to 90°. Steel pipes EN 10255 Ø ¼–1¼", stainless steel pipes EN ISO 1127, EN 10217-7, Ø ½–1¼", s ≤ 2.6 mm, hard, semi-hard, soft copper pipes, Ø 10–42 mm, thin-walled copper pipes Ø 10–35 mm, thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1 Ø ¾–1½", pipes of the press fitting systems of stainless steel Ø 12–42 mm, carbon steel Ø 12–42 mm, coated carbon steel Ø 12–28 mm, composite tubes Ø 14–50 mm, etc. Drive unit with maintenance-free gear and safety slipping clutch, universal motor 230 V or 110 V, 50–60 Hz, 1000 W, stepless electronic safety switch, right and left-hand rotation. Adaptor block 35–50, Support 35–50, insert bolt. In sturdy carrying case.

	Art.-No.	€
	580110R220	3 477,30

Other voltages on request.



Accessories

Description	Art.-No.	€
Bending formers and back formers see page 143.		
REMS Curvo 50 drive unit	580100R220	3 072,48
Adaptor block 35–50, Support 35–50, for bending formers and back formers Ø 35 R 100, Ø 42 R 140, Ø 50 R 135, Ø 1" R 100, Ø 1¼" R 140 (see page 143).	582110R	184,76
Adaptor block 10–40, Support 10–40, for bending formers and back formers REMS Curvo, REMS Curvo 22 V, REMS Sinus (see page 143).	582120R	303,10
Insert bolt	582036	40,79
REMS bending spray, 400 ml	140120R	28,86
Carrying case with practical handles	590160R	247,04
Steel case with insert for each bending former and back former R 100 and R 135/R 140, 90°	586012R	110,03



REMS Curvo 22V

Universal, mobile electric tool for cold bending of pipes up to 180°. Can be used anywhere, without vice. For trade and industry. For the building site and the workshop. Li-Ion 22V Technology. For battery and corded operation.

Hard, half-hard, soft copper tubes also thin-wall	Ø 10–28 mm Ø 3/8–1 1/8"
Coated soft copper tubes, also thin-wall	Ø 10–18 mm
Thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1	Ø 3/8–1 1/8"
Pipes of press fitting systems made of stainless steel	Ø 12–28 mm
Carbon steel, also coated	Ø 12–28 mm
Soft precision steel tubes	Ø 10–28 mm
Steel pipes EN 10255	Ø 1/4–3/4"
Electric conduit EN 50086	Ø 16–25 mm
Multi-layer composite tubes	Ø 14–40 mm

REMS Curvo 22V – wrinkle-free bending of pipes.

**Mobile, handy, light. Universal for many pipe types.
Ready to use immediately without setting. Fast and
creep speed with immediate stop for precise bending.
Quick change of bending and back formers.**

**Li-Ion 21.6 V, 5.0 Ah battery, for approx. 90 pipe bends
of the stainless steel Ø 22 mm press fitting systems
with one battery charge*.**

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Mains independent. Specially suited for tubes of pressfitting systems, for hard and half-hard copper tubes and for thin-walled copper heating tubes according to EN 1057.

System advantage

Only one type of bending and back formers for REMS Curvo 22V, REMS Curvo, REMS Curvo 50 and REMS Sinus. Therefore simple, inexpensive stocking. No confusion possible.

Cost advantage

Bender cost recovered after a small number of bends. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Compact, mobile, handy electric tool with integral absorbtion of torque during bending. Super light, drive machine with battery pack weights only 8.5 kg. Electronic charging status check with low discharge protection. Practical D-shaped handle with soft grip. Can be used anywhere, anytime. No setting. Simple, effortless, fast working, e.g. 90° bend Ø 22 mm only 6 s. Fast and creep speed with immediate stop for precise bending. Overbend, double bend, tier bend, reversed bend possible. Height adjustable machine support as accessory.

Bending formers and back formers

Form and pressure resistant, in high-strength, high-slide, glass-fibre reinforced polyamide. Optimum matching of bending former and back former guarantees material-compatible gliding without cracks and creases. Angle scale 0 to 180° provided on each bending former and mark on the back former ensure precise bending. Rapid change of bending formers and back formers. Bending formers and back formers for different sizes, materials and bending radii (page 143).

Drive

Robust, maintenance-free gear. Final point safety in both directions through safety slipping clutch. Powerful battery motor 21.6 V, with large power reserve, 500 W output. Right and left-hand rotation. Stepless electronic safety switch for fast and creep speed, with immediate stop. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check with charging level indication by a 2-coloured green/red LED.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 4.4 Ah battery, for approx. 79 pipe bends, 5.0 Ah battery, for approx. 90 pipe bends, 9.0 Ah for approx. 160 pipe bends of the stainless steel Ø 22 mm press fitting systems with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range -10 to +60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6 V, 40 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.


Cordless tube bender



German Quality Product



Info



Bending lubricant

REMS bending spray ensures a permanent lubricating film for reducing energy expenditure and uniform bending. High-pressure-proof, acid-free. CFC-free, so ozone-harmless.

Supply format

REMS Curvo 22V Set. Cordless tube bender Ø 10–40 mm, Ø ¼–1½", to 180°. Hard, semi-hard, soft copper pipes, also thin-walled, Ø 10–28 mm, Ø ¾–1½", soft coated copper pipes, also thin-walled, Ø 10–18 mm, thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1 Ø ¾–1½", pipes of the press fitting systems of stainless steel Ø 12–28 mm, carbon steel, also coated, Ø 12–28 mm, soft precision steel pipes Ø 10–28 mm, steel pipes EN 10255 Ø ¼–¾", electrical installation pipes EN 50086 Ø 16–25 mm, composite tubes Ø 14–40 mm, etc. Drive machine with D-shaped handle, maintenance-free gear with safely slipping clutch, powerful battery motor 21.6 V, stepless, electronic safety switch with immediate stop, right and left-hand rotation. Machine status check with overload protection, temperature monitoring, battery charging status check. Li-Ion 21.6 V, 5.0 Ah battery, 100–240V, 50–60 Hz, 90W rapid charger. Insert bolt. Bending and back formers. In sturdy steel case.

Description	Art.-No.	€
Set 15+18+22	580051R220	2 539,99
Set 15+18+22+28¹⁾	580052R220	2 818,17
Set 15+18+22+28²⁾	580053R220	2 792,22
Set 15+18+22+28³⁾	580054R220	2 750,70
Set 12+15+18+22	580055R220	2 574,24
Set 12+15+18+22+28¹⁾	580056R220	2 844,12
Set 12+15+18+22+28²⁾	580057R220	2 885,64
Set 15+22+28¹⁾	580058R220	2 574,24
Set 15+22+28²⁾	580059R220	2 688,42
Set 17+20+24	580060R220	2 646,90
Set 12+14+16+18+22	580061R220	2 667,66
Set 12+14+16+18+22+28¹⁾	580062R220	2 875,26
Set 12+14+16+18+22+28²⁾	580063R220	2 979,06
Set 14+16+18+22+28¹⁾	580064R220	2 771,46
Set 14+16+18+22+28²⁾	580065R220	2 885,64
Set ¾+½+⅓+⅔+⅕"	580066R220	3 082,86
Set 16+20+26+32	580067R220	2 968,68
Set 16+20+25+32	580068R220	2 885,64
Set 20+25+32	580069R220	2 854,50
Basic-Pack (without bending and back formers)	580014R220	2 065,62

Other voltages on request.

REMS Curvo 22V Set delivered with the smaller radius bending and back former (except Art.-No. 580069), see page 143.

- ¹⁾ Bending former and back former 28, R102, Art. No. 581070, for hard, semi-hard copper pipes, also thin-walled. See page 143.
- ²⁾ Bending former and back former 28, ¾" (DN 20), R102, Art. No. 581260, for hard copper pipes Ø 28 mm, Ø 1½", pipes of the press fitting systems of stainless steel/carbon steel Ø 28 mm. See page 143.
- ³⁾ Bending former and back former 28, ¾" (DN 20), R114, Art. No. 581310, for hard, semi-hard copper pipes Ø 28 mm, pipes of the press fitting systems of stainless steel/carbon steel Ø 28 mm, steel pipes ¾". According to DVGW work sheet GW 392 for hard and semi-hard copper pipes Ø 28 mm minimum bending radius 114 mm necessary. Wall thickness ≥ 0.9 mm. See page 143.

Accessories

Description	Art.-No.	€
Bending formers and back formers see page 143.		
REMS Curvo 22V drive unit, without battery	580004R22	1 442,82
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6 V, 50–60Hz, 40 A, for mains operation instead of battery Li-ion 21.6 V	571578R220	517,96
Insert bolt	582036	40,79
REMS bending spray, 400 ml	140120R	28,86
Steel case with inlay	566030R	128,71
Machine support 3B, height adjustable, on tripod	586100R	243,93
Machine support WB, height adjustable, for mounting on work bench	586150R	171,27
REMS Lumen 2800 22V, cordless LED flood light, see page 111		



REMS Sinus

Universal, robust hand tool for cold bending up to 180°. Can be used anywhere. For trade and industry. For the building site and the workshop.

Hard, half-hard, soft copper tubes, also thin-wall	Ø 10 – 22 mm Ø 3/8 – 7/8"
Coated soft copper tubes, also thin-wall	Ø 10 – 18 mm
Pipes of press fitting systems made of stainless steel, carbon steel (coated)	Ø 12 – 18 mm
Carbon steel	Ø 12 – 22 mm
Soft precision steel tubes	Ø 10 – 20 mm
Electric conduit EN 50086	Ø 16 – 20 mm
Multi-layer composite tubes	Ø 14 – 32 mm

REMS Sinus – wrinkle-free bending.

Universal for many tubes. Easy bending through long lever arms. Selectable lever positioning ensures optimum bending position and power transmission. Only one type of bending and back formers for REMS Sinus and REMS Curvo.

Universal use

For sanitary, heating, air conditioning, refrigerating and hydraulic applications. Specially suited for tubes of pressfitting systems, for hard and half-hard copper tubes and for thin-walled copper heating tubes according to EN 1057.

System advantage

Only one type of bending and back formers for REMS Curvo 22V, REMS Curvo, REMS Curvo 50 and REMS Sinus. Therefore simple, inexpensive stocking. No confusion possible.

Cost advantage

Bender cost recovered after a small number of bends. No costs for fittings, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety thanks to fewer pipe joints.

Design

Compact, handy unit of bender drive and bending tools. Can be used anywhere, in parallel vice or free hand as double-hand-bender. Easy bending through long lever arms. Selectable lever positioning ensures optimum bending position and power transmission. Robust design, drive unit in hardened steel for high stress. Simple and rapid changing of bending and back formers. Crossover, swan-neck and U-bends possible.

Bending formers and back formers

For different pipe sizes, materials and bending radii, see page 143.

Bending lubricant

REMS bending spray ensures a permanent lubricating film for reducing energy expenditure and for uniform bending. High-pressure-proof, acid-free. CFC-free, so ozone-harmless.

Supply format

REMS Sinus Set. Hand tube bender Ø 10 – 32 mm, Ø 3/8 – 7/8", up to 180°. Hard, half-hard, soft copper tubes, also thin-wall Ø 10 – 22 mm, Ø 3/8 – 7/8", coated soft copper tubes, also thin-wall Ø 10 – 18 mm, pipes of the press fitting systems made of stainless steel, carbon steel (coated) Ø 12 – 18 mm, soft precision steel tubes Ø 10 – 22 mm, soft precision steel tubes, Ø 10 – 20 mm, electric conduit EN 50086, Ø 16 – 20 mm, multi-layer composite tubes Ø 14 – 32 mm and others. Drive unit, insert bolt. Bending formers and back formers. REMS bending spray. In sturdy steel case.


Description	Art.-No.	€
Set 15 + 18 + 22	154001R	803,41
Set 14 + 16 + 18	154002R	774,35
Set 12 + 15 + 18 + 22	154003R	903,06
Set 10 + 12 + 14 + 16 + 18 + 22	154004R	1 137,65
Basic-Pack (without bending and back formers and bending spray)	154010R	468,14

REMS Sinus Set is delivered with bending formers and back formers of the smaller radius, see page 143.

Accessories

Description	Art.-No.	€
Bending and back formers see page 143.		
Insert bolt	582036	40,79
REMS Curvo drive unit	580000R220	1 183,32
REMS Sinus drive unit	154000R	299,98
REMS bending spray, 400 ml	140120R	28,86
Steel case with inlay	154160R	128,71

Hand tube bender



German Quality Product



Info



Bending formers and back formers


Accessories for REMS Curvo 50, REMS Curvo, REMS Curvo 22V and REMS Sinus

Bending formers and back formers, 180°, form and pressure resistant, in high-strength, high-slide, glass-fibre reinforced polyamide or aluminum 90° (Ø 21.3 R 103, Ø 26.9 R 102, Ø 33.7 R 100, Ø 35 R 100, Ø 42 R 140, Ø 42.4 R 140, Ø 50 R 135, Ø 1" R 100, Ø 1 1/4" R 140). Optimum matching of bending former and back former guarantees material-compatible gliding without cracks and creases. Angle scale provided on each bending former and mark on the back former ensure precise bending. Rapid change of bending formers and back formers.



Bending former and back former for pipes Ø mm/inch O.D.	R mm	X mm 90°	X mm 45°	Bending former material	REMS Sinus					REMS Curvo					REMS Curvo 22 V					REMS Curvo 50					Art.-No.	€		
					Cu	Cu-U	St10312	St10305-U	St10305	Cu	Cu 12735	Cu-U	St10312	St10305-U	St10305	Cu	Cu 12735	Cu-U	St10312	St10305-U	St10305	Cu	Cu 12735	Cu-U	St10312	St10305-U	St10305	St10255
10	40	45	20	P	●					●					●	●			●	●		●	●		●	●	581400	180,61
12	45	49	22	P	●	●	●	●		●					●	●			●	●		●	●		●	●	581410	135,98
14, 10 U, 1/4" (DN 6)	50	53	23	P	●	●	●	●		●					●	●			●	●		●	●		●	●	581420	131,83
15, 12 U	55	56	25	P	●	●	●	●		●					●	●			●	●		●	●		●	●	581430	147,40
16, 12 U	60	62	28	P	●	●	●	●		●					●	●			●	●		●	●		●	●	581440	148,43
17, 15 U	56	60	27	P						●					●				●	●		●	●		●	●	581110	181,65
18, 14 U, 15 U, 3/8" (DN 10)	70	75	33	P	●	●	●	●		●					●	●			●	●		●	●		●	●	581450	149,47
20, 16 U, 18 U	75	80	36	P	●	●	●	●		●					●	●			●	●		●	●		●	●	581080	237,70
21.3, 1/2" (s = 1.6/2.0/2.6)	103	110	50	S																							581480	536,65
22, 18 U, 1/2" (DN 15)	77	81	36	A	●	●	●	●		●					●	●			●	●		●	●		●	●	581460	177,50
22, 18 U, 1/2" (DN 15)	88	91	41	P						●					●	●			●	●		●	●		●	●	581470	260,54
24, 22 U	75	85	38	P																							581130	288,56
25	98	103	46	P						●					●	●			●	●		●	●		●	●	581180	317,63
26	98	108	49	A						●					●	●			●	●		●	●		●	●	581270	438,04
26.9, 3/4" (s = 1.6/2.0/2.6)	102	108	49	S																							581490	598,93
28 ¹⁾	102 ³⁾	108	49	P																							581070	278,18
28, 3/4" (DN 20) ²⁾	102	110	50	A						●					●	●			●	●		●	●		●	●	581260	428,69
28, 3/4" (DN 20) ²⁾	114	120	54	A						●					●	●			●	●		●	●		●	●	581310	371,60
30, 28 U	98	105	47	P						●					●	●			●	●		●	●		●	●	581150	349,81
32	98	110	50	P						●					●	●			●	●		●	●		●	●	581280	339,43
32	114	121	54	A						●					●	●			●	●		●	●		●	●	581320	438,04
1" (DN 25)	100	105	47	S																							581520	498,24
33.7, 1" (s = 1.6/2.0/2.6)	100	105	47	S																							581520	498,24
35	100	105	47	S																							581500	498,24
35	140	150	68	A						●																581350	585,43	
40	140	148	67	A						●																581330	589,58	
42	140	155	70	S																							581510	532,49
1 1/4" (DN 32)	140	150	68	S																							581530	517,96
42.4, 1 1/4" (s = 2.0/2.6)	140	150	68	S																							581540	699,61
50	135	143	64	S																								
9/16" (9.5 mm)	43	48	22	P	●					●	●				●	●			●	●		●	●		●	●	581200	228,36
1/2" (12.7 mm)	52	60	27	P	●					●	●				●	●			●	●		●	●		●	●	581210	217,98
5/8" (15.9 mm)	63	70	32	P	●					●	●				●	●			●	●		●	●		●	●	581220	244,97
3/4" (19.1 mm)	75	82	37	P	●					●	●				●	●			●	●		●	●		●	●	581230	291,68
7/8" (22.2 mm)	98	107	48	P	●					●	●				●	●			●	●		●	●		●	●	581240	341,50
1" (25.4 mm)	101	112	50	A						●					●	●			●	●		●	●		●	●	581360R	445,30
1" (25.4 mm)	101	112	50	P						●					●	●			●	●		●	●		●	●	581370	338,39
1 1/8" (28.6 mm)	102	110	44	A						●	●				●	●			●	●		●	●		●	●	581260	428,69
1 1/8" (28.6 mm)	115	117	53	A						●					●	●			●	●		●	●		●	●	581380	371,60
1 1/4" (31.8 mm)	114	123	55	A						●					●	●			●	●		●	●		●	●	581320	438,04
1 1/4" (31.8 mm)	133	145	65	A						●					●	●			●	●		●	●		●	●	581390	618,65
1 3/8" (34.9 mm)	100	105	47	S																							581500	498,24
1 3/8" (34.9 mm)	140	150	68	A						●	●				●	●			●	●		●	●		●	●	581350	585,43
1 1/2" (41.3 mm)	140	155	70	S																							581510	532,49


- R mm: Bending radius mm at the neutral axis of the bend (DVGW GW 392)
X mm: Correction dimension for a 90° or 45° bend
s mm: Wall thickness
¹⁾: hard, semi-hard copper pipes, also thin-walled, EN 1057
²⁾: hard copper pipes EN 1057
³⁾: According to DVGW work sheet GW 392 for hard and semi-hard copper pipes Ø 28 mm minimum bending radius 114 mm necessary. Wall thickness ≥ 0.9 mm.
Cu: Adaptor block 10–40, support 10–40 (Art.-No. 582120) necessary.
Cu: Adaptor block 35–50, support 35–50 (Art.-No. 582110) necessary.
Cu: hard, half-hard, soft copper tubes, also thin-wall, EN 1057
Cu: Copper pipes K65 for refrigeration and air conditioning technology in accordance with EN 12735-1, EN 12449
St 10312: stainless steel pipes of the press fitting systems EN 10312, series 2, EN 10088, EN 10217-7
St 1127: stainless steel pipes EN ISO 1127, EN 10217-7
St 10305-U: coated, soft carbon steel pipes of the press fitting systems EN 10305-3
St 10305: soft precision steel pipes EN 10305-1, EN 10305-2, EN 10305-3, carbon steel pipes EN 10305-3
St 10255: Steel pipes (threaded pipes) EN 10255
St 50086: Electrical installation pipes DIN EN 50086
U: coated
V: multi-layer composite tubes of pressfitting systems
P: Bending former made of glass fibre-reinforced polyamide
A: Bending former made of aluminium
S: Bending former made of spheroidal iron





Radial Press Jointing

	Cordless radial press Mini	147
	Pressing tongs Mini	152
	Cropping tongs Mini	184
	Manual radial press	185
	Electric radial press	186
	Electro-hydraulic radial presses	187
	Cordless radial presses	190
	Pressing tongs / pressing rings	198
	Hold-Harmless and Indemnification Agreement	240
	Cropping tongs	241
	Cable shears	241



6 million!

REMS produced 6 million pressing tongs/pressing rings up to the end of 2023. This success confirms the leading role of REMS in press-jointing technology.

REMS Mini-Press 14 V ACC

Cordless radial press 22 kN with automatic circuit control

Universal, super handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. For battery and corded operation.

Pipe pressing joints Ø 10–40 mm 7 Ø 3/8–1 1/4"

Complete range of REMS pressing tongs Mini/pressing rings for all common pressfitting systems, see page 152–183.

**REMS Mini-Press 14 V ACC – universal up to Ø 40 mm.
Super light, super small, super handy. Secure crimping in seconds. With automatic circuit control. Automatic locking of the pressing tongs.**

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 152–183). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 183. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (Patent EP 1 952 948). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (Patent EP 2 347 862).

Design

Super light, super small, super handy. Drive unit with battery only 2.4 kg. Drive unit with pressing tongs V22 only 33 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Ergonomically designed housing. LED work light for illuminating the workplace. Swivelling pressing tongs seat. Secure seating of pressing tongs/adapter tongs by automatic locking. Electronic charging status check with flat battery protection and charging status indicator with 2-coloured LED.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 14.4 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion PLUS technology. Highly resistant Li-Ion 14.4 V battery with 2.5 or 5.0 Ah capacity for long service life. Light and powerful. Li-Ion 14.4 V, 2.5 Ah batteries for approx. 275 pressings, 5.0 Ah for approx. 550 pressings Viegia Profipress DN 15 with one battery charge*. Operating temperature range -10 to +60 °C. No memory effect for maximum battery power. Rapid charger 220–240V, 10.8–18V, 65W, for short charging times. Voltage supply 220–240V/14.4V, 33A output, for mains operation instead of Li-Ion battery 14.4 V, as accessory.

Supply format

REMS Mini-Press 14 V ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints Ø 10–40 mm, Ø 3/8–1 1/4". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 14.4 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, Safety tip switch. LED work light. Battery Li-Ion 14.4 V, 2.5 Ah, rapid charger 220–240V, 50–60 Hz, 10.8–18V, 65W.

Version	Art.-No.	€
In sturdy steel case.	578012R220	1 505,10
In L-Boxx system case.	578013R220	1 546,62

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS pressing tongs Mini/pressing rings see page 152–183.		
Adapter tongs Mini Z8 for driving REMS pressing rings S (PR-2B)	574700R	144,28
REMS cropping tongs Mini for threaded rods see page 184.		
REMS Mini-Press 14 V ACC drive unit, without battery	578001R14	1 079,52
Battery Li-Ion 14.4 V, 2.5 Ah	571545R14	160,89
Battery Li-Ion 14.4 V, 5.0 Ah	571555R14	227,32
Rapid charger 220–240V, 50–60 Hz, 10.8–18V, 65W	571560R220	154,66
Voltage supply 220–240V/14.4V, 50–60Hz, 33A, for mains operation instead of battery Li-Ion 14.4 V.	571565R220	351,88
Steel case with inlay	578290R	110,03
L-Boxx system case with inserts	578299R	146,36



German Quality Product



REMS Mini-Press 22 V ACC

Cordless radial press 22 kN with automatic circuit control

Universal, super handy electric tool with automatic circuit control for all common pressfitting systems.
Li-Ion 22 V Technology. For battery and corded operation.

Pipe pressing joints Ø 10 – 40 mm
 Ø 3/8 – 1 1/4 "

Complete range of REMS pressing tongs Mini/
pressing rings for all common pressfitting systems,
see page 152 – 183.

REMS Mini-Press 22 V ACC – universal up to Ø 40 mm.
Super light, super small, super handy, ultra fast.
Pressing under 4 s. With automatic circuit control,
Automatic locking of pressing tongs. Li-Ion 21.6 V, 2.5 Ah
battery for approx. 390 pressings Viega Profipress
DN 15 with one battery charge*.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 152 – 183). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 183. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

Design

Super light, super small, super handy. Drive unit with battery only 2.5 kg. Drive unit with pressing tongs V15 only 31 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Swivelling pressing tongs seat, rotation angle > 360°. Secure seating of pressing tongs/adapter tongs by automatic locking.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control). Ultra fast Pressing under 4 s.

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah batteries for approx. 390 pressings, 4.4 Ah for approx. 685 pressings, 5.0 Ah for approx. 780 pressings, 9.0 Ah for approx. 1400 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W. Rapid charger 100 – 240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220 – 240 V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.



←ACC→

Automatic Circuit Control

with automatic circuit control
and charging status check



German Quality Product





Supply format

REMS Mini-Press 22V ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints Ø 10–40 mm, Ø $\frac{3}{8}$ –1 $\frac{1}{4}$ ". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240V or 110 V, 50–60 Hz, 70 W.

Version	Art.-No.	€
In sturdy steel case.	578010R220	1 785,36
In L-Boxx system case.	578014R220	1 826,88

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS pressing tongs Mini/pressing rings see page 152–183.		
Adapter tongs Mini 28 for driving REMS pressing rings S (PR-2B)	574700R	144,28
REMS cropping tongs Mini for threaded rods see page 184.		
REMS Mini-Press 22V ACC drive unit, without battery	578002R22	1 266,36
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6 V, 50–60Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	414,16
Steel case with inlay	578290R	110,03
L-Boxx system case with inserts	578299R	146,36
REMS Lumen 2800 22V , cordless LED flood light, see page 111		



REMS Mini-Press S 22V ACC

Cordless radial press 22 kN with automatic circuit control

Universal, super handy electric tool with automatic circuit control for all common pressfitting systems.
Li-Ion 22 V Technology. For battery and corded operation.

Pipe pressing joints Ø 10 – 40 mm
 Ø 3/8 – 1 1/4 "

Complete range of REMS pressing tongs Mini/
pressing rings for all common pressfitting systems,
see page 152 – 183.

REMS Mini-Press S 22V ACC – universal up to Ø 40 mm.
Super light, super small, super handy, ultra fast.
Pressing under 4 s. With automatic circuit control,
Automatic locking of pressing tongs. Li-Ion 21.6 V, 2.5 Ah
battery for approx. 390 pressings VEGA Profipress
DN 15 with one battery charge*.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 152 – 183). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 183. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

Design

Super light, super small, super handy. Drive unit with battery only 2.6 kg. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Swivelling pressing tongs seat, rotation angle > 360 °. Secure seating of pressing tongs/adapter tongs by automatic locking.

Pressing operation by touch-control with ACC


For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control). Ultra fast Pressing under 4 s.

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah batteries for approx. 390 pressings, 4.4 Ah for approx. 685 pressings, 5.0 Ah for approx. 780 pressings, 9.0 Ah for approx. 1400 pressings VEGA Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 15A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.



German Quality Product



REMS Mini-Press S 22 V ACC

Cordless radial press 22 kN with automatic circuit control



Supply format

REMS Mini-Press S 22 V ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints Ø 10–40 mm, Ø $\frac{3}{8}$ –1 $\frac{1}{4}$ ". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240V or 110 V, 50–60 Hz, 70 W.

Version	Art.-No.	€
In sturdy steel case.	578015R220	1 785,36
In L-Boxx system case.	578016R220	1 826,88

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS pressing tongs Mini/pressing rings see page 152–183.		
Adapter tongs Mini 28 for driving REMS pressing rings S (PR-2B)	574700R	144,28
REMS cropping tongs Mini for threaded rods see page 184.		
REMS Mini-Press S 22 V ACC drive unit, without battery	578003R22	1 266,36
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60 Hz, 90 W	571585R220	175,42
Rapid charger 100–240V, 50–60 Hz, 290 W	571587R220	414,16
Voltage supply 220–240V/21.6 V, 50–60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	414,16
Steel case with inlay	578290R	110,03
L-Boxx system case with inserts	578299R	146,36
REMS Lumen 2800 22V , cordless LED flood light, see page 111		



for all common pressfitting systems

Select REMS pressing tongs Mini/

REMS pressing rings yourself!

Find the desired press fitting system in the table below and choose the size of pressing tongs/pressing rings that you require. Please note that pressfitting systems for gas installation may only be pressed with the REMS pressing tongs Mini/pressing rings which are highlighted in yellow in the table.

Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond with the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Pressing jaws of pressing tongs/pressing rings manufactured on CNC production centres ensure high-precision machining of pressing contour. Low production tolerances as a result.

Can be driven by all REMS radial presses 22 kN. Adapter tongs (page 183) required for driving REMS pressing rings. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press (page 185) using the adapter tong Z8.

Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

REMS pressing tongs Mini (PZ-2B)

REMS Mini pressing tongs (PZ-2B) with 2 swivellable monoblock pressing jaws. Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

REMS Mini ACz, Fz, HEz, RFz, RFIz pressing tongs with teeth prevent formation of burr on the pressfitting (**Patent EP 2 027 971**).

REMS pressing ring S (PR-2B)

REMS pressing ring S (PR-2B), continuously swivellable, with 2 pressing jaws, for secure engagement of the pressing jaws in places of difficult access. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 183.

Traceability according to EN 1775:2007

REMS pressing tongs Mini with pressing contour F, M, V, SA, B, RN and UP have worked a specific marking into the pressing contour which leaves a lasting impression on the pressed fitting after the pressing process. This enables the user to check again whether the most suitable pressing tongs have been used to make the pressfit connection even after the pressing process.

With this traceability REMS fulfills the recommendations of the European standard EN 1775:2007 for the installation of pressfitting systems for gas.



Patent EP 1 952 948

Patent EP 2 347 862

German Quality Product



REMS Mini pressing tongs (PZ-2B)

REMS pressing ring S (PR-2B),
continuously swivellable

Confirmation of suitability

See page 239.

Hold-Harmless and Indemnification Agreement


See page 240.




REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN



Pressing tongs with teeth prevent formation of burr on the pressfitting.
Patent EP 2 027 971



Example REMS pressing tongs Mini V:
"V" imprint on pressed fitting for
traceability according to EN 1775:2007

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.
A			
Aalberts integrated piping systems	U 14	578372	174,38
	U 16	578374	165,66
VSH MultiPress	U 20	578378	165,66
	U 25	578380	165,66
	U 32	578382	194,31
	U 40	578386	236,66
	TH 14	578348	177,08
	TH 16	578352 R	177,08
	TH 20	578358 R	177,08
	TH 25	578360	177,08
	TH 32	578364	177,08
	TH 40	578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R
	TH 16 S (PR-2B)**	Mini Z8	574782 R
	TH 20 S (PR-2B)**	Mini Z8	574788 R
	TH 25 S (PR-2B)**	Mini Z8	574792 R
	TH 32 S (PR-2B)	Mini Z8	574798 R
Aalberts integrated piping systems	U 16	578374	165,66
	U 20	578378	165,66
VSH MultiPress Gas	U 25	578380	165,66
	TH 16	578352 R	177,08
	TH 20	578358 R	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R
	TH 20 S (PR-2B)**	Mini Z8	574788 R
Aalberts integrated piping systems	V 12	578324	146,98
	V 15	578328	146,98
VSH SudoPress Carbon	V 18	578332	146,98
	V 22	578334	146,98
	V 28	578336	146,98
	V 35	578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R
	V 15 S (PR-2B)	Mini Z8	574752 R
	V 18 S (PR-2B)	Mini Z8	574756 R
	V 22 S (PR-2B)	Mini Z8	574758 R
	V 28 S (PR-2B)	Mini Z8	574760 R
	V 35 S (PR-2B)	Mini Z8	574762 R
Aalberts integrated piping systems	V 12	578324	146,98
	V 14	578326	146,98
VSH SudoPress Copper	VG 14	578338	146,98
	V 15	578328	146,98
	V 16	578330	146,98
	V 6 16	578340	146,98
	V 18	578332	146,98
	V 22	578334	146,98
	V 28	578336	146,98
	V 35	578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R
	V 14 S (PR-2B)	Mini Z8	574800 R
	V 6 14 S (PR-2B)	Mini Z8	574750 R
	V 15 S (PR-2B)	Mini Z8	574752 R
	V 16 S (PR-2B)	Mini Z8	574802 R
	VG 16 S (PR-2B)	Mini Z8	574754 R
	V 18 S (PR-2B)	Mini Z8	574756 R
	V 22 S (PR-2B)	Mini Z8	574758 R
	V 28 S (PR-2B)	Mini Z8	574760 R
	V 35 S (PR-2B)	Mini Z8	574762 R
Aalberts integrated piping systems	V 12	578324	146,98
	V 14	578326	146,98
VSH SudoPress Copper	VG 14	578338	146,98
Gas	V 15	578328	146,98
	V 16	578330	146,98
	V 6 16	578340	146,98
	V 18	578332	146,98
	V 22	578334	146,98
	V 28	578336	146,98
	V 35	578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R
	V 14 S (PR-2B)	Mini Z8	574800 R
	V 6 14 S (PR-2B)	Mini Z8	574750 R
	V 15 S (PR-2B)	Mini Z8	574752 R
	V 16 S (PR-2B)	Mini Z8	574802 R
	VG 16 S (PR-2B)	Mini Z8	574754 R
	V 18 S (PR-2B)	Mini Z8	574756 R
	V 22 S (PR-2B)	Mini Z8	574758 R
	V 28 S (PR-2B)	Mini Z8	574760 R
	V 35 S (PR-2B)	Mini Z8	574762 R
Aalberts integrated piping systems	V 15	578328	146,98
	V 18	578332	146,98
VSH SudoPress	V 22	578334	146,98
Stainless	V 28	578336	146,98
	V 35	578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R
	V 18 S (PR-2B)	Mini Z8	574756 R
	V 22 S (PR-2B)	Mini Z8	574758 R
	V 28 S (PR-2B)	Mini Z8	574760 R
	V 35 S (PR-2B)	Mini Z8	574762 R
Aalberts integrated piping systems	M 12	578310	146,98
	M 15	578312	146,98
VSH XPress Carbon	M 18 ¹⁾	578314	146,98
	M 22	578316	146,98
	M 28 ¹⁾	578318	146,98
	M 35	578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R
	M 15 S (PR-2B)	Mini Z8	574738 R
	M 18 S (PR-2B)	Mini Z8	574740 R
	M 22 S (PR-2B)	Mini Z8	574742 R
	M 28 S (PR-2B)	Mini Z8	574744 R
	M 35 S (PR-2B)	Mini Z8	574746 R

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
AHLSELL A-press elförzinkad M	M 12		578310	146,98	ALB Sistema Multicapa para calefacción y sanitario	TH 16		578352 R	177,08
	M 15		578312	146,98		TH 18		578356	177,08
	M 18		578314	146,98		TH 20		578358 R	177,08
	M 22		578316	146,98		TH 26		578362 R	177,08
	M 28		578318	146,98		TH 32		578364	177,08
	M 35		578390	178,12		TH 40		578624	234,69
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					
AHLSELL A-press elförzinkad V	V 12		578324	146,98	H 16			578400	159,75
	V 15		578328	146,98	H 18			578404	159,75
	V 18		578332	146,98	H 20			578406	159,75
	V 22		578334	146,98	H 26			578410	159,75
	V 28		578336	146,98	H 32			578412	159,75
	V 35		578604	178,12	U 16			578374	165,66
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51	U 18			578376	165,66
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	U 20			578378	165,66
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	U 26 ⁷⁾			578392	194,31
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	U 32			578382	194,31
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	U 40			578386	236,66
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96					
AHLSELL A-press koppar M	M 12		578310	146,98	ALB	TH 16		578352 R	177,08
	M 15		578312	146,98	Sistema Multicapa	TH 20		578358 R	177,08
	M 18		578314	146,98	para gas	TH 26		578362 R	177,08
	M 22		578316	146,98		TH 32		578364	177,08
	M 28		578318	146,98		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 35		578390	178,12		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	H 16			578400	159,75
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	H 20			578406	159,75
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					
AHLSELL A-press koppar V	V 12		578324	146,98	ALTECH Altech	RFz 12		578490	184,45
	V 15		578328	146,98		RFz 16		578492	184,45
	V 18		578332	146,98		RFz 20		578494	184,45
	V 22		578334	146,98		RFz 25		578496	184,45
	V 28		578336	146,98	APE MULTYGAS	TH 16		578352 R	177,08
	V 35		578604	178,12	Serie AP Gas	TH 20		578358 R	177,08
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51		TH 26		578362 R	177,08
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		TH 32		578364	177,08
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
AHLSELL A-press rostfritt	M 15		578312	146,98	APE Serie AP	B 16		578468	193,28
	M 18		578314	146,98		B 20		578472	193,28
	M 22		578316	146,98		B 26		578474	213,00
	M 28		578318	146,98		B 32		578476	213,00
	M 35		578390	178,12		H 16		578400	159,75
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		H 20		578406	159,75
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		H 26		578410	159,75
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		H 32		578412	159,75
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 16		578352 R	177,08
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		TH 18		578356	177,08
	M 15		578312	146,98		TH 20		578358 R	177,08
	M 18		578314	146,98					
AIRBEL PRESSCLIM	M 22		578316	146,98					
	M 28		578318	146,98					
	M 35		578390	178,12					
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51					
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51					
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51					
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					
	M 15		578312	146,98					
	M 18		578314	146,98					
	M 22		578316	146,98					
	M 28		578318	146,98					
AIRBEL SERTINOX	M 35		578390	178,12					
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51					
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51					
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51					
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					
	M 15		578312	146,98					
	M 18		578314	146,98					
	M 22		578316	146,98					
	M 28		578318	146,98					
	M 35		578390	178,12					
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51					
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51					
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51					
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

^{**} Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
APE Serie APL	H 16		578400	159,75	ASSOTHERM	M 15		578312	146,98
	H 18		578404	159,75	IPI-RAX	M 18		578314	146,98
	H 20		578406	159,75	Inox	M 22		578316	146,98
	H 25		578408	159,75		M 28		578318	146,98
	H 26		578410	159,75		M 35		578390	178,12
	H 32		578412	159,75		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	TH 16		578352 R	177,08		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	TH 18		578356	177,08		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	TH 20		578358 R	177,08		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	TH 25		578360	177,08		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	TH 26		578362 R	177,08					
	TH 32		578364	177,08	ASSOTHERM	M 15		578312	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	IPI-RAX	M 18		578314	146,98
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	Inox Gas	M 22		578316	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		M 28		578318	146,98
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51		M 35		578390	178,12
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	U 16		578374	165,66		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	U 18		578376	165,66		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	U 20		578378	165,66		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
AQUATECHNIK	H 16		578400	159,75					
Press-fitting metal	H 20		578406	159,75	ASSOTHERM	H 16		578400	159,75
	H 26		578410	159,75	IPM-Multistrato	H 20		578406	159,75
	H 32		578412	159,75		H 26		578410	159,75
	TH 16		578352 R	177,08		H 32		578412	159,75
	TH 20		578358 R	177,08		TH 16		578352 R	177,08
	TH 26		578362 R	177,08		TH 20		578358 R	177,08
	TH 32		578364	177,08		TH 26		578362 R	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		TH 32		578364	177,08
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		THL 32		578368	177,08
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		TH 40		578624	234,69
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	U 16		578374	165,66		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	U 20		578378	165,66		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	U 26 ⁷⁾		578392	194,31		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 32		578382	194,31		U 16		578374	165,66
AQUATECHNIK	B 16		578468	193,28		U 20		578378	165,66
Universal	B 20		578472	193,28		U 26 ⁷⁾		578392	194,31
	B 26		578474	213,00		U 32		578382	194,31
	B 32		578476	213,00	ASSOTHERM	M 15		578312	146,98
	F 16		578456	168,68	IPR-RRA	M 18		578314	146,98
	F 20		578460	168,68	Copper	M 22		578316	146,98
	F 26		578462	182,48		M 28		578318	146,98
	F 32		578464	182,48		M 35		578390	178,12
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	H 16		578400	159,75		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	H 20		578406	159,75	ASSOTHERM	M 15		578312	146,98
	H 26		578410	159,75	IPR-RRA	M 18		578314	146,98
	H 32		578412	159,75	Copper Gas	M 22		578316	146,98
	TH 16		578352 R	177,08		M 28		578318	146,98
	TH 20		578358 R	177,08		M 35		578390	178,12
	TH 26		578362 R	177,08		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	TH 32		578364	177,08		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	ASTM F 1807	US 3/8"		578534	201,16
	U 16		578374	165,66		(Fittings with US 1/2"		578536	201,16
	U 20		578378	165,66				578538	201,16
	U 26 ⁷⁾		578392	194,31		US 3/4"		578540	201,16
	U 32		578382	194,31	ATUSA ITALIA	M 15		578312	146,98
ARKA	H 16		578400	159,75	INSTALPRESS	M 18		578314	146,98
DUROsystem	H 20		578406	159,75	CARBON STEEL	M 22		578316	146,98
	H 25		578408	159,75	PRESS FITTINGS	M 28		578318	146,98
	H 26		578410	159,75		M 35		578390	178,12
	H 32		578412	159,75		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	TH 16		578352 R	177,08		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	TH 20		578358 R	177,08		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	TH 25		578360	177,08		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	TH 26		578362 R	177,08		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	TH 32		578364	177,08	ATUSA ITALIA	M 15		578312	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	INSTALPRESS	M 18		578314	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	STAINLESS STEEL	M 22		578316	146,98
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51	PRESS FITTINGS	M 28		578318	146,98
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		M 35		578390	178,12
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	U 16		578374	165,66		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	U 20		578378	165,66		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
Aschl NIR	M 15		578312	146,98		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 18		578314	146,98		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	M 22		578316	146,98	AUSTEC	TH 16		578352 R	177,08
	M 28		578318	146,98	PEX-B, PEX-AL-PEX (AUS)	TH 20		578358 R	177,08
	M 35		578390	178,12		TH 25		578360	177,08
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 32		578364	177,08
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		U 16		578374	165,66
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		U 20		578378	165,66
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		U 25		578380	165,66
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		U 32		578382	194,31
ASSOTHERM	M 15		578312	146,98	AUSTEC	TH 16		578352 R	177,08
IPC-RAC	M 18		578314	146,98	PEX-AL-PEX GAS (AUS)	TH 20		578358 R	177,08
Carbon Steel	M 22		578316	146,98		TH 25		578360	177,08
	M 28		578318	146,98		TH 32		578364	177,08
	M 35		578390	178,12		U 16		578374	165,66
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		U 20		578378	165,66
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		U 25		578380	165,66
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		U 32		578382	194,31
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
AYOR FIXOCONNECT Press	H 12		578396	159,75
	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	RFz 12		578490	184,45
	RFz 16		578492	184,45
	RFz 20		578494	184,45
	RFz 25		578496	184,45
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
AYOR FIXOMULTIX	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
AYOR SOMATHERM FOR YOU -1	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
	U 32		578382	194,31
	U 40		578386	236,66
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	U 16		578374	165,66
AYOR SOMATHERM FOR YOU -2	U 20		578378	165,66
	H 12		578396	159,75
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
AYOR SOMATHERM FOR YOU -2	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66

B

Bampi BALPEX serie LP	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
Bampi BALPEX serie MP	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Bampi BALPEX Gas	TH 16		578352 R	177,08
	TH 20		578356	177,08
	TH 26		578362 R	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	U 16		578374	165,66
	U 20		578378	165,66
	U 26		578382	194,31
	U 32		578386	236,66
BARBI EASYPRESS (Industrial Blansol)	H 12		578396	159,75
	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 32		578410	159,75
	RFz 12		578412	184,45
	RFz 16		578414	184,45
	RFz 20		578416	184,45
	RFz 25		578418	184,45
	RFz 32		578420	184,45
BARBI MULTIPLEX (Industrial Blansol)	H 14		578398	159,75
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	RFz 16		578414	184,45
	RFz 20		578416	184,45
	RFz 25		578418	184,45
BEGETUBE/ IVAR	H 16		578466	193,28
	H 18		578468	193,28
	H 20		578470	193,28
	H 25		578472	193,28
	H 26		578474	213,00
	H 32		578476	213,00
	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
Béné inox Série 41	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	Brass Form	H 16	578400	159,75
	Master-Al-Pex	H 18	578404	159,75
	H 20		578406	159,75
	TH 16		578352 R	177,08
Brass Form Master-Al-Pex	TH 18		578356	177,08
	TH 20		578362 R	177,08
	TH 26		578364	177,08
	TH 32		578366	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

^{**} Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Brass & Fittings	RFz 16		578492	184,45
PRESSMAN	RFz 18		578638	184,45
MultiPress	ACz 20		578612	184,45
	RFz 25		578496	184,45
	RFz 32		578498	184,45
Brass & Fittings	RFz 16		578492	184,45
PRESSMAN RetiPress	RFz 18		578638	184,45
	ACz 20		578612	184,45
	RFz 25		578496	184,45
	RFz 32		578498	184,45
BRASSTECH	B 16		578468	193,28
MULTitempoSAN	B 20		578472	193,28
Brasspress	B 26		578474	213,00
	B 32		578476	213,00
	F 16		578456	168,68
	F 20		578460	168,68
	F 26		578462	182,48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31

C

Cello Products	VUS 1/2" (OD 15,9 mm) Press		578566	177,50
	VUS 3/4" (OD 22,2 mm)		578568	177,50
	VUS 1" (OD 28,6 mm)		578570	177,50
	VUS 1 1/4" (OD 34,9 mm)		578606	177,50
CGR	H 16		578400	159,75
DYNALFLU	H 20		578406	159,75
multicouche	H 26		578410	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
	U 40		578386	236,66
CGR	H 12		578396	159,75
DYNALFLU	H 16		578400	159,75
PER	H 20		578406	159,75
	H 25		578408	159,75
	RFz 12		578490	184,45
	RFz 16		578492	184,45
	RFz 20		578494	184,45
	RFz 25		578496	184,45
CHIALI	TH 16		578352 R	177,08
CHIALIPEX	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
Climatrix	H 16		578400	159,75
Climatrix Rhinopex	H 20		578406	159,75
	U 16		578374	165,66
	U 20		578378	165,66
	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Climatrix	TH 11,6		578344	177,08
Variotherm	TH 16		578352 R	177,08
System TH	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
ClouSet	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
Comap	RFz 12		578490	184,45
PEX Press	RFz 16		578492	184,45
	RFz 20		578494	184,45
	RFz 25		578496	184,45
Comap	TH 14		578348	177,08
Multiskin	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	THL 32		578368	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 14		578372	174,38
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 32		578382	194,31
Comap	TH 16		578352 R	177,08
Multiskin Gas	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	THL 32		578368	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
COMISA	TH 14		578348	177,08
Press System	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	H 14		578398	159,75
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	B 14		578466	193,28
	B 16		578468	193,28
	B 18		578470	193,28
	B 20		578472	193,28
	B 26		578474	213,00
	B 32		578476	213,00
COMISA	TH 16		578352 R	177,08
Press System Gas	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
CONEL	M 15		578312	146,98	Conex Bänninger	F 16		578456	168,68
CONNECT INOX	M 18		578314	146,98	>B< Flex	F 18		578458	168,68
	M 22		578316	146,98		F 20		578460	168,68
	V 15		578328	146,98		F 32		578464	182,48
	V 18		578332	146,98		F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	V 22		578334	146,98		F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
CONEL	F 16		578456	168,68		F 32 S (PR-2B)	Mini Z8	574734 R	136,96
CONNECT	F 20		578460	168,68		H 16		578400	159,75
MULTI	F 26		578462	182,48		H 18		578404	159,75
	F 32		578464	182,48		H 20		578406	159,75
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51		H 25		578408	159,75
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51		H 32		578412	159,75
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51		RFz 16		578492	184,45
	F 32 S (PR-2B)**	Mini Z8	574734 R	136,96		RFz 18		578638	184,45
	H 16		578400	159,75		RFz 20		578494	184,45
	H 20		578406	159,75		RFz 25		578496	184,45
	H 26		578410	159,75		RFz 32		578498	184,45
	H 32		578412	159,75		TH 16		578352 R	177,08
	TH 16		578352 R	177,08		TH 18		578356	177,08
	TH 20		578358 R	177,08		TH 20		578358 R	177,08
	TH 26		578362 R	177,08		TH 25		578360	177,08
	TH 32		578364	177,08		TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66		U 16		578374	165,66
	U 20		578378	165,66		U 18		578376	165,66
(DN 26)	U 25		578380	165,66		U 20		578378	165,66
	U 32		578382	194,31		U 25		578380	165,66
	VP 16		578482	176,56		U 32		578382	194,31
	VP 20		578484	176,56					
	VP 32		578488	195,25					
CONEL	F 16		578456	168,68	Conex Bänninger	F 16		578456	168,68
CONNECT	F 20		578460	168,68		F 18		578458	168,68
MV2	F 26		578462	182,48		F 20		578460	168,68
	F 32		578464	182,48		F 32		578444	182,48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51		F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51		F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51		F 32 S (PR-2B)	Mini Z8	574734 R	136,96
	F 32 S (PR-2B)**	Mini Z8	574734 R	136,96		H 16		578400	159,75
	TH 16		578352 R	177,08		H 18		578404	159,75
	TH 20		578358 R	177,08		H 20		578406	159,75
	TH 26		578362 R	177,08		H 25		578408	159,75
	TH 32		578364	177,08		H 32		578412	159,75
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		RFz 16		578492	184,45
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		RFz 18		578638	184,45
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		RFz 20		578494	184,45
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96		RFz 25		578496	184,45
Conex Bänninger	M 15		578312	146,98		RFz 32		578498	184,45
<A> Press Inox (304)	M 18		578314	146,98		TH 16		578352 R	177,08
	M 22		578316	146,98		TH 18		578360	177,08
	M 28		578318	146,98		TH 20		578364	177,08
	M 35		578390	178,12		TH 25			
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 32			
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
Conex Bänninger	M 15		578312	146,98		U 16		578374	165,66
<A> Press Inox (316L)	M 18		578314	146,98		U 18		578376	165,66
	M 22		578316	146,98		U 20		578378	165,66
	M 28		578318	146,98		U 25		578380	165,66
	M 35		578390	178,12		U 32		578382	194,31
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51					
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51					
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51					
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					
Conex Bänninger	BMP 1/4"				Conex Bänninger	BMP 1/4"		578700	175,53
>B< MaxiPro	BMP 3/8"					BMP 3/8"		578702	175,53
	BMP 1/2"					BMP 1/2"		578704	175,53
	BMP 5/8"					BMP 5/8"		578706	175,53
	BMP 3/4"					BMP 3/4"		578708	175,53
	BMP 7/8"					BMP 7/8"		578710	175,53
	BMP 1"					BMP 1"		578712	175,53
	BMP 1 1/8"					BMP 1 1/8"		578714	175,53

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Conex Bänninger >B< Press	V 12		578324	146,98
	V 14		578326	146,98
	V 15		578328	146,98
	V 16		578330	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	M 15		578312	146,98
	M 22		578316	146,98
	M 28		578318	146,98
Conex Bänninger >B< Press Carbon	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
Conex Bänninger >B< Press Gas	V 12		578324	146,98
	V 14		578326	146,98
	V 15		578328	146,98
	V 16		578330	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
Conex Bänninger >B< Press Inox	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
Conex Bänninger >B< Press Solar	V 12		578324	146,98
	V 14		578326	146,98
	V 15		578328	146,98
	V 16		578330	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
D				
Debrunner Acifer d-a Presssystem C-Stahl	M 12		578310	146,98
	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574762 R	136,96
DUOPIPE SYSTEMS DUOFIL MKSYSTEM	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
DW Verbundrohr multitubo systems	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
E				
EBRILLE	U 16		578374	165,66
Isomorflex	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	H 26		578410	159,75
	TH 26		578362 R	177,08
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
EBRILLE	U 16		578374	165,66
Monflex	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	H 26		578410	159,75
	TH 26		578362 R	177,08
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
EFFEBI	M 15		578312	146,98
EFFEBI-PRESS	M 18		578314	146,98
Aisi316	M 22		578316	146,98
System M Profile ¹⁾	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
EFFEBI	V 12		578324	146,98
EFFEBI-PRESS	V 15		578328	146,98
Aisi316	V 18		578332	146,98
System V Profile	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
EFFEBI	M 12		578310	146,98
EFFEBI-PRESS	M 15		578312	146,98
Carbon-S	M 18		578314	146,98
System M Profile ¹⁾	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574762 R	136,96
EFFEBI	V 12		578324	146,98
EFFEBI-PRESS	V 14		578326	146,98
COPPER	V 15		578328	146,98
	V 16		578330	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
EFFEBI	V 12		578324	146,98
EFFEBI-PRESS	V 15		578328	146,98
UNICO	V 18		578330	146,98
	V 22		578332	146,98
	V 28		578334	146,98
	V 35		578336	146,98
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574800 R	124,51
	V 18 S (PR-2B)	Mini Z8	574752 R	124,51
	V 22 S (PR-2B)	Mini Z8	574802 R	124,51
	V 28 S (PR-2B)	Mini Z8	574756 R	124,51
	V 35 S (PR-2B)	Mini Z8	574760 R	124,51
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
EFFEBI	V 12		578324	146,98	EFFEBI	TH 16		578352 R	177,08
EFFEBI-PRESS	V 15		578328	146,98	TOF	TH 18		578356	177,08
UNICO (GAS)	V 18		578332	146,98	MULTIPINZA	TH 20		578358 R	177,08
	V 22		578334	146,98		TH 25		578360	177,08
	V 28		578336	146,98		TH 26		578362 R	177,08
	V 35		578604	178,12		TH 32		578364	177,08
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51		TH 40		578624	234,69
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
EFFEBI	M 15		578312	146,98		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
PRESSTIGE	M 18		578314	146,98		F 16		578456	168,68
	M 22		578316	146,98		F 18		578458	168,68
	M 28		578318	146,98		F 20		578460	168,68
	M 35		578390	178,12		F 26		578462	182,48
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		F 32		578464	182,48
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		Fz 40		578478	247,15
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	V 15		578328	146,98		F 32 S (PR-2B)	Mini Z8	574734 R	136,96
	V 18		578332	146,98		H 16		578400	159,75
	V 22		578334	146,98		H 18		578404	159,75
	V 28		578336	146,98		H 20		578406	159,75
	V 35		578604	178,12		H 25		578408	159,75
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		H 26		578410	159,75
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		H 32		578412	159,75
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		U 16		578374	165,66
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		U 18		578376	165,66
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		U 20		578378	165,66
EFFEBI	M 15		578312	146,98		U 25		578380	165,66
PRESSTIGE 4E05	M 18		578314	146,98		U 26 ⁷⁾		578392	194,31
	M 22		578316	146,98		U 32		578382	194,31
	M 28		578318	146,98		U 40		578386	236,66
	M 35		578390	178,12		B 16		578468	193,28
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		B 18		578470	193,28
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		B 20		578472	193,28
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		B 26		578474	213,00
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		B 32		578476	213,00
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		U 25		578380	165,66
EFFEBI	M 15		578312	146,98		U 32		578382	194,31
PRESSTIGE-GAS	M 18		578314	146,98		U 40		578386	236,66
	M 22		578316	146,98		B 16		578468	193,28
	M 28		578318	146,98		B 18		578470	193,28
	M 35		578390	178,12		B 20		578472	193,28
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		B 26		578474	213,00
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		B 32		578476	213,00
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		U 25		578380	165,66
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		U 32		578382	194,31
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		U 32		578374	165,66
	V 15		578328	146,98		U 40		578376	165,66
	V 18		578332	146,98		B 16		578378	165,66
	V 22		578334	146,98		B 18		578380	165,66
	V 28		578336	146,98		B 20		578382	194,31
	V 35		578604	178,12		B 26		578384	194,31
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		B 32		578386	194,31
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		F 16		578374	165,66
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		F 20		578376	165,66
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		H 16		578400	159,75
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		H 20		578404	159,75
EFFEBI	TH 16		578352 R	177,08		H 25		578408	168,68
TOF-GAS	TH 20		578358 R	177,08		H 32		578364	177,08
MULTIPINZA	TH 26		578362 R	177,08		TH 40		578624	234,69
	TH 32		578364	177,08		U 16		578374	165,66
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		U 20		578376	165,66
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51				578378	165,66
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51				578380	177,08
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96				578382	177,08
	H 16		578400	159,75		TH 14		578348	177,08
	H 20		578406	159,75		TH 15		578350	177,08
	H 26		578410	159,75		TH 16		578352 R	177,08
	H 32		578412	159,75		TH 17		578354	177,08
	U 16		578374	165,66		TH 20		578358 R	177,08
	U 20		578378	165,66		TH 25		578360	177,08
	U 32		578382	194,31		TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
						TH 15 S (PR-2B)**	Mini Z8	574780 R	124,51
						TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
						TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51
						TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
						TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

^{**} Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Esta Rohr simplesta SH M	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
Esta Rohr simplesta ST M	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
EUROTUBI EUROPA C-Steel Pressfitting System M-Profile ¹⁾	M 12		578310	146,98
	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
EUROTUBI EUROPA Inox Pressfitting System M-Profile ¹⁾	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
Evans Components Presslok	VAU 15 (1/2") (OD 12,7 mm)		578630	151,86
	VAU 20 (3/4") (OD 19,1 mm)		578632	151,86
	VAU 25 (1") (OD 25,4 mm)		578634	151,86

F

FAR Rubinetterie PRESSFAR	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 17		578354	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	H 14		578398	159,75
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	U 14		578372	174,38
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
F.B.Q. BARONIO	V 12		578324	146,98
BQ PRESS SOLAR	V 14		578326	146,98
	V 15		578328	146,98
	V 16		578330	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
F.B.Q. BARONIO	V 12		578324	146,98
BQ PRESS WATER	V 14		578326	146,98
	V 15		578328	146,98
	V 16		578330	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
F.B.Q. BARONIO	V 12		578324	146,98
BQ PRESS GAS	V 14		578326	146,98
	V 15		578328	146,98
	V 16		578330	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
FERCOFLOOR	RFz 16		578492	184,45
DUO Press	RFz 20		578494	184,45
FERCO PEX	RFz 25		578496	184,45
	RFz 32		578498	184,45
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
FERCOFLOOR	RFz 16		578492	184,45
DUO Press	RFz 20		578494	184,45
MULTIFER	RFz 25		578496	184,45
	RFz 32		578498	184,45
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
FERRO systems	TH 16		578352 R	177,08
BRASELI	TH 20		578358 R	177,08
GPF GAS	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
FERRO systems	U 16		578374	165,66
BRASELI	U 18		578376	165,66
GPF MULT	U 20		578378	165,66
Pressfitting	U 25		578380	165,66
MULTICAPPA	U 32		578382	194,31
	U 40		578386	236,66
FERRO systems	U 16		578374	165,66
BRASELI	U 18		578376	165,66
GPF PPSU	U 20		578378	165,66
Pressfitting PEX y	U 25		578380	165,66
MULTICAPPA	U 32		578382	194,31
	U 40		578386	236,66
FERRO systems	Rfz 16		578492	184,45
BRASELI	Rfz 20		578494	184,45
GPF PRESS	Rfz 25		578496	184,45
Pressfitting PEX	Rfz 32		578498	184,45
FILINOX	M 15		578312	146,98
Instalpress Steel	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
FILINOX	M 15		578312	146,98	FORZA	V 15		578328	146,98
Instalpress Inox	M 18		578314	146,98	STAINLESS V PRESS (AUS)	V 22		578334	146,98
	M 22		578316	146,98		V 28		578336	146,98
	M 28		578318	146,98		V 35		578604	178,12
	M 35		578390	178,12		V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	FRABO	M 15		578312	146,98
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	FRABOPRESS	M 18		578314	146,98
FITTINGS ESTÁNDAR	RFz 16		578492	184,45	316 GAS M	M 22		578316	146,98
ECO-PRESS	RFz 20		578494	184,45		M 28		578318	146,98
	RFz 25		578496	184,45		M 35		578390	178,12
	RFz 32		578498	184,45		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
FITTINGS ESTÁNDAR	RFz 16		578492	184,45		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
MULTICAPA	RFz 18		578638	184,45		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	RFz 20		578494	184,45		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	RFz 25		578496	184,45		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	RFz 32		578498	184,45	FRABO	V 15		578328	146,98
FITTINGS ESTÁNDAR	RFz 16		578492	184,45	FRABOPRESS	V 18		578332	146,98
PE-X	RFz 20		578494	184,45	316 GAS V	V 22		578334	146,98
	RFz 25		578496	184,45		V 28		578336	146,98
	RFz 32		578498	184,45		V 35		578604	178,12
FITTINGS ESTÁNDAR	RFz 16		578492	184,45		V 15 S (PR-2B)	Mini Z8	574752 R	124,51
PE-X	RFz 20		578494	184,45		V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	RFz 25		578496	184,45		V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	RFz 32		578498	184,45		V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)					V 35 S (PR-2B)	Mini Z8	574762 R	136,96
FORNARA	B 16		578468	193,28	FRABO	M 15		578312	146,98
ForPress	B 20		578472	193,28	FRABOPRESS	M 18		578314	146,98
	B 26		578474	213,00	316 M	M 22		578316	146,98
	B 32		578476	213,00		M 28		578318	146,98
	F 16		578456	168,68		M 35		578390	178,12
	F 20		578460	168,68		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	F 26		578462	182,48		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	F 32		578464	182,48		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51	FRABO	V 12		578324	146,98
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96	FRABOPRESS	V 15		578328	146,98
	H 16		578400	159,75	316 V	V 18		578332	146,98
	H 20		578406	159,75		V 22		578334	146,98
	H 26		578410	159,75		V 28		578336	146,98
	H 32		578412	159,75		V 35		578604	178,12
	TH 16		578352 R	177,08		V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	TH 20		578358 R	177,08		V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	TH 26		578362 R	177,08		V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	TH 32		578364	177,08		V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	FRABO	V 12		578324	146,98
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	FRABOPRESS	V 15		578328	146,98
	U 16		578374	165,66	CHROME	V 18		578332	146,98
	U 20		578378	165,66		V 22		578334	146,98
	U 26 ⁷⁾		578392	194,31		V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	U 32		578382	194,31		V 15 S (PR-2B)	Mini Z8	574752 R	124,51
FORZA	K16/P18		578592	184,45		V 18 S (PR-2B)	Mini Z8	574756 R	124,51
WATER CRIMP (AUS)	K/20		578594	184,45		V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	K/25		578596	184,45		V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	K32		578598	184,45		V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	K140		578600	184,45	FRABO	M 15		578312	146,98
FORZA STAINLESS WATER CRIMP	K16/P18		578592	184,45	FRABOPPRESS	M 18		578314	146,98
	K/20		578594	184,45	C-STEEL M	M 22		578316	146,98
FORZA	U 16		578374	165,66		M 28		578318	146,98
STESSO PEX	U 20		578378	165,66		M 35		578390	178,12
WATER AND GAS CRIMP AUS)	U 25		578380	165,66		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	U 32		578382	194,31		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	U 40		578386	236,66		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	K32		578598	184,45		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	K140		578600	184,45		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
FORZA GAS CRIMP (AUS)	K16/P18		578592	184,45	FRABO	V 12		578324	146,98
	K/20		578594	184,45	FRABOPPRESS	V 15		578328	146,98
	K/25		578596	184,45	C-STEEL V	V 18		578332	146,98
	K32		578598	184,45		V 22		578334	146,98
	K140		578600	184,45		V 28		578336	146,98
FORZA COPPER V PRESS (AUS)	VAU 15 (OD 12,7 mm)		578630	151,86		V 35		578604	178,12
	VAU 20 (OD 19,1 mm)		578632	151,86		V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	VAU 25 (OD 25,4 mm)		578634	151,86		V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	VAU 32 (OD 31,8 mm)		578636	159,75		V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	124,51		V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	124,51		V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	136,96		V 35 S (PR-2B)	Mini Z8	574762 R	136,96

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
FRABO	M 12		578310	146,98	Fränkische alpex F50 PROFI	F 16		578456	168,68
FRABOPRESS	M 15		578312	146,98		F 20		578460	168,68
GAS M	M 18		578314	146,98		F 26		578462	182,48
	M 22		578316	146,98		F 32		578464	182,48
	M 28		578318	146,98		F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	M 35		578390	178,12		F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		F 32 S (PR-2B)**	Mini Z8	574734 R	136,96
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		H 16		578400	159,75
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		H 20		578406	159,75
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		H 26		578410	159,75
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		H 32		578412	159,75
FRABO	V 12		578324	146,98		TH 16		578352 R	177,08
FRABOPRESS	V 15		578328	146,98		TH 20		578358 R	177,08
GAS V	V 18		578332	146,98		TH 26		578362 R	177,08
	V 22		578334	146,98		TH 32		578364	177,08
	V 28		578336	146,98		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	V 35		578604	178,12		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	(DN 26)	U 16		578374	165,66
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		U 20		578378	165,66
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		U 32		578382	194,31
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		VP 16		578482	176,56
FRABO	V 12		578324	146,98		VP 20		578484	176,56
FRABOPRESS	V 15		578328	146,98		VP 32		578488	195,25
KOMBI	V 18		578332	146,98	Fränkische alpex L	Fz 40		578478	247,15
	V 22		578334	146,98					
	V 28		578336	146,98					
	V 35		578604	178,12					
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51					
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51					
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51					
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51					
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51					
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96					
FRABO	M 12		578310	146,98		TH 17		578354	177,08
FRABOPRESS M	M 15		578312	146,98		TH 18		578356	177,08
	M 18		578314	146,98		TH 20		578358 R	177,08
	M 22		578316	146,98		TH 25		578360	177,08
	M 28		578318	146,98		TH 26		578362 R	177,08
	M 35		578390	178,12		TH 32		578364	177,08
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		TH 40		578624	234,69
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 10 S (PR-2B)**	Mini Z8	574772 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 12 S (PR-2B)**	Mini Z8	574776 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 15 S (PR-2B)**	Mini Z8	574780 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
FRABO	V 15		578328	146,98		TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51
FRABOPRESS	V 18		578332	146,98		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
SOLAR	V 22		578334	146,98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	V 28		578336	146,98		TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	V 35		578604	178,12		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	Gallagher USA	H 12 (1/4")		578396	159,75
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		U 14 (3/8")		578372	174,38
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		U 16 (1/2")		578374	165,66
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		U 18 (5/8")		578376	165,66
FRABO	V 15		578324	146,98		U 20 (3/4")		578378	165,66
FRABOPRESS V	V 15		578328	146,98				578380	165,66
	V 18		578332	146,98				578382	194,31
	V 22		578334	146,98	Geberit Mapress C-STAHL	M 12		578310	146,98
	V 28		578336	146,98		M 15		578312	146,98
	V 35		578604	178,12		M 18		578314	146,98
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51		M 22		578316	146,98
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		M 28		578318	146,98
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		M 35		578390	178,12
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
Fränkische alpex-duo XS	F 16		578456	168,68		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	F 20		578460	168,68		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	F 26		578462	182,48		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	F 32		578464	182,48	Geberit Mapress C-STAHL Sprinkler	M 22		578316	146,98
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51		M 28		578318	146,98
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51				578318	146,98
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51				578314	146,98
	F 32 S (PR-2B)**	Mini Z8	574734 R	136,96				578316	146,98
	TH 16		578352 R	177,08				578318	146,98
	TH 20		578358 R	177,08				578318	178,12
	TH 26		578362 R	177,08				578316	146,98
	TH 32		578364	177,08				578316	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51				578318	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51				578318	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51				578316	124,51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96				578316	124,51

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Geberit Mapress	M 15		578312	146,98	General Fittings	B 16		578468	193,28
Edelstahl Gas	M 18		578314	146,98	Serie 5500	B 18		578470	193,28
	M 22		578316	146,98		B 20		578472	193,28
	M 28		578318	146,98		B 26		578474	213,00
	M 35		578390	178,12		B 32		578476	213,00
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		F 16		578456	168,68
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		F 20		578460	168,68
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		F 26		578462	182,48
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		F 32		578464	182,48
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
Geberit Mapress	M 22		578316	146,98		F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
Edelstahl Sprinkler	M 28		578318	146,98		F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
Geberit Mapress	M 12		578310	146,98		F 32 S (PR-2B)	Mini Z8	574734 R	136,96
Kupfer	M 15		578312	146,98		H 16		578400	159,75
	M 18		578314	146,98		H 18		578404	159,75
	M 22		578316	146,98		H 20		578406	159,75
	M 28		578318	146,98		H 25		578408	159,75
	M 35		578390	178,12		H 26		578410	159,75
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		H 32		578412	159,75
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 16		578352 R	177,08
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 18		578356	177,08
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 20		578358 R	177,08
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 25		578360	177,08
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		TH 26		578362 R	177,08
Geberit Mapress	M 15		578312	146,98		TH 32		578364	177,08
Kupfer Gas	M 18		578314	146,98		TH 40		578624	234,69
	M 22		578316	146,98		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 28		578318	146,98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 35		578390	178,12		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		U 16		578374	165,66
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		U 18		578376	165,66
Geberit Mepla	G 16		578444	177,50		U 20		578378	165,66
	G 20		578446	177,50		U 25		578380	165,66
	G 26		578448	188,40		U 32		578382	194,31
	G 32		578450	201,16		U 40		578386	236,66
	G 40		578452	260,33	General Fittings	H 16		578400	159,75
Geberit Mepla	G 16		578444	177,50	Trident	H 20		578406	159,75
Therm	G 20		578446	177,50		H 26		578410	159,75
	G 26		578448	188,40		H 32		578412	159,75
Geberit Volex	TH 16		578352 R	177,08		TH 16		578352 R	177,08
	TH 20		578358 R	177,08		TH 20		578358 R	177,08
	TH 26		578362 R	177,08		TH 26		578362 R	177,08
General Fittings	H 16		578400	159,75		TH 32		578364	177,08
5T00	H 20		578406	159,75		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	H 26		578410	159,75		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	H 32		578412	159,75		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 16		578352 R	177,08		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	TH 20		578358 R	177,08		U 16		578374	165,66
	TH 26		578362 R	177,08		U 20		578378	165,66
	TH 32		578364	177,08		U 32		578382	194,31
	TH 40		578624	234,69	General Fittings	H 16		578400	159,75
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	Trident Gas	H 20		578406	159,75
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		H 26		578410	159,75
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		TH 16		578352 R	177,08
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		TH 20		578358 R	177,08
	U 16		578374	165,66		TH 26		578362 R	177,08
	U 20		578378	165,66		TH 32		578364	177,08
	U 32		578382	194,31		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	U 40		578386	236,66		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
General Fittings	H 16		578400	159,75		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
Ewoprex	H 20		578406	159,75		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	H 26		578410	159,75		U 16		578374	165,66
	H 32		578412	159,75		U 20		578378	165,66
	TH 16		578352 R	177,08		U 32		578382	194,31
	TH 20		578358 R	177,08	Giacomini	H 16		578400	159,75
	TH 26		578362 R	177,08	Raccordi RM	H 20		578406	159,75
	TH 32		578364	177,08	Giacomini	H 26		578410	159,75
	TH 40		578624	234,69		H 32		578412	159,75
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		TH 16		578352 R	177,08
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		TH 20		578358 R	177,08
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		TH 26		578362 R	177,08
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		TH 32		578364	177,08
	U 16		578374	165,66		TH 40		578624	234,69
	U 20		578378	165,66		U 16		578374	165,66
	U 32		578382	194,31		U 20		578378	165,66
	U 40		578386	236,66		U 32		578382	194,31
						U 40		578386	236,66

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

**) Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Giacomini RM MULTIGAS	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	U 16		578374	165,66
	U 20		578378	165,66
	U 32		578382	194,31
Giacomini Valvole Giacomini serie R850V	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	SA 15		578514	176,56
	SA 18		578518	176,56
	SA 22		578520	176,56
	SA 28		578522	176,56
	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
Golan Pipe Systems (Scandinavia) Alu-Pres	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
	VUS ½" (OD 15,9 mm)		578566	177,50
Grinnell G-PRESS Copper Fittings	VUS ¾" (OD 22,2 mm)		578568	177,50
	VUS 1" (OD 28,6 mm)		578570	177,50
	VUS 1¼" (OD 34,9 mm)		578606	177,50
	VUS 1½" (OD 41,6 mm)			
GS Wärmesysteme System TH	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
GS Wärmesysteme System V	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
heima24	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
HELIROMA Klimapress	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
	U 16		578374	165,66
HELIROMA Klimapress PPSU	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
Henco	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	TH 14		578348	177,08
	TH 16		578352 R	177,08
HITEMC Sistema Multistrato	TH 18		578358 R	177,08
	TH 20		578362 R	177,08
	TH 26		578364	177,08
	TH 32		578366	177,08
	H 14		578398	159,75
	H 16		578400	159,75
HIDRONIX MULTIGAS	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	TH 14		578412	159,75
	TH 20		578372	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		57824	234,69
	TH 10 S (PR-2B)**	Mini Z8	574772 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
HIDRONIX MULTIPIPE	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	H 14		578398	159,75
	H 16		578400	159,75
	H 18		578404	159,75
HIDRONIX UNICO	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	H 14		578372	174,38
	H 16		578374	174,38
	H 18		578376	174,38
	H 20		578378	174,38
	H 26		578380	174,38
	H 32		578382	174,38
	U 14		578384	174,38
HIDRONIX UNICO	U 16		578386	174,38
	U 18		578387	174,38
	U 20		578388	174,38
	U 26 ¹⁾		578389	174,38
	U 32		578390	174,38
	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
HITEC Sistema Multistrato	H 14		578398	159,75
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	U 14		578372	174,38
	U 16		578374	174,38
	U 18		578376	174,38
	U 20		578378	174,38
HITEMC Sistema Multistrato	U 26 ¹⁾		578380	174,38
	U 32		578382	174,38
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574798 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	TH 14		578348	177,08
	TH 16		578352 R	177,08
HITEMC Sistema Multistrato	TH 18		578358 R	177,08
	TH 20		578362 R	177,08
	TH 26		578364	177,08
	TH 32		578366	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574798 R	124,51
HITHERM-ISOTUBI NUMEPRESS	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
HITHERM-ISOTUBI HTpress	M 15		578312	146,98	ICMA Sempigas	TH 16		578352 R	177,08
	M 18		578314	146,98		TH 20		578358 R	177,08
	M 22		578316	146,98		TH 25		578360	177,08
	M 28		578318	146,98		TH 26		578362 R	177,08
	M 35		578390	178,12		TH 32		578364	177,08
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					
HITHERM-ISOTUBI HTfire	M 15		578312	146,98	Idrosanitaria Bonomi Homegas	TH 16		578352 R	177,08
	M 18		578314	146,98		TH 20		578358 R	177,08
	M 22		578316	146,98		TH 26		578362 R	177,08
	M 28		578318	146,98		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 35		578390	178,12		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51					
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					
HITHERM-ISOTUBI HTair	M 15		578312	146,98	Idrosanitaria Bonomi Idropress	TH 16		578352 R	177,08
	M 18		578314	146,98		TH 18		578356	177,08
	M 22		578316	146,98		TH 20		578358 R	177,08
	M 28		578318	146,98		TH 26		578362 R	177,08
	M 35		578390	178,12		TH 32		578364	177,08
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 40		578624	234,69
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
Hopewell press fit system	M 15		578312	146,98	IDROSISTEMI Ta-Press	TH 16		578352 R	177,08
	M 18		578314	146,98		TH 20		578358 R	177,08
	M 22		578316	146,98		TH 26		578362 R	177,08
	M 28		578318	146,98		TH 32		578364	177,08
	M 35		578390	178,12		TH 40		578624	234,69
	hp praski	TH 10	578342	177,08		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	BAVARIA-press	TH 12	578344	177,08		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
		TH 14	578348	177,08		F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
		TH 16	578352 R	177,08		F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
		TH 17	578354	177,08		F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
IDROSYSTEMI Ta-Press	TH 20		578358 R	177,08		F 32 S (PR-2B)	Mini Z8	574734 R	136,96
	TH 25		578360	177,08		Fz 40		578478	247,15
	TH 26		578362 R	177,08		H 16		578400	159,75
	TH 32		578364	177,08		H 20		578406	159,75
	TH 40		578624	234,69		H 26		578410	159,75
	TH 10 S (PR-2B)**	Mini Z8	574772 R	124,51		H 32		578412	159,75
	TH 12 S (PR-2B)**	Mini Z8	574776 R	124,51		U 16		578374	165,66
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51		U 20		578378	165,66
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		U 26 ⁽⁷⁾		578392	194,31
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51		U 32		578382	194,31
IDROTRADE Storm Multipinza	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		U 40		578386	236,66
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51		B 16		578468	193,28
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		B 20		578472	193,28
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		B 26		578474	213,00
	U 16		578374	165,66		B 32		578476	213,00
	U 20		578378	165,66					
	U 25		578380	165,66					
	U 26 ⁽⁷⁾		578392	194,31					
	U 32		578382	194,31					
	U 40		578386	236,66					
ICMA Sempiter	H 16		578400	159,75	IDROTRADE Storm PRES ^{II}	H 16		578400	159,75
	H 20		578406	159,75		H 20		578406	159,75
	H 25		578408	159,75		H 26		578410	159,75
	H 26		578410	159,75		H 32		578412	159,75
	H 32		578412	159,75		TH 16		578352 R	177,08
	TH 16		578352 R	177,08		TH 20		578358 R	177,08
	TH 20		578358 R	177,08		TH 26		578362 R	177,08
	TH 25		578360	177,08		TH 32		578364	177,08
	TH 26		578362 R	177,08		THL 32		578368	177,08
	TH 32		578364	177,08		TH 40		578624	234,69
IDROTRADE Storm PRES ^{II}	TH 40		578624	234,69		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66		U 16		578374	165,66
	U 20		578378	165,66		U 20		578378	165,66
	U 25		578380	165,66		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	U 26 ⁽⁷⁾		578392	194,31		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	U 32		578382	194,31		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	U 40		578386	236,66		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
						M 35 S (PR-2B)	Mini Z8	574746 R	136,96

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

^{**} Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
IDROTRADE StormSTEEL ¹⁾	M 12		578310	146,98	IPLEX PIPELINES AUSTRALIA Iplex K2	K16/P18		578592	184,45
	M 15		578312	146,98		K/20		578594	184,45
	M 18		578314	146,98		K/25		578596	184,45
	M 22		578316	146,98					
	M 28		578318	146,98					
	M 35		578390	178,12					
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51					
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51					
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51					
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51					
ILTA INOX/CHIBRO Pressfitting Cuni	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					
	M 15		578312	146,98	ISOTUBI NUMEPRESS	M 15		578312	146,98
	M 18		578314	146,98		M 18		578314	146,98
	M 22		578316	146,98		M 22		578316	146,98
	M 28		578318	146,98		M 28		578318	146,98
	M 35		578390	178,12		M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
ILTA INOX/CHIBRO Pressfitting inox	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	M 15		578312	146,98	IVAR ALPEX-GAS	B 20		578472	193,28
	M 18		578314	146,98		B 26		578474	213,00
	M 22		578316	146,98		B 32		578476	213,00
	M 28		578318	146,98					
	M 35		578390	178,12					
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51					
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51					
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51					
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					
Instantor Press System	M 15		578312	146,98	IVAR MULTI PRESS GAS ITALIA	B 26		578474	213,00
	M 18		578314	146,98		B 32		578476	213,00
	M 22		578316	146,98		Fz 40		578478	247,15
	M 28		578318	146,98					
	M 35		578390	178,12					
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51					
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51					
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51					
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					
Instantor Copper Press Imperial	TH 16		578352 R	177,08	IVAR Multi Press MP	U 16		578374	165,66
	TH 20		578358 R	177,08		U 20		578378	165,66
	TH 26		578362 R	177,08					
	TH 32		578364	177,08					
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51					
	TH 20 S (PR-2B)**	Mini Z8	574786 R	124,51					
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51					
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96					
	VI ½" (OD 14,7 mm)		578716	175,53					
	VI ¾" (OD 21,0 mm)		578718	175,53					
Instantor Copper Press Metric	VI 1" (OD 27,4 mm)		578720	175,53	IVAR Multi Press MP	TH 16		578352 R	177,08
	VI ½" S (PR-2B)	Mini Z8	574850 R	124,51		TH 18		578358 R	177,08
	VI ¾" S (PR-2B)	Mini Z8	574852 R	124,51		TH 20		578362 R	177,08
	VI 1" S (PR-2B)	Mini Z8	574854 R	124,51		TH 25		578400	159,75
	M 15		578312	146,98		TH 26		578406	159,75
	M 22		578316	146,98		TH 32		578410	159,75
	M 28		578318	146,98		TH 40		578374	165,66
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	M 28 S (PR-2B)	Mini Z8	574746 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
IPA IPANA Press	TH 10		578342	177,08		TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 11,6		578344	177,08		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 12		578346	177,08		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	TH 14		578348	177,08		F 16		578400	159,75
	TH 15		578350	177,08		F 18		578404	159,75
	TH 16		578352 R	177,08		F 20		578406	159,75
	TH 17		578354	177,08		H 25		578408	159,75
	TH 18		578356	177,08		H 26		578410	159,75
	TH 20		578358 R	177,08		H 32		578412	159,75
	TH 22		578358	177,08		U 16		578374	165,66
IPALPEX (Industrie du Plastique et Accessoires)	TH 25		578360	177,08		U 18		578376	165,66
	TH 26		578362 R	177,08		U 20		578378	165,66
	TH 28		578364	177,08		H 26		578380	165,66
	TH 32		578366	177,08		H 32		578382	194,31
	TH 40		578624	234,69		U 32		578382	194,31
	TH 10 S (PR-2B)**	Mini Z8	574772 R	124,51		U 40		578386	236,66
	TH 11,6 S (PR-2B)**	Mini Z8	574774 R	124,51		B 16		578468	193,28
	TH 12 S (PR-2B)**	Mini Z8	574776 R	124,51		B 18		578470	193,28
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51		B 20		578472	193,28
	TH 15 S (PR-2B)**	Mini Z8	574780 R	124,51		B 26		578474	213,00
IPA Thu IPANA Press	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		B 32		578476	213,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51					
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51					
	TH 28 S (PR-2B)**	Mini Z8	574796 R	136,96					
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96					
	TH 16		578352 R	177,08	IVAR Multi Press Leak (MPL)	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20		578358 R	177,08		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26		578362 R	177,08		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32		578364	177,08		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	TH 40		578624	234,69		F 16		578456	168,68
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		F 20		578460	168,68
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		F 26		578462	182,48
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		F 32		578464	182,48
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96					
IPLEX PIPELINES AUSTRALIA Iplex Pro-fit	TH 14		578348	177,08	IPLEX PIPELINES AUSTRALIA Iplex K1 (gas)	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	TH 16		578352 R	177,08		F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	TH 18		578356	177,08		F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	TH 20		578358 R	177,08		F 32 S (PR-2B)	Mini Z8	574734 R	136,96
	TH 26		578362 R	177,08		H 16		578400	159,75
	THL 32		578368	177,08		H 20		578406	159,75
	TH 40		578624	234,69		H 26		578410	159,75
	K16/P18		578592	184,45		H 32		578412	159,75
	K16/P18		578592	184,45		U 16		578374	165,66
	K16/P18		578594	184,45		U 20		578378	165,66
IPLEX PIPELINES AUSTRALIA Iplex K1 (gas)	K16/P18		578596	184,45		U 26 ⁽¹⁾		578392	194,31
	K16/P18		578598	184,45					
	K16/P18		578600	184,45					
	K16/P18		578600	184,45					

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
IVAR	TH 16		578352 R	177,08
Plastic Multi Press	TH 20		578358 R	177,08
PMP	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	F 16		578456	168,68
	F 20		578460	168,68
	F 26		578462	182,48
	F 32		578464	182,48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96
	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
	B 16		578468	193,28
	B 20		578472	193,28
	B 26		578474	213,00
	B 32		578476	213,00
IVAR	TH 16		578352 R	177,08
Plastic Multi Press	TH 20		578358 R	177,08
Leak (PMPL)	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	F 16		578456	168,68
	F 20		578460	168,68
	F 26		578462	182,48
	F 32		578464	182,48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	U 16		578374	165,66
	U 20		578378	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
	B 16		578468	193,28
	B 20		578472	193,28
	B 26		578474	213,00
	B 32		578476	213,00
IVT Edelstahl-Presssystem	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
IVT PRIPRESS	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
		J		
Jäger - Aquatec	H 14		578398	159,75
Aquapress H	H 16		578400	159,75
	H 17		578402	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	U 40		578386	236,66
Jäger - Aquatec	M 15		578312	146,98
C-Stahl	M 18		578314	146,98
Press Typ M	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
Jäger - Aquatec	V 15		578328	146,98
Kupfer	V 18		578332	146,98
Press Typ V	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
Jansen AG	TH 14		578348	177,08
JANSEN COMISA	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
Jaraflex-Presssystem	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 17		578354	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
JUNGWOO	VUS ½" (OD 15,9 mm)		578566	177,50
JWPress	VUS ¾" (OD 22,2 mm)		578568	177,50
	VUS 1" (OD 28,6 mm)		578570	177,50
	VUS 1¼" (OD 34,9 mm)		578606	177,50

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
K				
KAN	TH 14		578348	177,08
KAN-therm Press LBP	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 14		578372	174,38
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
	U 40		578386	236,66
KAN	M 15		578312	146,98
KAN-therm Inox	M 18 ¹⁾		578314	146,98
	M 22		578316	146,98
	M 28 ¹⁾		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
KAN	M 12		578310	146,98
KAN-therm Steel	M 15		578312	146,98
	M 18 ¹⁾		578314	146,98
	M 22		578316	146,98
	M 28 ¹⁾		578318	146,98
	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
KAN	TH 14		578348	177,08
KAN-therm UltraPRESS	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 14		578372	174,38
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
	U 40		578386	236,66
KE KELIT	M 15		578312	146,98
COPPERFIX	M 18		578314	146,98
Kupfer	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
KE KELIT	U 16		578374	165,66
KELIT KELOX	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
KE KELIT	U 16		578374	165,66
KELOX-PPS-W	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
KE KELIT	U 16		578374	165,66
KELOX-ULTRAX	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
KE KELIT	U 16		578374	165,66
KELOX-ULTRAX-W	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
KE KELIT	U 16		578374	165,66
KELOX-WINDOX-U	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
KE KELIT	U 16		578374	165,66
KELOX-WINDOX-U	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
KE KELIT	U 16		578374	165,66
KELOX-WINDOX-W	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
K				
KE KELIT	M 15		578312	146,98
steelFIX	M 18		578314	146,98
C-Stahl	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578319	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
KE KELIT	M 15		578312	146,98
steelFIX	M 18		578314	146,98
Edelstahl	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578319	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
KEMBLA	VAU 15 (OD 12,7 mm)		578630	151,86
KemPress	VAU 20 (OD 19,1 mm)		578632	151,86
(AUS)	VAU 25 (OD 25,4 mm)		578634	151,86
	VAU 32 (OD 31,8 mm)		578636	159,75
KEMBLA	VAU 15 (OD 12,7 mm)		578630	151,86
KemPress Gas	VAU 20 (OD 19,1 mm)		578632	151,86
(AUS)	VAU 25 (OD 25,4 mm)		578634	151,86
	VAU 32 (OD 31,8 mm)		578636	159,75
KISAN	KI 16		578524	187,36
Kisan KD	KI 20		578526	187,36
	KI 25		578528	187,36
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360 R	177,08
	TH 32		578362 R	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
KISAN	KI 16		578524	187,36
Kisan WM	KI 20		578526	187,36
	KI 25		578528	187,36
	KI 32		578530	252,44
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360 R	177,08
	TH 32		578362 R	177,08
	TH 40		578624	234,69
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
KISAN	M 15		578312	146,98
Kistal C	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578319	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
KISAN	M 15		578312	146,98
Kistal Inox	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578319	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
LEGEND-PRESS	VUS ½" (OD 15,9 mm)		578566	177,50
press fitting	VUS ¾" (OD 22,2 mm)		578568	177,50
system	VUS 1" (OD 28,6 mm)		578570	177,50
	VUS 1¼" (OD 34,9 mm)		578606	177,50
LK Systems	V 12		578324	146,98
LK >B-Press	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
LK Systems	V 12		578324	146,98
LK >B>Press	V 15		578328	146,98
Elförzinkat	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
LK Systems	V 15		578328	146,98
LK >B>Press	V 18		578332	146,98
Gas	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
LK Systems	TH 16		578352 R	177,08
LK Universal	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69

M

MAINCOR	U 16		578374	165,66
MAINPRESS	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
MAINCOR	U 16		578374	165,66
MAINFLOR	U 20		578378	165,66
Mair Heiztechnik	H 11,5		578394	159,75
M-Press	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
Ma.s.ter System	TH 14		578348	177,08
PRESSMASTER	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	H 14		578398	159,75
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	U 14		578372	174,38
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Meier Tobler	H 16		578400	159,75
Metalplast - Stramax	H 20		578406	159,75
Serie MM	H 25		578408	159,75
	H 32		578412	159,75
	RFz 16		578492	184,45
	RFz 20		578494	184,45
	RFz 25		578496	184,45
	RFz 32		578498	184,45
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
METALGRUP	U 16		578374	165,66
Permatubo	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
METALGRUP	RFz 16		578492	184,45
PexGrup	RFz 20		578494	184,45
	RFz 25		578496	184,45
	RFz 32		578498	184,45
METALGRUP	U 16		578374	165,66
MultiGrup	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
Mueller Streamline	VUS ½" (OD 15,9 mm)		578566	177,50
PRS Copper Press	VUS ¾" (OD 22,2 mm)		578568	177,50
	VUS 1" (OD 28,6 mm)		578570	177,50
	VUS 1¼" (OD 34,9 mm)		578606	177,50
MULTITHERM	TH 16		578352 R	177,08
PRESSSYSTEM	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
Multicapas Industrial	RFz 16		578492	184,45
AIS PEX	RFz 20		578494	184,45
	RFz 25		578496	184,45
	RFz 32		578498	184,45
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
Multicapas Industrial	H 16		578400	159,75
AIS XPRT	H 20		578406	159,75
	H 25		578408	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	RFz 16		578492	184,45
	RFz 20		578494	184,45
	RFz 25		578496	184,45
	RFz 32		578498	184,45
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Multicapas Industrial multitubo systems MC	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
Multicapas Industrial multitubo systems MM	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	RFz 16		578492	184,45
	RFz 20		578494	184,45
	RFz 25		578496	184,45
	RFz 32		578498	184,45
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
multipipe Deutschland multipipe mp	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
N				
NEUTHERM MEKUPPRESS-HT	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
NIBCO Press System Copper	VUS ½" (OD 15,9 mm)		578566	177,50
	VUS ¾" (OD 22,2 mm)		578568	177,50
	VUS 1" (OD 28,6 mm)		578570	177,50
	VUS 1¼" (OD 34,9 mm)		578606	177,50
NICOLL FLUXO	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
NUPI Industrie Italiane Multinupi	B 16		578468	193,28
	B 18		578470	193,28
	B 20		578472	193,28
	B 26		578474	213,00
	B 32		578476	213,00
	F 16		578456	168,68
	F 18		578458	168,68
	F 20		578460	168,68
	F 26		578462	182,48
	F 32		578464	182,48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 14		578372	174,38
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
	U 40		578386	236,66
Nussbaum Optiflitt-Press	VMP ⅜" (OD 17,2 mm)		578660	204,17
	VMP ½" (OD 21,3 mm)		578666 R	204,17
	VMPz ¾" (OD 26,9 mm)		578664	204,17

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Nussbaum	VRX 16		578640	186,42
Optiflex-Flowpress	VRX 20		578642	186,42
	VRX 25		578644	204,17
	VRX 32		578646	204,17
Nussbaum	V 15		578328	146,98
Optipress	V 18		578332	146,98
Aquaplus	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
Nussbaum	V 15		578328	146,98
Optipress Gaz	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
O				
Oventrop	H 16 A		578420	204,17
Cofit P	H 20 A		578426	204,17
	H 26 A		578430	204,17
	H 32 A		578432	204,17
Oventrop	H 16 A		578420	204,17
Cofit PD	H 20 A		578426	204,17
	H 26 A		578430	204,17
Oventrop	H 16 A		578420	204,17
Cofit PD-HT	H 20 A		578426	204,17
	H 32 A		578432	204,17
Oventrop	H 16 A		578420	204,17
Cofit PDK-HT	H 20 A		578426	204,17
P				
PBTub	RFz 12		578490	184,45
SERTIPRESS	RFz 16		578492	184,45
	RFz 20		578494	184,45
	RFz 25		578496	184,45
PBTub	M 15		578312	146,98
SERTI-STEEL ¹⁾	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
Pegler Yorkshire	> Aalberts integrated piping systems			
PERFEXIM	U 16		578374	165,66
PERFEKT	U 20		578378	165,66
SYSTEM	U 25		578380	165,66
	U 32		578382	194,31
PERFEXIM	U 16		578374	165,66
PERFEKT	U 20		578378	165,66
SYSTEM PLUS	U 25		578380	165,66
	U 32		578382	194,31
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
PERFILTUBO	U 16		578374	165,66
PERFILALUPEX	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
PERFILTUBO	M 15		578312	146,98
PERFILPRESS	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
PEXTUBE	RFz 16		578492	184,45
PexTube	RFz 20		578494	184,45
	RFz 25		578496	184,45
	RFz 32		578498	184,45

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Pipelife C-PRESS	M 15		578312	146,98	PLÁSTICOS FERRO	U 16		578374	165,66
	M 18		578314	146,98	FERROPLAST	U 20		578378	165,66
	M 22		578316	146,98	GPF MULT Pressfitting	U 25		578380	165,66
	M 28		578318	146,98	MULTICAPA	U 32		578382	194,31
	M 35		578390	178,12	PLÁSTICOS FERRO	U 16		578374	165,66
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	FERROPLAST	U 20		578378	165,66
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	GPF PPSU	U 25		578380	165,66
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	Pressfitting PEX	U 32		578382	194,31
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	y MULTICAPA				
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	PLÁSTICOS FERRO	RFz 16		578492	184,45
	TH 16		578352 R	177,08	FERROPLAST	RFz 20		578494	184,45
Pipelife RADOPRESS	TH 18		578356	177,08	GPF PRESS	RFz 25		578496	184,45
	TH 20		578358 R	177,08	Pressfitting PEX	RFz 32		578498	184,45
	TH 26		578362 R	177,08	PLUMBING PLUS	K16/P18		578592	184,45
	TH 32		578364	177,08	EZIPEX Crimp	K/20		578594	184,45
	TH 40		578624	234,69	(AUS)	K/25		578596	184,45
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	K32			578598	184,45
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	K140			578600	184,45
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	PLUMBING PLUS	K16/P18		578592	184,45
Pipetec Connect	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	EZIPEX Gas	K/20		578594	184,45
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	(AUS)	K/25		578596	184,45
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	K32			578598	184,45
	U 16		578374	165,66	K140			578600	184,45
	U 20		578378	165,66	PLUMBING PLUS	Yz 16 UNI		578740	184,45
	U 32		578382	194,31	UNIPEX	Yz 20 UNI		578742	184,45
	TH 16		578352 R	177,08	Water & Gas (AUS)	Yz 25 UNI		578744	184,45
	TH 20		578358 R	177,08	Yz 32 UNI			578746	184,45
PLASTICA ALFA Multypex	TH 26		578362 R	177,08	PLUMBING PLUS	VAU 15 (OD 12,7 mm)		578630	151,86
	TH 32		578364	177,08	EZIPRESS Gas	VAU 20 (OD 19,1 mm)		578632	151,86
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	(AUS)	VAU 25 (OD 25,4 mm)		578634	151,86
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	VAU 32 (OD 31,8 mm)			578636	159,75
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8		574804 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8		574806 R	124,51
	TH 16		578352 R	177,08	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8		574808 R	136,96
	TH 20		578358 R	177,08	PLUMBING PLUS	VAU 15 (OD 12,7 mm)		578630	151,86
PLASTICA ALFA Multypex Air	TH 26		578362 R	177,08	EZIPRESS Solar	VAU 20 (OD 19,1 mm)		578632	151,86
	TH 32		578364	177,08	(AUS)	VAU 25 (OD 25,4 mm)		578634	151,86
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8		574804 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8		574806 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8		574808 R	136,96
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	PLUMBING PLUS	VAU 15 (OD 12,7 mm)		578630	151,86
	TH 16		578352 R	177,08	EZIPRESS Water	VAU 20 (OD 19,1 mm)		578632	151,86
	TH 20		578358 R	177,08	(AUS)	VAU 25 (OD 25,4 mm)		578634	151,86
PLASTICA ALFA Multypexalpha Gas	TH 26		578362 R	177,08	VAU 32 (OD 31,8 mm)			578636	159,75
	TH 32		578364	177,08	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8		574804 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8		574806 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8		574808 R	136,96
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	POLYPipe	TH 10		578342	177,08
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	POLYSURE	TH 15		578350	177,08
	TH 16		578352 R	177,08	TH 22			578588	177,08
	TH 20		578358 R	177,08	TH 28			578590	177,08
PLASTICA ALFA Multypexalpha Gas protek	TH 26		578362 R	177,08	POLYSAN	M 15		578312	146,98
	TH 32		578364	177,08	Handelsges.	M 18		578314	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	m.b.H. & Co KG	M 22		578316	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	(Krems/Oster- reich)	M 28		578318	146,98
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	M 35			578390	178,12
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	TH 16		578352 R	177,08	C Stahl-Press-	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	TH 20		578358 R	177,08	System M	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
PLASTICA ALFA Multypex Plus	TH 26		578362 R	177,08	M 28 S (PR-2B)	Mini Z8		574744 R	124,51
	TH 32		578364	177,08	M 35 S (PR-2B)	Mini Z8		574746 R	136,96
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	POLYSAN	M 15		578312	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	Handelsges.	M 18		578314	146,98
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	m.b.H. & Co KG	M 22		578316	146,98
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	(Krems/Oster- reich)	M 28		578318	146,98
	TH 16		578352 R	177,08	M 35			578390	178,12
	TH 20		578358 R	177,08	POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
PLASTICA ALFA Multypex Thermo	TH 26		578362 R	177,08	Edelstahl	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	TH 32		578364	177,08	Press-System	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	1.4520	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	M 35 S (PR-2B)	Mini Z8		574746 R	136,96
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	POLYSAN	M 15		578312	146,98
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	Handelsges.	M 18		578314	146,98
	TH 16		578352 R	177,08	m.b.H. & Co KG	M 22		578316	146,98
	TH 20		578358 R	177,08	(Krems/Oster- reich)	M 28		578318	146,98
PLASTICA ALFA Multypex Thermo Plus	TH 26		578362 R	177,08	M 35			578390	178,12
	TH 32		578364	177,08	POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	Edelstahl	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	Press-System	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	M 28 S (PR-2B)	Mini Z8		574744 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	M 35 S (PR-2B)	Mini Z8		574746 R	136,96
	TH 16		578352 R	177,08	POLYSAN	M 15		578312	146,98
	TH 20		578358 R	177,08	Handelsges.	M 18		578314	146,98
PLASTICA ALFA Multypex Thermo Plus	TH 26		578362 R	177,08	m.b.H. & Co KG	M 22		578316	146,98
	TH 32		578364	177,08	(Krems/Oster- reich)	M 28		578318	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	M 35			578390	178,12
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	Edelstahl	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	Press-System Gas	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	TH 16		578352 R	177,08	M 28 S (PR-2B)	Mini Z8		574744 R	124,51
	TH 20		578358 R	177,08	M 35 S (PR-2B)	Mini Z8		574746 R	136,96

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

**) Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
POLYSAN	M 15		578312	146,98	R				
Handelsges.	M 18		578314	146,98	Raccorderie	M 15		578312	146,98
m.b.H. & Co KG	M 22		578316	146,98	Metalliche	M 18		578314	146,98
(Krems/Öster- reich)	M 28		578318	146,98	aesPRES ^{II}	M 22		578316	146,98
POLYSAN-	M 35		578390	178,12	M 28			578318	146,98
Edelstahl	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	M 35			578390	178,12
Press-System	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	M 15 S (PR-2B)	Mini Z8		574738 R	124,51
Wasser	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	M 18 S (PR-2B)	Mini Z8		574740 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	M 22 S (PR-2B)	Mini Z8		574742 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	M 28 S (PR-2B)	Mini Z8		574744 R	124,51
POLYSAN	TH 14		578348	177,08	M 35 S (PR-2B)	Mini Z8		574746 R	136,96
Handelsges.	TH 16		578352 R	177,08	Raccorderie	M 15		578312	146,98
m.b.H. & Co KG	TH 17		578354	177,08	Metalliche	M 18		578314	146,98
(Krems/Öster- reich)	TH 18		578356	177,08	inoxPRES ^{II}	M 22		578316	146,98
POLYSAN-	TH 20		578358 R	177,08	M 28			578318	146,98
Press-System	TH 26		578362 R	177,08	M 35			578390	178,12
	TH 32		578364	177,08	M 15 S (PR-2B)	Mini Z8		574738 R	124,51
	TH 40		578624	234,69	M 18 S (PR-2B)	Mini Z8		574740 R	124,51
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51	M 22 S (PR-2B)	Mini Z8		574742 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	M 28 S (PR-2B)	Mini Z8		574744 R	124,51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51	M 35 S (PR-2B)	Mini Z8		574746 R	136,96
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	Raccorderie	M 15		578312	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	Metalliche	M 18		578314	146,98
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	inoxPRES ^{II}	M 22		578316	146,98
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	M 28			578318	146,98
POLYSAN	TH 14		578348	177,08	M 35			578390	178,12
Handelsges.	TH 16		578352 R	177,08	M 15 S (PR-2B)	Mini Z8		574738 R	124,51
m.b.H. & Co KG	TH 17		578354	177,08	M 18 S (PR-2B)	Mini Z8		574740 R	124,51
(Krems/Öster- reich)	TH 18		578356	177,08	M 22 S (PR-2B)	Mini Z8		574742 R	124,51
POLYSAN-Henco-	TH 20		578358 R	177,08	M 28 S (PR-2B)	Mini Z8		574744 R	124,51
Press-System	TH 26		578362 R	177,08	M 35 S (PR-2B)	Mini Z8		574746 R	136,96
	HE3 32		578370 R	212,06	Raccorderie	M 15		578312	146,98
	HEz 40 ³⁾		578572	307,66	Metalliche	M 18		578314	146,98
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51	inoxPRES ^{II}	M 22		578316	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	M 28			578318	146,98
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51	M 35			578390	178,12
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	M 15 S (PR-2B)	Mini Z8		574738 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	M 18 S (PR-2B)	Mini Z8		574740 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	M 22 S (PR-2B)	Mini Z8		574742 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	M 28 S (PR-2B)	Mini Z8		574744 R	124,51
POLYSAN (España) „Rainbow“	U 16		578374	165,66	M 35 S (PR-2B)	Mini Z8		574746 R	136,96
	U 18		578376	165,66	Raccorderie	M 15		578466	193,28
	U 20		578378	165,66	M 18			578468	193,28
	U 25		578380	165,66	steelPRES ^{II}	M 22		578470	193,28
	U 32		578382	194,31	M 28			578472	193,28
	U 40		578386	236,66	M 35			578474	193,28
Prandelli Multyrama Pf	H 14		578398	159,75	M 15 S (PR-2B)	Mini Z8		578476	193,28
	H 16		578400	159,75	M 18 S (PR-2B)	Mini Z8		578478	193,28
	H 18		578404	159,75	M 22 S (PR-2B)	Mini Z8		578480	193,28
	H 20		578406	159,75	M 28 S (PR-2B)	Mini Z8		578482	193,28
	H 26		578410	159,75	M 35 S (PR-2B)	Mini Z8		578484	193,28
	H 32		578412	159,75	RBM Tita-fix	B 14		578486	193,28
	TH 16		578352 R	177,08	F 16			578488	193,28
	TH 18		578356	177,08	F 20			578490	193,28
	TH 20		578358 R	177,08	F 16 S (PR-2B)**	Mini Z8		578492	193,28
	TH 26		578362 R	177,08	F 20 S (PR-2B)**	Mini Z8		578494	193,28
	TH 32		578364	177,08	H 14			578496	193,28
	TH 40		578624	234,69	H 16			578498	193,28
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	H 18			578500	193,28
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	H 26			578502	193,28
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	H 32			578504	193,28
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	TH 14			578506	193,28
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	TH 16			578508	193,28
	U 16		578374	165,66	TH 18			578510	193,28
	U 18		578376	165,66	TH 20			578512	193,28
	U 20		578378	165,66	TH 26			578514	193,28
	U 40		578386	236,66	TH 32			578516	193,28
PURMO Cleverfit Radial	F 16		578400	159,75	TH 40			578518	193,28
	F 20		578404	159,75	TH 16 S (PR-2B)**	Mini Z8		578520	193,28
	F 26		578406	159,75	TH 20 S (PR-2B)**	Mini Z8		578522	193,28
	F 32		578408	159,75	TH 26 S (PR-2B)**	Mini Z8		578524	193,28
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51	TH 32 S (PR-2B)	Mini Z8		578526	193,28
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51	RBM Tita-gas	TH 16		578528	177,08
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51	TH 20			578530	177,08
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96	TH 26			578532	177,08
	H 16		578400	159,75	TH 32			578534	177,08
	H 20		578406	159,75	TH 16 S (PR-2B)**	Mini Z8		578536	177,08
	H 26		578410	159,75	TH 20 S (PR-2B)**	Mini Z8		578538	177,08
	H 32		578412	159,75	TH 26 S (PR-2B)**	Mini Z8		578540	177,08
	TH 14		578348	177,08	TH 32 S (PR-2B)	Mini Z8		578542	177,08
	TH 16		578352 R	177,08	Redi Nicoll Fluxo	TH 14		578544	177,08
	TH 17		578354	177,08	TH 16			578546	177,08
	TH 20		578358 R	177,08	TH 18			578548	177,08
	TH 26		578362 R	177,08	TH 20			578550	177,08
	TH 32		578364	177,08	TH 26			578552	177,08
	TH 40		578624	234,69	TH 32			578554	177,08
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51	TH 40			578556	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	TH 16 S (PR-2B)**	Mini Z8		578558	177,08
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51	TH 20 S (PR-2B)**	Mini Z8		578560	177,08
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	TH 26 S (PR-2B)**	Mini Z8		578562	177,08
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	TH 32 S (PR-2B)	Mini Z8		578564	177,08
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	TH 16			578566	177,08
	U 16		578374	165,66	TH 18			578568	177,08
	U 20		578378	165,66	TH 20			578570	177,08
	U 32		578382	194,31	TH 26			578572	177,08
	VP 16		578482	176,56	TH 32			578574	177,08
	VP 20		578484	176,56	TH 40			578576	177,08
	VP 32		578488	195,25	TH 16 S (PR-2B)**	Mini Z8		578578	177,08
					TH 20 S (PR-2B)**	Mini Z8		578580	177,08
					TH 26 S (PR-2B)**	Mini Z8		578582	177,08
					TH 32 S (PR-2B)	Mini Z8		578584	177,08

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Redi Nicoll Fluxo Gas	TH 16		578352 R	177,08	Rubinetterie	M 15		578312	146,98
	TH 20		578358 R	177,08		M 18		578314	146,98
	TH 26		578362 R	177,08		M 22		578316	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		M 28		578318	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		M 35		578390	178,12
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
RIFENG LD PRESS FITTING (F8)	LD 16		578652	182,69		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	LD 20		578654	182,69		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	LD 25		578656	182,69		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
RIFENG U PRESS FITTING (F5)	U 14		578372	174,38		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	U 16		578374	165,66	Rubinetterie	B 14		578466	193,28
	U 18		578376	165,66		B 16		578468	193,28
	U 20		578378	165,66		B 18		578470	193,28
	U 25		578380	165,66		B 20		578472	193,28
RIFENG TH PRESS FITTING (F9)	U 32		578382	194,31		B 26		578474	213,00
	U 40		578386	236,66		B 32		578476	213,00
	TH 16		578352 R	177,08		H 14		578398	159,75
	TH 20		578358 R	177,08		H 16		578400	159,75
RIQUIER A SERTIR	TH 25		578360	177,08		H 18		578404	159,75
	TH 26		578362 R	177,08		H 20		578406	159,75
	TH 32		578364	177,08		H 26		578410	159,75
	TH 40		578624	234,69		H 32		578412	159,75
	RFz 12		578490	184,45		TH 14		578348	177,08
RIQUIER Système multicouche	RFz 16		578492	184,45		TH 16		578352 R	177,08
	RFz 20		578494	184,45		TH 18		578356	177,08
	RFz 25		578496	184,45		TH 20		578358 R	177,08
	TH 16		578352 R	177,08		TH 26		578362 R	177,08
Roth PressCheck	TH 20		578358 R	177,08		TH 32		578364	177,08
	TH 26		578362 R	177,08		TH 40		578624	234,69
	TH 32		578364	177,08		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 40		578624	234,69		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		U 14		578372	174,38
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		U 16		578374	165,66
	U 16		578374	165,66		U 18		578376	165,66
	U 20		578378	165,66		U 20		578378	165,66
Rubinetterie	U 32		578382	194,31		U 26 ⁶⁾		578392	194,31
	U 40		578386	236,66		U 32		578382	194,31
	RN 14		578434	165,66	Rubinetterie	TH 16		578352 R	177,08
	RN 16		578454	165,66		TH 20		578358 R	177,08
	RN 17		578436	165,66		TH 26		578362 R	177,08
	RN 20		578438	165,66		TH 32		578364	177,08
RN 25/26	RN 25/26		578440	165,66		TH 40		578366	177,08
	RN 32		578442	194,31		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
Bresciane Bonomi TURBO CuNi	M 15		578312	146,98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 18		578314	146,98		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 22		578316	146,98		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 28		578318	146,98	TURBO PRESS GAS	U 26 ⁷⁾		578352 R	177,08
	M 35		578390	178,12		TH 16		578358 R	177,08
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 20		578362 R	177,08
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 26		578364	177,08
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 32		578366	177,08
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 40		578624	234,69
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
Rubinetterie	M 15		578312	146,98		TH 18 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 18		578314	146,98		TH 16 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 22		578316	146,98		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TURBO INOX		578318	146,98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 35		578390	178,12		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	SA.MI PLASTIC	TH 14		578348	177,08
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 16		578352 R	177,08
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 18		578356	177,08
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		TH 20		578358 R	177,08
Rubinetterie	M 15		578312	146,98		TH 26		578362 R	177,08
	M 18		578314	146,98		TH 32		578364	177,08
	M 22		578316	146,98		TH 40		578624	234,69
	TURBO INOX GAS		578318	146,98		TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	M 35		578390	178,12		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574798 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	SA.MI PLASTIC	TH 16		578352 R	177,08
Bresciane Bonomi	M 15		578312	146,98		TH 20		578358 R	177,08
	M 18		578314	146,98		TH 26		578362 R	177,08
	M 22		578316	146,98		TH 32		578364	177,08
	M 28		578318	146,98		TH 40		578624	234,69
	M 35		578390	178,12		TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
TURBO INOX GAS	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574798 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 15		578312	146,98	Multistrato Gas	TH 16		578352 R	177,08
	M 18		578314	146,98		TH 20		578358 R	177,08
SA.MI PLASTIC	M 22		578316	146,98		TH 26		578362 R	177,08
	M 28		578318	146,98		TH 32		578364	177,08
	M 35		578390	178,12		TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
SA.MI PLASTIC	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.](http://www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.</p>
</div>
<div data-bbox=)

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
SANHA	B 16		578468	193,28	SANHA-NiroSan	SA 15		578514	176,56
3fit-Press Pb-free	B 20		578472	193,28	Industry	SA 18		578518	176,56
Serie 25000	B 26		578474	213,00	Presssystem	SA 22		578520	176,56
	B 32		578476	213,00	Serie 18000	SA 28		578522	176,56
	F 16		578456	168,68		M 15 ¹⁾		578312	146,98
	F 20		578460	168,68		M 18 ¹⁾		578314	146,98
	F 26		578462	182,48		M 22 ¹⁾		578316	146,98
	F 32		578464	182,48		M 28		578318	146,98
	Fz 40		578478	247,15		M 35		578390	178,12
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	H 16		578400	159,75		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	H 20		578406	159,75		V 15 ¹⁾		578328	146,98
	H 26		578410	159,75		V 18 ¹⁾		578332	146,98
	H 32		578412	159,75		V 22 ¹⁾		578334	146,98
	TH 16		578352 R	177,08		V 28		578336	146,98
	TH 20		578358 R	177,08		V 35		578604	178,12
	TH 26		578362 R	177,08	SANHA-NiroSan-	SA 15		578514	176,56
	TH 32		578364	177,08	Presssystem	SA 18		578518	176,56
	TH 40		578624	234,69	Serie 9000	SA 22		578520	176,56
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		SA 28		578522	176,56
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		M 15 ¹⁾		578312	146,98
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		M 18 ¹⁾		578314	146,98
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		M 22 ¹⁾		578316	146,98
	U 16		578374	165,66		M 28		578318	146,98
	U 20		578378	165,66		M 35		578390	178,12
	U 26 ⁷⁾		578392	194,31		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	U 32		578382	194,31		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	U 40		578386	236,66		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
SANHA	B 16		578468	193,28		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
3fit-Press PPSU	B 20		578472	193,28		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
Serie 35000	B 26		578474	213,00		V 15 ¹⁾		578328	146,98
	B 32		578476	213,00		V 18 ¹⁾		578332	146,98
	F 16		578456	168,68		V 22 ¹⁾		578334	146,98
	F 20		578460	168,68		V 28		578336	146,98
	F 26		578462	182,48		V 35		578604	178,12
	F 32		578464	182,48		V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51		V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51		V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51		V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96		V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	H 16		578400	159,75	SANHA-NiroSan	SA 15		578514	176,56
	H 20		578406	159,75	SF Presssystem	SA 18		578518	176,56
	H 26		578410	159,75	Serie 19000	SA 22		578520	176,56
	H 32		578412	159,75	(silicone free)	SA 28		578522	176,56
	TH 16		578352 R	177,08		M 15 ¹⁾		578312	146,98
	TH 20		578358 R	177,08		M 18 ¹⁾		578314	146,98
	TH 26		578362 R	177,08		M 22 ¹⁾		578316	146,98
	TH 32		578364	177,08		M 28		578318	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		M 35		578390	178,12
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	U 16		578374	165,66		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	U 20		578378	165,66		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	U 26 ⁷⁾		578392	194,31		V 15 ¹⁾		578328	146,98
	U 32		578382	194,31		V 18 ¹⁾		578332	146,98
SANHA	VMP ½" G (OD 21,3mm)		578666 R	204,17		V 22 ¹⁾		578334	146,98
Heavy Steel Press	VMP ¾" G (OD 26,9 mm)		578664	204,17		V 28		578336	146,98
SANHA	VMP ½" G (OD 21,3mm) ^{b)}		578666 R	204,17		V 35		578604	178,12
Heavy Steel Press Gas	VMP ¾" G (OD 26,9 mm)		578664	204,17		V 15 S (PR-2B)	Mini Z8	574752 R	124,51
SANHA-NiroSan	SA 15		578514	176,56		V 18 S (PR-2B)	Mini Z8	574756 R	124,51
Gas Presssystem	SA 18		578518	176,56		V 22 S (PR-2B)	Mini Z8	574758 R	124,51
Serie 17000	SA 22		578520	176,56		V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	SA 28		578522	176,56		V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	M 15 ¹⁾		578312	146,98	SANHA	SA 15		578514	176,56
	M 18 ¹⁾		578314	146,98	NiroTherm	SA 18		578518	176,56
	M 22 ¹⁾		578316	146,98	Serie 91000	SA 22		578520	176,56
	M 28		578318	146,98		SA 28		578522	176,56
	M 35		578390	178,12		M 15 ¹⁾		578312	146,98
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		M 18 ¹⁾		578314	146,98
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		M 22 ¹⁾		578316	146,98
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		M 28		578318	146,98
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		M 35		578390	178,12
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	V 15 ¹⁾		578328	146,98		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	V 18 ¹⁾		578332	146,98		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	V 22 ¹⁾		578334	146,98		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	V 28		578336	146,98		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	V 35		578604	178,12		V 15 ¹⁾		578328	146,98
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		V 18 ¹⁾		578332	146,98
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		V 22 ¹⁾		578334	146,98
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		V 28		578336	146,98
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		V 35		578604	178,12
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		V 15 S (PR-2B)	Mini Z8	574752 R	124,51

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
SANHA NiroTherm Industry Serie 98000	SA 15		578514	176,56	SANHA-Press	SA 12		578510	256,39
	SA 18		578518	176,56	Pressfittings	SA 14		578512	256,39
	SA 22		578520	176,56	Serie 6000	SA 15		578514	176,56
	SA 28		578522	176,56		SA 16		578516	176,56
	M 15 ¹⁾		578312	146,98		SA 18		578518	176,56
	M 18 ¹⁾		578314	146,98		SA 22		578520	176,56
	M 22 ¹⁾		578316	146,98		SA 28		578522	176,56
	M 28		578318	146,98		M 12		578310	146,98
	M 35		578390	178,12		M 15 ¹⁾		578312	146,98
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		M 18 ¹⁾		578314	146,98
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		M 22 ¹⁾		578316	146,98
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		M 28		578318	146,98
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		M 35		578390	178,12
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	V 15 ¹⁾		578328	146,98		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	V 18 ¹⁾		578332	146,98		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	V 22 ¹⁾		578334	146,98		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	V 28		578336	146,98		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	V 35		578604	178,12		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		V 12		578324	146,98
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		V 14		578326	146,98
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		V 6 14		578338	146,98
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		V 15 ¹⁾		578328	146,98
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		V 16		578330	146,98
SANHA-Press Chrom Serie 16000	SA 12		578510	256,39		VG 16		578340	146,98
	SA 15		578514	176,56		V 18 ¹⁾		578332	146,98
	SA 18		578518	176,56		V 22 ¹⁾		578334	146,98
	SA 22		578520	176,56		V 28		578336	146,98
	SA 28		578522	176,56		V 35		578604	178,12
	M 12		578310	146,98		V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	M 15 ¹⁾		578312	146,98		VG 14 S (PR-2B)	Mini Z8	574750 R	124,51
	M 18 ¹⁾		578314	146,98		V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	M 22 ¹⁾		578316	146,98		VG 16 S (PR-2B)	Mini Z8	574754 R	124,51
	M 28		578318	146,98		V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51					
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	V 12		578324	146,98					
	V 15 ¹⁾		578328	146,98					
	V 18 ¹⁾		578332	146,98					
	V 22 ¹⁾		578334	146,98					
	V 28		578336	146,98					
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51					
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51					
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51					
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51					
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51					
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96					
SANHA-Press GAS Pressfittings Serie 10000/ Serie 11000	SA 12		578510	256,39	SANHA-Press	SA 12		578510	256,39
	SA 14		578512	256,39		SOLAR	SA 15	578514	176,56
	SA 15		578514	176,56		Pressfittings	SA 18	578518	176,56
	SA 16		578516	176,56		Serie 12000/	SA 22	578520	176,56
	SA 18		578518	176,56		Serie 13000	SA 28	578522	176,56
	SA 22		578520	176,56		M 12		578310	146,98
	SA 28		578522	176,56		M 15 ¹⁾		578312	146,98
	M 12		578310	146,98		M 18 ¹⁾		578314	146,98
	M 15 ¹⁾		578312	146,98		M 22 ¹⁾		578316	146,98
	M 18 ¹⁾		578314	146,98		M 28		578318	146,98
	M 22 ¹⁾		578316	146,98		M 35		578390	178,12
	M 28		578318	146,98		M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 35		578390	178,12		M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		M 28 S (PR-2B)	Mini Z8	574746 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		M 35 S (PR-2B)	Mini Z8	574748 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		V 12		578324	146,98
	V 12		578324	146,98		V 14		578326	146,98
	V 16		578326	146,98		V 6 14		578328	146,98
	V 15 ¹⁾		578328	146,98		V 15 ¹⁾		578330	146,98
	V 16		578330	146,98		V 18 ¹⁾		578332	146,98
	V 6 16		578340	146,98		V 22 ¹⁾		578334	146,98
	V 18 ¹⁾		578332	146,98		V 28		578336	146,98
	V 22 ¹⁾		578334	146,98		V 35		578604	178,12
	V 28		578336	146,98					
	V 35		578604	178,12					
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51					
	V 16 S (PR-2B)	Mini Z8	574750 R	124,51					
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51					
	V 16 S (PR-2B)	Mini Z8	574754 R	124,51					
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51					
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51					
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51					
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96					

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP ½ G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
SANHA PURAPRESS Serie 8000	SA 12		578510	256,39
	SA 14		578512	256,39
	SA 15		578514	176,56
	SA 16		578516	176,56
	SA 18		578518	176,56
	SA 22		578520	176,56
	SA 28		578522	176,56
	M 12 ¹⁾		578310	146,98
	M 15 ¹⁾		578312	146,98
	M 18 ¹⁾		578314	146,98
	M 22 ¹⁾		578316	146,98
	M 28 ¹⁾		578318	146,98
	M 35 ¹⁾		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
SANHA-Therm Serie 24000	V 12		578324	146,98
	V 14		578326	146,98
	VG 14		578338	146,98
	V 15 ¹⁾		578328	146,98
	V 16		578330	146,98
	VG 16		578340	146,98
	V 18 ¹⁾		578332	146,98
	V 22 ¹⁾		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	VG 14 S (PR-2B)	Mini Z8	574750 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	VG 16 S (PR-2B)	Mini Z8	574754 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
SANHA-Therm Industry Serie 28000	SA 12		578510	256,39
	SA 15		578514	176,56
	SA 18		578518	176,56
	SA 22		578520	176,56
	SA 28		578522	176,56
	M 12		578310	146,98
	M 15 ¹⁾		578312	146,98
	M 18 ¹⁾		578314	146,98
	M 22 ¹⁾		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	V 12		578324	146,98
	V 15 ¹⁾		578328	146,98
	V 18 ¹⁾		578332	146,98
	V 22 ¹⁾		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
SANITOP PERMATUBO INOX	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
SANPRO THPRESS	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	SATEC SK VI Term		578352 R	177,08
	TH 18		578356	177,08
SAVEUR REFLEX PEX Water	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	U 40		578386	236,66
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 32		578364	177,08
SAVEUR REFLEX PEX-AL-PEX Gas	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 25		578364	177,08
	TH 32		578364	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
Schwer Fittings AQUApres	M 12		578310	146,98
	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
Seppelfricke	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	TH 16		578352 R	177,08
	TH 18		578356	177,08
SESTA SESTA GAS	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 20		578364	177,08
	TH 25		578366	177,08
	TH 32		578366	177,08
	TH 16		578352 R	177,08
	TH 18		578356	177,08
SESTA sistema multistrato	H 16		578400	159,75
	H 20		578406	159,75
	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16		578352 R	177,08
	TH 18		578356	177,08
SIGMA LI Premium	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
SLOVARM PEX-THERM	U 16		578374	165,66
	U 20		578378	165,66
	H 26		578410	159,75
	U 32		578382	194,31
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	H 16		578410	159,75
	H 20		578412	159,75

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
STANDARD	H 16		578400	159,75	TDM BRASS	H 16		578400	159,75	
HIDRAULICA	H 20		578406	159,75	Serie 2600	H 18		578406	159,75	
MultiStandard	H 25		578408	159,75		H 20		578408	159,75	
	H 32		578412	159,75		H 25		578410	159,75	
	RFz 16		578492	184,45		H 26		578410	159,75	
	RFz 20		578494	184,45		H 32		578412	159,75	
	RFz 25		578496	184,45		TH 16		578352 R	177,08	
	RFz 32		578498	184,45		TH 18		578356	177,08	
	TH 16		578352 R	177,08		TH 20		578358 R	177,08	
	TH 20		578358 R	177,08		TH 25		578360	177,08	
	TH 25		578360	177,08		TH 26		578362 R	177,08	
	TH 32		578364	177,08		THL 32		578368	177,08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51	
steeltrade	U 16		578374	165,66		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
Presssystem	U 18		578376	165,66		U 16		578374	165,66	
Edelstahl	U 20		578378	165,66		U 18		578376	165,66	
Kontur M	U 25		578380	165,66		U 20		578378	165,66	
M 32			578382	194,31						
M 40			578386	236,66						
STELBI	M 15		578312	146,98						
Polikraft	M 18 ¹⁾		578314	146,98						
	M 22		578316	146,98						
	M 28 ¹⁾		578318	146,98						
	M 35		578390	178,12						
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51						
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51						
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51						
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51						
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96						
STELBI	H 16		578400	159,75						
	H 20		578406	159,75						
	H 26		578410	159,75						
	TH 16		578352 R	177,08						
	TH 20		578358 R	177,08						
	TH 26		578362 R	177,08						
	TH 32		578364	177,08						
	TH 40		578624	234,69						
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51						
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51						
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51						
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96						
	U 16		578374	165,66						
	U 20		578378	165,66						
	U 26 ²⁾		578392	194,31						
STELBI	TH 16		578352 R	177,08						
Stelgas	TH 20		578358 R	177,08						
	TH 26		578362 R	177,08						
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51						
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51						
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51						
STH Westco	M 15		578312	146,98						
COPPER PRESS	M 22		578316	146,98						
	M 28		578318	146,98						
	M 35		578390	178,12						
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51						
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51						
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51						
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96						
T										
TDM BRASS	H 16		578400	159,75						
Serie 1600	H 18		578404	159,75						
	H 20		578406	159,75						
	H 25		578408	159,75						
	H 26		578410	159,75						
	H 32		578412	159,75						
	TH 16		578352 R	177,08						
	TH 18		578356	177,08						
	TH 20		578358 R	177,08						
	TH 25		578360	177,08						
	TH 26		578362 R	177,08						
	THL 32		578368	177,08						
	TH 40		578624	234,69						
	TH 14 S (PR-2B)**	Mini Z8	574782 R	124,51						
	TH 16 S (PR-2B)**	Mini Z8	574788 R	124,51						
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51						
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51						
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51						
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51						
	U 16		578374	165,66						
	U 18		578376	165,66						
	U 20		578378	165,66						
	U 25		578380	165,66						
	U 26 ²⁾		578392	194,31						
	U 32		578382	194,31						
	T									
TIEMME	TH 14									
1650 AL-COBRAPEX	TH 16									
	TH 18									
	TH 20									
	TH 25									
	TH 26									
	THL 32									
	TH 40									
	TH 14 S (PR-2B)**	Mini Z8								
	TH 16 S (PR-2B)**	Mini Z8								
	TH 18 S (PR-2B)**	Mini Z8								
	TH 20 S (PR-2B)**	Mini Z8								
	TH 25 S (PR-2B)**	Mini Z8								
	TH 26 S (PR-2B)**	Mini Z8								
	TIEMME	RFz 12								
	1700 COBRAPEX	RFz 16								
	RFz 20									
	RFz 25									
	RFz 32									
	TH 40									

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
TIEMME 1650 AL-COBRAPEX GAS	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	THL 32		578368	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
TIGRE ALPEX GÁS	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
TKM Systemtechnik	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
TRA Multi TRA+	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
	U 40		578386	236,66
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
	U 40		578386	236,66
TRA MULTITRAPRESS	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
TRA TRAPRESS	H 12		578396	159,75
	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 32		578412	159,75
	RFz 12		578490	184,45
	RFz 16		578492	184,45
	RFz 20		578494	184,45
	RFz 25		578496	184,45
	RFz 32		578498	184,45
	K16/P18		578592	184,45
	K20		578594	184,45
Water	K25		578596	184,45
	K32		578598	184,45
	K1/40		578600	184,45
	K16/P18		578592	184,45
	K20		578594	184,45
	K25		578596	184,45
Tradelink TradePex Crimp Gas	K32		578598	184,45
	K1/40		578600	184,45
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
TUBIPLAST ITALY MULTILAYER PIPE	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
TUBIPLAST ITALY MULTILAYER PIPE GAS SYSTEM	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
TWEETOP	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
	U			
UNICAL AG	U 16		578374	165,66
	U 20		578378	165,66
	H 26		578410	159,75
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
	U			
UNIDELTA	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
DELTAPRESS	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
UNIDELTA	H 32		578412	159,75
	H 40		578416	159,75
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
UNIDELTA	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
DELTAPRESS GAS	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
UPONOR	H 32		578412	159,75
	H 40		578416	159,75
	UP 14		578576	165,66
	UP 16		578578	165,66
	UP 20		578582	165,66
	UP 25		578584	165,66
VALSR PEXAL	UP 32		578586	194,31
	U 16		578374	165,66
	U 20		578378	165,66
	U 26 ⁷⁾		578392	194,31
	U 32		578382	194,31
	V			
VALSR BRAVOPRESS	B 16		578468	193,28
	B 20		578472	193,28
	B 26		578474	213,00
	B 32		578476	213,00
	F 16		578456	168,68
	F 20		578460	168,68
VALSR PEXAL	F 26		578462	182,48
	F 32		578464	177,08
	F 40		578386	236,66
	Mini Z8		574728 R	124,51
	Mini Z8		574730 R	124,51
	Mini Z8		574732 R	124,51
VALSR PEXAL	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578412	159,75
	H 32		578416	159,75
	H 40		578420	159,75
	H 32 V		578424	159,75
	H 32 V		578426	159,75
	H 32 V		578428	159,75
	H 32 V		578430	159,75
	H 32 V		578432	159,75
	H 32 V		578434	159,75
	H 32 V		578436	159,75
VALSR PEXAL	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578412	159,75
	H 32		578416	159,75
	H 40		578420	159,75
	H 32 V		578424	159,75
	H 32 V		578426	159,75
	H 32 V		578428	159,75
	H 32 V		578430	159,75
	H 32 V		578432	159,75
	H 32 V		578434	159,75
	H 32 V		578436	159,75
VALSR PEXAL	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578412	159,75
	H 32		578416	159,75
	H 40		578420	159,75
	H 32 V		578424	159,75
	H 32 V		578426	159,75
	H 32 V		578428	159,75
	H 32 V		578430	159,75
	H 32 V		578432	159,75
	H 32 V		578434	159,75
	H 32 V		578436	159,75

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Van Marcke NV SYSTEMPEX	TH 16		578352 R	177,08	Viega MegaPress 316 (ASTM) ³⁾	VMP ½" G (OD 21,3 mm) VMPz ¾" (OD 26,9 mm)		578666 R	204,17
	TH 20		578358 R	177,08	Viega MegaPress 316 (ASTM) ³⁾	VMP ½" G (OD 21,3 mm) VMPz ¾" (OD 26,9 mm)		578664	204,17
	TH 26		578362 R	177,08	Viega MegaPress FKM (ASTM) ⁵⁾	VMP ½" G (OD 21,3 mm) VMPz ¾" (OD 26,9 mm)		578666 R	204,17
	TH 32		578364	177,08	Viega MegaPress FKM (ASTM) ⁵⁾	VMP ½" G (OD 21,3 mm) VMPz ¾" (OD 26,9 mm)		578664	204,17
	TH 40		578624	234,69	Viega MegaPress CuNi (ASTM) ³⁾	VMP ½" G (OD 21,3 mm) VMPz ¾" (OD 26,9 mm)		578666 R	204,17
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	Viega MegaPress CuNi (ASTM) ³⁾	VMP ½" G (OD 21,3 mm) VMPz ¾" (OD 26,9 mm)		578664	204,17
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	Viega MegaPress FKM (ASTM) ³⁾	VMP ½" G (OD 21,3 mm) VMPz ¾" (OD 26,9 mm)		578666 R	204,17
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	Viega MegaPress FKM (ASTM) ⁵⁾	VMP ½" G (OD 21,3 mm) VMPz ¾" (OD 26,9 mm)		578664	204,17
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	Viega MegaPresG (ASTM) ³⁾	VMP ½" G (OD 21,3 mm) VMPz ¾" (OD 26,9 mm)		578666 R	204,17
	M 12		578310	146,98	Viega Megapress (EN) ⁴⁾	VMP ½" G (OD 21,2 mm) VMPz ¾" (OD 26,9 mm)		578660	204,17
Van Marcke NV Tubipress	M 15		578312	146,98	Viega Megapress (EN) ⁴⁾	VMP ½" G (OD 21,3 mm) VMPz ¾" (OD 26,9 mm)		578666 R	204,17
	M 18		578314	146,98	Viega Megapress S (EN) ⁴⁾	VMP ¾" (OD 17,2 mm) VMP ½" G (OD 21,3 mm)		578660	204,17
	M 22		578316	146,98	Viega Megapress S (EN) ⁴⁾	VMP ¾" (OD 17,2 mm) VMP ½" G (OD 21,3 mm)		578666 R	204,17
	M 28		578318	146,98	Viega Pexfit	VX 16		578552	204,17
	M 35		578390	178,12	Viega Pexfit	VX 20		578554	204,17
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51	Viega Pexfit	VX 25		578556	204,17
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	Viega Prestabo	V 12		578324	146,98
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	Viega Prestabo	V 15		578328	146,98
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	Viega Prestabo	V 18		578332	146,98
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	Viega Prestabo	V 22		578334	146,98
Variotherm System TH	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	Viega Prestabo	V 28		578336	146,98
	TH 11,6		578344	177,08	Viega Profipress	V 12		578324	146,98
	TH 16		578352 R	177,08	Viega Profipress	VG 14		578338	146,98
	TH 20		578358 R	177,08	Viega Profipress	V 15		578328	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	Viega Profipress	V 18		578340	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	Viega Profipress	V 22		578332	146,98
	M 15		578312	146,98	Viega Profipress	V 28		578334	146,98
	M 18		578314	146,98	Viega Profipress	V 35		578336	146,98
	M 22		578316	146,98	Viega Profipress G	V 12		578324	146,98
	M 28		578318	146,98	Viega Profipress G	VG 14		578338	146,98
VESBO CARBON	M 35		578390	178,12	Viega Profipress G	V 15		578328	146,98
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	Viega Profipress G	V 18		578340	146,98
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	Viega Profipress G	V 22		578332	146,98
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	Viega Profipress G	V 28		578334	146,98
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	Viega Profipress G	V 35		578336	146,98
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	Viega Profipress G	V 12 S (PR-2B)		578324	146,98
	M 15		578312	146,98	Viega Profipress G	VG 14 S (PR-2B)		578338	146,98
	M 18		578314	146,98	Viega Profipress G	V 15 S (PR-2B)		578328	146,98
	M 22		578316	146,98	Viega Profipress G	V 18 S (PR-2B)		578340	146,98
	M 28		578318	146,98	Viega Profipress G	V 22 S (PR-2B)		578332	146,98
VESBO INOX	M 35		578390	178,12	Viega Profipress G	V 28 S (PR-2B)		578334	146,98
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	Viega Profipress G	V 35 S (PR-2B)		578336	146,98
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	Viega Profipress G	V 12		578324	146,98
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	Viega Profipress G	VG 14		578338	146,98
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	Viega Profipress G	V 15		578328	146,98
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	Viega Profipress G	V 18		578340	146,98
	U 16		578374	165,66	Viega Profipress G	V 22		578332	146,98
	U 20		578378	165,66	Viega Profipress G	V 28		578334	146,98
	U 26 ⁷⁾		578392	194,31	Viega Profipress G	V 35		578336	146,98
	U 32		578382	194,31	Viega Profipress G	V 12 S (PR-2B)		578324	146,98
VESBO MULTIPRESS TH-U	U 16		578374	165,66	Viega Profipress G	VG 14 S (PR-2B)		578338	146,98
	U 20		578378	165,66	Viega Profipress G	V 15 S (PR-2B)		578328	146,98
	U 25		578380	165,66	Viega Profipress G	V 18 S (PR-2B)		578340	146,98
	U 32		578382	194,31	Viega Profipress G	V 22 S (PR-2B)		578332	146,98
	U 40		578386	236,66	Viega Profipress G	V 28 S (PR-2B)		578334	146,98
Viega Fonterra	VX 12		578550	204,17	Viega Profipress G	V 35 S (PR-2B)		578336	146,98
	VP 14/15		578480	176,56	Viega Profipress G	V 12		578324	146,98
	VP 16/17		578482	176,56	Viega Profipress G	VG 14		578338	146,98
	VP 20		578484	176,56	Viega Profipress G	V 15		578328	146,98
	VP 25		578486	176,56	Viega Profipress G	V 18		578340	146,98
Viega MegaPress FKM (ASTM) ⁵⁾	VMP ½" G (OD 21,3 mm) (ASTM) ⁵⁾		578666 R	204,17	Viega Profipress G	V 22		578332	146,98
	VMPz ¾" (OD 26,9 mm)		578664	204,17	Viega Profipress G	V 28		578334	146,98
	Viega MegaPress 304	VMP ½" G (OD 21,3 mm)	578666 R	204,17	Viega Profipress G	V 35		578336	146,98
	FKM (ASTM) ⁵⁾	VMPz ¾" (OD 26,9 mm)	578664	204,17	Viega Profipress G	V 12 S (PR-2B)		578324	146,98
			182,50		Viega Profipress G	VG 14 S (PR-2B)		578338	146,98

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

**) Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Viega Profipress Therm	V 12		578324	146,98
	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
Viega ProPress (ASTM) ⁵	VUS ½" (OD 15,9 mm)		578566	177,50
	VUS ¾" (OD 22,2 mm)		578568	177,50
	VUS 1" (OD 28,6 mm)		578570	177,50
	VUS 1¼" (OD 34,9 mm)		578606	177,50
	VUS ½" S (PR-2B) (OD 15,9 mm)	Mini Z8	574764 R	124,51
	VUS ¾" S (PR-2B) (OD 22,2 mm)	Mini Z8	574766 R	124,51
	VUS 1" S (PR-2B) (OD 28,6 mm)	Mini Z8	574768 R	124,51
	VUS 1¼" S (PR-2B) (OD 34,9 mm)	Mini Z8	574770 R	124,51
Viega ProPress 304 FKM (ASTM) ⁵	VUS ½" (OD 15,9 mm)		578566	177,50
	VUS ¾" (OD 22,2 mm)		578568	177,50
	VUS 1" (OD 28,6 mm)		578570	177,50
	VUS 1¼" (OD 34,9 mm)		578606	177,50
Viega ProPress 316 (ASTM) ⁵	VUS ½" (OD 15,9 mm)		578566	177,50
	VUS ¾" (OD 22,2 mm)		578568	177,50
	VUS 1" (OD 28,6 mm)		578570	177,50
	VUS 1¼" (OD 34,9 mm)		578606	177,50
Viega Propress WATER System AUS	VAU 15 (OD 12,7 mm)		578630	151,86
	VAU 20 (OD 19,1 mm)		578632	151,86
	VAU 25 (OD 25,4 mm)		578634	151,86
	VAU 32 (OD 31,8 mm)		578636	159,75
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	124,51
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	124,51
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	136,96
	VAU 32 S (PR-2B) (OD 31,8 mm)	Mini Z8	574856 R	136,96
Viega Propress GAS System AUS	VAU 15 (OD 12,7 mm)		578630	151,86
	VAU 20 (OD 19,1 mm)		578632	151,86
	VAU 25 (OD 25,4 mm)		578634	151,86
	VAU 32 (OD 31,8 mm)		578636	159,75
Viega Raxinox	VRX 16		578640	186,42
	VRX 20		578642	186,42
Viega Raxofix	VRX 16		578640	186,42
	VRX 20		578642	186,42
	VRX 25		578644	204,17
	VRX 32		578646	204,17
Viega Sanfix	VP 16/17		578482	176,56
	VP 20		578484	176,56
	VP 25		578486	176,56
	VP 32		578488	195,25
Viega Sanfix Fosta	VP 16/17		578482	176,56
	VP 20		578484	176,56
	VP 25		578486	176,56
	VP 32		578488	195,25
Viega Sanpress	V 12		578324	146,98
	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
Viega Sanpress Inox	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
Viega Sanpress Inox G	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
Viega Smartpress	VX 16		578552	204,17
	VX 20		578554	204,17
	VX 25		578556	204,17
Viega Temponox	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Viessmann	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
Vogel & Noot	TH 16		578352 R	177,08
EASYTEC	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,49
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
VSH	> Alaberts integrated piping systems			
	W			
Watts MTR	TH 16		578352 R	177,08
Art press	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
WATTS	US ¾"		578534	201,16
RADIANT	US ½"		578536	201,16
Watts WaterPEX	US ¾"		578538	201,16
	US 1"		578540	201,16
WATTS	US ¾"		578534	201,16
RADIANT	US ½"		578536	201,16
Watts	US ¾"		578538	201,16
RadiantPEX	US 1"		578540	201,16
WATTS	U 16 (½")		578374	165,66
RADIANT	U 20 (¾")		578378	165,66
Watts	U 25 (¾")		578380	165,66
RadiantPEX-AL	U 32 (1")		578382	194,31
Wavin	B 16		578468	193,28
Tigris K5/M5	B 20		578472	193,28
	B 32		578476	213,00
	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 40		578624	234,49
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
	UP 16		578578	165,66
	UP 20		578582	165,66
	UP 25		578584	165,66
	UP 32		578586	194,31
WEECON	M 15		578312	146,98
PRESS-C-Stahl	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
WEECON	M 15		578312	146,98
PRESS-Edelstahl	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
WEECON	V 15		578328	146,98
PRESS-Kupfer	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
WEM	U 16		578374	165,66
WIELAND-WERKE	TH 14		578348	177,08
cuprotherm CTX	TH 16		578352 R	177,08
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
WKS-Press	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 17		578354	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
WÜRTH	TH 16		578352 R	177,08
Würth	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	HE 32		578370 R	212,06

X

XtraConnect	F 16		578456	168,68
	F 20		578460	168,68
	F 26		578462	182,48
	F 32		578464	182,48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
(DN 26)	U 25		578380	165,66
	U 32		578382	194,31
	VP 16		578482	176,56
	VP 20		578484	176,56
	VP 32		578488	195,25

Y

YX COPPER	Yz 16 UNI	578740	184,45
UNIPEX Water & Gas (AUS)	Yz 20 UNI	578742	184,45
	Yz 25 UNI	578744	184,45
	Yz 32 UNI	578746	184,45

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

Accessories

Description	Art.-No.	€
Adapter tongs Mini Z8 for driving REMS pressing rings S (PR-2B)	574700R	144,28
Steel case with insert for adapter tongs Mini Z8 and adapter tongs Z8 as well as 6 REMS pressing rings S (PR-2B)	574516R	96,53
L-Boxx system case with inlay for Mini Z8 adapter tongs and Z8 adapter tongs as well as 14 REMS S pressing rings (PR-2B)	574704R	146,36
Steel case with insert for 8 pressing tongs Mini/cropping tongs Mini and compartment for pipe cutter up to 42 mm	578295R	96,53
L-Boxx system case with insert for 11 pressing tongs Mini and 6 pressing rings S (PR-2B)	578659R	146,36



REMS cropping tongs Mini

Accessories for REMS radial presses 22 kN

High performance cropping tongs Mini in forged and specially hardened steel for cutting threaded rods.

Steel, stainless steel up to hardness classification 4.8 (400 N/mm²) M 6 – M 10

REMS cropping tongs Mini – cuts in just 2 seconds!

Made of forged and specially hardened steel.

Reversible cropping inserts for double service life.

M cropping inserts with high precision thread contour machined on CNC machining centres for exact guiding of the threaded rod in the cutting process
Pliers parts, cropping inserts and specially machined and hardened cutting edges, made to fit exactly, for cutting without burr

Threaded rod can be screwed into a threaded connection of the pipe clip or the nut without rework after cutting

Cutting device in pliers design (Patent EP 1 459 825, patent US 7,284,330). Very compact design and low weight of the REMS Mini cropping tongs due to special arrangement of the cropping tongs connection (Patent EP 1 952 948). Recesses in the connecting plate for safe guidance of the connecting lugs for offset-free pressing (Patent EP 2 347 862).

Can be driven by all REMS radial presses 22 kN.



German Quality Product



Patent EP 1 952 948
Patent EP 1 459 825
Patent US 7,284,330
Patent EP 2 347 862

Supply format

REMS cropping tongs Mini. Cropping tongs with 1 pair of reversible cropping inserts for steel, stainless steel, M 6 – M 10. In a carton.

Description	for threaded rods	Art.-No.	€
REMS cropping tongs Mini M 6	M 6	578620	241,85
REMS cropping tongs Mini M 8	M 8	578621	241,85
REMS cropping tongs Mini M 10	M 10	578622	241,85

Accessories

Description	for threaded rods	Art.-No.	€
Cropping inserts M 6 (pair)	M 6	571891	111,07
Cropping inserts M 8 (pair)	M 8	571896	111,07
Cropping inserts M 10 (pair)	M 10	571866	111,07
Steel case with insert for 8 pressing tongs Mini/cropping tongs Mini and compartment for pipe cutter up to 42 mm	578295R		96,53



REMS Eco-Press

Universal, manual radial press for producing pipe pressing joints for common pressfitting systems.

Pressing joints with plastic
and multi-layer composite tubes

Ø 10–26 mm
Ø $\frac{3}{8}$ – 1"

Complete range of REMS pressing tongs/
pressing rings for all common pressfitting systems,
see page 198–238.

REMS Eco-Press – universal up to Ø 26 mm.

Secure crimping in seconds.

System advantage

Only one type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198–238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. For driving the REMS pressing rings S (PR-2B) adapter tongs Z8 are required, see page 238.


Design

Compact, handy, light. Drive unit with short tubular arms only 1.6 kg. Works anywhere, free-hand, overhead, in confined areas. Secure seating of pressing tongs through locking pins. Dividable tubular arms for individual adjustment of leverage to accommodate different force demands of different pressfitting systems.

Pressing operation

A perfect joint is achieved when pressing tongs close completely. Final-lock-positioning, the pressing jaws remain in a closed position until opening. This way, the perfect pressing joint (completely closed pressing jaws) can be observed.

Manual radial press



German Quality Product



Info

Supply format

REMS Eco-Press drive unit. Manual radial press with final-lock-positioning for producing pressing joints of plastic and multi-layer composite tubes Ø 10–26 mm, Ø $\frac{3}{8}$ – 1". For driving REMS pressing tongs/pressing rings. With dividable tubular arms. In skin package.

	Art.-No.	€
	574000R	227,32



Accessories

Description	Art.-No.	€
REMS pressing tongs/pressing rings , see page 198–238.		
Adapter tongs Z8 for driving REMS pressing rings S (PR-2B)	574702R	144,28
REMS cropping tongs for threaded rods see page 241.		
Carrying bag for drive unit and for 3 pressing tongs	574436R	38,41
Steel case with insert for drive unit and for 3 pressing tongs	574430R	96,53



REMS Power-Press SE

Universal, handy electric tool for producing pipe pressing joints for all common pressfitting systems.

Pipe pressing joints Ø 10–108 (110) mm
Ø $\frac{3}{8}$ –4"

Complete range of REMS pressing tongs/
pressing rings for all common pressfitting systems,
see page 198–238.

REMS Power-Press SE – universal up to Ø 110 mm.

Secure crimping in seconds.

Automatic locking of pressing tongs.

System advantage

Only one type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198–238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 238.

Design

Compact, robust, job site-proven. Small in size, slender design, drive unit only 4.7 kg. Works anywhere, free-hand, overhead, in confined areas. Secure seating of pressing tongs/adapter tongs by automatic locking. Also suitable for other suitable makes of pressing tongs/pressing chains.

Pressing operation by touch-control

For reliable service, operating and functional safety. A perfect joint is achieved when pressing tongs close completely. The pressing tongs remain in a closed position until machine is switched and runs into reverse. The perfect pressing joint (completely closed pressing jaws) can be observed.

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-mechanical drive with proven universal motor, 450 W, maintenance-free gear with safety slipping clutch and in-feed system with machine screw spindle. Overload protection. Safety tip switch.

Electric radial press 32 kN



German Quality Product



Info

Supply format

REMS Power-Press SE Basic-Pack. Electric radial press 32 kN for producing pressing joints Ø 10–108 (110) mm, Ø $\frac{3}{8}$ –4". For driving REMS pressing tongs/pressing rings and other suitable makes of pressing tongs/pressing rings. Pressing tongs seat with automatic locking. Electro-mechanical drive with proven universal motor 230 V or 110 V, 50–60 Hz, 450 W, maintenance-free gear with safety slipping clutch and in-feed system with machine screw spindle, overload protection, safety tip switch. In sturdy steel case.

Art.-No.	€
572111R220	964,30

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Power-Press SE Drive Unit	572101R220	912,40
REMS pressing tongs/pressing rings	see page 198–238.	
Adapter tongs for REMS pressing rings	see page 238.	
REMS cropping tongs for threaded rods	see page 241.	
REMS cable shear for electric cable	see page 241.	
Steel case with insert	570280R	110,03



REMS Power-Press ACC

Electro-hydraulic radial press 32 kN
with automatic retraction

Universal, handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems.

Pipe pressing joints Ø 10–108 (110) mm
Ø 3/8–4"

Complete range of REMS pressing tongs/pressing rings for all common pressfitting systems, see page 198–238.

**REMS Power-Press ACC – universal up to Ø 110 mm.
Secure crimping in seconds. With automatic circuit control. Automatic locking of pressing tongs.**

System advantage

Only one type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198–238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 238.

Design

Compact, robust, job site-proven. Small in size, slender design, drive unit only 4.7 kg. Works anywhere, free-hand, overhead, in confined areas. Ideal weight distribution for single handed operation. Ergonomically designed housing with recessed grip. Swivelling pressing tongs/adapter tongs seat. Secure seating of pressing tongs by automatic locking. Also suitable for other suitable makes of pressing tongs/pressing rings.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with proven universal motor 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.



German Quality Product



Supply format

REMS Power-Press ACC Basic-Pack. Electro-hydraulic radial press 32 kN with automatic retraction for producing pressing joints Ø 10–108 (110) mm, Ø 3/8–4". For driving REMS pressing tongs/pressing rings and other suitable makes of pressing tongs/pressing rings. Pressing tongs seat with automatic locking. Electro-hydraulic drive with proven universal motor 230 V or 110 V, 50–60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Version	Art.-No.	€
In sturdy steel case.	577010R220	1 462,54
In L-Boxx system case.	577013R220	1 504,06

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Power-Press ACC Drive Unit	577000R220	1 358,74
REMS pressing tongs/pressing rings see page 198–238.		
Adapter tongs for REMS pressing rings see page 238.		
REMS cropping tongs for threaded rods see page 241.		
REMS cable shear for electric cable see page 241.		
Steel case with insert	570280R	110,03
L-Boxx system case with inserts	571283R	146,36



REMS Power-Press XL ACC

Universal, powerful power tool with automatic circuit control for making press joints of all common press fitting systems.

Pipe pressing joints Ø 10–108 (110) mm Ø ¾–4"

Complete range of REMS pressing tongs/pressing rings/pressing rings XL for all common pressfitting systems, see page 198–238.

REMS Power-Press XL ACC – universal up to Ø 110 mm.

Pressing of Ø 10–108 mm in just one action.

Ultra-fast, e.g. Geberit Mapress stainless steel Ø 108 mm in only 15 seconds. With automatic circuit control.

Automatic locking of pressing tongs.

System advantage

Only one type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings/pressing rings XL for all common pressfitting systems (page 198–238). Highly durable pressing tongs/XL pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings/pressing rings XL are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs are required, as an accessory, for driving the REMS (PR) pressing rings.

Design

Compact, robust, job site-proven. Small in size, slender design, drive unit only 5.5 kg. Long working stroke for pressings in a single action, ideal for large dimensions. Ultra-fast, e.g. Geberit Mapress stainless steel Ø 108 mm in only 15 seconds. Ergonomically designed housing with soft grip and recessed handle. Swivelling pressing tongs/adapter tongs seat. Secure seating of pressing tongs by automatic locking. Also suitable for other suitable makes of pressing tongs/pressing rings. Adjustable hand guard.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with proven universal motor 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Supply format

REMS Power-Press XL ACC Basic-Pack. Electro-hydraulic radial press 32 kN with automatic retraction for producing pressing joints Ø 10–108 (110) mm, Ø ¾–4". For driving REMS pressing tongs/pressing rings/pressing rings XL and other suitable makes of pressing tongs/pressing rings. Pressing tongs seat with automatic locking. Electro-hydraulic drive with proven universal motor 230 V or 110 V, 50–60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Version	Art.-No.	€
In transport case XL.	579010R220	2 385,32
In XL-Boxx system case.	579012R220	2 344,84

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Power-Press XL ACC drive Unit	579000R220	2 096,76
Adapter tongs Z6 XL for driving REMS pressing rings 64.0–108.0 XL (PR-3S), 2½–4" XL (PR-3S) with REMS Power-Press XL ACC	579120R	373,68
Adapter tongs for other REMS pressing rings see page 238.		
REMS pressing tongs/pressing rings/pressing rings XL see page 198–238.		
REMS cropping tongs for threaded rods see page 241.		
REMS cable shear for electric cable see page 241.		
Transport case XL with inlays and practical carrying handles	579240R	288,56
XL-Boxx system case with inserts	579601R	248,08

Electro-hydraulic radial press XL 32 kN with automatic retraction



German Quality Product



Info





REMS Akku-Press E 22 V ACC

Universal, handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. Li-Ion 22V Technology. For battery and corded operation.

Pipe pressing joints Ø 10–108 (110) mm
Ø 3/8–4"

Complete range of REMS pressing tongs/pressing rings for all common pressfitting systems, see page 198–238.

REMS Akku-Press E 22 V ACC – universal up to Ø 110 mm. Secure crimping in seconds. With automatic circuit control. Anti-vibration system. Automatic locking of pressing tongs. Li-Ion 21.6V, 2.5Ah battery for approx. 200 pressings Viega Profipress DN 15 with one battery charge*.

System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198–238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 238.

Design

Compact, handy, super light. Drive unit with battery only 3.3 kg. Drive unit with pressing tongs V15 only 35.5 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing and soft grips. LED work light for illuminating the work place. Machine status check. Swivelling pressing tongs seat, rotation angle >360°. Secure seating of pressing tongs/adapter tongs by automatic locking. Also for other suitable makes of pressing tongs/pressing rings.

Anti-vibration system

Special drive technology with weight balancing and soft grips for low-vibration, fatigue-free pressing.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6V, 2.5Ah batteries for approx. 200 pressings, 4.4 Ah for approx. 350 pressings, 5.0 Ah for approx. 400 pressings, 9.0 Ah for approx. 720 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 70W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 15A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.


Cordless radial press 32 kN with automatic circuit control



German Quality Product



Info



The little one amongst the big. Only 3.3 kg.



Supply format

REMS Akku-Press E 22 V ACC Basic-Pack. Cordless radial press 32 kN with automatic circuit control for making press joints Ø 10–108 (110) mm, Ø ¾–4". For driving REMS pressing tongs/pressing rings and other suitable makes of pressing tongs/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6V, 380W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Anti-vibration system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 100–240V, 50–60Hz, 70W.

Version	Art.-No.	€
In sturdy steel case.	576016R220	1 806,12
In L-Boxx system case.	576017R220	1 847,64
Other voltages on request.		

Accessories

Description	Art.-No.	€
REMS pressing tongs/pressing rings see page 198–238.		
Adapter tongs for REMS pressing rings see page 238.		
REMS cropping tongs for threaded rods see page 241.		
REMS cable shear for electric cable see page 241.		
REMS Akku-Press E 22 V ACC drive unit, without battery	576006R22	1 255,98
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 15A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	414,16
Steel case with inlay	571290R	110,03
L-Boxx system case with inserts	576345R	146,36
REMS Lumen 2800 22V , cordless LED flood light, see page 111		



REMS Akku-Press 22V ACC

Universal, handy electric tool with automatic circuit control, pressure monitoring and result display, for producing pipe pressing joints for all common pressfitting systems. Li-Ion 22V Technology. For battery and corded operation.

Pipe pressing joints Ø 10 – 108 (110) mm
Ø 3/8 – 4"

Complete range of REMS pressing tongs/pressing rings for all common pressfitting systems, see page 198 – 238.

REMS Akku-Press 22V ACC – universal up to Ø 110 mm.

Secure crimping in seconds. With automatic circuit control, pressure monitoring and result display.

Anti-vibration system. Automatic locking of pressing tongs. Li-Ion 21.6 V, 2.5 Ah battery for approx.

200 pressings Viega Profipress DN 15 with one battery charge*.

System advantage

Only one type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198 – 238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 238.

Design

Compact, handy, super light. Drive unit with battery only 3.3 kg. Drive unit with pressing tongs V15 only 35.5 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing and soft grips. LED work light for illuminating the work place. Machine status check. Swivelling pressing tongs seat, rotation angle > 360°. Secure seating of pressing tongs/adapter tongs by automatic locking. Also for other suitable makes of pressing tongs/pressing rings.

Pressure monitoring and result display

Electronic pressure sensor for thrust force monitoring. Pressure evaluation after the pressing process. Result display with 2-coloured white/red LED.

Anti-vibration system

Special drive technology with weight balancing and soft grips for low-vibration, fatigue-free pressing.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah batteries for approx. 200 pressings, 4.4 Ah for approx. 350 pressings, 5.0 Ah for approx. 400 pressings, 9.0 Ah for approx. 720 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.


Cordless radial press 32 kN with automatic circuit control, pressure monitoring and result display



German Quality Product



Info



The little one amongst the big. Only 3.3 kg.

REMS Akku-Press 22V ACC

Cordless radial press 32 kN with automatic circuit control, pressure monitoring and result display



Supply format

REMS Akku-Press 22V ACC Basic-Pack. Cordless radial press 32 kN with automatic circuit control, pressure monitoring and result display, for making press joints Ø 10–108 (110) mm, Ø 3/8–4". For driving REMS pressing tongs/pressing rings and other suitable makes of pressing tongs/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Anti-vibration system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 100–240V, 50–60Hz, 90W.

Version	Art.-No.	€
In sturdy steel case.	576010R220	2 117,52
In L-Boxx system case.	576011R220	2 159,04

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS pressing tongs/pressing rings see page 198–238.		
Adapter tongs for REMS pressing rings see page 238.		
REMS cropping tongs for threaded rods see page 241.		
REMS cable shear for electric cable see page 241.		
REMS Akku-Press 22V ACC drive unit, without battery	576000R22	1 546,62
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 15A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	414,16
Steel case with inlay	571290R	110,03
L-Boxx system case with inserts	576345R	146,36
REMS Lumen 2800 22V, cordless LED flood light, see page 111		



REMS Akku-Press 22 V Connected

Cordless radial press 32 kN with Connected functionality via Wi-Fi radio standard and OLED display

Universal, handy electric tool with Connected functionality via Wi-Fi radio standard and OLED display for producing pipe pressing joints for all common pressfitting systems. Li-Ion 22 V Technology. For battery and corded operation.

Pipe pressing joints Ø 10 – 108 (110) mm
Ø 3/8 – 4"

Complete range of REMS pressing tongs/pressing rings for all common pressfitting systems, see page 198 – 238.

REMS Akku-Press 22 V Connected – universal up to Ø 110 mm. Secure crimping in seconds. With selectable ACC drive mode. Connected functionality via Wi-Fi radio standard and OLED display. Pressure monitoring and result display. Anti-vibration system. Automatic locking of pressing tongs. Electrically monitored closing position of the tong retaining bolt. Voice recordings with voice recognition. Creating reports with texts and pictures. Geolocalisation of the pressing sites.

Li-Ion 21.6 V, 2.5 Ah battery for approx. 200 pressings

Viega Profipress DN 15 with one battery charge*.

System advantage

Only one type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198 – 238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 238.

Design

Compact, handy, super light. Drive unit with battery only 3.3 kg. Drive unit with pressing tongs V15 only 36.3 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing with strong carrying ring for a shoulder strap. Soft-grip surfaces. Two rows of LED work lights for illuminating the workplace as required, adjustable brightness in 4 stages and lighting time. Machine status check with charging state indication by 2-coloured green/red LED. Swivelling pressing tongs seat, rotation angle > 360 °. Secure seating of pressing tongs/adapter tongs by automatic locking. Electrically monitored closing position of the tong retaining bolt. Also for other suitable makes of pressing tongs/pressing rings.

Connected functionality

REMS Akku-Press 22 V Connected offers various additional functionalities such as, for example: Recording of measuring/pressing data, creation of reports with your own company logo, display of error messages, configuration of the product (language, date, time, time zone, pressure unit, LED lighting time and LED brightness, standby time, ACC drive mode, information signal tones, etc.), set-up of usage bars (immediate bar or feedback interval as anti-theft, time and date ranges for barring times, limitation of the number of performable pressings), geolocalisation of the pressing sites, conversion of voice recordings into editable text, upload and save images of pressings, display of notices (annual inspection and periodic testing, new firmware version, battery state, etc.), download and installation of new firmware version.

Pressure monitoring and result display

Electronic pressure sensor for thrust force monitoring. Monitoring and display of pressure and maximum pressure during the pressing process. Pressure analysis after the pressing process with result display in the OLED display and with coloured LEDs. Display of the pressure-time diagram of the performed pressing directly in the OLED display. Storage of the measured/pressing data.

Voice recordings with voice recognition

A voice recording can be made and stored for every pressing with the microphone integrated into the drive unit. These can be converted into editable text and transferred to reports in the Service Portal.



German Quality Product



REMS Akku-Press 22V Connected

Cordless radial press 32 kN with Connected functionality via Wi-Fi radio standard and OLED display

Wi-Fi connection to the Cloud

REMS Akku-Press 22V Connected sends collected data (measuring and pressing data, error messages, configuration of the product, voice recordings, etc.) to the Cloud after registration and with an existing Internet connection. The data are processed and stored there. The user can access these data, upload and store pictures of pressings, create reports with texts and pictures and change the drive unit settings through the REMS Service Portal. The changes are transferred back to the drive unit via an existing Internet connection.

Selectable ACC drive mode

When ACC drive mode is switched on, the drive unit ends the pressing process automatically, emits an acoustic signal (clicking) and automatically returns (automatic circuit control). When ACC mode is switched off, the drive unit stops just before reaching the required pressure to be able to monitor complete closing of the pressing tongs, pressing ring and pressing segments better at the end of the pressing process. The pressing process must be continued by pressing the safety switch again. The drive unit ends the pressing process automatically, emits an acoustic signal (clicking) and automatically returns (automatic circuit control).

Drive


Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. High-performance, electro-hydraulic drive with powerful, brushless, maintenance free 21.6 V, 400 W battery motor, robust planetary gear, eccentric piston pump and compact high-performance hydraulic system. Safety switch.

Anti-vibration system

Special drive technology with weight balancing and soft grips for low-vibration, fatigue-free pressing.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah batteries for approx. 210 pressings, 4.4 Ah for approx. 370 pressings, 5.0 Ah for approx. 420 pressings, 9.0 Ah for approx. 750 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.



The little one amongst the big. Only 3.3 kg.



Electrically monitored closing position of the tong retaining bolt.



Supply format

REMS Akku-Press 22V Connected Basic-Pack. Cordless radial press 32 kN with selectable ACC drive mode, Connected functionality via Wi-Fi radio standard and OLED display, pressure monitoring and result display, for making press joints Ø 10–108 (110) mm, Ø 3/8–4". For driving REMS pressing tongs/pressing rings and other suitable makes of pressing tongs/pressing rings. Swivelling pressing tongs seat with automatic locking. Electrically monitored closing position of the tong retaining bolt. Electro-hydraulic drive with powerful, brushless, maintenance free 21.6 V, 400 W battery motor, robust planetary gear, eccentric piston pump and compact high-performance hydraulic system. Anti-vibration system. Safety tip switch. LED work lights. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 100–240V, 50–60Hz, 90W.

Version	Art.-No.	€
In sturdy steel case.	576014R220	3 155,52
In L-Boxx system case.	576015R220	3 197,04

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS pressing tongs/pressing rings see page 198–238.		
Adapter tongs for REMS pressing rings see page 238.		
REMS cropping tongs for threaded rods see page 241.		
REMS cable shear for electric cable see page 241.		
REMS Akku-Press 22V Connected		
drive unit, without battery	576003R22	2 584,62
Battery Li-Ion 21.6V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	414,16
Steel case with inlay	571290R	110,03
L-Boxx system case with inserts	576345R	146,36
REMS Lumen 2800 22V , cordless LED flood light, see page 111		



REMS Akku-Press XL 45 kN 22 V ACC

Universal, powerful electric tool with automatic circuit control for producing XL pipe pressing joints for all common pressfitting systems. Thrust force 45 kN. Li-Ion 22V Technology. For battery and corded operation.

Pipe pressing joints XL Ø 64–108 mm
Ø 2½–4"

Complete range of REMS pressing rings XL for all common pressfitting systems, see page 198–238.

REMS Akku-Press XL 45 kN 22 V ACC – the powerful one with 45 kN thrust force. Pressing of Ø 64–108 mm in a single action. Anti-vibration system. Super fast, e.g. Geberit Mapress stainless steel Ø 108 mm in just 15 s. With automatic circuit control. Secure seating of adapter tongs by automatic locking.

**Li-Ion 21.6 V, 5.0 Ah battery, for approx. 150 pressings
Geberit Mapress stainless steel Ø 108.0 mm with one battery charge*.**

Pressing rings XL for all common systems

Full range of REMS pressing rings XL for driving by REMS Akku-Press XL 45 kN 22 V ACC (page 198–238). Highly durable pressing rings XL made of tenacious, specially hardened special steel. Pressing contours of REMS pressing rings XL are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing.

Adapter tongs Z7 XL 45 kN

For driving REMS pressing rings XL by REMS Akku-Press XL 45 kN 22 V ACC adapter tongs Z7 XL 45 kN are required.

Design

Compact, robust, job site-proven. Small in size, slender design, drive unit with battery only 6.5 kg. Long working stroke for pressings in a single action. Super fast, e.g. Geberit Mapress stainless steel Ø 108 mm in just 15 s. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing and soft grips. LED work light for illuminating the work place. Machine status check. Swivelling pressing ring seat, rotation angle > 360°. Secure seating of adapter tongs by automatic locking.

Anti-vibration system

Special drive technology with weight balancing and soft grips for low-vibration, fatigue-free pressing.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 45 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric dual-piston pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 4.4 Ah batteries for approx. 130 pressings, 5.0 Ah batteries for approx. 150 pressings, 9.0 Ah for approx. 270 pressings Geberit Mapress stainless steel Ø 108.0 mm with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. Rapid charger 100–240 V, 90 W. Rapid charger 100–240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220–240 V/21.6 V, 40 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Cordless radial press XL 45 kN with automatic circuit control



German Quality Product



Info



Supply format

REMS Akku-Press XL 45 kN 22V ACC Basic-Pack Z7. Cordless radial press 45 kN with automatic circuit control for making press joints XL Ø 64–108 mm, Ø 2½–4". For driving REMS pressing rings XL. Swivelling pressing ring seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric dual-piston pump and compact high power hydraulic system. Anti-vibration system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 5.0 Ah, rapid charger 100–240 V, 50–60 Hz, 90 W. Adapter tongs Z7 XL 45 kN. In XL-Boxx system case.

	Art.-No.	€
	579014R220	3 193,93

Other voltages on request.

**Accessories**

Description	Art.-No.	€
REMS Akku-Press XL 45 kN 22V ACC drive unit, without battery	579001R22	2 065,62
Adapter tongs Z7 XL 45 kN for driving REMS pressing rings 64.0–108.0 XL (PR-3S), 2½–4" XL (PR-3S), 2½–4" XL (PR-3B) with REMS Akku-Press XL 45 kN 22V ACC	579123R	394,44

REMS pressing rings XL see page 198–238

Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240 V, 50–60 Hz, 90 W	571585R220	175,42
Rapid charger 100–240 V, 50–60 Hz, 290 W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 40 A, for mains operation instead of battery Li-Ion 21.6 V	571578R220	517,96
XL-Boxx system case with inserts	579601R	248,08

REMS Lumen 2800 22V, cordless LED flood light, see page 111



REMS pressing tongs

REMS pressing rings

for all common pressfitting systems

Select REMS pressing tongs/ REMS pressing rings yourself!

Find the desired press fitting system in the table below and choose the size of pressing tongs/pressing rings that you require. Please note that pressfitting systems for gas installation may only be pressed with the pressing tongs/pressing rings which are highlighted in yellow in the table.

Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond with the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Pressing jaws of pressing tongs/pressing rings manufactured on CNC production centres ensure high-precision machining of pressing contour. Low production tolerances as a result.

Driven by REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force or, if the system requires, by REMS Akku-Press XL 45 kN 22V ACC with 45 kN thrust force, see the table below. Adapter tongs (page 238) required for driving REMS (PR) pressing rings. All pressing tongs marked with * have an optional connection for manual drive through the radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press (page 185) using the adapter tong Z8.

Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

REMS pressing tongs (PZ-2B)

REMS pressing tongs (PZ-2B) with 2 swivelable monoblock pressing jaws. Most sold standard version. REMS ACz, Fz, RFz, RFlz, VMPz pressing tongs with teeth prevent formation of burr on the pressfitting (**Patent EP 2 027 971**).

REMS pressing tongs (PZ-4G)

REMS pressing tongs (PZ-4G) with two pivoted, parallel aligned pressing segments for linear pressing of midsize dimensions.

REMS pressing tongs (PZ-S)

REMS pressing tongs (S) with one fixed and two pivoted pressing segments, for midsize dimensions. REMS VMPz pressing tongs with teeth prevent formation of burr on the pressfitting.

REMS pressing rings (PR-3S)

REMS pressing ring (PR-3S) with 3 pressing segments, 2 swivel guided, for large dimension complex pressings. Ideal pressing through radially controlled movement of pressing segments. Adapter tongs required, see page 238.

REMS pressing rings (PR-3B)

REMS pressing rings (PR-3B) with 3 pressing segments for high quality, large dimension pressings. Optimum pressing by radially controlled movement of the pressing segments. Adapter tongs required, see page 238. REMS VAUFz, VFz, VMPz, VUSFz pressing rings with teeth prevent formation of burr on the pressfitting.

REMS pressing ring (PR-2B)

REMS pressing ring (PR-2B) with 2 pressing jaws, for secure engagement of the pressing jaws in tight spaces, for midsize dimensions. Adapter tongs required for driving the REMS (PR-2B) pressing rings, see page 238.

REMS pressing ring S (PR-2B)

REMS pressing ring S (PR-2B), continuously swivelable, with 2 pressing jaws, for secure engagement of the pressing jaws in places of difficult access. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 238.

Traceability according to EN 1775:2007

REMS pressing tongs/pressing rings with pressing contour F, M, V, SA, B, RN and UP have worked a specific marking into the pressing contour which leaves a lasting impression on the pressed fitting after the pressing process. This enables the user to check again whether the most suitable pressing tongs or the suitable pressing ring have been used to make the pressfit connection even after the pressing process.

With this traceability REMS fulfils the recommendations of the European standard EN 1775:2007 for the installation of pressfitting systems for gas.

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

Two connections
for REMS Eco-Press
manual radial press
and REMS 32 kN radial
presses.



German Quality Product



REMS pressing tongs (PZ-2B)



REMS pressing tongs (PZ-4G)



REMS pressing tongs (PZ-S)



REMS pressing rings (PR-3S)



REMS pressing rings (PR-3B)



REMS pressing rings (PR-2B)



REMS pressing ring S (PR-2B),
continuously swivelable

Confirmation of suitability

See page 239.

Hold-Harmless and Indemnification Agreement


See page 240.



REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes



Pressing tongs with teeth prevent formation of burr on the pressfitting.
Patent EP 2 027 971

Example REMS pressing tongs M:
"M" imprint on pressed fitting for
traceability according to EN 1775:2007

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
A				
Aalberts integrated piping systems	U 14*		570760	174,33
VSH MultiPress	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
Aalberts integrated piping systems	U 16 ²⁾		570765	174,33
VSH MultiPress Gas ³⁾	U 20 ²⁾		570775	174,33
	U 25 ²⁾		570780	174,33
	TH 16 ²⁾		570460	186,32
	TH 20 ²⁾		570470	186,32
	TH 16 S (PR-2B) ²⁾	Z8	574782 R	124,51
	TH 20 S (PR-2B) ²⁾	Z8	574788 R	124,51
Aalberts integrated piping systems	V 12		570107	154,61
VSH SudoPress Carbon	V 15		570115	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	XP 66,7 XL (PR-3S)		579108 R	1 161,47
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾			
	M 76,1 XL (PR-3S)		579101 R	1 161,47
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾			
	M 88,9 G XL (PR-3S)		579110 R	1 355,58
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾			
	M 108,0 G XL (PR-3S)		579111 R	1 355,58
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾			
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
Aalberts integrated piping systems	V 12		570107	154,61
VSH SudoPress Copper	V 14		570112	154,61
	VG 14		570132	154,61
	V 15		570115	154,61
	V 16		570117	154,61
	VG 16		570137	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 14 S (PR-2B)	Z8	574800 R	124,51
	VG 14 S (PR-2B)	Z8	574750 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	VG 16 S (PR-2B)	Z8	574754 R	124,51
	V 16 S (PR-2B)	Z8	574802 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
Aalberts integrated piping systems	V 12		570107	154,61
VSH SudoPress Copper	V 14		570112	154,61
	VG 14		570132	154,61
Gas	V 15		570115	154,61
	V 16		570117	154,61
	VG 16		570137	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 14 S (PR-2B)	Z8	574800 R	124,51
	VG 14 S (PR-2B)	Z8	574750 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	VG 16 S (PR-2B)	Z8	574754 R	124,51
	V 16 S (PR-2B)	Z8	574802 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
A				
Aalberts integrated piping systems	V 15		570115	154,61
VSH SuoPress	V 18		570125	154,61
Stainless	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	M 76,1 XL (PR-3S)		579101 R	1 161,47
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾			
	M 88,9 G XL (PR-3S)		579110 R	1 355,58
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾			
	M 108,0 G XL (PR-3S)		579111 R	1 355,58
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾			
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
Aalberts integrated piping systems	M 12		570100	154,61
VSH XPress Carbon	M 15		570110	154,61
	M 18 ¹⁾		570120	154,61
	M 22		570130	154,61
	M 28 ¹⁾		570140	154,61
	M 35		570150	154,61
	M 42 (PZ-4G)	Z2	572706 R	498,19
	M 54 (PZ-4G)	Z2	572708 R	498,19
	M 42 (PR-3S)	Z2	572708 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	XP 66,7 XL (PR-3S)		579108 R	1 161,47
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾			
	M 76,1 XL (PR-3S)		579110 R	1 161,47
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾			
	M 88,9 G XL (PR-3S)		579111 R	1 355,58
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾			
	M 108,0 G XL (PR-3S)		579111 R	1 355,58
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾			
	V 18 S (PR-2B)	Z8	574736 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
Aalberts integrated piping systems	M 12		570100	154,61
VSH XPress Copper	M 15		570110	154,61
	M 18 ¹⁾		570120	154,61
	M 22		570130	154,61
	M 28 ¹⁾		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
Aalberts integrated piping systems	M 15		570110	154,61
VSH XPress Copper	M 18 ¹⁾		570120	154,61
	M 22		570130	154,61
	M 28 ¹⁾		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
Aalberts integrated piping systems	M 15		570110	154,61
VSH XPress Stainless	M 18 ¹⁾		570120	154,61
	M 22		570130	154,61
	M 28 ¹⁾		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
AC-FIX PRESS (Global Piping Systems)	H 12*		570300	168,10	AHLSSELL	V 12		570107	154,61
	H 16*		570320	168,10	A-press elförzinkad V	V 15		570115	154,61
	H 20*		570350	168,10		V 18		570125	154,61
	H 25*		570360	168,10		V 22		570135	154,61
	H 32		570380	168,10		V 28		570145	154,61
	RFz 12*		571320	194,05		V 35		570155	154,61
	RFz 16*		571325	194,05		V 42		570165	360,13
	RFz 20*		571330	194,05		V 54		570175	370,51
	RFz 25		571335	194,05		V 12 S (PR-2B)	Z8	574748 R	124,51
	RFz 32		571340	194,05		V 15 S (PR-2B)	Z8	574752 R	124,51
	U 16*		570765	174,33		V 18 S (PR-2B)	Z8	574756 R	124,51
	U 20*		570775	174,33		V 22 S (PR-2B)	Z8	574758 R	124,51
	U 25*		570780	174,33		V 28 S (PR-2B)	Z8	574760 R	124,51
	U 32		570785	204,43		V 35 S (PR-2B)	Z8	574762 R	136,96
	VX 16*		571635	214,81	AHLSSELL	M 12		570100	154,61
	VX 20*		571640	214,81	A-press koppar M	M 15		570110	154,61
AC-FIX PRESS DUO (Global Piping Systems)	RFz 16*		571325	194,05		M 18		570120	154,61
	RFz 20*		571330	194,05		M 22		570130	154,61
	RFz 25		571335	194,05		M 28		570140	154,61
	RFz 32		571340	194,05		M 35		570150	154,61
	TH 16*		570460	186,32		M 42 (PR-3S)	Z2	572706 R	672,57
	TH 20*		570470	186,32		M 54 (PR-3S)	Z2	572708 R	672,57
	TH 25*		570495	186,32		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	TH 26*		570475	186,32		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	TH 32		570480	186,32		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		M 15 S (PR-2B)	Z8	574738 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		M 22 S (PR-2B)	Z8	574742 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51		M 28 S (PR-2B)	Z8	574744 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		M 35 S (PR-2B)	Z8	574746 R	136,96
	TH 32 S (PR-2B)	Z8	574798 R	136,96	AHLSSELL	V 12		570107	154,61
	U 16*		570765	174,33	A-press koppar V	V 15		570115	154,61
	U 20*		570775	174,33		V 18		570125	154,61
	U 25*		570780	174,33		V 22		570135	154,61
	U 32		570785	204,43		V 28		570145	154,61
	V 42					V 35		570155	154,61
AC-FIX PRESS-MULTI (Global Piping Systems)	H 16*		570320	168,10		V 42		570165	360,13
	H 18*		570340	168,10		V 54		570175	370,51
	H 20*		570350	168,10		V 12 S (PR-2B)	Z8	574748 R	124,51
	H 25*		570360	168,10		V 15 S (PR-2B)	Z8	574752 R	124,51
	H 32		570380	168,10		V 18 S (PR-2B)	Z8	574756 R	124,51
	RFz 16*		571325	194,05		V 22 S (PR-2B)	Z8	574758 R	124,51
	RFz 20*		571330	194,05		V 28 S (PR-2B)	Z8	574760 R	124,51
	RFz 25		571335	194,05		V 35 S (PR-2B)	Z8	574762 R	136,96
	RFz 32		571340	194,05	AHLSSELL	M 15		570110	154,61
	U 16*		570765	174,33	A-press rostfrärt	M 18		570120	154,61
	U 18*		570770	174,33		M 22		570130	154,61
	U 20*		570775	174,33		M 28		570140	154,61
	U 25*		570780	174,33		M 35		570150	154,61
	U 32		570785	204,43		M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57		M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 12 S (PR-2B)	Z8	574736 R	124,51		M 15 S (PR-2B)	Z8	574738 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51		M 18 S (PR-2B)	Z8	574740 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51		M 22 S (PR-2B)	Z8	574742 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51		M 28 S (PR-2B)	Z8	574744 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51		M 35 S (PR-2B)	Z8	574746 R	136,96
ACOME MT	ACz 12*		572642	194,05	AIRBEL	M 15		570110	154,61
	ACz 16*		572644	194,05	PRESSCLIM	M 18		570120	154,61
	ACz 20*		572646	194,05		M 22		570130	154,61
	ACz 25		572648	194,05		M 28		570140	154,61
AHLSSELL	M 12		570100	154,61		M 35		570150	154,61
A-press elförzinkad M	M 15		570110	154,61		M 42 (PR-3S)	Z2	572706 R	672,57
	M 18		570120	154,61		M 54 (PR-3S)	Z2	572708 R	672,57
	M 22		570130	154,61		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 28		570140	154,61		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 35		570150	154,61		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 42 (PR-3S)	Z2	572706 R	672,57		M 15 S (PR-2B)	Z8	574738 R	124,51
	M 54 (PR-3S)	Z2	572708 R	672,57		M 18 S (PR-2B)	Z8	574740 R	124,51
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		M 22 S (PR-2B)	Z8	574742 R	124,51
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		M 28 S (PR-2B)	Z8	574744 R	124,51
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		M 35 S (PR-2B)	Z8	574746 R	136,96
	M 12 S (PR-2B)	Z8	574736 R	124,51					
	M 15 S (PR-2B)	Z8	574738 R	124,51					
	M 18 S (PR-2B)	Z8	574740 R	124,51					
	M 22 S (PR-2B)	Z8	574742 R	124,51					
	M 28 S (PR-2B)	Z8	574744 R	124,51					
	M 35 S (PR-2B)	Z8	574746 R	136,96					

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
AIRBEL	M 15		570110	154,61	APE Serie APL	H 16*		570320	168,10
SERTINOX	M 18		570120	154,61		H 18*		570340	168,10
	M 22		570130	154,61		H 20*		570350	168,10
	M 28		570140	154,61		H 25*		570360	168,10
	M 35		570150	154,61		H 26*		570370	168,10
	M 42 (PR-3S)	Z8	572706 R	672,57		H 32		570380	168,10
	M 54 (PR-3S)	Z8	572708 R	672,57		TH 16*		570460	186,32
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		TH 18*		570465	186,32
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		TH 20*		570470	186,32
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		TH 25*		570495	186,32
	M 15 S (PR-2B)	Z8	574738 R	124,51		TH 26*		570475	186,32
	M 18 S (PR-2B)	Z8	574740 R	124,51		TH 32		570480	186,32
	M 22 S (PR-2B)	Z8	574742 R	124,51		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51		TH 18 S (PR-2B)**	Z8	574786 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96		TH 20 S (PR-2B)**	Z8	574788 R	124,51
ALB	TH 16*		570460	186,32		TH 25 S (PR-2B)**	Z8	574792 R	124,51
Sistema Multicapa para calefacción y sanitario	TH 18*		570465	186,32		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 20*		570470	186,32		TH 32 S (PR-2B)	Z8	574798 R	136,96
	TH 26*		570475	186,32		U 16*		570765	174,33
	TH 32		570480	186,32		U 18*		570770	174,33
	TH 40		570485	246,99		U 20*		570775	174,33
	TH 50 (PZ-S)		572400	645,58		U 26*			
	TH 63 (PZ-S)		572405	645,58		TH 16*		570320	168,10
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		H 16*		570350	168,10
	TH 18 S (PR-2B)**	Z8	574786 R	124,51		H 20*		570370	168,10
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		H 26*		570380	168,10
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		TH 32		570460	186,32
	TH 32 S (PR-2B)	Z8	574798 R	136,96		TH 40		570470	186,32
	H 16*		570320	168,10		TH 50 (PZ-S)		570475	186,32
	H 18*		570340	168,10		TH 63 (PZ-S)		572400	645,58
	H 20*		570350	168,10		TH 16 S (PR-2B)**	Z8	572405	645,58
	H 26*		570370	168,10		TH 20 S (PR-2B)**	Z8	574782 R	124,51
	H 32		570380	168,10		TH 26 S (PR-2B)**	Z8	574786 R	124,51
	H 40 (PZ-4G)		570390	565,67		TH 32 S (PR-2B)	Z8	574794 R	124,51
	U 16*		570765	174,33		U 16*		570765	174,33
	U 18*		570770	174,33		U 20*		570775	174,33
	U 20*		570775	174,33		U 26* ⁽¹²⁾		570750	204,43
	U 26* ⁽¹²⁾		570750	204,43		U 32		570785	204,43
	U 32		570785	204,43					
	U 40		570790	249,07					
ALB	TH 16*		570460	186,32	AQUATECHNIK	B 16*		570850	203,40
Sistema Multicapa para Gas	TH 20*		570470	186,32	Universal	B 20*		570860	203,40
	TH 26*		570475	186,32		B 26		570870	224,16
	TH 32		570480	186,32		B 32		570880	224,16
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		F 16*		570717	177,45
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		F 20*		570727	177,45
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		F 26*		570730	191,98
	TH 32 S (PR-2B)	Z8	574798 R	136,96		F 32		570735	191,98
	H 16*		570320	168,10		F 16 S (PR-2B)**	Z8	574728 R	124,51
	H 20*		570350	168,10		F 20 S (PR-2B)**	Z8	574730 R	124,51
	H 26*		570370	168,10		F 26 S (PR-2B)**	Z8	574732 R	124,51
	H 32		570380	168,10		F 32 S (PR-2B)	Z8	574734 R	136,96
	U 16*		570765	174,33		H 16*		570320	168,10
	U 20*		570775	174,33		H 26*		570370	168,10
	U 26* ⁽¹²⁾		570750	204,43		H 32		570380	168,10
	U 32		570785	204,43		TH 16*		570460	186,32
ALTECH Altech	RFz 12*		571320	194,05		TH 20*		570470	186,32
	RFz 16*		571325	194,05		TH 26*		570480	186,32
	RFz 20*		571330	194,05		TH 32		570480	186,32
	RFz 25		571335	194,05		TH 16 S (PR-2B)**	Z8	574782 R	124,51
APE MULTYGAS Serie AP Gas	TH 16*		570460	186,32		TH 20 S (PR-2B)**	Z8	574786 R	124,51
	TH 20*		570470	186,32		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 26*		570475	186,32		TH 32 S (PR-2B)	Z8	574798 R	136,96
	TH 32		570480	186,32		U 16*		570765	174,33
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		U 20*		570775	174,33
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		U 26* ⁽¹²⁾		570750	204,43
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		U 32		570785	204,43
	TH 32 S (PR-2B)	Z8	574798 R	136,96					
APE Serie AP	B 16*		570850	203,40	ARKA	H 16*		570320	168,10
	B 20*		570860	203,40	DUROsystem	H 20*		570350	168,10
	B 26		570870	224,16		H 25*		570360	168,10
	B 32		570880	224,16		H 26*		570370	168,10
	H 16*		570320	168,10		H 32		570380	168,10
	H 20*		570350	168,10		TH 16*		570460	186,32
	H 26*		570370	168,10		TH 20*		570470	186,32
	H 32		570380	168,10		TH 26*		570475	186,32
	TH 16*		570460	186,32		TH 32		570480	186,32
	TH 18*		570465	186,32		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20*		570470	186,32		TH 20 S (PR-2B)**	Z8	574786 R	124,51
	TH 26*		570475	186,32		TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32		570480	186,32		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		TH 32 S (PR-2B)	Z8	574798 R	136,96
	TH 18 S (PR-2B)**	Z8	574786 R	124,51		U 16*		570765	174,33
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		U 20*		570775	174,33
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		U 26* ⁽¹²⁾		570750	204,43
	TH 32 S (PR-2B)	Z8	574798 R	136,96		U 32		570785	204,43
	U 16*		570765	174,33					
	U 20*		570775	174,33					
Aschl NIR	M 15		570110	154,61					
	M 18		570120	154,61					
	M 22		570130	154,61					
	M 28		570140	154,61					
	M 35		570150	154,61					
	M 42 (PR-3S)	Z2	572706 R	672,57					
	M 54 (PR-3S)	Z2	572708 R	672,57					
	M 76,1 XL (PR-3S)		579101 R	1 161,47					
	M 88,9 G XL (PR-3S)		579110 R	1 355,58					
	M 108,0 G XL (PR-3S)		579111 R	1 355,58					
	M 15 S (PR-2B)	Z8	574738 R	124,51					
	M 18 S (PR-2B)	Z8	574740 R	124,51					
	M 22 S (PR-2B)	Z8	574742 R	124,51					
	M 28 S (PR-2B)	Z8	574744 R	124,51					
	M 35 S (PR-2B)	Z8	574746 R	136,96					

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
ASSOTHERM	M 15		570110	154,61	ASSOTHERM	M 15		570110	154,61
IPC-RAC	M 18		570120	154,61	IPR-RRA	M 18		570120	154,61
Carbon Steel	M 22		570130	154,61	Copper	M 22		570130	154,61
	M 28		570140	154,61		M 28		570140	154,61
	M 35		570150	154,61		M 35		570150	154,61
	M 42 (PZ-4G)		570160	498,19		M 42 (PZ-4G)		570160	498,19
	M 54 (PZ-4G)		570170	498,19		M 54 (PZ-4G)		570170	498,19
	M 42 (PR-3S)	Z2	572706 R	672,57		M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57		M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51		M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51		M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51		M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51		M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96		M 35 S (PR-2B)	Z8	574746 R	136,96
ASSOTHERM	M 15		570110	154,61	ASSOTHERM	M 15		570110	154,61
IPI-RAX	M 18		570120	154,61	IPI-RAX	M 18		570120	154,61
Inox	M 22		570130	154,61	Copper Gas	M 22		570130	154,61
	M 28		570140	154,61		M 28		570140	154,61
	M 35		570150	154,61		M 35		570150	154,61
	M 42 (PZ-4G)		570160	498,19		M 15 S (PR-2B)	Z8	574738 R	124,51
	M 54 (PZ-4G)		570170	498,19		M 18 S (PR-2B)	Z8	574740 R	124,51
	M 42 (PR-3S)	Z2	572706 R	672,57		M 22 S (PR-2B)	Z8	574742 R	124,51
	M 54 (PR-3S)	Z2	572708 R	672,57		M 28 S (PR-2B)	Z8	574744 R	124,51
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		M 35 S (PR-2B)	Z8	574746 R	136,96
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58	ASTM F 1807	US 9/16"		571450	211,70
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58	(Fittings with US 1/2"	571455	211,70		
	M 15 S (PR-2B)	Z8	574738 R	124,51	Copper Crimp	US 9/16"	571460	211,70	
	M 18 S (PR-2B)	Z8	574740 R	124,51	Ring for PEX	US 1"	571465	211,70	
	M 22 S (PR-2B)	Z8	574742 R	124,51	tubing)	US 1 1/4"	571470	211,70	
	M 28 S (PR-2B)	Z8	574744 R	124,51		US 1 1/2"	571475	211,70	
	M 35 S (PR-2B)	Z8	574746 R	136,96		US 2"	571477	285,40	
ASSOTHERM	M 15		570110	154,61	ATUSA ITALIA	M 15		570110	154,61
IPI-RAX	M 18		570120	154,61	INSTALPRESS	M 18		570120	154,61
Inox Gas	M 22		570130	154,61	CARBON STEEL	M 22		570130	154,61
	M 28		570140	154,61	PRESS FITTINGS	M 28		570140	154,61
	M 35		570150	154,61		M 35		570150	154,61
	M 42 (PZ-4G)		570160	498,19		M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PZ-4G)		570170	498,19		M 54 (PR-3S)	Z2	572708 R	672,57
	M 42 (PR-3S)	Z2	572706 R	672,57		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 54 (PR-3S)	Z2	572708 R	672,57		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 76,1 XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 88,9 G XL (PR-3S) ⁷⁾	Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		M 15 S (PR-2B)	Z8	574738 R	124,51
	M 108,0 G XL (PR-3S) ⁷⁾	Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		M 18 S (PR-2B)	Z8	574740 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51		M 22 S (PR-2B)	Z8	574742 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51		M 28 S (PR-2B)	Z8	574744 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51		M 35 S (PR-2B)	Z8	574746 R	136,96
	M 28 S (PR-2B)	Z8	574744 R	124,51	ATUSA ITALIA	M 15		570110	154,61
	M 35 S (PR-2B)	Z8	574746 R	136,96	INSTALPRESS	M 18		570120	154,61
ASSOTHERM	H 16*		570320	168,10	STAINLESS STEEL	M 22		570130	154,61
IPM-Multistrato	H 20*		570350	168,10	PRESS FITTINGS	M 28		570140	154,61
	H 26*		570370	168,10		M 35		570150	154,61
	H 32		570380	168,10		M 42 (PR-3S)	Z2	572706 R	672,57
	TH 16*		570460	186,32		M 54 (PR-3S)	Z2	572708 R	672,57
	TH 20*		570470	186,32		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	TH 26*		570475	186,32		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	TH 32		570480	186,32		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	THL 32		570487	186,32		M 15 S (PR-2B)	Z8	574738 R	124,51
	TH 40		570485	246,99		M 18 S (PR-2B)	Z8	574740 R	124,51
	TH 50 (PZ-S)		572400	645,58		M 22 S (PR-2B)	Z8	574742 R	124,51
	TH 63 (PZ-S)		572405	645,58		M 28 S (PR-2B)	Z8	574744 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		M 35 S (PR-2B)	Z8	574746 R	136,96
	TH 20 S (PR-2B)**	Z8	574788 R	124,51	AUSTEC	TH 16*		570460	186,32
	TH 26 S (PR-2B)**	Z8	574794 R	124,51	PEX-B, PEX-AL-PEX	TH 20*		570470	186,32
	TH 32 S (PR-2B)	Z8	574798 R	136,96	(AUS)	TH 25*		570495	186,32
	U 16*		570765	174,33		TH 32		570480	186,32
	U 20*		570775	174,33		U 16*		570765	174,33
	U 26* ¹²⁾		570750	204,43		U 20*		570775	174,33
	U 32		570785	204,43		U 32		570780	174,33
								570785	204,43

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
AUSTEC PEX-AL-PEX GAS (AUS)	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570480	186,32
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
AYOR FIXOCONNECT Press	H 12*		570300	168,10
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 25*		570360	168,10
	RFz 12*		571320	194,05
	RFz 16*		571325	194,05
	RFz 20*		571330	194,05
	RFz 25		571335	194,05
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
AYOR FIXOMULTIX	H 16*		570320	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
	U 75 (PR-3B)	Z4	572828 R	645,58
AYOR SOMATHERM FOR YOU -1	H 16*		570320	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	U 16*		570765	174,33
	U 20*		570775	174,33
AYOR SOMATHERM FOR YOU -2	H 12*		570300	168,10
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 25*		570360	168,10
	RFz 12*		571320	194,05
	RFz 16*		571325	194,05
	RFz 20*		571330	194,05
	RFz 25		571335	194,05
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
B				
Bampi BALPEX serie LP	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 26* ¹²⁾		570750	204,43
Bampi BALPEX serie MP	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Bampi BALPEX Gas	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	H 12*		570300	168,10
	H 16*		570320	168,10
BARBI EASYPRESS (Industrial Blansol)	H 20*		570350	168,10
	H 25*		570370	168,10
	H 32		570380	168,10
	RFz 12*		571320	194,05
	RFz 16*		571325	194,05
	RFz 20*		571330	194,05
	RFz 25		571335	194,05
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
BARBI MULTIPLEX (Industrial Blansol)	H 14*		570310	168,10
	H 16*		570320	168,10
	H 18*		570340	168,10
	H 20*		570350	168,10
	H 25*		570360	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	RFz 16*		571325	194,05
	RFz 18*		571327	194,05
	RFz 20*		571330	194,05
	RFz 25		571335	194,05
BEGETUBE/ IVAR	RFz 25		571340	194,05
	RFz 32		571340	194,05
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
Béné inox Série 41	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
Brass Form Master-Al-Pex	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 116,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574748 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	124,51
Brass & Fittings PRESSMAN MultiPress	H 16*		570320	168,10
	H 18*		570340	168,10
	H 20*		570350	168,10
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
Brass & Fittings PRESSMAN RetiPress	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	RFz 16*		571325	194,05
	RFz 18*		571327	194,05
	ACz 20*		572646	194,05
	RFz 25		571335	194,05
	RFz 32		571340	194,05
	RFz 16*		571325	194,05
	RFz 18*		571327	194,05
	ACz 20*		572646	194,05
	RFz 25		571335	194,05
	RFz 32		571340	194,05

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
BRASSTECH	B 16*		570850	203,40	CHIALI	TH 16*		570460	186,32
MULTItermoSAN	B 20*		570860	203,40	CHIALIPEX	TH 20*		570470	186,32
Brasspress	B 26		570870	224,16		TH 26*		570475	186,32
	B 32		570880	224,16		TH 32		570480	186,32
	F 16*		570717	177,45		TH 40		570485	246,99
	F 20*		570727	177,45		TH 50 (PZ-S)		572400	645,58
	F 26*		570730	191,98		TH 63 (PZ-S)		572405	645,58
	F 16 S (PR-2B)**	Z8	574728 R	124,51	Climatrix	H 16*		570320	168,10
	F 20 S (PR-2B)**	Z8	574730 R	124,51	Climatrix Rhinopex	H 20*		570350	168,10
	F 26 S (PR-2B)**	Z8	574732 R	124,51		U 16*		570765	174,33
	H 16*		570320	168,10		U 20*		570775	174,33
	H 18*		570340	168,10		U 26* ¹²⁾		570750	204,43
	H 20*		570350	168,10		TH 14*		570455	186,32
	H 26*		570370	168,10		TH 16*		570460	186,32
	TH 16*		570460	186,32		TH 18*		570465	186,32
	TH 18*		570465	186,32		TH 20*		570470	186,32
	TH 20*		570470	186,32		TH 26*		570475	186,32
	TH 26*		570475	186,32		TH 32		570480	186,32
	TH 32		570480	186,32		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 40		570485	246,99		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 50 (PZ-S)		572400	645,58		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 63 (PZ-S)		572405	645,58		TH 32 S (PR-2B)	Z8	574798 R	136,96
	TH 16 S (PR-2B)**	Z8	574782 R	124,51	Climatrix	TH 11,6*		570482	186,32
	TH 18 S (PR-2B)**	Z8	574786 R	124,51	Variotherm	TH 16*		570460	186,32
	TH 20 S (PR-2B)**	Z8	574788 R	124,51	System TH	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51	ClouSet	TH 16*		570460	186,32
	TH 32 S (PR-2B)	Z8	574798 R	136,96		TH 18*		570465	186,32
	U 16*		570765	174,33		TH 20*		570470	186,32
	U 18*		570770	174,33		TH 26*		570475	186,32
	U 20*		570775	174,33		TH 32		570480	186,32
	U 26* ¹²⁾		570750	204,43		THL 32		570487	186,32
	U 32		570785	204,43		TH 40		570485	246,99
Cello Products >B< Press	VUS ½" (OD 15,9 mm)		571770	186,79		TH 50 (PZ-S)		572400	645,58
	VUS ¾" (OD 22,2 mm)		571775	186,79		TH 63 (PZ-S)		572405	645,58
	VUS 1" (OD 28,6 mm)		571780	186,79		TH 75 (PR-3B)	Z4	572829 R	609,25
	VUS 1¼" (OD 34,9 mm)		571785	186,79		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	VUS 1½" (OD 41,3 mm)		571790	360,13		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	VUS 2" (OD 54,0 mm)		571795	370,51		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 16*		570320	168,10		TH 32 S (PR-2B)	Z8	574798 R	136,96
	H 20*		570350	168,10		U 14*		570760	174,33
CGR DYNALU multicouche	H 26*		570370	168,10		U 16*		570765	174,33
	H 32		570380	168,10		U 18*		570770	174,33
	TH 16*		570460	186,32		U 20*		570775	174,33
	TH 20*		570470	186,32		U 26*		570785	204,43
	TH 26*		570475	186,32		U 32		570790	249,07
	TH 32		570480	186,32		U 40		570795	249,07
	TH 40		570485	246,99		U 50		570799	298,89
	TH 50 (PZ-S)		572400	645,58		U 63 (PR-3B)	Z4	572837 R	733,81
	TH 63 (PZ-S)		572405	645,58		U 63 (PZ-S)	Z4	572365	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		U 75 (PR-3B)	Z4	572828 R	645,58
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		TH 16*		570310	168,10
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		TH 18*		570320	168,10
	TH 32 S (PR-2B)	Z8	574798 R	136,96		TH 20*		570340	168,10
	U 16*		570765	174,33		TH 26*		570350	168,10
	U 20*		570775	174,33		TH 32		570370	168,10
	U 26* ¹²⁾		570750	204,43		U 40		570380	168,10
	U 32		570785	204,43		U 50		570390	565,67
	U 40		570790	249,07		U 63 (PZ-S)			
	U 50		570795	298,89		U 75 (PR-3B)			
	U 63 (PR-3B)	Z4	572837 R	733,81		TH 16*			
	U 63 (PZ-S)		572365	645,58		TH 18*			
CGR DYNALU PER	H 12*		570300	168,10		TH 20*			
	H 16*		570320	168,10		TH 26*			
	H 20*		570350	168,10		TH 32			
	H 25*		570360	168,10		U 14*			
	RFz 12*		571320	194,05		U 16*			
	RFz 16*		571325	194,05		U 18*			
	RFz 20*		571330	194,05		U 20*			
	RFz 25		571335	194,05		U 26*			

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Comap Multiskin Gas	TH 16*		570460	186,32	Conex Bänninger <A> Press Inox (304)	M 15 M 18 M 22 M 28 M 35 M 35 (PR-3S) M 42 (PZ-4G) M 54 (PZ-4G) M 42 (PR-3S) M 54 (PR-3S) M 15 S (PR-2B) M 18 S (PR-2B) M 22 S (PR-2B) M 28 S (PR-2B) M 35 S (PR-2B)	Z8 Z8	570110 570120 570130 570140 570150 572727 R 570160 570170 572706 R 572708 R 574738 R 574740 R 574742 R 574744 R 574746 R	154,61 154,61 154,61 154,61 154,61 672,57 498,19 498,19 672,57 672,57 124,51 124,51 124,51 124,51 124,51 136,96
COMISA Press System	TH 14*		570465	186,32	Conex Bänninger <A> Press Inox (316L)	M 15 M 18 M 22 M 28 M 35 M 35 (PR-3S) M 42 (PZ-4G) M 54 (PZ-4G) M 42 (PR-3S) M 54 (PR-3S) M 15 S (PR-2B) M 18 S (PR-2B) M 22 S (PR-2B) M 28 S (PR-2B) M 35 S (PR-2B)	Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8	570110 570120 570130 570140 570150 572727 R 570160 570170 572706 R 572708 R 574738 R 574740 R 574742 R 574744 R 574746 R	154,61 154,61 154,61 154,61 154,61 672,57 498,19 498,19 672,57 672,57 124,51 124,51 124,51 124,51 124,51 136,96
COMISA Press System Gas	TH 16*		570460	186,32	Conex Bänninger >B< Flex	F 16* F 18* F 20* F 32 F 16 S (PR-2B)** F 20 S (PR-2B)** F 25 S (PR-2B)** F 32 S (PR-2B)	Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8	570717 570720 570727 570735 574728 R 574730 R 574734 R 570320 570340 570350 570360 570380 571325 571327 571330 571335 571340 570460 570465 570470 570495 570480 574782 R 574786 R 574788 R 574798 R 574798 R	177,45 177,45 177,45 191,98 124,51 124,51 124,51 168,10 168,10 168,10 168,10 168,10 194,05 194,05 194,05 194,05 186,32 124,51 124,51 124,51 136,96
CONEC CONNECT INOX	M 15 M 18 M 22 M 42 (PR-3S) M 54 (PR-3S)	Z2 Z2	570110 570120 570130 572706 R 572708 R	154,61 154,61 154,61 672,57 672,57	Conex Bänninger >B< Flex Gas	F 16* F 18* F 20* F 32 F 16 S (PR-2B)** F 20 S (PR-2B)** F 32 S (PR-2B)	Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8	570717 570720 570727 570735 574728 R 574730 R 574734 R 570320 570340 570350 570360 570380 571325 571327 571330 571335 571340 570460 570465 570470 570495 570480 574782 R 574786 R 574788 R 574798 R 574798 R	177,45 177,45 177,45 191,98 124,51 124,51 124,51 124,51 136,96
CONEC CONNECT MULTI	F 16* F 20* F 26* F 32 F 16 S (PR-2B)** F 20 S (PR-2B)** F 26 S (PR-2B)** F 32 S (PR-2B)**	Z2 Z2	570717 570727 570730 570735 574728 R 574730 R 574732 R 574734 R	177,45 177,45 191,98 191,98 124,51 124,51 124,51 136,96	Conex Bänninger >B< Flex Gas	F 16* F 18* F 20* F 32 F 16 S (PR-2B)** F 20 S (PR-2B)** F 32 S (PR-2B)	Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8	570717 570720 570727 570735 574728 R 574730 R 574732 R 574734 R 570320 570340 570350 570360 570380 571325 571327 571330 571335 571340 570460 570465 570470 570495 570480 574782 R 574786 R 574788 R 574798 R 574798 R	174,43 204,43 177,45 177,45 191,98 124,51 124,51 124,51 136,96
(DN 26)	H 16* H 20* H 26* H 32 TH 16* TH 20* TH 26* TH 32 TH 16 S (PR-2B)** TH 20 S (PR-2B)** TH 26 S (PR-2B)** TH 32 S (PR-2B)**	Z2 Z2 Z2 Z2 Z2 Z2 Z2 Z2 Z8 Z8 Z8 Z8 Z8	570320 570350 570370 570380 570460 570470 570475 570480 574782 R 574788 R 574794 R 574798 R	168,10 168,10 168,10 168,10 186,32 186,32 186,32 186,32 124,51 124,51 124,51 136,96	Conex Bänninger >B< Flex Gas	H 16* H 18* H 20* H 25* H 32 RFz 16* RFz 18* RFz 20* RFz 25 RFz 32 TH 16* TH 18* TH 20* TH 25* TH 32 S (PR-2B)	Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8	570765 570770 570775 570780 570785 570790 570795 570800 574782 R 574786 R 574792 R 574798 R 574798 R	174,33 174,33 174,33 174,33 168,10 168,10 168,10 168,10 124,51 124,51 124,51 136,96
(DN 26)	U 16* U 20* U 25* U 32 VP 16* VP 20* VP 32	Z2 Z2 Z2 Z2 Z2 Z2 Z2	570765 570775 570780 570785 570910 570915 570925	174,33 174,33 174,33 204,43 185,75 185,75 205,47	Conex Bänninger >B< Flex Gas	U 16* U 18* U 20* U 25* U 32 RFz 16* RFz 18* RFz 20* RFz 25 RFz 32 TH 16* TH 18* TH 20* TH 25* TH 32 TH 20 S (PR-2B)**	Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8	570780 570785 570785 570785 570785 570785 570785 570785 574782 R 574786 R 574792 R 574798 R 574798 R	174,33 204,43 177,45 177,45 191,98 124,51 124,51 124,51 136,96
CONEC CONNECT MV2	F 16* F 20* F 26* F 32 F 16 S (PR-2B)** F 20 S (PR-2B)** F 26 S (PR-2B)** F 32 S (PR-2B)**	Z2 Z2 Z2 Z2 Z2 Z2 Z2	570717 570727 570730 570735 574728 R 574730 R 574732 R 574734 R	177,45 177,45 191,98 191,98 124,51 124,51 124,51 136,96	Conex Bänninger >B< MaxiPro	BMP 1/4" BMP 1/2" BMP 1/2" BMP 5/8" BMP 3/4" BMP 7/8" BMP 1" BMP 1 1/8"	Z8 Z8 Z8 Z8 Z8 Z8 Z8 Z8	571700 R 571702 R 571704 R 571706 R 571708 R 571710 R 571712 R 571714 R	184,71 184,71 184,71 184,71 184,71 184,71 184,71 184,71

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Conex Bänninger >B< Press	V 12		570107	154,61
	V 14		570112	154,61
	V 15		570115	154,61
	V 16		570117	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 54		570175	370,51
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 14 S (PR-2B)	Z8	574800 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 16 S (PR-2B)	Z8	574802 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
	M 15		570110	154,61
	M 22		570130	154,61
	M 28		570140	154,61
Conex Bänninger >B< Press XL copper	VFz 64,0 (PR-3B)	Z5	572815 R	609,25
	CBVFz 66,7 (PR-3B)	Z5	572847 R	609,25
	VFz 76,1 (PR-3B) ⁽¹⁾	Z5	572816 R	609,25
	VFz 88,9 (PR-3B) ⁽¹⁾	Z5	572817 R	645,58
	VFz 108,0 (PR-3B) ⁽¹⁾	Z5	572818 R	645,58
Conex Bänninger >B< Press carbon	V 15		570115	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
Conex Bänninger >B< Press XL carbon	XP 64,0 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579100 R	1 056,63
	XP 66,7 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579108 R	1 161,47
	M 76,1 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579101 R	1 161,47
	CBM 88,9 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579110 R	1 355,58
	CBM 108,0 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579144 R	1 355,58
Conex Bänninger >B< Press Gas	V 12		570107	154,61
	V 14		570112	154,61
	V 15		570115	154,61
	V 16		570117	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 54		570175	370,51
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 14 S (PR-2B)	Z8	574800 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 16 S (PR-2B)	Z8	574802 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
Conex Bänninger >B< Press Inox	V 15		570115	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Conex Bänninger >B< Press XL stainless	XP 64,0 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579100 R	1 056,63
	XP 66,7 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579108 R	1 161,47
	M 76,1 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579101 R	1 161,47
	CBM 88,9 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579144 R	1 355,58
	CBM 108,0 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579146 R	1 355,58
Conex Bänninger >B< Press Solar	V 12		570107	154,61
	V 14		570112	154,61
	V 15		570115	154,61
	V 16		570117	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 54		570175	370,51
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 14 S (PR-2B)	Z8	574800 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 16 S (PR-2B)	Z8	574802 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

D

Debrunner Acifer	M 12	570100	154,61
d-a Pressystem	M 15	570110	154,61
C-Stahl	M 18	570120	154,61
	M 22	570130	154,61
	M 28	570140	154,61
	M 35	570150	154,61
	M 42 (PR-3S)	Z2	572706 R
	M 54 (PR-3S)	Z2	572708 R
	M 76,1 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579101 R
	M 88,9 G XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579110 R
	M 108,0 G XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579111 R
	M 12,5 (PR-2B)	Z8	574736 R
	M 15 S (PR-2B)	Z8	574738 R
	M 18 S (PR-2B)	Z8	574740 R
	M 22 S (PR-2B)	Z8	574742 R
	M 28 S (PR-2B)	Z8	574744 R
	M 35 S (PR-2B)	Z8	574746 R
DUPIPE SYSTEMS	U 16*	570765	174,33
DUOFIL MKSYSTEM	U 18*	570770	174,33
	U 20*	570775	174,33
	U 25*	570780	174,33
	U 32	570785	204,43
DW Verbundrohr multitubo systems	U 16*	570765	174,33
	U 18*	570770	174,33
	U 20*	570775	174,33
	U 25*	570780	174,33
	U 32	570785	204,43
	U 40	570790	249,07
	U 50	570795	298,89
	U 63 (PR-3B)	Z4	572837 R
	U 63 (PZ-S)	Z4	572365
	U 75 (PR-3B)	Z4	572828 R

E

EBRILLE	U 16*	570765	174,33
Isomonflex	U 20*	570775	174,33
	U 25*	570780	174,33
	H 26*	570370	168,10
	TH 26*	570475	186,32
	TH 26 S (PR-2B)**	Z8	574794 R
	U 32	570785	204,43
EBRILLE	U 16*	570765	174,33
Monflex	U 20*	570775	174,33
	U 25*	570780	174,33
	H 26*	570370	168,10
	TH 26*	570475	186,32
	TH 26 S (PR-2B)**	Z8	574794 R
	U 32	570785	204,43

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue. See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
EFFEBI	M 15		570110	154,61	EFFEBI	V 12		570107	154,61
EFFEBI-PRESS	M 18		570120	154,61	EFFEBI-PRESS	V 15		570115	154,61
Aisi316	M 22		570130	154,61	UNICO	V 18		570125	154,61
System M Profile ¹⁾	M 28		570140	154,61	(GAS)	V 22		570135	154,61
	M 35		570150	154,61		V 28		570145	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57		V 35		570155	154,61
	M 54 (PR-3S)	Z2	572708 R	672,57		V 42		570165	360,13
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		V 42 (PR-2B)	Z2	572850 R	322,77
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		V 54		570175	370,51
	M 108,0 G XL (PR-3S) ⁵⁾	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		V 54 (PR-2B)	Z2	572851 R	348,72
	M 15 S (PR-2B)	Z8	574738 R	124,51		V 12 S (PR-2B)	Z8	574748 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51		V 15 S (PR-2B)	Z8	574752 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51		V 18 S (PR-2B)	Z8	574756 R	124,51
System V Profile	M 28 S (PR-2B)	Z8	574744 R	124,51		V 22 S (PR-2B)	Z8	574758 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96		V 28 S (PR-2B)	Z8	574760 R	124,51
	V 12		570107	154,61		V 35 S (PR-2B)	Z8	574762 R	136,96
	V 15		570115	154,61	EFFEBI	M 15		570110	154,61
	V 18		570125	154,61		M 18		570120	154,61
	V 22		570135	154,61		M 22		570130	154,61
	V 28		570145	154,61		M 35		570140	154,61
	V 35		570155	154,61		M 35 S (PR-2B)	Z8	570150	154,61
	V 42		570165	360,13		M 15 S (PR-2B)	Z8	574738 R	124,51
	V 42 (PR-2B)	Z2	572850 R	322,77		M 18 S (PR-2B)	Z8	574740 R	124,51
	V 54		570175	370,51		M 22 S (PR-2B)	Z8	574742 R	124,51
	V 54 (PR-2B)	Z2	572851 R	348,72		M 28 S (PR-2B)	Z8	574744 R	124,51
	V 12 S (PR-2B)	Z8	574748 R	124,51		M 35 S (PR-2B)	Z8	574746 R	136,96
System M Profile ¹⁾	V 15 S (PR-2B)	Z8	574752 R	124,51		V 15		570115	154,61
	V 18 S (PR-2B)	Z8	574756 R	124,51		V 18		570125	154,61
	V 22 S (PR-2B)	Z8	574758 R	124,51		V 22		570135	154,61
	V 28 S (PR-2B)	Z8	574760 R	124,51		V 28 S (PR-2B)	Z8	570145	154,61
	V 35 S (PR-2B)	Z8	574762 R	136,96		V 35 S (PR-2B)	Z8	570155	154,61
	V 12		570107	154,61		M 15		570110	154,61
	V 15		570115	154,61		M 18		570120	154,61
	Carbon-S		570125	154,61		M 22		570130	154,61
	M 22		570130	154,61		M 28		570140	154,61
	M 28		570140	154,61		M 35		570150	154,61
System V Profile	M 35		570150	154,61		M 42 (PR-2B)	Z2	572850 R	322,77
	M 42 (PR-3S)	Z2	572706 R	672,57		V 54 (PR-2B)	Z2	572851 R	348,72
	M 54 (PR-3S)	Z2	572708 R	672,57		V 15 S (PR-2B)	Z8	574752 R	124,51
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		V 18 S (PR-2B)	Z8	574756 R	124,51
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		V 22 S (PR-2B)	Z8	574758 R	124,51
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		V 28 S (PR-2B)	Z8	574760 R	124,51
	M 12 S (PR-2B)	Z8	574736 R	124,51		V 35 S (PR-2B)	Z8	574762 R	136,96
	M 15 S (PR-2B)	Z8	574738 R	124,51		V 54 (PR-2B)	Z2	572851 R	348,72
	M 18 S (PR-2B)	Z8	574740 R	124,51		V 15 S (PR-2B)	Z8	574752 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51		M 22 S (PR-2B)	Z8	574742 R	124,51
System V Profile	M 28 S (PR-2B)	Z8	574744 R	124,51		M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96		M 35 S (PR-2B)	Z8	574746 R	136,96
	V 12		570107	154,61	EFFEBI	M 15		570110	154,61
	V 15		570115	154,61		M 18		570120	154,61
	Carbon-S		570125	154,61		M 22		570130	154,61
	V 18		570135	154,61		M 28		570140	154,61
	V 22		570145	154,61		M 35		570150	154,61
	V 28		570155	154,61		M 42 (PR-2B)	Z2	572706 R	672,57
	V 35		570155	154,61		M 54 (PR-3S)	Z2	572708 R	672,57
	V 42		570165	360,13		M 15 S (PR-2B)	Z8	574738 R	124,51
	V 42 (PR-2B)	Z2	572850 R	322,77		M 18 S (PR-2B)	Z8	574740 R	124,51
	V 54		570175	370,51		M 22 S (PR-2B)	Z8	574742 R	124,51
System V Profile	V 54 (PR-2B)	Z2	572851 R	348,72		M 28 S (PR-2B)	Z8	574744 R	124,51
	V 12 S (PR-2B)	Z8	574748 R	124,51		M 35 S (PR-2B)	Z8	574746 R	136,96
	V 15 S (PR-2B)	Z8	574752 R	124,51	EFFEBI	M 15		570110	154,61
	V 18 S (PR-2B)	Z8	574756 R	124,51		M 18		570120	154,61
	V 22 S (PR-2B)	Z8	574758 R	124,51		M 22		570130	154,61
	V 28 S (PR-2B)	Z8	574760 R	124,51		M 28		570140	154,61
	V 35 S (PR-2B)	Z8	574762 R	136,96		M 35		570150	154,61
	V 54 (PR-2B)	Z2	572850 R	322,77		M 42 (PR-3S)	Z2	572706 R	672,57
	V 12 S (PR-2B)	Z8	574748 R	124,51		M 54 (PR-3S)	Z2	572708 R	672,57
	V 14 S (PR-2B)	Z8	574800 R	124,51		M 15 S (PR-2B)	Z8	574738 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51		M 18 S (PR-2B)	Z8	574740 R	124,51
	V 16 S (PR-2B)	Z8	574802 R	124,51		M 22 S (PR-2B)	Z8	574742 R	124,51
COPPER	V 18 S (PR-2B)	Z8	574756 R	124,51		M 28 S (PR-2B)	Z8	574744 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51		M 35 S (PR-2B)	Z8	574746 R	136,96
	V 28 S (PR-2B)	Z8	574760 R	124,51		V 15		570115	154,61
	V 35 S (PR-2B)	Z8	574762 R	136,96		V 18		570125	154,61
	V 12		570107	154,61		V 22		570135	154,61
	V 14		570112	154,61		V 28		570145	154,61
	V 15		570115	154,61		V 35		570155	154,61
	V 16		570117	154,61		V 42		570165	360,13
	V 18		570125	154,61		V 54 (PR-2B)		572850 R	322,77
	V 22		570135	154,61		V 15		570175	370,51
COPPER	V 28		570145	154,61		M 28		570185	348,72
	V 35		570155	154,61		M 35		570195	124,51
	V 42		570165	360,13		M 15 S (PR-2B)	Z8	574738 R	124,51
	V 42 (PR-2B)	Z2	572850 R	322,77		M 18 S (PR-2B)	Z8	574740 R	124,51
	V 54		570175	370,51		M 22 S (PR-2B)	Z8	574742 R	124,51
	V 54 (PR-2B)	Z2	572851 R	348,72		M 28 S (PR-2B)	Z8	574744 R	124,51
	V 12 S (PR-2B)	Z8	574748 R	124,51		M 35 S (PR-2B)	Z8	574746 R	136,96
	V 15 S (PR-2B)	Z8	574752 R	124,51		H 16*		570320	168,10
	V 18 S (PR-2B)	Z8	574756 R	124,51		H 20*		570350	168,10
	V 22 S (PR-2B)	Z8	574758 R	124,51		H 26*		570370	168,10
UNICO	V 28 S (PR-2B)	Z8	574760 R	124,51		H 32		570380	168,10
	V 35 S (PR-2B)	Z8	574762 R	136,96		H 40 (PZ-4G)		570390	565,67
	V 12		570107	154,61		H 16*		570765	174,33
	V 18		570115	154,61		H 20*		570775	174,33
	V 22		570125	154,61		H 32		570785	204,43
	V 28		570135	154,61		H 40 (PZ-4G)			
	V 35		570155	154,61		U 16*			
	V 42		570165	360,13		U 20*			
	V 42 (PR-2B)	Z2	572850 R	322,77		U 32			
	V 54		570175	370,51					
UNICO	V 54 (PR-2B)	Z2	572851 R	348,72					
	V 12 S (PR-2B)	Z8	574748 R	124,51					
	V 15 S (PR-2B)	Z8	574752 R	124,51					
	V 18 S (PR-2B)	Z8	574756 R	124,51					
	V 22 S (PR-2B)	Z8	574758 R	124,51					
	V 28 S (PR-2B)	Z8	574760 R	124,51					
	V 35 S (PR-2B)	Z8	574762 R	136,96					
	V 12		570107	154,61					
	V 18		570115	154,61					
	V 22		570125	154,61			</		

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
EFFEBI	TH 16*		570460	186,32	EMMETI	B 16*		570850	203,40
TOF	TH 18*		570465	186,32	GERPEX-	B 20*		570860	203,40
MULTIPINZA	TH 20*		570470	186,32	FIVPRESS	B 26		570870	224,16
	TH 25*		570495	186,32		B 32		570880	224,16
	TH 26*		570475	186,32		H 16*		570320	168,10
	TH 32		570480	186,32		H 20*		570350	168,10
	TH 40		570485	246,99		TH 16*		570460	186,32
	TH 50 (PZ-S)		572400	645,58		TH 20*		570470	186,32
	TH 63 (PZ-S)		572405	645,58		TH 26*		570475	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		TH 32		570480	186,32
	TH 18 S (PR-2B)**	Z8	574786 R	124,51		TH 40		570485	246,99
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		TH 50 (PZ-S)		572400	645,58
	TH 25 S (PR-2B)**	Z8	574792 R	124,51		TH 63 (PZ-S)		572405	645,58
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		U 16*		570765	174,33
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		U 20*		570775	174,33
	TH 32 S (PR-2B)	Z8	574798 R	136,96		EMPUR	TH 14*	570455	186,32
	F 16*		570717	177,45		TH 15*		570457	186,32
	F 18*		570720	177,45		TH 16*		570460	186,32
	F 20*		570727	177,45		TH 17*		570462	186,32
	F 26*		570730	191,98		TH 20*		570470	186,32
	F 32		570735	191,98		TH 25*		570495	186,32
	Fz 40		570742	205,47		TH 14 S (PR-2B)**	Z8	574778 R	124,51
	Fz 50		570747	311,35		TH 15 S (PR-2B)**	Z8	574780 R	124,51
	F 63 (PZ-S)		572385	645,58		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	F 16 S (PR-2B)**	Z8	574728 R	124,51		TH 17 S (PR-2B)**	Z8	574784 R	124,51
	F 20 S (PR-2B)**	Z8	574730 R	124,51		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	F 26 S (PR-2B)**	Z8	574732 R	124,51		TH 25 S (PR-2B)**	Z8	574792 R	124,51
	F 32 S (PR-2B)	Z8	574734 R	136,96					
	H 16*		570320	168,10	Esta Rohr simplesta SH M	M 15		570110	154,61
	H 18*		570340	168,10		M 18		570120	154,61
	H 20*		570350	168,10		M 22		570130	154,61
	H 25*		570360	168,10		M 28		570140	154,61
	H 26*		570370	168,10		M 35		570150	154,61
	H 32		570380	168,10		M 42 (PZ-4G)		570160	498,19
	H 40 (PZ-4G)		570390	565,67		M 54 (PZ-4G)		570170	498,19
	U 16*		570765	174,33		M 42 (PR-3S)	Z2	572706 R	672,57
	U 18*		570770	174,33		M 54 (PR-3S)	Z2	572708 R	672,57
	U 20*		570775	174,33		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	U 25*		570780	174,33		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	U 26*		570750	204,43		M 108,0 G XL (PR-3S) ⁵⁾	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	U 32		570785	204,43		M 15 S (PR-2B)	Z8	574738 R	124,51
	U 40		570790	249,07		M 18 S (PR-2B)	Z8	574740 R	124,51
	U 50		570795	298,89		M 22 S (PR-2B)	Z8	574742 R	124,51
	U 63 (PR-3B)	Z4	572837 R	733,81		M 28 S (PR-2B)	Z8	574744 R	124,51
	U 63 (PZ-S)		572365	645,58		M 35 S (PR-2B)	Z8	574746 R	136,96
EFIELD	U 16*		570765	174,33	Esta Rohr simplesta ST M	M 15		570110	154,61
MULTILAYER PRESS	U 18*		570770	174,33		M 18		570120	154,61
DINGAS	U 20*		570775	174,33		M 22		570130	154,61
	U 25*		570780	174,33		M 28		570140	154,61
	U 32		570785	204,43		M 35		570150	154,61
EFIELD	U 16*		570765	174,33		M 42 (PZ-4G)		570160	498,19
MULTILAYER PRESS	U 18*		570770	174,33		M 54 (PZ-4G)		570170	498,19
WATER	U 20*		570775	174,33		M 42 (PR-3S)	Z2	572706 R	672,57
	U 25*		570780	174,33		M 54 (PR-3S)	Z2	572708 R	672,57
	U 32		570785	204,43		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
Elkhart	VUS ½" (OD 15,9 mm)		571770	186,79		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
APOLLOXPRESS	VUS ¾" (OD 22,2 mm)		571775	186,79		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
Fittings Copper and Low-Lead Brass	VUS 1" (OD 28,6 mm)		571780	186,79		M 12 S (PR-2B)	Z8	574736 R	124,51
	VUS 1½" (OD 34,9 mm)		571785	186,79		M 15 S (PR-2B)	Z8	574738 R	124,51
	VUS 1½" (OD 41,3 mm)		571790	360,13		M 18 S (PR-2B)	Z8	574740 R	124,51
	VUS 2" (OD 54,0 mm)		571795	370,51		M 22 S (PR-2B)	Z8	574742 R	124,51
Elkhart	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	609,25		M 28 S (PR-2B)	Z8	574744 R	124,51
APOLLOXPRESS	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	609,25		M 35 S (PR-2B)	Z8	574746 R	136,96
LD-C Fittings Copper	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	645,58					

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
EUROTUBI	M 15		570110	154,61
EUROPA	M 18		570120	154,61
Inox Pressfitting	M 22		570130	154,61
System M-Profile ¹⁾	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
Evans Components Presslok	VAU 15 (1/2") (OD 12,7 mm)		572687	159,80
	VAU 20 (3/4") (OD 19,1 mm)		572689	159,80
	VAU 25 (1") (OD 25,4 mm)		572691	159,80
	ECI 1 1/2"		571932	200,28
	ECI 2" (PZ-4G)		571934	498,19
	ECI 2 1/2" XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579104 R	1 056,63
	ECI 3" XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579105 R	1 161,47
	ECI 4" XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579106 R	1 355,58

F

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
FAR Rubinetterie PRESSFAR	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 17*		570462	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Z8	574784 R	124,51
	TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	H 14*		570310	168,10
	H 16*		570320	168,10
	H 18*		570340	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	H 40 (PZ-4G)		570390	565,67
	U 14*		570760	174,33
	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
F.B.Q. BARONIO BQ PRESS SOLAR	V 12		570107	154,61
	V 14		570112	154,61
	V 15		570115	154,61
	V 16		570117	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 14 S (PR-2B)	Z8	574800 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	VG 16 S (PR-2B)	Z8	574754 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
F.B.Q. BARONIO BQ PRESS WATER	V 12		570107	154,61
	V 14		570112	154,61
	V 15		570115	154,61
	V 16		570117	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 14 S (PR-2B)	Z8	574800 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	VG 16 S (PR-2B)	Z8	574754 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
F.B.Q. BARONIO BQ PRESS GAS	V 12		570107	154,61
	V 14		570112	154,61
	V 15		570115	154,61
	V 16		570117	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 14 S (PR-2B)	Z8	574800 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	VG 16 S (PR-2B)	Z8	574754 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
FERCO systems	TH 16*		570140	194,05
BRASELI	TH 20*		571330	194,05
GPF GAS	TH 25*		571335	194,05
	TH 32		571340	194,05
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
FERCO systems	RFz 16*		571325	194,05
DUO Press	RFz 20*		571330	194,05
FERCO PEX	RFz 25		571335	194,05
	RFz 32		571340	194,05
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
FERRO systems	U 16*		570765	174,33
BRASELI	U 18*		570770	174,33
GPF MULT	U 20*		570775	174,33
Pressfitting	U 25*		570780	174,33
MULTICAPPA	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
FERRO systems	U 16*		570765	174,33
BRASELI	U 18*		570770	174,33
GPF PPSU	U 20*		570775	174,33
Pressfitting	U 25*		570780	204,43
PEX y MULTICAPPA	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
FERRO systems	RFz 16*		571325	194,05
BRASELI	RFz 20*		571330	194,05
GPF PRESS	RFz 25		571335	194,05
Pressfitting PEX	RFz 32		571340	194,05
FILINOX	FTB 15		571432	224,16
Filpress	FTB 18		571434	224,16
	FTB 22		571436	224,16
	FTB 28		571438	224,16
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579111 R	1 355,58

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
FILINOX	M 15		570110	154,61
Instalpress Steel	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
FILINOX	M 15		570110	154,61
Instalpress Inox	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
FITTINGS ESTÁNDAR	RFz 16*		571325	194,05
ECO-PRESS	RFz 20*		571330	194,05
	RFz 25		571335	194,05
	RFz 32		571340	194,05
FITTINGS ESTÁNDAR	RFz 16*		571325	194,05
MULTICAPA	RFz 18*		571327	194,05
	RFz 20*		571330	194,05
	RFz 25		571335	194,05
	RFz 32		571340	194,05
FITTINGS ESTÁNDAR	RFz 16*		571325	194,05
PE-X	RFz 20*		571330	194,05
	RFz 25		571335	194,05
	RFz 32		571340	194,05
FORNARA	B 16*		570850	203,40
ForPress	B 20*		570860	203,40
	B 26		570870	224,16
	B 32		570880	224,16
	F 16*		570717	177,45
	F 20*		570727	177,45
	F 26*		570730	191,98
	F 32		570735	191,98
	F 16 S (PR-2B)**	Z8	574728 R	124,51
	F 20 S (PR-2B)**	Z8	574730 R	124,51
	F 26 S (PR-2B)**	Z8	574732 R	124,51
	F 32 S (PR-2B)	Z8	574734 R	136,96
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 26* ¹²⁾		570750	204,43
	U 32		570785	204,43

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
FORZA	K16/P18*		572600	194,05
WATER CRIMP (AUS)	K/20*		572605	194,05
	K/25*		572610	194,05
	K32		572615	194,05
	K1/40		572620	194,05
	K1/50		572625	318,61
FORZA STAINLESS	K16/P18*		572600	194,05
WATER CRIMP	K/20*		572605	194,05
FORZA	K 16*		570765	174,33
STESSO PEX	U 20*		570775	174,33
WATER AND GAS	U 25*		570780	174,33
CRIMP (AUS)	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PZ-S)		572365	645,58
FORZA	K16/P18*		572600	194,05
GAS CRIMP (AUS)	K/20*		572605	194,05
	K/25*		572610	194,05
	K32		572615	194,05
	K1/40		572620	194,05
	K1/50		572625	318,61
FORZA	VAU 15 (OD 12,7 mm)		572687	159,80
COPPER V PRESS (AUS)	VAU 20 (OD 19,1 mm)		572689	159,80
	VAU 25 (OD 25,4 mm)		572691	159,80
	VAU 32 (OD 31,8 mm)		572693	168,10
	VAU 40 (OD 38,1 mm)		572695	249,07
	VAU 50 (OD 50,8 mm)		572697	441,10
	VAU F 65 (PR-3B) (OD 63,5 mm)	Z5	572839 R	609,25
	VAU F 80 (PR-3B) (OD 76,2 mm)	Z5	572840 R	609,25
	VAU F 100 (PR-3B) (OD 101,6 mm)	Z5	572841 R	645,58
	VAU 15 S (PR-2B) (OD 12,7 mm)	Z8	574804 R	124,51
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Z8	574806 R	124,51
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Z8	574808 R	136,96
FORZA	V 15		570115	154,61
STAINLESS V PRESS (AUS)	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 54		570175	370,51
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
FRABO	M 15		570110	154,61
FRABOPRESS	M 18		570120	154,61
316 GAS M	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z!	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
FRABO	V 15		570115	154,61
FRABOPRESS	V 18		570125	154,61
316 GAS V	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
FRABO	M 15		570110	154,61	FRABO	V 12		570107	154,61
FRABOPRESS	M 18		570120	154,61	FRABOPRESS	V 15		570115	154,61
316 M	M 22		570130	154,61	KOMBI	V 18		570125	154,61
	M 28		570140	154,61		V 22		570135	154,61
	M 35		570150	154,61		V 28		570145	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57		V 35		570155	154,61
	M 54 (PR-3S)	Z2	572708 R	672,57		V 42		570165	360,13
	M 66,7 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579107 R	1 161,47	Z2	V 42 (PR-2B)		572850 R	322,77
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579101 R	1 161,47		V 54		570175	370,51
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579110 R	1 355,58		V 54 (PR-2B)	Z2	572851 R	348,72
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579111 R	1 355,58		M 66,7 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579107 R	1 161,47
	M 15 S (PR-2B)	Z8	574738 R	124,51		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579101 R	1 161,47
	M 18 S (PR-2B)	Z8	574740 R	124,51		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579110 R	1 355,58
	M 22 S (PR-2B)	Z8	574742 R	124,51		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579111 R	1 355,58
	M 28 S (PR-2B)	Z8	574744 R	124,51		V 12 S (PR-2B)	Z8	574748 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96		V 15 S (PR-2B)	Z8	574752 R	124,51
FRABO	V 15		570115	154,61		V 18 S (PR-2B)	Z8	574756 R	124,51
FRABOPRESS	V 18		570125	154,61		V 22 S (PR-2B)	Z8	574760 R	124,51
316 V	V 22		570135	154,61		V 28 S (PR-2B)	Z8	574762 R	136,96
	V 28		570145	154,61	FRABO	M 12		570100	154,61
	V 35		570155	154,61		M 15		570110	154,61
	V 42		570165	360,13		M 18		570120	154,61
	V 42 (PR-2B)	Z2	572850 R	322,77		M 22		570130	154,61
	V 54		570175	370,51		M 35		570150	154,61
	V 54 (PR-2B)	Z2	572851 R	348,72		M 42 (PR-3S)	Z2	572706 R	672,57
	V 15 S (PR-2B)	Z8	574752 R	124,51		M 54 (PR-3S)	Z2	572708 R	672,57
	V 18 S (PR-2B)	Z8	574756 R	124,51		M 66,7 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579107 R	1 161,47
	V 22 S (PR-2B)	Z8	574758 R	124,51		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579101 R	1 161,47
	V 28 S (PR-2B)	Z8	574760 R	124,51		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579110 R	1 355,58
	V 35 S (PR-2B)	Z8	574762 R	136,96		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579111 R	1 355,58
FRABO	V 12		570107	154,61		M 12 S (PR-2B)	Z8	574736 R	124,51
FRABOPRESS	V 15		570115	154,61		M 15 S (PR-2B)	Z8	574738 R	124,51
CHROME	V 18		570125	154,61		M 18 S (PR-2B)	Z8	574740 R	124,51
	V 22		570135	154,61		M 22 S (PR-2B)	Z8	574742 R	124,51
	V 12 S (PR-2B)	Z8	574748 R	124,51		M 28 S (PR-2B)	Z8	574744 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51		M 35 S (PR-2B)	Z8	574746 R	136,96
	V 18 S (PR-2B)	Z8	574756 R	124,51	FRABO	V 15		570115	154,61
	V 22 S (PR-2B)	Z8	574760 R	124,51		V 18		570125	154,61
FRABO	M 15		570110	154,61		V 22		570135	154,61
FRABOPRESS	M 18		570120	154,61		V 28		570145	154,61
C-STEEL M	M 22		570130	154,61		V 35		570155	154,61
	M 28		570140	154,61		V 15 S (PR-2B)	Z8	574752 R	124,51
	M 35		570150	154,61		V 18 S (PR-2B)	Z8	574754 R	124,51
	M 42 (PR-3S)	Z2	572706 R	672,57		V 22 S (PR-2B)	Z8	574758 R	124,51
	M 54 (PR-3S)	Z2	572708 R	672,57		V 28 S (PR-2B)	Z8	574760 R	124,51
	M 66,7 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579107 R	1 161,47		V 35 S (PR-2B)	Z8	574762 R	136,96
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579101 R	1 161,47	FRABO	V 12		570107	154,61
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579110 R	1 355,58		V 15		570115	154,61
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁽⁴⁾	579111 R	1 355,58		V 18		570125	154,61
	M 15 S (PR-2B)	Z8	574738 R	124,51		V 22		570135	154,61
	M 18 S (PR-2B)	Z8	574740 R	124,51		V 28		570145	154,61
	M 22 S (PR-2B)	Z8	574742 R	124,51		V 35		570155	154,61
	M 28 S (PR-2B)	Z8	574744 R	124,51		V 42 (PR-2B)	Z2	572850 R	322,77
	M 35 S (PR-2B)	Z8	574746 R	136,96		V 54		570175	370,51
FRABO	V 12		570107	154,61		V 54 (PR-2B)	Z2	572851 R	348,72
FRABOPRESS	V 15		570115	154,61		V 12 S (PR-2B)	Z8	574748 R	124,51
C-STEEL V	V 18		570125	154,61		V 15 S (PR-2B)	Z8	574752 R	124,51
	V 22		570135	154,61		V 18 S (PR-2B)	Z8	574754 R	124,51
	V 28		570145	154,61		V 22 S (PR-2B)	Z8	574758 R	124,51
	V 35		570155	154,61		V 28 S (PR-2B)	Z8	574760 R	124,51
	V 42		570165	360,13		V 35 S (PR-2B)	Z8	574762 R	136,96
	V 42 (PR-2B)	Z2	572850 R	322,77	Fränkische	F 16*		570717	177,45
	V 54		570175	370,51		F 20*		570727	177,45
	V 54 (PR-2B)	Z2	572851 R	348,72		F 26*		570730	191,98
	V 12 S (PR-2B)	Z8	574748 R	124,51		F 32		570735	191,98
	V 15 S (PR-2B)	Z8	574752 R	124,51		F 16 S (PR-2B)**	Z8	574728 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51		F 20 S (PR-2B)**	Z8	574730 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51		F 26 S (PR-2B)**	Z8	574732 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51		F 32 S (PR-2B)**	Z8	574734 R	136,96
	V 35 S (PR-2B)	Z8	574762 R	136,96		TH 16*		570460	186,32
FRABO	M 12		570100	154,61		TH 20*		570470	186,32
FRABOPRESS	M 15		570110	154,61		TH 26*		570475	186,32
GAS M	M 18		570120	154,61		TH 32		570480	186,32
	M 22		570130	154,61		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	M 28		570140	154,61		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	M 35		570150	154,61		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	M 42 (PR-3S)	Z2	572706 R	672,57		TH 32 S (PR-2B)**	Z8	574798 R	136,96
	M 54 (PR-3S)	Z2	572708 R	672,57	Fränkische	F 16*		570717	177,45
	M 12 S (PR-2B)	Z8	574736 R	124,51		F 20*		570727	177,45
	M 15 S (PR-2B)	Z8	574738 R	124,51		F 26*		570730	191,98
	M 18 S (PR-2B)	Z8	574740 R	124,51		F 32		570735	191,98
	M 22 S (PR-2B)	Z8	574742 R	124,51		F 16 S (PR-2B)**	Z8	574728 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51		F 20 S (PR-2B)**	Z8	574730 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96		F 26 S (PR-2B)**	Z8	574732 R	124,51
FRABO	V 12		570107	154,61		F 32 S (PR-2B)**	Z8	574734 R	136,96
FRABOPRESS	V 15		570115	154,61		H 16*		570320	168,10
GAS V	V 18		570125	154,61		H 20*		570350	168,10
	V 22		570135	154,61		H 26*		570370	168,10
	V 28		570145	154,61		H 32		570380	168,10
	V 35		570155	154,61		TH 16*		570460	186,32
	V 42		570165	360,13		TH 20*		570470	186,32
	V 42 (PR-2B)	Z2	572850 R	322,77		TH 26*		570475	186,32
	V 54		570175	370,51		TH 32		570480	186,32
	V 54 (PR-2B)	Z2	572851 R	348,72		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	V 12 S (PR-2B)	Z8	574748 R	124,51		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51		TH 32 S (PR-2B)**	Z8	574798 R	136,96
	V 22 S (PR-2B)	Z8	574758 R	124,51		U 16*		570765	174,33
	V 28 S (PR-2B)	Z8	574760 R	124,51		U 20*		570775	174,33
	V 35 S (PR-2B)	Z8	574762 R	136,96	(DN 26)	U 25*		570780	174,33
						U 32		570785	204,43
						VP 16*		570910	185,75
						VP 20*		570915	185,75
						VP 32		570925	205,47

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Fränkische alpex L	Fz 40	Z4	570742	205,47
	Fz 50		570747	311,35
	F 63 (PZ-S)		572385	645,58
	Fz 75 (PR-3B)		572830 R	609,25

G

gabotherm H+S	TH 10*		570467	186,32
	TH 12*		570452	186,32
	TH 14*		570455	186,32
	TH 15*		570457	186,32
	TH 16*		570460	186,32
	TH 17*		570462	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 10 S (PR-2B)**	Z8	574772 R	124,51
	TH 12 S (PR-2B)**	Z8	574776 R	124,51
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 15 S (PR-2B)**	Z8	574780 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Z8	574784 R	124,51
	TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
Gallagher USA YogaPipe ACR	H 12" (1/4")		570300	168,10
	U 14" (3/8")		570760	174,33
	U 16" (1/2")		570765	174,33
	U 18" (5/8")		570770	174,33
	U 20" (3/4")		570775	174,33
	U 25" (7/8")		570780	174,33
	U 32 (1 1/8")		570785	204,43
Geberit Mapress C-STAHL	M 12		570100	154,61
	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 35 (PR-35)	Z2	572727 R	672,57
	M 42 (PZ-46)		570160	498,19
	M 54 (PZ-46)		570170	498,19
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 66,7 XL (PR-3S)		572708 R	672,57
	M 66,7 XL (PR-3S)		579107 R	1161,47
	M 76,1 XL (PR-3S)		579101 R	1161,47
	M 88,9 G XL (PR-3S)		579110 R	1355,58
	M 108,0 G XL (PR-3S)		579111 R	1355,58
	M 12 S (PR-2B)	Z8	574736 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
Geberit Mapress C-STAHL Sprinkler nass	M 22		570130	154,61
	M 28		570140	154,61
	M 35 (PR-35)	Z2	572727 R	672,57
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 66,7 XL (PR-3S)		572708 R	672,57
	M 66,7 XL (PR-3S)		579107 R	1161,47
	M 76,1 XL (PR-3S)		579101 R	1161,47
	M 88,9 G XL (PR-3S)		579110 R	1355,58
	M 108,0 G XL (PR-3S)		579111 R	1355,58
	M 12 S (PR-2B)	Z8	574736 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
Geberit Mapress Kupfer	M 22		570100	154,61
	M 28		570120	154,61
	M 35 (PR-3S)	Z2	572727 R	672,57
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 66,7 XL (PR-3S)		572708 R	672,57
	M 66,7 XL (PR-3S)		579107 R	1161,47
	M 76,1 XL (PR-3S)		579101 R	1161,47
	M 88,9 G XL (PR-3S)		579110 R	1355,58
	M 108,0 G XL (PR-3S)		579111 R	1355,58
	M 12 S (PR-2B)	Z8	574736 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
Geberit Mapress Kupfer Gas	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 35 (PR-3S)	Z2	572727 R	672,57
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 66,7 S (PR-2B)	Z8	574736 R	124,51
	M 88,9 G S (PR-2B)	Z8	574738 R	124,51
	M 108,0 G S (PR-2B)	Z8	574740 R	124,51
	M 12 S S (PR-2B)	Z8	574742 R	124,51
	M 18 S S (PR-2B)	Z8	574744 R	124,51
	M 22 S S (PR-2B)	Z8	574746 R	136,96

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

① Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

② For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

③ Driven by REMS Power-Press XL ACC, see page 188.

④ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⑤ For taking suitable pressing inserts.

⑥ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⑦ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⑧ For making press joints for operating pressure ≤ PN 10.

⑨ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⑩ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⑪ Only use pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.

⑫ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Geberit Mepla	G 16*		570400	186,79	General Fittings	H 16*		570320	168,10
	G 20*		570410	186,79	Trident	H 20*		570350	168,10
	G 26*		570420	198,21		H 26*		570370	168,10
	G 32		570430	211,70		H 32		570380	168,10
	G 40		570440	273,98		TH 16*		570460	186,32
	G 50		570450	286,44		TH 20*		570470	186,32
	G 63 (PZ-S)		572470	809,59		TH 26*		570475	186,32
Geberit Mepla	G 16*		570400	186,79		TH 32		570480	186,32
Therm	G 20*		570410	186,79		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	G 26*		570420	198,21		TH 20 S (PR-2B)**	Z8	574788 R	124,51
Geberit Volex	TH 16*		570460	186,32		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 20*		570470	186,32		TH 32 S (PR-2B)	Z8	574798 R	136,96
	TH 26*		570475	186,32		U 16*		570765	174,33
General Fittings	H 16*		570320	168,10		U 20*		570775	174,33
5T00	H 20*		570350	168,10		U 32		570785	204,43
	H 26*		570370	168,10	General Fittings	TH 16*		570460	186,32
	H 32		570380	168,10	Trident Gas	TH 20*		570470	186,32
	TH 16*		570460	186,32		TH 26*		570475	186,32
	TH 20*		570470	186,32		TH 32		570480	186,32
	TH 26*		570475	186,32		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 32		570480	186,32		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 40		570485	246,99		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 50 (PZ-S)		572400	645,58		TH 32 S (PR-2B)	Z8	574798 R	136,96
	TH 63 (PZ-S)		572405	645,58		H 16*		570320	168,10
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		H 20*		570350	168,10
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		H 26*		570370	168,10
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		H 32		570380	168,10
	TH 32 S (PR-2B)	Z8	574798 R	136,96		TH 16*		570460	186,32
General Fittings	U 16*		570765	174,33		TH 20*		570470	186,32
Ewoprex	U 20*		570775	174,33		TH 26*		570475	186,32
	U 32		570785	204,43		TH 32		570480	186,32
	U 40		570790	249,07		TH 40		570765	174,33
	U 63 (PZ-S)		572365	645,58		U 16*		570775	174,33
	U 63 (PR-3B)	Z4	572837 R	733,81		U 20*		570785	204,43
General Fittings	H 16*		570320	168,10		U 32		570785	204,43
	H 20*		570350	168,10	Giacomini	H 16*		570320	168,10
	H 26*		570370	168,10	Raccordi RM	H 20*		570350	168,10
	H 32		570380	168,10	Giacomini	H 26*		570370	168,10
	TH 16*		570460	186,32		H 32		570380	168,10
	TH 20*		570470	186,32		TH 16*		570460	186,32
	TH 26*		570475	186,32		TH 20*		570470	186,32
	TH 32		570480	186,32		TH 26*		570475	186,32
	TH 40		570485	246,99		TH 32		570480	186,32
	TH 50 (PZ-S)		572400	645,58		TH 40		570765	174,33
	TH 63 (PZ-S)		572405	645,58		U 16*		570775	174,33
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		U 20*		570785	204,43
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		U 32		570785	204,43
	TH 26 S (PR-2B)**	Z8	574794 R	124,51	Giacomini	H 16*		570320	168,10
	TH 32 S (PR-2B)	Z8	574798 R	136,96	RM MULTIGAS	H 20*		570350	168,10
	U 16*		570765	174,33		H 26*		570370	168,10
	U 20*		570775	174,33		H 32		570380	168,10
	U 32		570785	204,43		TH 16*		570460	186,32
	U 40		570790	249,07		TH 20*		570470	186,32
	U 63 (PZ-S)		572365	645,58		TH 26*		570475	186,32
	U 63 (PR-3B)	Z4	572837 R	733,81		TH 32		570480	186,32
General Fittings	B 16*		570850	203,40		U 16*		570765	174,33
Serie 5S00	B 18*		570855	203,40		U 20*		570775	174,33
	B 20*		570860	203,40		U 26*		570780	174,33
	B 26		570870	224,16		U 32		570785	204,43
	B 32		570880	224,16	Giacomini	V 15		570115	154,61
	F 16*		570717	177,45	Valvole Giacomini	V 18		570125	154,61
	F 20*		570727	177,45	serie R850V	V 22		570135	154,61
	F 26*		570730	191,98		V 28		570145	154,61
	F 32		570735	191,98		V 35		570155	154,61
	F 16 S (PR-2B)**	Z8	574728 R	124,51		V 42		570165	360,13
	F 20 S (PR-2B)**	Z8	574730 R	124,51		V 54		570175	370,51
	F 26 S (PR-2B)**	Z8	574732 R	124,51		V 15 S (PR-2B)	Z8	574752 R	124,51
	F 32 S (PR-2B)	Z8	574734 R	136,96		V 18 S (PR-2B)	Z8	574756 R	124,51
	H 16*		570320	168,10		V 22 S (PR-2B)	Z8	574758 R	124,51
	H 18*		570340	168,10		V 28 S (PR-2B)	Z8	574760 R	124,51
	H 20*		570350	168,10		V 35 S (PR-2B)	Z8	574762 R	136,96
	H 25*		570360	168,10		SA 15		570935	185,75
	H 26*		570370	168,10		SA 18		570940	185,75
	H 32		570380	168,10		SA 22		570945	185,75
	H 40 (PZ-G)		570390	565,67		SA 28		570950	185,75
	TH 16*		570460	186,32		SA 35		570955	185,75
	TH 18*		570465	186,32		M 15		570110	154,61
	TH 20*		570470	186,32		M 18		570120	154,61
	TH 25*		570495	186,32		M 22		570130	154,61
	TH 26*		570475	186,32		M 28		570140	154,61
	TH 32		570480	186,32		M 35		570150	154,61
	TH 40		570485	246,99		M 15 S (PR-2B)	Z8	574738 R	124,51
	TH 50 (PZ-S)		572400	645,58		M 18 S (PR-2B)	Z8	574740 R	124,51
	TH 63 (PZ-S)		572405	645,58		M 22 S (PR-2B)	Z8	574742 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		M 28 S (PR-2B)	Z8	574744 R	124,51
	TH 18 S (PR-2B)**	Z8	574786 R	124,51		M 35 S (PR-2B)	Z8	574746 R	136,96
	TH 20 S (PR-2B)**	Z8	574788 R	124,51	Golan Pipe	H 16*		570765	174,33
	TH 25 S (PR-2B)**	Z8	574792 R	124,51	Systems	H 20*		570775	174,33
	TH 26 S (PR-2B)**	Z8	574794 R	124,51	(Scandinavia)	H 25*		570780	174,33
	TH 32 S (PR-2B)	Z8	574798 R	136,96	Alu-Pres	U 32		570785	204,43
	U 16*		570765	174,33		U 40		570790	249,07
	U 18*		570770	174,33		U 50		570795	298,89
	U 20*		570775	174,33		U 63 (PZ-S)		572365	645,58
	U 25*		570780	174,33		U 63 (PR-3B)	Z4	572837 R	733,81
	U 32		570785	204,43		U 75 (PR-3B)	Z4	572828 R	645,58
	U 40		570790	249,07	Grinnell G-PRESS	VUS ½" (OD 15,9 mm)		571770	186,79
	U 63 (PZ-S)		572365	645,58	Copper Fittings	VUS ¾" (OD 22,2 mm)		571775	186,79
	U 63 (PR-3B)	Z4	572837 R	733,81		VUS 1" (OD 28,6 mm)		571780	186,79

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
GS Wärmesysteme System TH	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
GS Wärmesysteme System V	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	V 15		570115	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
V 15 S (PR-2B)	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

H

HASTINIK Hastinik/Hitpress	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PZ-46)		570160	498,19
	M 54 (PZ-46)		570170	498,19
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
heima24	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
HELIROMA Klimapress	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 20*		570775	174,33
HELIROMA Klimapress PPSU	U 32		570780	174,33
	U 40		570785	204,43
	U 50		570790	249,07
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
	U 75 (PR-3B)	Z4	572828 R	645,58
	U 16*		570765	174,33
	U 20*		570775	174,33
Henco	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
HIDRONIX MULTIGAS	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
	U 75 (PR-3B)	Z4	572828 R	645,58
	TH 16*		570765	174,33
	TH 20*		570775	174,33
	TH 26*		570780	174,33
	TH 32		570785	204,43
	TH 40		570790	249,07
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
HERZ PIPEFIX	TH 10*		570467	186,32
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
HIDRONIX MULTIGAS	TH 75 (PR-3B)	Z4	572829 R	609,25
	TH 10 S (PR-2B)**	Z8	574772 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)**	Z8	574798 R	136,96
	TH 16*		570460	186,32
	TH 20*		570470	186,32

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
HIDRONIX	TH 14*		570455	186,32	HITHERM	M 15		570110	154,61
MULTIPIPE	TH 16*		570460	186,32	HTair	M 18		570120	154,61
	TH 20*		570470	186,32		M 22		570130	154,61
	TH 26*		570475	186,32		M 28		570140	154,61
	TH 32		570480	186,32		M 35		570150	154,61
	H 14*		570310	168,10		M 42 (PR-3S)	Z2	572706 R	672,57
	H 16*		570320	168,10		M 54 (PR-3S)	Z2	572708 R	672,57
	H 18*		570340	168,10		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	H 20*		570350	168,10		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	H 26*		570370	168,10		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	H 32		570380	168,10		M 15 S (PR-2B)	Z8	574738 R	124,51
	U 14*		570760	174,33		M 18 S (PR-2B)	Z8	574740 R	124,51
	U 16*		570765	174,33		M 22 S (PR-2B)	Z8	574742 R	124,51
	U 18*		570770	174,33		M 28 S (PR-2B)	Z8	574744 R	124,51
	U 20*		570775	174,33		M 35 S (PR-2B)	Z8	574746 R	136,96
	U 26* ¹²⁾		570750	204,43					
	U 32		570785	204,43					
HIDRONIX	TH 14*		570455	186,32	Hopewell	M 15		570110	154,61
UNICO	TH 16*		570460	186,32	press fit system	M 18		570120	154,61
	TH 20*		570470	186,32		M 22		570130	154,61
	TH 26*		570475	186,32		M 28		570140	154,61
	TH 32		570480	186,32		M 35		570150	154,61
	H 14*		570310	168,10		M 42 (PZ-4G)	Z2	572706 R	672,57
	H 16*		570320	168,10		M 54 (PZ-4G)	Z2	572708 R	672,57
	H 18*		570340	168,10		M 76,1 XL (PZ-4G)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	H 20*		570350	168,10		M 88,9 G XL (PZ-4G)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	H 26*		570370	168,10		M 108,0 G XL (PZ-4G)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	H 32		570380	168,10		M 15 S (PZ-2B)	Z8	574738 R	124,51
	U 14*		570760	174,33		M 18 S (PZ-2B)	Z8	574740 R	124,51
	U 16*		570765	174,33		M 22 S (PZ-2B)	Z8	574742 R	124,51
	U 18*		570770	174,33		M 28 S (PZ-2B)	Z8	574744 R	124,51
	U 20*		570775	174,33		M 35 S (PZ-2B)	Z8	574746 R	136,96
	U 26* ¹²⁾		570750	204,43					
	U 32		570785	204,43					
HITEC	TH 14*		570455	186,32	hp praski	TH 10*		570467	186,32
Sistema Multistrato	TH 16*		570460	186,32	BAVARIA-press	TH 12*		570452	186,32
	TH 18*		570465	186,32		TH 14*		570455	186,32
	TH 20*		570470	186,32		TH 16*		570460	186,32
	TH 26*		570475	186,32		TH 17*		570462	186,32
	TH 32		570480	186,32		TH 20*		570470	186,32
	H 40		570485	246,99		TH 25*		570495	186,32
	TH 50 (PZ-S)		572400	645,58		TH 26*		570475	186,32
	TH 14 S (PR-2B)**	Z8	574778 R	124,51		TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		TH 40		570485	246,99
	TH 18 S (PR-2B)**	Z8	574786 R	124,51		TH 10 S (PR-2B)**	Z8	574772 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		TH 12 S (PR-2B)**	Z8	574776 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96		TH 16 S (PR-2B)**	Z8	574782 R	124,51
HITHERM-ISOTUBI	M 15		570110	154,61		TH 17 S (PR-2B)**	Z8	574784 R	124,51
NUMEPRESS	M 18		570120	154,61		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	M 22		570130	154,61		TH 25 S (PR-2B)**	Z8	574792 R	124,51
	M 28		570140	154,61		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	M 35		570150	154,61		TH 32 S (PR-2B)	Z8	574798 R	136,96
	M 42 (PR-3S)	Z2	572706 R	672,57		U 16*		570765	174,33
	M 54 (PR-3S)	Z2	572708 R	672,57		U 20*		570775	174,33
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		U 25*		570780	174,33
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		U 26* ¹²⁾		570780	204,43
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58					
	M 15 S (PR-2B)	Z8	574738 R	124,51					
	M 18 S (PR-2B)	Z8	574740 R	124,51					
	M 22 S (PR-2B)	Z8	574742 R	124,51					
	M 28 S (PR-2B)	Z8	574744 R	124,51					
	M 35 S (PR-2B)	Z8	574746 R	136,96					
HITHERM	M 15		570110	154,61					
HTpress	M 18		570120	154,61					
	M 22		570130	154,61					
	M 28		570140	154,61					
	M 35		570150	154,61					
	M 42 (PR-3S)	Z2	572706 R	672,57					
	M 54 (PR-3S)	Z2	572708 R	672,57					
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47					
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58					
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58					
	M 15 S (PR-2B)	Z8	574738 R	124,51					
	M 18 S (PR-2B)	Z8	574740 R	124,51					
	M 22 S (PR-2B)	Z8	574742 R	124,51					
	M 28 S (PR-2B)	Z8	574744 R	124,51					
	M 35 S (PR-2B)	Z8	574746 R	136,96					
HITHERM	M 15		570110	154,61					
HTfire	M 18		570120	154,61					
	M 22		570130	154,61					
	M 28		570140	154,61					
	M 35		570150	154,61					
	M 42 (PR-3S)	Z2	572706 R	672,57					
	M 54 (PR-3S)	Z2	572708 R	672,57					
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47					
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58					
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58					
	M 15 S (PR-2B)	Z8	574738 R	124,51					
	M 18 S (PR-2B)	Z8	574740 R	124,51					
	M 22 S (PR-2B)	Z8	574742 R	124,51					
	M 28 S (PR-2B)	Z8	574744 R	124,51					
	M 35 S (PR-2B)	Z8	574746 R	136,96					
ICMA	H 16*		570320	168,10					
Sempiter	H 20*		570350	168,10					
	H 25*		570360	168,10					
	H 26*		570370	168,10					
	H 32		570380	168,10					
	H 40 (PZ-4G)		570390	565,67					
	TH 16*		570460	186,32					
	TH 20*		570470	186,32					
	TH 25*		570495	186,32					
	TH 26*		570475	186,32					
	TH 32		570480	186,32					
	TH 40 (PZ-S)		570485	246,99					
	TH 63 (PZ-S)		572400	645,58					
	TH 16 S (PZ-2B)**	Z8	574782 R	124,51					
	TH 20 S (PZ-2B)**	Z8	574788 R	124,51					
	TH 25 S (PZ-2B)**	Z8	574794 R	124,51					
	TH 32 S (PZ-2B)	Z8	574798 R	136,96					
	U 32		570785	204,43					
	U 40		570790	249,07					
	U 50		570795	298,89					
	U 63 (PZ-3B)	Z4	572837 R	733,81					
	U 63 (PZ-S)	Z4	572365	645,58					
	TH 16*		570460	186,32					
	TH 20*		570470	186,32					
	TH 25*		570495	186,32					
	TH 26*		570475	186,32					
	TH 32		570480	186,32					
	TH 16 S (PR-2B)**	Z8	574782 R	124,51					
	TH 20 S (PR-2B)**	Z8	574788 R	124,51					
	TH 25 S (PR-2B)**	Z8	574794 R	124,51					
	TH 32 S (PR-2B)	Z8	574798 R	136,96					
	Idrosanitaria	TH 16*	570460	186,32					
	Bonomi	TH 20*	570470	186,32					
	Homegas	TH 26*	570475	186,32					
		TH 16 S (PR-2B)**	Z8	574782 R	124,51				
		TH 20 S (PR-2B)**	Z8	574788 R	124,51				
		TH 25 S (PR-2B)**	Z8	574794 R	124,51				
		TH 32 S (PR-2B)	Z8	574798 R	136,96				
	Idrosanitaria	TH 16*	570460	186,32					
	Bonomi	TH 18*	570465	186,32					
	Idropress	TH 20*	570470	186,32					
		TH 26*</td							

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
IDROISTEMI	TH 16*		570460	186,32	IDROTRADE	M 12		570100	154,61
Ta-Press	TH 20*		570470	186,32	StormSTEEL ¹⁾	M 15		570110	154,61
	TH 26*		570475	186,32		M 18		570120	154,61
	TH 32		570480	186,32		M 22		570130	154,61
	TH 40		570485	246,99		M 28		570140	154,61
	TH 50 (PZ-S)		572400	645,58		M 35		570150	154,61
	TH 63 (PZ-S)		572405	645,58		M 42 (PR-3S)	Z8	572706 R	672,57
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		M 54 (PR-3S)	Z8	572708 R	672,57
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		M 76,1 XL (PR-3S) ⁸⁾	Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		M 88,9 G XL (PR-3S) ⁸⁾	Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	TH 32 S (PR-2B)	Z8	574798 R	136,96		M 108,0 G XL (PR-3S) ⁸⁾	Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	F 16*		570717	177,45		M 12 S (PR-2B)	Z8	574736 R	124,51
	F 20*		570727	177,45		M 15 S (PR-2B)	Z8	574738 R	124,51
	F 26*		570730	191,98		M 18 S (PR-2B)	Z8	574740 R	124,51
	F 32		570735	191,98		M 22 S (PR-2B)	Z8	574742 R	124,51
	F 16 S (PR-2B)**	Z8	574728 R	124,51		M 28 S (PR-2B)	Z8	574744 R	124,51
	F 20 S (PR-2B)**	Z8	574730 R	124,51		M 35 S (PR-2B)	Z8	574746 R	136,96
	F 26 S (PR-2B)**	Z8	574732 R	124,51					
	F 32 S (PR-2B)	Z8	574734 R	136,96	ILTA	M 15		570110	154,61
	Fz 40		570742	205,47		M 18		570120	154,61
	Fz 50		570747	311,35	INOX/CHIBRO	M 22		570130	154,61
	F 63 (PZ-S)		572385	645,58		M 28		570140	154,61
	H 16*		570320	168,10		M 35		570150	154,61
	H 20*		570350	168,10		M 42 (PR-3S)	Z8	572706 R	672,57
	H 26*		570370	168,10		M 54 (PR-3S)	Z8	572708 R	672,57
	H 32		570380	168,10		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	H 40 (PZ-4G)		570390	565,67		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	U 16*		570765	174,33		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	U 20*		570775	174,33		M 15 S (PR-2B)	Z8	574738 R	124,51
	U 26 ¹²⁾		570750	204,43		M 18 S (PR-2B)	Z8	574740 R	124,51
	U 32		570785	204,43		M 22 S (PR-2B)	Z8	574742 R	124,51
	U 40		570790	249,07		M 28 S (PR-2B)	Z8	574744 R	124,51
	U 50		570795	298,89		M 35 S (PR-2B)	Z8	574746 R	136,96
	U 63 (PZ-S)		572365	645,58	ILTA	M 15		570110	154,61
	B 16*		570850	203,40		M 18		570120	154,61
	B 20*		570860	203,40	INOX/CHIBRO	M 22		570130	154,61
	B 26		570870	224,16		M 28		570140	154,61
	B 32		570880	224,16	Pressfitting Cuni	M 35		570150	154,61
IDROTRADE	H 16*		570320	168,10		M 42 (PR-3S)	Z2	572706 R	672,57
Storm Multipinza	H 20*		570350	168,10		M 54 (PR-3S)	Z2	572708 R	672,57
	H 26*		570370	168,10		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	H 32		570380	168,10		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	TH 16*		570460	186,32		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	TH 20*		570470	186,32		M 15 S (PR-2B)	Z8	574738 R	124,51
	TH 26*		570475	186,32		M 18 S (PR-2B)	Z8	574740 R	124,51
	TH 32		570480	186,32		M 22 S (PR-2B)	Z8	574742 R	124,51
	THL 32		570487	186,32		M 28 S (PR-2B)	Z8	574744 R	124,51
	TH 40		570485	246,99		M 35 S (PR-2B)	Z8	574746 R	136,96
	TH 50 (PZ-S)		572400	645,58	Instantor	TH 16*		570460	186,32
	TH 63 (PZ-S)		572405	645,58		TH 20*		570470	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		TH 26*		570475	186,32
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		TH 32		570480	186,32
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	U 16*		570765	174,33		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	U 20*		570775	174,33		TH 32 S (PR-2B)	Z8	574798 R	136,96
IDROTRADE	M 15		570110	154,61	Instantor	V1 1/2" S (PR-2B)	Z8	574850 R	124,51
StormPRES ¹⁾	M 18		570120	154,61		V1 3/4" S (PR-2B)	Z8	574852 R	124,51
	M 22		570130	154,61	Copper Press Imperial	VI 1" S (PR-2B)	Z8	574854 R	124,51
	M 28		570140	154,61					
	M 35		570150	154,61	Instantor	M 15		570110	154,61
	M 42 (PR-3S)	Z8	572706 R	672,57		M 22		570130	154,61
	M 54 (PR-3S)	Z8	572708 R	672,57		M 28		570140	154,61
	M 76,1 XL (PR-3S) ⁸⁾	Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		M 15 S (PR-2B)	Z8	574738 R	124,51
	M 88,9 G XL (PR-3S) ⁸⁾	Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		M 22 S (PR-2B)	Z8	574740 R	124,51
	M 108,0 G XL (PR-3S) ⁸⁾	Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		M 28 S (PR-2B)	Z8	574742 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51		M 35 S (PR-2B)	Z8	574744 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51					
	M 22 S (PR-2B)	Z8	574742 R	124,51					
	M 28 S (PR-2B)	Z8	574744 R	124,51					
	M 35 S (PR-2B)	Z8	574746 R	136,96					

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
IPA IPANA Press	TH 10*		570467	186,32	IVAR	B 20		570860	203,40
	TH 11,6*		570482	186,32	ALPEX-GAS	B 26		570870	224,16
	TH 12*		570452	186,32		B 32		570880	224,16
	TH 14*		570455	186,32	IVAR	B 14*		570845	203,40
	TH 15*		570457	186,32	Ivar-Press	B 16*		570850	203,40
	TH 16*		570460	186,32		B 18*		570855	203,40
	TH 17*		570462	186,32		B 20*		570860	203,40
	TH 18*		570465	186,32		B 26		570870	224,16
	TH 20*		570470	186,32		B 32		570880	224,16
	TH 22*		570472	186,32		Fz 40		570742	205,47
	TH 25*		570495	186,32		Fz 50		570747	311,35
	TH 26*		570475	186,32		F 63 (PZ-S)		572385	645,58
	TH 28		570477	186,32	IVAR	TH 16*		570460	186,32
	TH 32		570480	186,32	MULTI PRESS	TH 20*		570470	186,32
	TH 40		570485	246,99	GAS ITALIA	TH 26*		570475	186,32
	TH 50 (PZ-S)		572400	645,58		H 16*		570320	168,10
	TH 63 (PZ-S)		572405	645,58		H 20*		570350	168,10
	THz 75 (PR-3B)	Z4	572829 R	609,25		H 26*		570370	168,10
	TH 10 S (PR-2B)**	Z8	574772 R	124,51		U 16*		570765	174,33
	TH 11,6 S (PR-2B)**	Z8	574774 R	124,51		U 20*		570775	174,33
	TH 12 S (PR-2B)**	Z8	574776 R	124,51	IVAR	TH 16*		570460	186,32
	TH 14 S (PR-2B)**	Z8	574778 R	124,51	Multi Press MP	TH 18*		570465	186,32
	TH 15 S (PR-2B)**	Z8	574780 R	124,51		TH 20*		570470	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		TH 25*		570495	186,32
	TH 17 S (PR-2B)**	Z8	574784 R	124,51		TH 26*		570475	186,32
	TH 18 S (PR-2B)**	Z8	574786 R	124,51		TH 32		570480	186,32
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		TH 40		570485	246,99
	TH 22 S (PR-2B)**	Z8	574790 R	124,51		TH 50 (PZ-S)		572400	645,58
	TH 25 S (PR-2B)**	Z8	574792 R	124,51		TH 63 (PZ-S)		572405	645,58
	TH 26 S (PR-2B)**	Z8	574794 R	124,51	IVAR	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 28 S (PR-2B)**	Z8	574796 R	136,96		TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 32 S (PR-2B)**	Z8	574798 R	136,96		TH 20 S (PR-2B)**	Z8	574788 R	124,51
IPA THu	TH 16*		570460	186,32		TH 25 S (PR-2B)**	Z8	574792 R	124,51
IPANA Press	TH 20*		570470	186,32		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 26*		570475	186,32		TH 32 S (PR-2B)	Z8	574798 R	136,96
	TH 32		570480	186,32		F 16*		570717	177,45
	TH 40		570485	246,99		F 18*		570720	177,45
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		F 20*		570727	177,45
	TH 20 S (PR-2B)**	Z8	574788 R	124,51	IPALPEX	TH 14*		570730	191,98
	TH 26 S (PR-2B)**	Z8	574794 R	124,51	(Industrie du Plastique et Accessoires)	TH 16*		570735	191,98
	TH 32 S (PR-2B)	Z8	574798 R	136,96		TH 18*		570742	205,47
	TH 14*		570455	186,32		F 26*		570747	311,35
	TH 16*		570460	186,32		F 32		572385	645,58
	TH 18*		570465	186,32		Fz 40		574728 R	124,51
	TH 20*		570470	186,32		Fz 50		574730 R	124,51
	TH 26*		570475	186,32		F 63 (PZ-S)		574732 R	124,51
	THL 32		570487	186,32		F 16 S (PR-2B)**	Z8	574728 R	124,51
	THL 40		570485	246,99		F 20 S (PR-2B)**	Z8	574730 R	124,51
	THL 50 (PZ-S)		572400	645,58		F 26 S (PR-2B)**	Z8	574732 R	124,51
	THL 63 (PZ-S)		572405	645,58		F 32 S (PR-2B)	Z8	574734 R	136,96
IPLEX PIPELINES AUSTRALIA	K16/P18*		572600	194,05		H 16*		570320	168,10
Iplex Pro-fit	PF 22*		571980	209,62		H 18*		570340	168,10
IPLEX PIPELINES AUSTRALIA	K16/P18*		572600	194,05		H 20*		570350	168,10
Iplex K1 (Gas)	K2/20*		572605	194,05		H 25*		570360	168,10
	K32		572610	194,05		H 26*		570370	168,10
	K1/40		572620	194,05		H 32		570380	168,10
	K1/50		572625	318,61		H 40 (PZ-4G)		570390	565,67
IPLEX PIPELINES AUSTRALIA	K16/P18*		572600	194,05		U 16*		570765	174,33
Iplex K2	K2/20*		572605	194,05		U 18*		570770	174,33
ISOLTUBEX ISOLPUBEK	RFz 16*		571325	194,05		U 20*		570775	174,33
ISOLPUBEK IPERT	RFz 20*		571330	194,05		U 25*		570780	174,33
	RFfz 25		571337	213,78		U 26* ¹²⁾		570750	204,43
	RFfz 32		571342	213,78		U 32		570785	204,43
ISOLTUBEX Multicapa	RFfz 16*		571325	194,05		U 40		570790	249,07
	RFfz 18*		571327	194,05		U 50		570795	298,89
	RFfz 20*		571330	194,05		U 63 (PZ-S)		572365	645,58
	RFfz 25		571337	213,78		B 16*		570850	203,40
	RFfz 32		571342	213,78		B 18*		570855	203,40
	U 16*		570765	174,33		B 20*		570860	203,40
	U 18*		570770	174,33		B 26		570870	224,16
	U 20*		570775	174,33		B 32		570880	224,16
	U 25*		570780	174,33	IVAR	TH 16*		570460	186,32
	U 32		570785	204,43		TH 20*		570470	186,32
	U 40		570790	249,07		TH 26*		570475	186,32
	U 50		570795	298,89		TH 32		570480	186,32
	U 63 (PZ-S)	Z4	572837 R	733,81		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	U 63 (PZ-S)		572365	645,58		TH 20 S (PR-2B)**	Z8	574788 R	124,51
ISOLTUBEX Multicapa GAS	RFfz 16*		571325	194,05		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	RFfz 20*		571330	194,05		TH 32 S (PR-2B)	Z8	574798 R	136,96
	RFfz 25		571337	213,78		F 16*		570717	177,45
	RFfz 32		571342	213,78		F 20*		570727	177,45
ISOLTUBEX Multicapa-PPSU	U 16*		570765	174,33		F 26*		570730	191,98
	U 20*		570775	174,33		F 32		570735	191,98
	U 25*		570780	174,33		F 16 S (PR-2B)**	Z8	574728 R	124,51
	U 32		570785	204,43		F 20 S (PR-2B)**	Z8	574730 R	124,51
ISOTUBI NUMEPRESS	M 15		570110	154,61		F 26 S (PR-2B)**	Z8	574732 R	124,51
	M 18 ¹⁾		570120	154,61		F 32 S (PR-2B)	Z8	574734 R	136,96
	M 22		570130	154,61		H 16*		570320	168,10
	M 28 ¹⁾		570140	154,61		H 20*		570350	168,10
	M 35		570150	154,61		H 26*		570370	168,10
	M 42 (PR-3S)	Z2	572706 R	672,57		H 32		570380	168,10
	M 54 (PR-3S)	Z2	572708 R	672,57		U 16*		570765	174,33
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 116,47		U 20*		570775	174,33
	M 88,9 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		U 26* ¹²⁾		570750	204,43
	M 108,0 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		U 32		570785	204,43
	M 15 S (PR-2B)	Z8	574738 R	124,51		B 16*		570850	203,40
	M 18 S (PR-2B)	Z8	574740 R	124,51		B 20*		570860	203,40
	M 22 S (PR-2B)	Z8	574742 R	124,51		B 26		570870	224,16
	M 28 S (PR-2B)	Z8	574744 R	124,51		B 32		570880	224,16
	M 35 S (PR-2B)	Z8	574746 R	136,96					

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
IVAR	TH 16*		570460	186,32
Plastic Multi Press	TH 20*		570470	186,32
Leak (PMPL)	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	F 16*		570717	177,45
	F 20*		570727	177,45
	F 26*		570730	191,98
	F 32		570735	191,98
	F 16 S (PR-2B)**	Z8	574728 R	124,51
	F 20 S (PR-2B)**	Z8	574730 R	124,51
	F 26 S (PR-2B)**	Z8	574732 R	124,51
	F 32 S (PR-2B)	Z8	574734 R	136,96
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 26* ⁽¹²⁾		570750	204,43
	U 32		570785	204,43
	B 16*		570850	203,40
	B 20*		570860	203,40
	B 26		570870	224,16
	B 32		570880	224,16
IVAR	TH 16*		570460	186,32
Plastic Multi Press	TH 20*		570470	186,32
PMP	TH 25*		570495	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	F 16*		570717	177,45
	F 20*		570727	177,45
	F 26*		570730	191,98
	F 32		570735	191,98
	F 16 S (PR-2B)**	Z8	574728 R	124,51
	F 20 S (PR-2B)**	Z8	574730 R	124,51
	F 26 S (PR-2B)**	Z8	574732 R	124,51
	F 32 S (PR-2B)	Z8	574734 R	136,96
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 25*		570360	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 26* ⁽¹²⁾		570750	204,43
	U 32		570785	204,43
	B 16*		570850	203,40
	B 20*		570860	203,40
	B 26		570870	224,16
	B 32		570880	224,16
IVT Edelstahl-Presssystem	M 15		570110	154,61
	M 18 ⁽¹⁾		570120	154,61
	M 22		570130	154,61
	M 28 ⁽¹⁾		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
IVT PRIPRESS	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	F 16*		570717	177,45
	F 20*		570727	177,45
	F 26*		570730	191,98
	F 32		570735	191,98
	F 16 S (PR-2B)**	Z8	574728 R	124,51
	F 20 S (PR-2B)**	Z8	574730 R	124,51
	F 26 S (PR-2B)**	Z8	574732 R	124,51
	F 32 S (PR-2B)	Z8	574734 R	136,96
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 26* ⁽¹²⁾		570750	204,43
	U 32		570785	204,43
	B 16*		570850	203,40
	B 20*		570860	203,40
	B 26		570870	224,16
	B 32		570880	224,16
Jäger - Aquatec	H 14*		570310	168,10
Aquapress H	H 16*		570320	168,10
	H 17*		570330	168,10
	H 18*		570340	168,10
	H 20*		570350	168,10
Jäger - Aquatec	H 26*		570370	168,10
	H 32		570380	168,10
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PZ-S)		572365	645,58
Jäger - Aquatec	M 15		570110	154,61
C-Stahl -	M 18		570120	154,61
Press Typ M	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
Jäger - Aquatec	V 15		570115	154,61
Kupfer -	V 18		570125	154,61
Press Typ V	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Jansen AG JANSEN COMISA	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
Jaraflex- Presssystem	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 17*		570462	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Z8	574784 R	124,51
	TH 18 S (PR-2B)**	Z8	574786 R	124,51
JUNGWOO JWPress	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	VUS ½" (OD 15,9 mm)		571770	186,79
	VUS ¾" (OD 22,2 mm)		571775	186,79
	VUS 1" (OD 28,6 mm)		571780	186,79
	VUS 1¼" (OD 34,9 mm)		571785	186,79
KAN	VUS 1½" (OD 41,3 mm)		571790	360,13
	VUS 2" (OD 54,0 mm)		571795	370,51
	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	609,25
	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	609,25
	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	645,58

K

KAN	U 14*		570760	174,33
KAN-therm Press LBP	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 26* ¹²⁾		570750	204,43
	U 32		570785	204,43
	U 40		570790	249,07
	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
KAN	M 15		570110	154,61
KAN-therm Inox	M 18 ¹⁾		570120	154,61
	M 22		570130	154,61
	M 28 ¹⁾		570140	154,61
	M 35		570150	154,61
	M 42 (PZ-4G)		570160	498,19
	M 54 (PZ-4G)		570170	498,19
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
KAN	M 12		570100	154,61
KAN-therm Steel	M 15		570110	154,61
	M 18 ¹⁾		570120	154,61
	M 22		570130	154,61
	M 28 ¹⁾		570140	154,61
	M 35		570150	154,61
	M 42 (PZ-4G)		570160	498,19
	M 54 (PZ-4G)		570170	498,19
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	XP 66,7 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579108 R	1 161,47
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 12 S (PR-2B)	Z8	574736 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
KAN	U 14*		570760	174,33
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 26* ¹²⁾		570750	204,43
	U 32		570785	204,43
	U 40		570790	249,07
	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 26*		570475	186,32
KE KELIT	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	Kupfer		570130	154,61
	M 22		570140	154,61
COPPERFIX	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
	KE KELIT		570110	154,61
KELOX	M 15		570120	154,61
	M 18		570130	154,61
	M 22		570140	154,61
	M 28		570150	154,61
	M 35		570160	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
KELOX-PPSU-W	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
	KE KELIT		570765	174,33
	KELOX-ULTRAX		570770	174,33
	U 18*		570775	174,33
	U 20*		570780	174,33
	U 25*		570785	174,33
	U 32		570788	204,43
	U 40		570790	249,07
KE KELIT	U 50		570795	298,89
	U 63 (PZ-S)		572365	645,58
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 75 (PR-3B)	Z4	572828 R	645,58
	KF KELIT		570765	174,33
	KELOX-WINDOX-U		570770	174,33
	U 18*		570775	174,33
	U 20*		570780	174,33
	U 25*		570785	174,33
	U 32		570788	204,43
	U 40		570790	249,07
KE KELIT	U 50		570795	298,89
	U 63 (PZ-S)		572365	645,58
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 75 (PR-3B)	Z4	572828 R	645,58
	KE KELIT		570765	174,33
	steelFIX		570770	174,33
	C-Stahl		570775	174,33
	M 22		570140	154,61
	M 28		570150	154,61
	M 35		570160	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
KE KELIT	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 12 S (PR-2B)	Z8	574736 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
KE KELIT steelFIX Edelstahl	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
KEMBLA KemPress (AUS)	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
	VAU 15 (OD 12,7 mm)		572687	159,80
	VAU 20 (OD 19,1 mm)		572689	159,80
	VAU 25 (OD 25,4 mm)		572691	159,80
	VAU 32 (OD 31,8 mm)		572693	168,10
	VAU 40 (OD 38,1 mm)		572695	249,07
KEMBLA KemPress Gas (AUS)	VAU 50 (OD 50,8 mm)		572697	441,10
	VAU 15 (OD 12,7 mm)		572687	159,80
	VAU 20 (OD 19,1 mm)		572689	159,80
	VAU 25 (OD 25,4 mm)		572691	159,80
	VAU 32 (OD 31,8 mm)		572693	168,10
	VAU 40 (OD 38,1 mm)		572695	249,07
	VAU 50 (OD 50,8 mm)		572697	441,10
	KI 16*		571360	197,17
	KI 20*		571370	197,17
	KI 25*		571375	197,17
KISAN Kisan KD	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	KI 16*		571360	197,17
	KI 20*		571370	197,17
	KI 25*		571375	197,17
	KI 32		571380	265,68
KISAN Kisan WL	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	KI 16*		571360	197,17
	KI 20*		571370	197,17
KISAN Kisan WM	KI 25*		571375	197,17
	KI 32		571380	265,68
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PZ-S)		572365	645,58
	U 75 (PR-3B)		572828 R	645,58
	TH 20*		570470	186,32
KISAN Kisan WR	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
KISAN Kistal C	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
KISAN Kistal Inox	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
	VAU 15 (OD 12,7 mm)		572687	159,80
	VAU 20 (OD 19,1 mm)		572689	159,80
	VAU 25 (OD 25,4 mm)		572691	159,80
	VAU 32 (OD 31,8 mm)		572693	168,10
	VAU 40 (OD 38,1 mm)		572695	249,07
KEMBLA KemPress Gas (AUS)	VAU 50 (OD 50,8 mm)		572697	441,10
	VAU 15 (OD 12,7 mm)		572687	159,80
	VAU 20 (OD 19,1 mm)		572689	159,80
	VAU 25 (OD 25,4 mm)		572691	159,80
	VAU 32 (OD 31,8 mm)		572693	168,10
	VAU 40 (OD 38,1 mm)		572695	249,07
	VAU 50 (OD 50,8 mm)		572697	441,10
	KI 16*		571360	197,17
	KI 20*		571370	197,17
	KI 25*		571375	197,17
KISAN Kisan KD	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	KI 16*		571360	197,17
	KI 20*		571370	197,17
	KI 25*		571375	197,17
	KI 32		571380	265,68
KISAN Kisan WL	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	KI 16*		571360	197,17
	KI 20*		571370	197,17
KISAN Kisan WM	KI 25*		571375	197,17
	KI 32		571380	265,68
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PZ-S)		572365	645,58
	U 75 (PR-3B)		572828 R	645,58
	TH 20*		570470	186,32
KISAN Kisan WR	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue. See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
LK Systems LK >B<Press Gas	V 15		570115	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 54		570175	370,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
LK Systems LK Universal	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58

M

MAINCOR MAINPRESS	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PZ-S)		572365	645,58
	U 63 (PR-3B)	Z4	572837 R	733,81
MAINCOR MAINFLOR	U 16*		570765	174,33
Mair Heiztechnik M-Press	H 11,5*		570315	168,10
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574786 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
Ma.s.ter System PRESSMASTER	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	H 14*		570310	168,10
	H 16*		570320	168,10
	H 18*		570340	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	H 40 (PZ-4G)		570390	565,67
	U 14*		570760	174,33
	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
Meier Tobler Metalplast - Stramax Serie MM	H 16*		570320	168,10
	H 20*		570350	168,10
	H 25*		570360	168,10
	H 32		570380	168,10
	RFz 16*		571325	194,05
	RFz 20*		571330	194,05
	RFz 25		571335	194,05
	RFz 32		571340	194,05
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PZ-S)		572365	645,58
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572837 R	733,81

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
METALGRUP Permatubo	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
	RFz 16*		571325	194,05
	RFz 20*		571330	194,05
	RFz 25		571335	194,05
METALGRUP MultiGrup	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
Mueller Streamline PRS Copper Press	VUS ½" (OD 15,9 mm)		571770	186,79
	VUS ¾" (OD 22,2 mm)		571775	186,79
	VUS 1" (OD 28,6 mm)		571780	186,79
	VUS 1 ¼" (OD 34,9 mm)		571785	186,79
	VUS 1 ½" (OD 41,3 mm)		571790	360,13
	VUS 2" (OD 54,0 mm)		571795	370,51
	VUSFz 2 ½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	609,25
MULTITHERM PRESSSYSTEM	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	609,25
	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	645,58
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
MULTICAPAS INDUSTRIAL AIS PEX	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	THz 75 (PR-3B)	Z4	572829 R	609,25
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	RFz 16*		571325	194,05
Multicapas Industrial AIS XPRT	RFz 20*		571330	194,05
	RFz 25		571335	194,05
	RFz 32		571340	194,05
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
Multicapas Industrial multilubo systems MC	TH 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
Multicapas Industrial U 63 (PZ-S)	U 63 (PZ-S)		572365	645,58
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 75 (PR-3B)	Z4	572828 R	645,58
	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
Multicapas Industrial U 63 (PZ-S)	U 20*		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PZ-S)		572365	645,58
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 75 (PR-3B)	Z4	572828 R	645,58

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Multicapas Industrial	H 16*		570320	168,10
multitubo systems MM H 20*			570350	168,10
H 25*			570360	168,10
H 26*			570370	168,10
H 32			570380	168,10
RFz 16*			571325	194,05
RFz 20*			571330	194,05
RFz 25			571335	194,05
RFz 32			571340	194,05
TH 16*			570460	186,32
TH 20*			570470	186,32
TH 25*			570495	186,32
TH 26*			570475	186,32
TH 32			570480	186,32
TH 40			570485	246,99
TH 50 (PZ-S)			572400	645,58
TH 63 (PZ-S)			572405	645,58
THz 75 (PR-3B)	Z4		572829 R	609,25
TH 16 S (PR-2B)**	Z8		574782 R	124,51
TH 20 S (PR-2B)**	Z8		574788 R	124,51
TH 25 S (PR-2B)**	Z8		574792 R	124,51
TH 26 S (PR-2B)**	Z8		574794 R	124,51
TH 32 S (PR-2B)	Z8		574798 R	136,96
U 16*			570765	174,33
U 20*			570775	174,33
U 25*			570780	174,33
U 32			570785	204,43
U 40			570790	249,07
U 50			570795	298,89
U 63 (PZ-S)			572365	645,58
U 63 (PR-3B)	Z4		572837 R	733,81
U 75 (PR-3B)	Z4		572828 R	645,58
multipipe Deutschland	TH 16*		570460	186,32
multipipe mp	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96

N

NEUTHERM	H 16*		570320	168,10
MEKUPRESS-HT	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	H 40 (PZ-4G)		570390	565,67
	U 40		570790	249,07
NIBCO	VUS ½" (OD 15,9 mm)		571770	186,79
Press System	VUS ¾" (OD 22,2 mm)		571775	186,79
Copper	VUS 1" (OD 28,6 mm)		571780	186,79
	VUS 1¼" (OD 34,9 mm)		571785	186,79
	VUS 1½" (OD 41,3 mm)		571790	360,13
	VUS 2" (OD 54,0 mm)		571795	370,51
NICOLL FLUXO	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	THz 75 (PR-3B)	Z4	572829 R	609,25
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
NUPI Industrie	B 16*		570850	203,40
Italiene	B 18*		570855	203,40
Multinupi	B 20*		570860	203,40
	B 26		570870	224,16
	B 32		570880	224,16
	F 16*		570717	177,45
	F 18*		570720	177,45
	F 20*		570727	177,45
	F 26*		570730	191,98
	F 32		570735	191,98
	F 16 S (PR-2B)**	Z8	574728 R	124,51
	F 20 S (PR-2B)**	Z8	574730 R	124,51
	F 26 S (PR-2B)**	Z8	574732 R	124,51
	F 32 S (PR-2B)	Z8	574734 R	136,96
	H 16*		570320	168,10
	H 18*		570340	168,10
	H 20*		570350	168,10
	H 25*		570360	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 25*		570475	186,32
	TH 26*		570478	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 14*		570760	174,33
	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 26*	¹²⁾	570785	204,43
	U 32		570788 R	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
	Nussbaum	VMP ⅝" (OD 17,2 mm)	571740	214,81
	Optifit-Press	VMP ½" G (OD 21,3 mm)	571766 R	214,81
		VMP ¾" (OD 26,9 mm)	571764	214,81
		VMP 1" (OD 33,7 mm)	571767	214,81
		VMP 1 ½" (PZ-S) (OD 42,4 mm)	572413	704,75
		VMP 2 ½" (PR-3B) (OD 48,3 mm)	572844 R	479,50
		VMP 2" (PR-3B) (OD 60,3 mm)	572845 R	479,50
	Nussbaum	VRX 16	571750	196,13
	Optiflex-Flowpress	VRX 20	571752	196,13
		VRX 25	571754	214,81
		VRX 32	571756	214,81
		VRX 40	571758	298,89
		VRX 50	571760	348,72
		VRX 63	571797	560,47
	Nussbaum	V 15	570115	154,61
	Optipress	V 18	570125	154,61
	Aquaplus	V 22	570135	154,61
		V 28	570145	154,61
		V 35	570155	154,61
		V 42	570165	360,13
		V 42 (PR-2B)	572850 R	322,77
		V 54	570175	370,51
		V 54 (PR-2B)	572851 R	348,72
		Vfz 64,0 (PR-3B)	572815 R	609,25
		Vfz 76,1 (PR-3B)	572816 R	609,25
		Vfz 88,9 (PR-3B)	572817 R	645,58
		Vfz 108,0 (PR-3B)	572818 R	645,58
		V 15 S (PR-2B)	574752 R	124,51
		V 18 S (PR-2B)	574756 R	124,51
		V 22 S (PR-2B)	574758 R	124,51
		V 28 S (PR-2B)	574760 R	124,51
		V 35 S (PR-2B)	574762 R	136,96

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Nussbaum	V 15		570115	154,61
Optipress-Gaz	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	VFz 64,0 (PR-3B)	Z5	572815 R	609,25
	VFz 76,1 (PR-3B)	Z5	572816 R	609,25
	VFz 88,9 (PR-3B)	Z5	572817 R	645,58
	VFz 108,0 (PR-3B)	Z5	572818 R	645,58
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

Nussbaum	V 15		570115	154,61
Optipress-Therm	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	VFz 64,0 (PR-3B)	Z5	572815 R	609,25
	VFz 76,1 (PR-3B)	Z5	572816 R	609,25
	VFz 88,9 (PR-3B)	Z5	572817 R	645,58
	VFz 108,0 (PR-3B)	Z5	572818 R	645,58
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

0

Oventrop	H 16 A*		570620	214,81
Cofit P	H 20 A*		570650	214,81
	H 26 A*		570670	214,81
	H 32 A		570680	214,81
	H 40 A		570690	373,63
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
Oventrop	H 16 A*		570620	214,81

Oventrop	H 16 A	570650	214,81
Cofit PD	H 20 A*	570670	214,81
	H 26 A*		
Oventrop	H 16 A*	570620	214,81
Cofit PDK	H 20 A*	570650	214,81
Oventrop	H 16 A*	570620	214,81
Cofit PD-HT	H 20 A*	570650	214,81
	H 25 A*	570660	214,81
	H 32 A	570680	214,81
Oventrop	H 16 A*	570620	214,81
Cofit PDK-HT	H 20 A*	570650	214,81

P

PBTub	RFz 12*	571320	194,05
SERTIPRESS	RFz 16*	571325	194,05
	RFz 20*	571330	194,05
	RFz 25	571335	194,05
PBTub	M 15	570110	154,61
SERTI-STEEL	M 18	570120	154,61
	M 22	570130	154,61
	M 28	570140	154,61
	M 35	570150	154,61
	M 42 (PR-3S)	Z2	572706 R
	M 54 (PR-3S)	Z2	572708 R
	M 15 S (PR-2B)	Z8	574738 R
	M 18 S (PR-2B)	Z8	574740 R
	M 22 S (PR-2B)	Z8	574742 R
	M 28 S (PR-2B)	Z8	574744 R
	M 35 S (PR-2B)	Z8	574746 R

Pegler Yorkshire	> Aalberts integrated piping systems		
PERFEXIM	U 16*	570765	174,33
PERFEKT	U 20*	570775	174,33
SYSTEM	U 25*	570780	174,33
	U 32	570785	204,43
PERFEXIM	U 16*	570765	174,33
PERFEKT	U 20*	570775	174,33
SYSTEM PLUS	U 25*	570780	174,33
	U 32	570785	204,43
	U 40	570790	249,07
	U 50	570795	298,89
	U 63 (PZ-S)	572365	645,58
	TH 16*	570460	186,32
	TH 20*	570470	186,32
	TH 25*	570495	186,32
	TH 32	570480	186,32
	TH 40	570485	246,99
	TH 50 (PZ-S)	572400	645,58
	TH 63 (PZ-S)	572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R
	TH 20 S (PR-2B)**	Z8	574788 R
	TH 25 S (PR-2B)**	Z8	574792 R
	TH 32 S (PR-2B)	Z8	574798 R

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
PERFILTUBO	U 16*		570765	174,33
PERFILALUPEX	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
	U 75 (PR-3B)	Z4	572828 R	645,58
PERFILTUBO	M 15		570110	154,61
PERFILPRESS	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579101 R	1 161,47
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
PEXTUBE	RFz 16*		571325	194,05
PexTube	RFz 20*		571330	194,05
	RFIz 25		571337	213,78
	RFIz 32		571342	213,78
Pipeline	M 15		570110	154,61
C-PRESS	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579110 R	1 355,58
	M 108,0 GXL (PR-3S)	Z6 XL ⁽³⁾ / Z7 XL 45 kN ⁽⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
Pipeline	TH 16*		570460	186,32
RADOPRESS	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
Pipetec Connect	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
PLASTICA ALFA	TH 16*		570460	186,32
Multiplex	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
PLASTICA ALFA	TH 16*		570460	186,32
Multiplex Air	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
PLASTICA ALFA	TH 16*		570460	186,32
Multiplexalpha Gas	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
PLASTICA ALFA	TH 16*		570460	186,32
Multiplexalpha Gas protek	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
PLASTICA ALFA	TH 16*		570460	186,32
Multiplex Plus	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
PLASTICA ALFA	TH 16*		570460	186,32
Multypex Thermo	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
PLASTICA ALFA	TH 16*		570460	186,32
Multypex Thermo Plus	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
PLÁSTICOS FERRO	U 16*		570765	174,33
FERROPLAST	U 20*		570775	174,33
GPF MULT Pressfitting	U 25*		570780	174,33
MULTICAPA	U 32		570785	204,43
PLÁSTICOS FERRO	U 16*		570765	174,33
FERROPLAST	U 20*		570775	174,33
GPF PPSU	U 25*		570780	174,33
Pressfitting PEX	U 32		570785	204,43
y MULTICAPA				
PLÁSTICOS FERRO	RFz 16*		571325	194,05
FERROPLAST	RFz 20*		571330	194,05
GPF PRESS	RFz 25		571335	194,05
Pressfitting PEX	RFz 32		571340	194,05
PLUMBING PLUS	K16/P18*		572600	194,05
EZIPEX Crimp (AUS)	K/20*		572605	194,05
	K/25*		572610	194,05
	K32		572615	194,05
	K1/40		572620	194,05
	K1/50		572625	318,61
PLUMBING PLUS	K16/P18*		572600	194,05
EZIPEX Gas (AUS)	K/20*		572605	194,05
	K/25*		572610	194,05
	K32		572615	194,05
	K1/40		572620	194,05
	K1/50		572625	318,61
PLUMBING PLUS	VAU 15 (OD 12,7 mm)		572687	159,80
EZIPRESS Gas (AUS)	VAU 20 (OD 19,1 mm)		572689	159,80
	VAU 25 (OD 25,4 mm)		572691	159,80
	VAU 32 (OD 31,8 mm)		572693	168,10
	VAU 40 (OD 38,1 mm)		572695	249,07
	VAU 50 (OD 50,8 mm)		572697	441,10
	VAUFz 65 (PR-3B) (OD 63,5 mm)	Z5	572839 R	609,25
	VAUFz 80 (PR-3B) (OD 76,2 mm)	Z5	572840 R	609,25
	VAUFz 100 (PR-3B) (OD 101,6 mm)	Z5	572841 R	645,58
PLUMBING PLUS	VAU 15 (OD 12,7 mm)		572687	159,80
EZIPRESS Solar (AUS)	VAU 20 (OD 19,1 mm)		572689	159,80
	VAU 25 (OD 25,4 mm)		572691	159,80
	VAU 15 S (PR-2B) (OD 12,7 mm)	Z8	574804 R	124,51
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Z8	574806 R	124,51
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Z8	574808 R	136,96
PLUMBING PLUS	VAU 15 (OD 12,7 mm)		572687	159,80
EZIPRESS Water (AUS)	VAU 20 (OD 19,1 mm)		572689	159,80
	VAU 25 (OD 25,4 mm)		572691	159,80
	VAU 32 (OD 31,8 mm)		572693	168,10
	VAU 40 (OD 38,1 mm)		572695	249,07
	VAU 50 (OD 50,8 mm)		572697	441,10
	VAUFz 65 (PR-3B) (OD 63,5 mm)	Z5	572839 R	609,25
	VAUFz 80 (PR-3B) (OD 76,2 mm)	Z5	572840 R	609,25
	VAUFz 100 (PR-3B) (OD 101,6 mm)	Z5	572841 R	645,58
	VAU 15 S (PR-2B) (OD 12,7 mm)	Z8	574804 R	124,51
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Z8	574806 R	124,51
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Z8	574808 R	136,96
POLYPIPE	TH 10*		570467	186,32
POLYSURE	TH 15*		570457	186,32
	TH 22*		570472	186,32
	TH 28		570477	186,32

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
POLYSAN	M 15		570110	154,61
Handelsges.	M 18		570120	154,61
m.b.H. & Co KG (Krems/Öster-reich)	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
POLYSAN-C-Stahl-Press-	M 42 (PR-3S)	Z2	572706 R	672,57
System M	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579112 R	1 355,58
	M 15 S (PR-2B)	Z8	574744 R	136,96
POLYSAN	M 15		570110	154,61
Handelsges.	M 18		570120	154,61
m.b.H. & Co KG (Krems/Öster-reich)	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
POLYSAN-Edelstahl	M 42 (PR-3S)	Z2	572706 R	672,57
Press-System 1.4520	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
POLYSAN	M 15		570110	154,61
Handelsges.	M 18		570120	154,61
m.b.H. & Co KG (Krems/Öster-reich)	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
POLYSAN-Edelstahl	M 42 (PR-3S)	Z2	572706 R	672,57
Press-System Gas	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 22 S (PR-2B)	Z8	574740 R	124,51
	M 28 S (PR-2B)	Z8	574742 R	124,51
	M 35 S (PR-2B)	Z8	574744 R	124,51
POLYSAN	M 15		570110	154,61
Handelsges.	M 18		570120	154,61
m.b.H. & Co KG (Krems/Öster-reich)	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
POLYSAN-Edelstahl	M 42 (PR-3S)	Z2	572706 R	672,57
Press-System Wasser	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
POLYSAN	TH 14*		570455	186,32
Handelsges.	TH 16*		570460	186,32
m.b.H. & Co KG (Krems/Öster-reich)	TH 17*		570462	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
POLYSAN-Press-System	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 75 (PZ-S)		572405	645,58
	TH 75 PR-3B	Z4	572829 R	609,25
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 14 S (PR-2B)**	Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Z8	574784 R	124,51
	TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

3) Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

5) For taking suitable pressing inserts.

6) Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

7) Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

8) For making press joints for operating pressure ≤ PN 10.

9) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

10) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

11) Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

12) Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Österreich)	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 17*		570462	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
POLYSAN-Henco-Press-System	TH 26*		570475	186,32
	HE 32		571900	223,12
	HEz 40		571904 R	323,80
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Z8	574784 R	124,51
	TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
POLYSAN (España) „Rainbow“	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
Prandelli Multyrama Pf	H 14*		570310	168,10
	H 16*		570320	168,10
	H 18*		570340	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Z8	574784 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
Purmo Cleverfit Radial	F 16*		570717	177,45
	F 20*		570727	177,45
	F 26*		570730	191,98
	F 32		570735	191,98
	F 16 S (PR-2B)**	Z8	574728 R	124,51
	F 20 S (PR-2B)**	Z8	574730 R	124,51
	F 26 S (PR-2B)**	Z8	574732 R	124,51
	F 32 S (PR-2B)	Z8	574734 R	136,96
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 17*		570462	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Z8	574784 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 32		570785	204,43
	VP 16*		570910	185,75
	VP 20*		570915	185,75
	VP 25		570920	185,75

R

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Raccorderie	M 15		570110	154,61
Metalliche	M 18		570120	154,61
aesPRES ⁱⁱ	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S) ⁱⁱ	Z2 XL 45 kN ⁱⁱ	579101 R	1 161,47
	M 88,9 G XL (PR-3S) ⁱⁱ	Z2 XL 45 kN ⁱⁱ	579110 R	1 355,58
	M 108,0 G XL (PR-3S) ⁱⁱ	Z2 XL 45 kN ⁱⁱ	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
Raccorderie	M 15		570110	154,61
Metalliche	M 18		570120	154,61
MARINEPRES ⁱⁱ	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S) ⁱⁱ	Z2 XL 45 kN ⁱⁱ	579101 R	1 161,47
	M 88,9 G XL (PR-3S) ⁱⁱ	Z2 XL 45 kN ⁱⁱ	579110 R	1 355,58
	M 108,0 G XL (PR-3S) ⁱⁱ	Z2 XL 45 kN ⁱⁱ	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
RBM Tita-fix	B 14*		570845	203,40
	B 16*		570850	203,40
	B 18*		570855	203,40
	B 20*		570860	203,40
	B 26		570870	224,16
	F 16*		570717	177,45
	F 18*		570720	177,45
	F 20*		570727	177,45
	F 16 S (PR-2B)**	Z8	574728 R	124,51
	F 20 S (PR-2B)**	Z8	574730 R	124,51
	H 14*		570310	168,10
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 14*		570760	174,33
	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
RBM Tita-gas	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
Redi Nicoll Fluxo	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 75 (PR-3B)	Z4	572829 R	609,25
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
Redi Nicoll Fluxo Gas	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
RIFENG U PRESS FITTING (F5)	U 14*		570760	174,33	Rubinetterie Bresciane Bonomi TURBO INOX GAS	M 15		570110	154,61
	U 16*		570765	174,33		M 18		570120	154,61
	U 18*		570770	174,33		M 22		570130	154,61
	U 20*		570775	174,33		M 28		570140	154,61
	U 25*		570780	174,33		M 35		570150	154,61
	U 32		570785	204,43		M 42 (PR-3S)	Z2	572706 R	672,57
	U 40		570790	249,07		M 54 (PR-3S)	Z2	572708 R	672,57
	U 50		570795	298,89		M 55 (PR-2B)	Z8	574738 R	124,51
	U 63 (PZ-S)		572365	645,58		M 18 S (PR-2B)	Z8	574740 R	124,51
	U 63 (PR-3B)	Z4	572837 R	733,81		M 22 S (PR-2B)	Z8	574742 R	124,51
	U 75 (PR-3B)	Z4	572828 R	645,58		M 28 S (PR-2B)	Z8	574744 R	124,51
						M 35 S (PR-2B)	Z8	574746 R	136,96
RIFENG TH PRESS FITTING (F9)	TH 16*		570460	186,32	Rubinetterie Bresciane Bonomi TURBO STEEL	M 15		570110	154,61
	TH 20*		570470	186,32		M 18		570120	154,61
	TH 25*		570495	186,32		M 22		570130	154,61
	TH 26*		570475	186,32		M 28		570140	154,61
	TH 32		570480	186,32		M 35		570150	154,61
	TH 40		570485	246,99		M 42 (PR-3S)	Z2	572706 R	672,57
RIQUIER A SERTIR	TH 50 (PZ-S)		572400	645,58		M 54 (PR-3S)	Z2	572708 R	672,57
	TH 63 (PZ-S)		572405	645,58		M 55 (PR-2B)	Z8	574738 R	124,51
	RFz 12*		571320	194,05		M 18 S (PR-2B)	Z8	574740 R	124,51
	RFz 16*		571325	194,05		M 22 S (PR-2B)	Z8	574742 R	124,51
RIQUIER Système multicouche	RFz 20*		571330	194,05		M 28 S (PR-2B)	Z8	574744 R	124,51
	RFz 25		571335	194,05		M 35 S (PR-2B)	Z8	574746 R	136,96
	TH 16*		570460	186,32	Rubinetterie Bresciane Bonomi TURBO PRESS	M 76,1 XL (PR-3S)	Z2	579101 R	1 116,47
	TH 20*		570470	186,32		M 88,9 G XL (PR-3S)	Z2	579110 R	1 355,58
	TH 26*		570475	186,32		M 108,0 G XL (PR-3S)	Z2	579111 R	1 355,58
	TH 32		570480	186,32		M 18 S (PR-2B)	Z8	574738 R	124,51
	TH 40		570485	246,99		M 22 S (PR-2B)	Z8	574740 R	124,51
	TH 50 (PZ-S)		572400	645,58		M 28 S (PR-2B)	Z8	574742 R	124,51
	TH 63 (PZ-S)		572405	645,58		M 35 S (PR-2B)	Z8	574744 R	124,51
	TH 14 S (PR-2B)**	Z8	574782 R	124,51		H 14*		570845	203,40
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		H 16*		570850	203,40
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		H 18*		570855	203,40
	TH 32 S (PR-2B)	Z8	574798 R	136,96		H 20*		570860	203,40
Roth PressCheck	U 16*		570765	174,33		H 26*		570870	224,16
	U 20*		570775	174,33		H 32		570880	224,16
	U 32		570785	204,43		TH 14*		570910	168,10
	U 40		570790	249,07		TH 16*		570930	168,10
	U 50		570795	298,89		H 14*		570932	168,10
	RN 14*		572672	174,33		H 16*		570940	168,10
	RN 16		572670	174,33		H 18*		570945	168,10
	RN 17*		572674	174,33		H 20*		570950	168,10
	RN 20*		572676	174,33		H 26*		570970	168,10
	RN 25/26		572678	174,33		H 32		570980	168,10
Rubinetterie Bresciane Bonomi TURBO CuNi	RN 32		572680	204,43		TH 14*		570990	168,10
	RN 40 (PR-3S)	Z2	572714 R	672,57		TH 16*		570995	168,10
	RN 50 (PR-3S)	Z2	572716 R	672,57		H 16*		570455	186,32
	RNz 63 (PR-3B)	Z4	572836 R	733,81		H 18*		570460	186,32
	M 15		570110	154,61		H 20*		570465	186,32
	M 18		570120	154,61		H 26*		570470	186,32
Rubinetterie Bresciane Bonomi TURBO INOX	M 22		570130	154,61		H 32		570475	186,32
	M 28		570140	154,61		TH 40		570480	186,32
	M 35		570150	154,61		TH 50 (PZ-S)		570485	246,99
	M 42 (PR-3S)	Z2	572706 R	672,57		TH 63 (PZ-S)		572400	645,58
	M 54 (PR-3S)	Z2	572708 R	672,57		TH 16 S (PR-2B)**	Z8	572405	645,58
	M 76,1 XL (PR-3S)	Z2	579101 R	1 161,47		TH 20 S (PR-2B)**	Z8	574782 R	124,51
	M 88,9 G XL (PR-3S)	Z2	579110 R	1 355,58		TH 26 S (PR-2B)**	Z8	574788 R	124,51
	M 108,0 G XL (PR-3S)	Z2	579111 R	1 355,58		TH 32 S (PR-2B)	Z8	574794 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51		U 14*		574798 R	136,96
	M 18 S (PR-2B)	Z8	574740 R	124,51		U 16*		570760	174,33
	M 22 S (PR-2B)	Z8	574742 R	124,51		U 18*		570770	174,33
	M 28 S (PR-2B)	Z8	574744 R	124,51		U 20*		570775	174,33
	M 35 S (PR-2B)	Z8	574746 R	136,96		U 26* ¹²⁾		570750	204,43
Rubinetterie Bresciane Bonomi TURBO INOX GAS	H 14*		570110	154,61		U 32		570785	204,43
	H 16*		570120	154,61		Rubinetterie	TH 16*	570460	186,32
	H 18*		570130	154,61		Bresciane	TH 20*	570470	186,32
	H 20*		570140	154,61		Bonomi	TH 26*	570475	186,32
	H 26*		570150	154,61		TURBO PRESS	TH 32	570480	186,32
	H 32		570160	154,61		GAS	TH 16 S (PR-2B)**	574782 R	124,51
Rubinetterie Bresciane Bonomi TURBO INOX	TH 14*		570110	154,61		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 16*		570120	154,61		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 18*		570130	154,61		TH 32 S (PR-2B)	Z8	574798 R	136,96
	TH 20*		570140	154,61		U 14*		570760	174,33
	TH 26*		570150	154,61		U 16*		570765	174,33
	TH 32		570160	154,61		U 18*		570770	174,33
Rubinetterie Bresciane Bonomi TURBO INOX	TH 40		572706 R	672,57		U 20*		570775	174,33
	TH 50 (PZ-S)	Z2	572708 R	672,57		U 26*	¹²⁾	570780	204,43
	TH 63 (PZ-S)	Z2	579101 R	1 161,47		U 32		570785	204,43
	TH 16 S (PR-3S)	Z2	579110 R	1 355,58		Rubinetterie	TH 16*	570460	186,32
	TH 88,9 G XL (PR-3S)	Z2	579110 R	1 355,58		Bresciane	TH 20*	570470	186,32
	TH 108,0 G XL (PR-3S)	Z2	579111 R	1 355,58		Bonomi	TH 26*	570475	186,32
	M 15 S (PR-2B)	Z8	574738 R	124,51		TURBO PRESS	TH 32	570480	186,32
	M 18 S (PR-2B)	Z8	574740 R	124,51		GAS	TH 16 S (PR-2B)**	574782 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96		TH 32 S (PR-2B)	Z8	574798 R	136,96

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
S									
SA.MI PLASTIC	TH 14*		570455	186,32	SANHA-NiroSan	SA 15		570935	185,75
	TH 16*		570460	186,32	Gas Presssystem	SA 18		570940	185,75
	TH 18*		570465	186,32	Serie 17000	SA 22		570945	185,75
	TH 20*		570470	186,32		SA 28		570950	185,75
	TH 26*		570475	186,32		SA 35		570955	185,75
	TH 32		570480	186,32		M 15		570110	154,61
	TH 40		570485	246,99		M 18		570120	154,61
	TH 50 (PZ-S)		572400	645,58		M 22		570130	154,61
	TH 63 (PZ-S)		572405	645,58		M 28		570140	154,61
	TH 14 S (PR-2B)**	Z8	574778 R	124,51		M 35		570150	154,61
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		M 42 (PR-3S)	Z2	572706 R	672,57
	TH 18 S (PR-2B)**	Z8	574786 R	124,51		M 54 (PR-3S)	Z2	572708 R	672,57
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		M 76,1 XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		M 88,9 G XL (PR-3S) ⁷⁾	Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	TH 32 S (PR-2B)	Z8	574798 R	136,96		M 108,0 G XL (PR-3S) ⁷⁾	Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
SA.MI PLASTIC Multistrato Gas	TH 16*		570460	186,32		M 15 S (PR-2B)	Z8	574738 R	124,51
	TH 20*		570470	186,32		M 18 S (PR-2B)	Z8	574740 R	124,51
	TH 26*		570475	186,32		M 22 S (PR-2B)	Z8	574742 R	124,51
	TH 32		570480	186,32		M 28 S (PR-2B)	Z8	574744 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		V 15	Z8	574746 R	136,96
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		V 18	Z8	574750 R	322,77
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		V 22	Z8	574755 R	370,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96		V 28	Z8	574758 R	348,72
SANHA 3fit-Press Pb-free Serie 25000	B 16*		570850	203,40		V 35	Z8	574762 R	124,51
	B 20*		570860	203,40	SANHA-NiroSan	SA 15		570935	185,75
	B 26		570870	224,16	Industry	SA 18		570940	185,75
	B 32		570880	224,16	Presssystem	SA 22		570945	185,75
	F 16*		570717	177,45	Serie 18000	SA 28		570950	185,75
	F 20*		570727	177,45		SA 35		570955	185,75
	F 26*		570730	191,98		M 15		570110	154,61
	F 32		570735	191,98		M 18		570120	154,61
	F 40		570742	205,47		M 22		570130	154,61
	F 50		570747	311,35		M 28		570140	154,61
	F 63 (PZ-S)		572385	645,58		M 35		570150	154,61
	F 16 S (PR-2B)**	Z8	574728 R	124,51		M 42 (PR-3S)	Z2	572706 R	672,57
	F 20 S (PR-2B)**	Z8	574730 R	124,51		M 54 (PR-3S)	Z2	572708 R	672,57
	F 26 S (PR-2B)**	Z8	574732 R	124,51		XP 64,0 XL / Z7 XL 45 kN ⁴⁾	Z7 XL 45 kN ⁴⁾	579100 R	1 056,63
	F 32 S (PR-2B)	Z8	574734 R	136,96		Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	H 16*		570320	168,10		Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	H 20*		570350	168,10		M 88,9 G XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	H 26*		570370	168,10		M 108,0 G XL (PR-3S)	Z7 XL 45 kN ⁴⁾	579112 R	1 355,58
	H 32		570380	168,10		Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	Z7 XL 45 kN ⁴⁾	579113 R	1 355,58
	H 40 (PZ-4G)		570390	565,67		M 15 S (PR-2B)	Z8	574738 R	124,51
	TH 16*		570460	186,32		M 18 S (PR-2B)	Z8	574740 R	124,51
	TH 20*		570470	186,32		M 22 S (PR-2B)	Z8	574742 R	124,51
	TH 26*		570475	186,32		M 28 S (PR-2B)	Z8	574744 R	124,51
	TH 32		570480	186,32		M 35 S (PR-2B)	Z8	574746 R	136,96
	TH 40		570485	246,99		V 15	Z8	570115	154,61
	TH 50 (PZ-S)		572400	645,58		V 18	Z8	570125	154,61
	TH 63 (PZ-S)		572405	645,58		V 22	Z8	570135	154,61
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		V 28	Z8	570145	154,61
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		V 35	Z8	570155	154,61
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		V 42	Z2	570165	360,13
	TH 32 S (PR-2B)	Z8	574798 R	136,96		V 54	Z2	572850 R	322,77
	U 16*		570765	174,33		V 54	Z2	570175	370,51
	U 20*		570775	174,33		V 54 (PR-2B)	Z2	572851 R	348,72
	U 26* ¹²⁾		570750	204,43		V 15 S (PR-2B)	Z8	574752 R	124,51
	U 32		570785	204,43		V 18 S (PR-2B)	Z8	574756 R	124,51
	U 40		570790	249,07		V 22 S (PR-2B)	Z8	574758 R	124,51
	U 50		570795	298,89		V 28 S (PR-2B)	Z8	574760 R	124,51
	U 63 (PR-3B)	Z4	572837 R	733,81		V 35 S (PR-2B)	Z8	574762 R	136,96
	U 63 (PZ-S)	Z4	572365	645,58		V 42 (PR-2B)	Z2	572850 R	322,77
SANHA 3fit-Press PPSU Serie 35000	B 16*		570850	203,40		V 54	Z2	570175	370,51
	B 20*		570860	203,40		V 54 (PR-2B)	Z2	572851 R	348,72
	B 26		570870	224,16		V 15 S (PR-2B)	Z8	574752 R	124,51
	B 32		570880	224,16		V 18 S (PR-2B)	Z8	574756 R	124,51
	F 16*		570717	177,45		V 22 S (PR-2B)	Z8	574758 R	124,51
	F 20*		570727	177,45		V 28 S (PR-2B)	Z8	574760 R	124,51
	F 26*		570730	191,98		V 35 S (PR-2B)	Z8	574762 R	136,96
	F 32		570735	191,98		V 42 (PR-2B)	Z2	570175	370,51
	F 16 S (PR-2B)**	Z8	574728 R	124,51		V 54 (PR-2B)	Z2	572851 R	348,72
	F 20 S (PR-2B)**	Z8	574730 R	124,51		V 15 S (PR-2B)	Z8	574752 R	124,51
	F 26 S (PR-2B)**	Z8	574732 R	124,51		V 18 S (PR-2B)	Z8	574756 R	124,51
	F 32 S (PR-2B)	Z8	574734 R	136,96		V 22 S (PR-2B)	Z8	574758 R	124,51
	H 16*		570320	168,10		V 28 S (PR-2B)	Z8	574760 R	124,51
	H 20*		570350	168,10		M 15 S (PR-2B)	Z8	574762 R	136,96
	H 26*		570370	168,10		M 18 S (PR-2B)	Z8	574764 R	124,51
	H 32		570380	168,10		M 22 S (PR-2B)	Z8	574766 R	124,51
	TH 16*		570460	186,32		M 28 S (PR-2B)	Z8	574768 R	124,51
	TH 20*		570470	186,32		M 35 S (PR-2B)	Z8	574770 R	124,51
	TH 26*		570475	186,32		V 15	Z8	570115	154,61
	TH 32		570480	186,32		V 18	Z8	570125	154,61
	TH 40		570485	246,99		V 22	Z8	570135	154,61
	TH 50 (PZ-S)		572400	645,58		V 28	Z8	570145	154,61
	TH 63 (PZ-S)		572405	645,58		V 35	Z8	570155	154,61
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		V 42	Z2	570165	360,13
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		V 54	Z2	572850 R	322,77
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		V 54	Z2	570175	370,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96		V 54	Z2	572851 R	348,72
	U 16*		570765	174,33		V 54	Z2	570175	370,51
	U 20*		570775	174,33		V 54	Z2	572851 R	348,72
	U 26* ¹²⁾		570750	204,43		V 54	Z2	570175	370,51
	U 32		570785	204,43		V 54	Z2	570175	370,51
SANHA Heavy Steel Press	VMP ½" G (OD 21,3 mm)		571766 R	214,81		V 22	Z8	570135	154,61
	VMP ¾" G (OD 26,9 mm)		571764 R	214,81		V 28	Z8	570145	154,61
	VMP 2" 1" (OD 33,7 mm)		571767	214,81		V 35	Z8	570155	154,61
	VMP 2" 1½" (PZ-S) (OD 42,4 mm)		572413	704,75		V 42	Z2	570165	360,13
	VMP 2" 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	479,50		V 42 (PR-2B)	Z2	572850 R	322,77
	VMP 2" 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	479,50		V 54	Z2	570175	370,51
SANHA Heavy Steel Press Gas ⁹⁾	VMP ½" G (OD 21,3 mm) ¹¹⁾		571766 R	214,81		V 54 (PR-2B)	Z2	572851 R	348,72
	VMP ¾" G (OD 26,9 mm)		571764 R	214,81		V 15 S (PR-2B)	Z8	574752 R	124,51
	VMP 2" 1" (OD 33,7 mm)		571767	214,81		V 18 S (PR-2B)	Z8	574756 R	124,51
	VMP 2" 1½" (PZ-S) (OD 42,4 mm)		572413	704,75		V 22 S (PR-2B)	Z8	574758 R	124,51
	VMP 2" 1½" (PR-3B) (OD 48,3 mm)	Z5	572844 R	479,50		V 28 S (PR-2B)	Z8	574760 R	124,51
	VMP 2" 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	479,50		V 35 S (PR-2B)	Z8	574762 R	136,96

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
SANHA-NiroSan	SA 15		570935	185,75	SANHA	SA 15		570935	185,75
SF Pressystem	SA 18		570940	185,75	NiroTherm	SA 18		570940	185,75
Serie 19000 (silicone free)	SA 22		570945	185,75	Industry	SA 22		570945	185,75
	SA 28		570950	185,75	Serie 98000	SA 28		570950	185,75
	SA 35		570955	185,75		SA 35		570955	185,75
	M 15		570110	154,61		M 15		570110	154,61
	M 18		570120	154,61		M 18		570120	154,61
	M 22		570130	154,61		M 22		570130	154,61
	M 28		570140	154,61		M 28		570140	154,61
	M 35		570150	154,61		M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57		M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57		M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 15 S (PR-2B)	Z8	574738 R	124,51		M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51		M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51		M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51		M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96		M 35 S (PR-2B)	Z8	574746 R	136,96
	V 15		570115	154,61		V 15		570115	154,61
	V 18		570125	154,61		V 18		570125	154,61
	V 22		570135	154,61		V 22		570135	154,61
	V 28		570145	154,61		V 28		570145	154,61
	V 35		570155	154,61		V 35		570155	154,61
	V 42		570165	360,13		V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77		V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51		V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72		V 54 (PR-2B)	Z2	572851 R	348,72
	V 15 S (PR-2B)	Z8	574752 R	124,51		V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51		V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51		V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51		V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96		V 35 S (PR-2B)	Z8	574762 R	136,96
SANHA	SA 15		570935	185,75	SANHA-Press	SA 12		570930	269,83
NiroTherm	SA 18		570940	185,75	Chrom	SA 15		570935	185,75
Serie 91000	SA 22		570945	185,75	Serie 16000	SA 18		570940	185,75
	SA 28		570950	185,75		SA 22		570945	185,75
	SA 35		570955	185,75		SA 28		570950	185,75
	M 15		570110	154,61		M 12		570100	154,61
	M 18		570120	154,61		M 15		570110	154,61
	M 22		570130	154,61		M 18		570120	154,61
	M 28		570140	154,61		M 22		570130	154,61
	M 35		570150	154,61		M 28		570140	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57		M 12 S (PR-2B)	Z8	574736 R	124,51
	M 54 (PR-3S)	Z2	572708 R	672,57		M 15 S (PR-2B)	Z8	574738 R	124,51
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		M 18 S (PR-2B)	Z8	574740 R	124,51
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		M 22 S (PR-2B)	Z8	574742 R	124,51
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		M 28 S (PR-2B)	Z8	574744 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51		V 12		570107	154,61
	M 18 S (PR-2B)	Z8	574740 R	124,51		V 15		570115	154,61
	M 22 S (PR-2B)	Z8	574742 R	124,51		V 18		570125	154,61
	M 28 S (PR-2B)	Z8	574744 R	124,51		V 22		570135	154,61
	M 35 S (PR-2B)	Z8	574746 R	136,96		V 28		570145	154,61
	V 15		570115	154,61		V 12 S (PR-2B)	Z8	574748 R	124,51
	V 18		570125	154,61		V 15 S (PR-2B)	Z8	574752 R	124,51
	V 22		570135	154,61		V 18 S (PR-2B)	Z8	574756 R	124,51
	V 28		570145	154,61		V 22 S (PR-2B)	Z8	574758 R	124,51
	V 35		570155	154,61		V 28 S (PR-2B)	Z8	574760 R	124,51
	V 42		570165	360,13					
	V 42 (PR-2B)	Z2	572850 R	322,77					
	V 54		570175	370,51					
	V 54 (PR-2B)	Z2	572851 R	348,72					
	V 15 S (PR-2B)	Z8	574752 R	124,51					
	V 18 S (PR-2B)	Z8	574756 R	124,51					
	V 22 S (PR-2B)	Z8	574758 R	124,51					
	V 28 S (PR-2B)	Z8	574760 R	124,51					
	V 35 S (PR-2B)	Z8	574762 R	136,96					

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
SANHA-Press	SA 12		570930	269,83
GAS Pressfittings	SA 14		570932	269,83
Serie 10000/	SA 15		570935	185,75
Serie 11000	SA 16		570937	185,75
	SA 18		570940	185,75
	SA 22		570945	185,75
	SA 28		570950	185,75
	SA 35		570955	185,75
	M 12		570100	154,61
	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 12 S (PR-2B)	Z8	574736 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
	V 12		570107	154,61
	V 14		570112	154,61
	V 6 14		570132	154,61
	V 15		570115	154,61
	V 16		570117	154,61
	V 6 16		570137	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 6 14 S (PR-2B)	Z8	574750 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 6 16 S (PR-2B)	Z8	574754 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
SANHA-Press	SA 12		570930	269,83
Pressfittings	SA 14		570932	269,83
Serie 6000	SA 15		570935	185,75
	SA 16		570937	185,75
	SA 18		570940	185,75
	SA 22		570945	185,75
	SA 28		570950	185,75
	SA 35		570955	185,75
	M 12		570100	154,61
	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	XP 64,0 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579100 R	1 056,63
	XP 66,7 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579108 R	1 161,47
	M 66,7 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579107 R	1 161,47
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 12 S (PR-2B)	Z8	574736 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
	V 12		570107	154,61
	V 14		570112	154,61
	V 6 14		570132	154,61
	V 15		570115	154,61
	V 16		570117	154,61
	V 6 16		570137	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 6 14 S (PR-2B)	Z8	574750 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 6 16 S (PR-2B)	Z8	574754 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
SANHA-Press	SA 12		570930	269,83
SOLAR	SA 15		570935	185,75
Pressfittings	SA 18		570940	185,75
Serie 12000/	SA 22		570945	185,75
Serie 13000	SA 28		570950	185,75
	SA 35		570955	185,75
	M 12		570100	154,61
	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	XP 64,0 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579100 R	1 056,63
	XP 66,7 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579108 R	1 161,47
	M 66,7 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579107 R	1 161,47
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 12 S (PR-2B)	Z8	574736 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
SANHA	SA 12		570930	269,83
PURAPRESS	SA 14		570932	269,83
Serie 8000	SA 15		570935	185,75
	SA 16		570937	185,75
	SA 18		570940	185,75
	SA 22		570945	185,75
	SA 28		570950	185,75
	SA 35		570955	185,75
	M 12		570100	154,61
	M 15 ¹⁾		570110	154,61
	M 18 ¹⁾		570120	154,61
	M 22 ¹⁾		570130	154,61
	M 28 ¹⁾		570140	154,61
	M 35 ¹⁾		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	XP 64,0 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579100 R	1 056,63
	XP 66,7 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579108 R	1 161,47
	M 66,7 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579107 R	1 161,47
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58
	M 12 S (PR-2B)	Z8	574736 R	124,51
	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
	V 12		570107	154,61
	V 14		570112	154,61
	V 6 14		570132	154,61
	V 15		570115	154,61
	V 16		570117	154,61
	V 6 16		570137	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 6 14 S (PR-2B)	Z8	574750 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 6 16 S (PR-2B)	Z8	574754 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
SANHA-Therm Serie 24000	SA 12		570930	269,83	SANITOP	M 15		570110	154,61
	SA 15		570935	185,75	PERMATUBO INOX	M 18 ⁱⁱ		570120	154,61
	SA 18		570940	185,75		M 22		570130	154,61
	SA 22		570945	185,75		M 28 ⁱⁱ		570140	154,61
	SA 28		570950	185,75		M 35		570150	154,61
	SA 35		570955	185,75		M 35 (PR-3S)	Z2	572727 R	672,57
	M 12		570100	154,61		M 42 (PZ-4G)		570160	498,19
	M 15		570110	154,61		M 54 (PZ-4G)		570170	498,19
	M 18		570120	154,61		M 42 (PR-3S)	Z2	572706 R	672,57
	M 22		570130	154,61		M 54 (PR-3S)	Z2	572708 R	672,57
	M 28		570140	154,61		M 7.61 XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579101 R	1 161,47
	M 35		570150	154,61		M 88,9 G XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579110 R	1 355,58
	M 42 (PR-3S)	Z2	572706 R	672,57		M 108,0 G XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579111 R	1 355,58
	M 54 (PR-3S)	Z2	572708 R	672,57		M 15 S (PR-2B)	Z8	574738 R	124,51
XP 66,7 XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579108 R	1 161,47		M 18 S (PR-2B)	Z8	574740 R	124,51	
M 66,7 XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579107 R	1 161,47		M 22 S (PR-2B)	Z8	574742 R	124,51	
M 76,1 XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579101 R	1 161,47		M 28 S (PR-2B)	Z8	574744 R	124,51	
M 88,9 G XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579110 R	1 355,58		M 35 S (PR-2B)	Z8	574746 R	136,96	
M 108,0 G XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579111 R	1 355,58						
M 12 S (PR-2B)	Z8	574736 R	124,51	SANPRO	TH 16*		570460	186,32	
M 15 S (PR-2B)	Z8	574738 R	124,51	THPRESS	TH 20*		570470	186,32	
M 18 S (PR-2B)	Z8	574740 R	124,51		TH 26*		570475	186,32	
M 22 S (PR-2B)	Z8	574742 R	124,51		TH 32		570480	186,32	
M 28 S (PR-2B)	Z8	574744 R	124,51		TH 16 S (PR-2B)**	Z8	574782 R	124,51	
M 35 S (PR-2B)	Z8	574746 R	136,96		TH 20 S (PR-2B)**	Z8	574788 R	124,51	
V 12		570107	154,61		TH 26 S (PR-2B)**	Z8	574794 R	124,51	
V 15		570115	154,61		TH 32 S (PR-2B)	Z8	574798 R	136,96	
V 18		570125	154,61	SATEC SK VI Term	TH 16*		570460	186,32	
V 22		570135	154,61		TH 18*		570465	186,32	
V 28		570145	154,61		TH 20*		570470	186,32	
V 35		570155	154,61		TH 26*		570475	186,32	
V 42		570165	360,13		TH 32		570475	186,32	
V 42 (PR-2B)	Z2	572850 R	322,77		U 40		570480	186,32	
V 54		570175	370,51		U 50		570795	298,89	
V 54 (PR-2B)	Z2	572851 R	348,72		U 63 (PZ-S)		572365	645,58	
V 12 S (PR-2B)	Z8	574748 R	124,51	SAVEUR REFLEX	TH 16*		570460	186,32	
V 15 S (PR-2B)	Z8	574752 R	124,51	PEX Water	TH 20*		570470	186,32	
V 18 S (PR-2B)	Z8	574756 R	124,51		TH 25*		570495	186,32	
V 22 S (PR-2B)	Z8	574758 R	124,51		TH 32		570480	186,32	
V 28 S (PR-2B)	Z8	574760 R	124,51	SAVEUR REFLEX	TH 16*		570460	186,32	
V 35 S (PR-2B)	Z8	574762 R	136,96	PEX AL PEX	TH 20*		570470	186,32	
SANHA-Therm Industry Serie 28000	SA 12		570930	269,83	Gas	TH 25*		570495	186,32
	SA 15		570935	185,75		TH 32		570480	186,32
	SA 18		570940	185,75	Schütz	TH 14*		570455	186,32
	SA 22		570945	185,75	duo-flex	TH 16*		570460	186,32
	SA 28		570950	185,75	tri-o-flex	TH 17*		570462	186,32
	SA 35		570955	185,75		TH 20*		570470	186,32
	M 12		570100	154,61		TH 25*		570495	186,32
	M 15		570110	154,61		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	M 18		570120	154,61		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	M 22		570130	154,61	AQUApress	M 12		570100	154,61
	M 28		570140	154,61		M 15		570110	154,61
	M 35		570150	154,61		M 18		570120	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57		M 22		570130	154,61
	M 54 (PR-3S)	Z2	572708 R	672,57		M 28		570140	154,61
XP 66,7 XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579108 R	1 161,47		M 35		570150	154,61	
M 66,7 XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579107 R	1 161,47		M 42 (PZ-4G)		570160	498,19	
M 76,1 XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579101 R	1 161,47		M 54 (PZ-4G)		570170	498,19	
M 88,9 G XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579110 R	1 355,58		M 42 (PR-3S)	Z2	572706 R	672,57	
M 108,0 G XL (PR-3S)	Z6 XL ⁱⁱ / Z7 XL 45 kN ⁱⁱ	579111 R	1 355,58		M 54 (PR-3S)	Z2	572708 R	672,57	
M 12 S (PR-2B)	Z8	574736 R	124,51		M 12 S (PR-2B)	Z8	574736 R	124,51	
M 15 S (PR-2B)	Z8	574738 R	124,51		M 18 S (PR-2B)	Z8	574738 R	124,51	
M 18 S (PR-2B)	Z8	574740 R	124,51		M 22 S (PR-2B)	Z8	574740 R	124,51	
M 22 S (PR-2B)	Z8	574742 R	124,51		M 28 S (PR-2B)	Z8	574742 R	124,51	
M 28 S (PR-2B)	Z8	574744 R	124,51		M 35 S (PR-2B)	Z8	574744 R	124,51	
M 35 S (PR-2B)	Z8	574746 R	136,96				574746 R	136,96	
V 12		570107	154,61	Seppelfricke	> Aalberts integrated piping systems				
V 15		570115	154,61						
V 18		570125	154,61	SESTA	TH 14*		570455	186,32	
V 22		570135	154,61	SESTA GAS	TH 16*		570460	186,32	
V 28		570145	154,61		TH 20*		570470	186,32	
V 35		570155	154,61		TH 26*		570475	186,32	
V 42		570165	360,13		TH 32		570480	186,32	
V 42 (PR-2B)	Z2	572850 R	322,77						
V 54		570175	370,51						
V 12 S (PR-2B)	Z8	572851 R	348,72						
V 15 S (PR-2B)	Z8	574748 R	124,51						
V 18 S (PR-2B)	Z8	574752 R	124,51						
V 22 S (PR-2B)	Z8	574756 R	124,51						
V 28 S (PR-2B)	Z8	574758 R	124,51						
V 35 S (PR-2B)	Z8	574760 R	124,51						

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
SESTA Sistema multistrato	H 16*		570320	168,10
	H 20*		570350	168,10
	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	U 16*		570765	174,33
SIGMA LI Premium	U 20*		570775	174,33
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
SLOVARM PEX-THERM	U 32		570785	204,43
	U 16*		570765	174,33
	U 20*		570775	174,33
	H 26*		570370	168,10
	U 32		570785	204,43
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 26*		570360	168,10
	H 32		570380	168,10
	RfZ 16*		571325	194,05
	RfZ 20*		571330	194,05
STANDARD HIDRAULICA MultiStandard	RfZ 25		571335	194,05
	RfZ 32		571340	194,05
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 18*		570770	174,33
steeltrade	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 25*		570360	168,10
	H 32		570380	168,10
	RfZ 16*		571325	194,05
	RfZ 20*		571330	194,05
	RfZ 25		571335	194,05
	RfZ 32		571340	194,05
TDM BRASS Serie 1600	TH 16*		570460	186,32
	TH 20*		570470	186,32
	H 25*		570360	168,10
	H 32		570370	168,10
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570487	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
STEELBI Polikraft	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
	H 16*		570320	168,10
	H 20*		570350	168,10
STEELBI Stelgas	H 25*		570360	168,10
	H 32		570380	168,10
	M 15		570110	154,61
	M 18 ¹⁾		570120	154,61
	M 22		570130	154,61
	M 22		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)		579101 R	1161,47
	M 88,9 G XL (PR-3S)		579110 R	1355,58
	M 108,0 G XL (PR-3S)		579111 R	1355,58
TDM BRASS Serie 2600	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		572706 R	672,57
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		572708 R	672,57
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	H 25*		570360	168,10
	H 32		570370	168,10
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570487	186,32
	TH 40		570485	246,99
THERMOCONCEPT TC-PRESS	TH 50 (PZ-S)		574782 R	124,51
	TH 63 (PZ-S)		574788 R	124,51
	TH 16 S (PR-2B)**	Z8	574788 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)**	Z8	574794 R	124,51
	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	Basic E01 ⁵⁾		571855	305,17
THERMOLUTZ	TH 16*		570460	186,32
	TH 20*		570470	186,32
	H 25*		570475	186,32
	THL 32		570487	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51
	TH 32 S (PR-2B)**	Z8	574794 R	124,51
	U 16*		570765	174,33
	U 18*		570770	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
TE-SA	U 26*		570785	204,43
	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	H 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
TERMACOME ACOPEX ALU	TH 18 S (PR-2B)**	Z8	574788 R	124,51
	TH 20 S (PR-2B)**	Z8	574792 R	124,51
	TH 25 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
STEELBI Stelgas	TH 32		570480	186,32
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 26*	¹²⁾	570780	204,43
	H 16*		570460	186,32
	H 20*		570470	186,32
	H 26*		570475	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
STH Westco	M 15		570110	154,61
COPPER PRESS	M 22		570130	154,61
	M 28 ¹⁾		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)		579101 R	1161,47
	M 88,9 G XL (PR-3S)		579110 R	1355,58
	M 108,0 G XL (PR-3S)		579111 R	1355,58
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		572706 R	672,57
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		572708 R	672,57
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	H 25*		570360	168,10
	H 32		570370	168,10
	TH 16*		570460	186,32
	TH 18*		570465	186,32
	TH 20*		570470	186,32
	TH 25*		570495	186,32
	TH 32		570487	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 14 S (PR-2B)**	Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Z8	574788 R	124,51
	TH 20 S (PR-2B)**	Z8	574792 R	124,51
	TH 25 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 26*	¹²⁾	570780	204,43
	H 16*		570460	186,32
	H 20*		570470	186,32
	H 26*		570475	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 26*	¹²⁾	570780	204,43
	H 16*		570460	186,32
	H 20*		570470	186,32
	H 26*		570475	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51

REMS pressing tools

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs/ pressing rings	Driven by adapter tongs	Art.-No.	€
TIEMME 1650 AL-COBRAPEX	TH 14*		570455	186,32	TRA MULTITRAPRESS	U 16*		570765	174,33
	TH 16*		570460	186,32		U 18*		570770	174,33
	TH 18*		570465	186,32		U 20*		570775	174,33
	TH 20*		570470	186,32		U 25*		570780	174,33
	TH 25*		570495	186,32		U 32		570785	204,43
	TH 26*		570475	186,32		U 40		570790	249,07
	THL 32		570487	186,32		U 50		570795	298,89
	TH 40		570485	246,99		U 63 (PR-3B)	Z4	572837 R	733,81
	TH 50 (PZ-S)		572400	645,58		U 63 (PZ-S)		572365	645,58
	TH 63 (PZ-S)		572405	645,58		U 75 (PR-3B)	Z4	572828 R	645,58
	THz 75 (PR-3B)	Z4	572829 R	609,25	TRA TRAPRESS	H 12*		570300	168,10
	TH 14 S (PR-2B)**	Z8	574778 R	124,51		H 16*		570320	168,10
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		H 20*		570350	168,10
	TH 18 S (PR-2B)**	Z8	574786 R	124,51		H 25*		570360	168,10
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		H 32		570380	168,10
	TH 25 S (PR-2B)**	Z8	574792 R	124,51		RFz 12*		571320	194,05
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		RFz 16*		571325	194,05
TIEMME 1700 COBRAPEX	RFz 12*		571320	194,05		RFz 20*		571330	194,05
	RFz 16*		571325	194,05		RFz 25		571335	194,05
	RFz 20*		571330	194,05		RFz 32		571340	194,05
	RFz 25		571335	194,05	Tradelink	K16/P18*		572600	194,05
	RFz 32		571340	194,05	TradePex Crimp	K/20*		572605	194,05
	TH 40		570485	246,99	Water	K/25*		572610	194,05
	TH 50 (PZ-S)		572400	645,58		K32		572615	194,05
	TH 63 (PZ-S)		572405	645,58		K1/40		572620	194,05
TIEMME 1650 AL-COBRAPEX GAS	TH 16*		570460	186,32		K1/50		572625	318,61
	TH 20*		570470	186,32	Tradelink	K16/P18*		572600	194,05
	TH 26*		570475	186,32	TradePex Crimp	K/20*		572605	194,05
	THL 32		570487	186,32	Gas	K/25*		572610	194,05
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		K32		572615	194,05
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		K1/40		572620	194,05
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		K1/50		572625	318,61
TIGRE	TH 16*		570460	186,32	TUBIPLAST ITALY MULTILAYER PIPE	TH 16*		570460	186,32
ALPEX GÁS	TH 20*		570470	186,32		TH 18*		570465	186,32
	TH 26*		570475	186,32		TH 20*		570470	186,32
	TH 32		570480	186,32		TH 26*		570475	186,32
TKM Systemtechnik	TH 14*		570455	186,32		TH 32		570480	186,32
	TH 16*		570460	186,32		TH 40		570485	246,99
	TH 20*		570470	186,32		TH 50 (PZ-S)		572400	645,58
	TH 26*		570475	186,32		TH 63 (PZ-S)		572405	645,58
	TH 32		570480	186,32		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 40		570485	246,99		TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 50 (PZ-S)		572400	645,58		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 63 (PZ-S)		572405	645,58		TH 26 S (PR-2B)**	Z8	574794 R	124,51
TRA Multi TRA+	H 16*		570320	168,10		TH 32 S (PR-2B)	Z8	574798 R	136,96
	H 20*		570350	168,10		H 16*		570320	168,10
	H 25*		570360	168,10		H 18*		570340	168,10
	H 26*		570370	168,10		H 20*		570350	168,10
	H 32		570380	168,10		H 26*		570370	168,10
	H 40 (PZ-4G)		570390	565,67		H 32		570380	168,10
	TH 16*		570460	186,32		U 16*		570765	174,33
	TH 20*		570470	186,32		U 18*		570770	174,33
	TH 25*		570495	186,32		U 20*		570775	174,33
	TH 26*		570475	186,32		U 26* ⁽¹²⁾		570750	204,43
	TH 32		570480	186,32		U 32		570785	204,43
	TH 40		570485	246,99	TUBIPLAST ITALY MULTILAYER PIPE GAS SYSTEM	TH 16*		570460	186,32
	TH 50 (PZ-S)		572400	645,58		TH 18*		570465	186,32
	TH 63 (PZ-S)		572405	645,58		TH 20*		570470	186,32
	Thz 75 (PR-3B)	Z4	572829 R	609,25		TH 26*		570475	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51		TH 32		570480	186,32
	TH 20 S (PR-2B)**	Z8	574788 R	124,51		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 25 S (PR-2B)**	Z8	574792 R	124,51		TH 18 S (PR-2B)**	Z8	574786 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51		TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	U 16*		570765	174,33		TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 20*		570775	174,33	TWEETOP	U 16*		570765	174,33
	U 25*		570780	174,33		U 20*		570775	174,33
	U 26* ⁽¹²⁾		570750	204,43		U 25*		570780	174,33
	U 32		570785	204,43		U 32		570785	204,43
	U 40		570790	249,07		U 40		570790	249,07
	U 50		570795	298,89		U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81		U 63 (PR-3B)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58		U 63 (PZ-S)		572365	645,58
	U 75 (PR-3B)	Z4	572828 R	645,58		U 75 (PR-3B)	Z4	572828 R	645,58

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can

²⁾ For this pressfitting system producing a pressing joint

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XL 45 k

⁵⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL).

carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressure

⁷⁾ Use pressing rings labelled "M 88.9 G" or "M 108 G" on the

8) For making press joints for operating pressure \leq PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system prior to use.

¹¹⁾ Only use pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tong

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
U				
UNICAL AG	U 16*		570765	174,33
MAX-MULTIPEX	U 20*		570775	174,33
	H 26*		570370	168,10
	U 26* ¹²⁾		570750	204,43
	U 32		570785	204,43
UNIDELTA DELTAPRESS	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	H 40 (PZ-4G)		570390	565,67
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 32		570785	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PZ-S)		572365	645,58
UNIDELTA DELTAPRESS GAS	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	H 16*		570320	168,10
	H 20*		570350	168,10
	H 26*		570370	168,10
	H 32		570380	168,10
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 32		570785	204,43
Uponor	UP 14*		572630	174,33
	UP 16*		572632	174,33
	UP 20*		572636	174,33
	UP 25		572638	174,33
	UP 32		572640	204,43
	U 40		570790	249,07
	U 50		570795	298,89
	U 63 (PZ-S)	Z4	572837 R	733,81
	U 63 (PZ-S)		572365	645,58
	U 75 (PR-3B)	Z4	572828 R	645,58

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Van Marcke NV SYSTEMPEX	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
Van Marcke NV Tubipress	M 12		570100	154,61
	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PZ-4G)		570160	498,19
	M 54 (PZ-4G)		570170	498,19
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)		579101 R	1 161,47
	M 88,9 G XL (PR-3S)		579110 R	1 355,58
	M 108,0 G XL (PR-3S)		579111 R	1 355,58
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		579101 R	1 161,47
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		579110 R	1 355,58
Variotherm System TH	TH 11,6*		570482	186,32
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 11,6 S (PR-2B)**	Z8	574774 R	124,51
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
VESBO CARBON	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)		579101 R	1 161,47
	M 88,9 G XL (PR-3S)		579110 R	1 355,58
	M 108,0 G XL (PR-3S)		579111 R	1 355,58
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		579101 R	1 161,47
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		579110 R	1 355,58
VESBO INOX	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)		579101 R	1 161,47
	M 88,9 G XL (PR-3S)		579110 R	1 355,58
	M 108,0 G XL (PR-3S)		579111 R	1 355,58
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		579101 R	1 161,47
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		579110 R	1 355,58
VESBO	M 15 S (PR-2B)	Z8	574738 R	124,51
	M 18 S (PR-2B)	Z8	574740 R	124,51
	M 22 S (PR-2B)	Z8	574742 R	124,51
	M 28 S (PR-2B)	Z8	574744 R	124,51
	M 35 S (PR-2B)	Z8	574746 R	136,96
VESBO MULTIPRESS TH-U	M 15		570110	154,61
	M 18		570120	154,61
	M 22		570130	154,61
	M 28		570140	154,61
	M 35		570150	154,61
	M 42 (PR-3S)	Z2	572706 R	672,57
	M 54 (PR-3S)	Z2	572708 R	672,57
	M 76,1 XL (PR-3S)		579101 R	1 161,47
	M 88,9 G XL (PR-3S)		579110 R	1 355,58
	M 108,0 G XL (PR-3S)		579111 R	1 355,58
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		579101 R	1 161,47
	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾		579110 R	1 355,58
VESBO VPREMIUM	U 16*		570460	186,32
	U 20*		570470	186,32
	U 26*		570475	186,32
	TH 32		570480	186,32
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 26* ¹²⁾		570785	204,43
Viega Fonterra	VX 12*		571630	214,81
	VP 14/15*		570905	185,75
	VP 16/17*		570910	185,75
	VP 20*		570915	185,75
	VP 25 ²⁾		570920	185,75
Viega MegaPress (ASTM) ¹⁰⁾	VMP 3/8" (OD 17,2 mm)		571740	214,81
	VMP 1/2" G (OD 21,3 mm)		571766 R	214,81
	VMP2 3/8" (OD 26,9 mm)		571764	214,81
	VMP2 1" (OD 33,7 mm)		571767	214,81
	VMP2 1 1/4" (PZ-S) (OD 42,4 mm)		572413	704,75
	VMP2 1 1/2" (PR-3B) (OD 48,3 mm)	Z5	572844 R	479,50
	VMP2 2" (PR-3B) (OD 60,3 mm)	Z5	572845 R	479,50

REMS pressing tools

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Viega MegaPress 304 FKM (ASTM) ¹⁰⁾	VMP ½" G (ØD 21,3 mm)	Z5	571766 R	214,81	Viega Profipress	V 12	Z2	570107	154,61
	VMPz ¾" (ØD 26,9 mm)		571764	214,81		VG 14		570132	154,61
	VMPz 1" (ØD 33,7 mm)		571767	214,81		V 15		570115	154,61
	VMPz 1½" (PZ-S) (ØD 42,4 mm)		572413	704,75		VG 16		570137	154,61
	VMPz 1½" (PR-3B) (ØD 48,3 mm)		572844 R	479,50		V 18		570125	154,61
	VMPz 2" (PR-3B) (ØD 60,3 mm)		572845 R	479,50		V 22		570135	154,61
Viega MegaPress 316 (ASTM) ¹⁰⁾	VMP ½" G (ØD 21,3 mm)	Z5	571766 R	214,81		V 28		570145	154,61
	VMPz ¾" (ØD 26,9 mm)		571764	214,81		V 35		570155	154,61
	VMPz 1" (ØD 33,7 mm)		571767	214,81		V 42		570165	360,13
	VMPz 1½" (PZ-S) (ØD 42,4 mm)		572413	704,75		V 42 (PR-2B)		572850 R	322,77
	VMPz 1½" (PR-3B) (ØD 48,3 mm)		572844 R	479,50		V 54		570175	370,51
	VMPz 2" (PR-3B) (ØD 60,3 mm)		572845 R	479,50		V 54 (PR-2B)		572851 R	348,72
Viega MegaPress 316 FKM (ASTM) ¹⁰⁾	VMP ½" G (ØD 21,3 mm)	Z5	571766 R	214,81		VFz 64,0 (PR-3B) ¹¹⁾		572815 R	609,25
	VMPz ¾" (ØD 26,9 mm)		571764	214,81		VFz 66,7 (PR-3B)		572846 R	609,25
	VMPz 1" (ØD 33,7 mm)		571767	214,81		VFz 76,1 (PR-3B) ¹¹⁾		572816 R	609,25
	VMPz 1½" (PZ-S) (ØD 42,4 mm)		572413	704,75		VFz 88,9 (PR-3B) ¹¹⁾		572817 R	645,58
	VMPz 1½" (PR-3B) (ØD 48,3 mm)		572844 R	479,50		VFz 108,0 (PR-3B) ¹¹⁾		572818 R	645,58
	VMPz 2" (PR-3B) (ØD 60,3 mm)		572845 R	479,50		V 12 S (PR-2B)		574748 R	124,51
Viega MegaPress CuNi (ASTM) ¹⁰⁾	VMP ½" G (ØD 21,3 mm)	Z5	571766 R	214,81		V 15 S (PR-2B)		574750 R	124,51
	VMPz ¾" (ØD 26,9 mm)		571764	214,81		V 16 S (PR-2B)		574752 R	124,51
	VMPz 1" (ØD 33,7 mm)		571767	214,81		V 18 S (PR-2B)		574754 R	124,51
	VMPz 1½" (PZ-S) (ØD 42,4 mm)		572413	704,75		V 22 S (PR-2B)		574758 R	124,51
	VMPz 1½" (PR-3B) (ØD 48,3 mm)		572844 R	479,50		V 28 S (PR-2B)		574760 R	124,51
	VMPz 2" (PR-3B) (ØD 60,3 mm)		572845 R	479,50		V 35 S (PR-2B)		574762 R	136,96
Viega MegaPress FKM (ASTM) ¹⁰⁾	VMP ½" G (ØD 21,3 mm)	Z5	571766 R	214,81	Viega Profipress 6	V 12	Z2	570107	154,61
	VMPz ¾" (ØD 26,9 mm)		571764	214,81		VG 14		570132	154,61
	VMPz 1" (ØD 33,7 mm)		571767	214,81		V 15		570115	154,61
	VMPz 1½" (PZ-S) (ØD 42,4 mm)		572413	704,75		V 16		570137	154,61
	VMPz 1½" (PR-3B) (ØD 48,3 mm)		572844 R	479,50		V 18		570125	154,61
	VMPz 2" (PR-3B) (ØD 60,3 mm)		572845 R	479,50		V 22		570135	154,61
Viega Megapress (EN) ⁹⁾	VMP ¾" (ØD 17,2 mm)	Z5	571740	214,81		V 28		570145	154,61
	VMP ½" G (ØD 21,3 mm)		571766 R	214,81		V 35		570155	154,61
	VMPz ¾" (ØD 26,9 mm)		571764	214,81		V 42		570165	360,13
	VMPz 1" (ØD 33,7 mm)		571767	214,81		V 42 (PR-2B)		572850 R	322,77
	VMPz 1½" (PZ-S) (ØD 42,4 mm)		572413	704,75		V 54		570175	370,51
	VMPz 1½" (PR-3B) (ØD 48,3 mm)		572844 R	479,50		V 54 (PR-2B)		572851 R	348,72
Viega Megapress S (EN) ⁹⁾	VMP ¾" (ØD 17,2 mm)	Z5	571740	214,81		VFz 64,0 (PR-3B) ¹¹⁾		572815 R	609,25
	VMP ½" G (ØD 21,3 mm)		571766 R	214,81		V 12 S (PR-2B)		574748 R	124,51
	VMPz ¾" (ØD 26,9 mm)		571764	214,81		V 14 S (PR-2B)		574750 R	124,51
	VMPz 1" (ØD 33,7 mm)		571767	214,81		V 15 S (PR-2B)		574752 R	124,51
	VMPz 1½" (PZ-S) (ØD 42,4 mm)		572413	704,75		V 16 S (PR-2B)		574754 R	124,51
	VMPz 1½" (PR-3B) (ØD 48,3 mm)		572844 R	479,50		V 18 S (PR-2B)		574756 R	124,51
Viega Megapress S XL (EN) ⁹⁾	VMPz 2½" XL (PR-3B) (ØD 76,1 mm)	Z5	579112 R	609,25		V 22 S (PR-2B)		574758 R	124,51
	VMPz 3" XL (PR-3B) (ØD 88,9 mm)		579113 R	609,25		V 28 S (PR-2B)		574760 R	124,51
	VMPz 4" XL (PR-3B) (ØD 114,3 mm)		579114 R	645,58		V 35 S (PR-2B)		574762 R	136,96
	Viega Pexfit	VX 16*	571635	214,81	Viega Profipress S	V 12	Z2	570107	154,61
		VX 20*	571640	214,81		V 15		570115	154,61
		VX 25*	571645	214,81		V 18		570125	154,61
	Viega Pexfit G	VX 16*	571635	214,81		V 22		570135	154,61
		VX 20*	571640	214,81		V 28		570145	154,61
		VX 25*	571645	214,81		V 35		570155	154,61
Viega Prestaboo	V 12	Z5	570107	154,61		V 12 S (PR-2B)		574748 R	124,51
	V 15		570115	154,61		V 15 S (PR-2B)		574750 R	124,51
	V 18		570125	154,61		V 18 S (PR-2B)		574752 R	124,51
	V 22		570135	154,61		V 22 S (PR-2B)		574756 R	124,51
	V 28		570145	154,61		V 28 S (PR-2B)		574760 R	124,51
	V 35		570155	154,61		V 35 S (PR-2B)		574762 R	136,96
Viega Profipress Therm	VX 16*	Z5	571635	214,81	Viega Profipress Therm	V 12	Z2	570107	154,61
			571640	214,81		V 15		570115	154,61
			571645	214,81		V 18		570125	154,61
			571645	214,81		V 22		570135	154,61
			571645	214,81		V 28		570145	154,61
			571645	214,81		V 35		570155	154,61
Viega ProPress (ASTM) ¹⁰⁾	VUS ½" (ØD 15,9 mm)	Z5	571770	186,79		V 12 S (PR-2B)	Z2	574748 R	124,51
	VUS ¾" (ØD 22,2 mm)		571775	186,79		V 15 S (PR-2B)		574750 R	124,51
	VUS 1" (ØD 28,6 mm)		571780	186,79		V 18 S (PR-2B)		574752 R	124,51
	VUS 1½" (ØD 34,9 mm)		571785	186,79		V 18 S (PR-2B)		574756 R	124,51
	VUS 1½" (ØD 41,3 mm)		571790	360,13		V 22 S (PR-2B)		574758 R	124,51
	VUS 2" (ØD 54,0 mm)		571795	370,51		V 22 S (PR-2B)		574760 R	124,51
XL-C/XL-S	VUSz 2½" (PR-3B) (ØD 66,7 mm)	Z5	572819 R	609,25	Viega ProPress Therm	V 12 S (PR-2B)	Z2	570107	154,61
	VUSz 3" (PR-3B) (ØD 79,4 mm)		572820 R	609,25		V 15 S (PR-2B)		570115	154,61
	VUSz 4" (PR-3B) (ØD 104,8 mm)		572821 R	645,58		V 18 S (PR-2B)		570125	154,61
	VUSz 5" (PR-3B) (ØD 126,7 mm)		572822 R	645,58		V 22 S (PR-2B)		570135	154,61
	VUSz 6" (PR-3B) (ØD 148,5 mm)		572823 R	645,58		V 28 S (PR-2B)		570145	154,61
	VUSz 7" (PR-3B) (ØD 170,3 mm)		572824 R	645,58		V 35 S (PR-2B)		570155	154,61

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

**** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.**

¹⁾ Only pressing tons from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can

²⁾ For this pressfitting system producing a pressing joint

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

4) Driven by REMS Akku-Press XI 45 k

⁵⁾ For taking suitable pressing inserts.
⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL).

Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings.

7) Use pressing rings labelled "M 88.9 G" or "M 108 G" on the

⁸⁾ For making press joints for operating pressure < PN 10

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provided.

¹¹⁾ Only use pressing tongs identified by "VME 16" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs.

The suitability of REMS pressing tools for prescuffing systems: Date 27.10.2023. For the updated situation reg.

The suitability of REMS pressing tools for pre-assembly
www.rems.de > Downloads > Product catalog

See page 238 for adapter fittings. Pressing fittings/pressing rings for additional pressfitting systems on request.

See page 256 for adapter tongs; Pressing tongs/pressing rings for additional pressure.

All prices excl. VAT

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Viega ProPress 304 FKM (ASTM) ⁽¹⁾	VUS ½" (OD 15,9 mm)		571770	186,79
	VUS ¾" (OD 22,2 mm)		571775	186,79
	VUS 1" (OD 28,6 mm)		571780	186,79
	VUS 1½" (OD 34,9 mm)		571785	186,79
	VUS 1¾" (OD 41,3 mm)		571790	360,13
	VUS 2" (OD 54,0 mm)		571795	370,51
XL-C/XL-S	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	609,25
XL-C/XL-S	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	609,25
XL-C/XL-S	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	645,58
Viega ProPress 316 (ASTM) ⁽¹⁾	VUS ½" (OD 15,9 mm)		571770	186,79
	VUS ¾" (OD 22,2 mm)		571775	186,79
	VUS 1" (OD 28,6 mm)		571780	186,79
	VUS 1½" (OD 34,9 mm)		571785	186,79
	VUS 1¾" (OD 41,3 mm)		571790	360,13
	VUS 2" (OD 54,0 mm)		571795	370,51
XL-C/XL-S	VUSFz 2½" (PR-3B) (OD 66,7 mm)	Z5	572819 R	609,25
XL-C/XL-S	VUSFz 3" (PR-3B) (OD 79,4 mm)	Z5	572820 R	609,25
XL-C/XL-S	VUSFz 4" (PR-3B) (OD 104,8 mm)	Z5	572821 R	645,58
Viega Propress WATER System AUS	VAU 15 (OD 12,7 mm)		572687	159,80
	VAU 20 (OD 19,1 mm)		572689	159,80
	VAU 25 (OD 25,4 mm)		572691	159,80
	VAU 32 (OD 31,8 mm)		572693	168,10
	VAU 40 (OD 38,1 mm)		572695	249,07
	VAU 50 (OD 50,8 mm)		572697	441,10
Viega ProPress GAS System AUS	VAU 15 (OD 12,7 mm)		572687	159,80
	VAU 20 (OD 19,1 mm)		572689	159,80
	VAU 25 (OD 25,4 mm)		572691	159,80
	VAU 32 (OD 31,8 mm)		572693	168,10
	VAU 40 (OD 38,1 mm)		572695	249,07
	VAU 50 (OD 50,8 mm)		572697	441,10
Viega Raxinox	VRX 16		571750	196,13
	VRX 20		571752	196,13
Viega Raxofix	VRX 16		571750	196,13
	VRX 20		571752	196,13
	VRX 25		571754	214,81
	VRX 32		571756	214,81
	VRX 40		571758	298,89
	VRX 50		571760	348,72
Viega Sanfix ⁽²⁾	VP 16/17 ⁽²⁾		570910	185,75
	VP 20 ⁽²⁾		570915	185,75
	VP 25 ⁽²⁾		570920	185,75
	VP 32		570925	205,47
	VP 40 (PZ-4G)		570970	493,00
	VPz 50 (PZ-S)		572350	645,58
Viega Sanfix Fosta ⁽²⁾	VP 16/17 ⁽²⁾		570910	185,75
	VP 20 ⁽²⁾		570915	185,75
	VP 25 ⁽²⁾		570920	185,75
	VP 32		570925	205,47
	VP 40 (PZ-4G)		570970	493,00
	VPz 50 (PZ-S)		572350	645,58
Viega Sanpress	VP 16/17 ⁽²⁾		570910	185,75
	VP 20 ⁽²⁾		570915	185,75
	VP 25 ⁽²⁾		570920	185,75
	VP 32		570925	205,47
	VP 40 (PZ-4G)		570970	493,00
	VPz 50 (PZ-S)		572350	645,58
Viega Sanpress Inox	V 12		570107	154,61
	V 15		570115	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	VR 76,1 (PR-3B) ⁽³⁾	Z5	572822 R	609,25
	VR 88,9 (PR-3B) ⁽³⁾	Z5	572823 R	645,58
	VR 108,0 (PR-3B) ⁽³⁾	Z5	572824 R	645,58
	V 12 S (PR-2B)	Z8	574748 R	124,51
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
Viega Sanpress Inox G	V 15		570115	154,61
	V 18		570125	154,61
	V 22		570135	154,61
	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
	VFz 64,0 (PR-3B) ⁽³⁾	Z5	572815 R	609,25
	VFz 76,1 (PR-3B) ⁽³⁾	Z5	572816 R	609,25
	VFz 88,9 (PR-3B) ⁽³⁾	Z5	572817 R	645,58
	VFz 108,0 (PR-3B) ⁽³⁾	Z5	572818 R	645,58
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
Viega Smartpress	VX 16*		571635	214,81
	VX 20*		571640	214,81
	VX 25*		571645	214,81
	V 15		570115	154,61
	V 18		570125	154,61
	V 22		570135	154,61
Viega Temponox	V 28		570145	154,61
	V 35		570155	154,61
	V 42		570165	360,13
	V 42 (PR-2B)	Z2	572850 R	322,77
	V 54		570175	370,51
	V 54 (PR-2B)	Z2	572851 R	348,72
Vogel & Noot	VFz 76,1 (PR-3B) ⁽³⁾	Z5	572816 R	609,25
	VFz 88,9 (PR-3B) ⁽³⁾	Z5	572817 R	645,58
	VFz 108,0 (PR-3B) ⁽³⁾	Z5	572818 R	645,58
	V 15 S (PR-2B)	Z8	574752 R	124,51
	V 18 S (PR-2B)	Z8	574756 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51
Viessmann	V 28 S (PR-2B)	Z8	574760 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96
	TH 14*		570455	186,32
	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
EASYTEC	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 50 (PZ-S)		572400	645,58
	TH 63 (PZ-S)		572405	645,58
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
VSH	TH 26 S (PR-2B)**	Z8	574794 R	124,51
	TH 32 S (PR-2B)	Z8	574798 R	136,96
	> Alaberts integrated piping systems			
W				
Watts MTR	TH 16*		570460	186,32
	TH 20*		570470	186,32
	TH 26*		570475	186,32
	TH 32		570480	186,32
	WATTS	US ¾"	571450	211,70
	RADIANT	US ½"	571455	211,70
Watts WaterPEX	Watts	US ¾"	571460	211,70
	Watts	US 1"	571465	211,70
	RadiantPEX	US 1"	571465	211,70
	Watts	US 1 ¼"	571470	211,70
	Watts	US 1 ½"	571475	211,70
	WATTS	US 1 ½"	571450	211,70
WATTS	RADIANT	US ½"	571455	211,70
	Watts	US ¾"	571460	211,70
	RadiantPEX	US 1"	571465	211,70
	Watts	US 1 ¼"	571470	211,70
	Watts	US 1 ½"	571475	211,70
	WATTS	U 16 (½")	570765	174,33
RADIAN	U 20 (½")		570775	174,33
	U 20 (¾")		570780	174,33
	U 25 (¾")		570780	174,33
	U 32 (1")		570785	204,43
	U 50		570795	298,89
	U 63 (PR-3B)	Z4	572837 R	733,81
Tigris K1/M1	U 63 (PZ-S)		572365	645,58
	U 75 (PR-3B)	Z4	572828 R	645,58
	B 16*		570850	203,40
	B 20*		570860	203,40
	B 32		570880	224,16
	H 16*		570320	168,10
Wavin	H 20*		570350	168,10
	H 25*		570360	168,10
	H 32		570380	168,10
	H 40 (PZ-4G)		570390	565,67
	H 40 (PZ-S)		570460	186,32
	H 20*		570470	186,32
Tigris K5/M5	TH 25*		570495	186,32
	TH 32		570480	186,32
	TH 40		570485	246,99
	TH 16 S (PR-2B)**	Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Z8	574794 R	124,51
Tigris K5/M5	TH 32 S (PR-2B)	Z8	574798 R	136,96
	U 16*		570765	174,33
	U 20*		570775	174,33
	U 25*		570780	174,33
	U 32		570785	204,43
	U 40		570790	249,07
Wavin	U 40		572632	174,33
	UP 16*		572636	174,33
	UP 20*		572636	174,33
	UP 25		572638	174,33
	UP 32		572640	204,43

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	€
WEECON	M 15		570110	154,61	XtraConnect	F 16*		570717	177,45
PRESS-C-Stahl	M 18		570120	154,61		F 20*		570727	177,45
	M 22		570130	154,61		F 26*		570730	191,98
	M 28		570140	154,61		F 32		570735	191,98
	M 35		570150	154,61		F 16 S (PR-2B)**	Z8	574728 R	124,51
	M 42 (PZ-4G)		570160	498,19		F 20 S (PR-2B)**	Z8	574730 R	124,51
	M 54 (PZ-4G)		570170	498,19		F 26 S (PR-2B)**	Z8	574732 R	124,51
	M 42 (PR-3S)	Z2	572706 R	672,57		F 32 S (PR-2B)	Z8	574734 R	136,96
	M 54 (PR-3S)	Z2	572708 R	672,57		H 16*		570320	168,10
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		H 20*		570350	168,10
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58		H 26*		570370	168,10
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58		H 32		570380	168,10
	M 15 S (PR-2B)	Z8	574738 R	124,51		TH 16*		570460	186,32
	M 18 S (PR-2B)	Z8	574740 R	124,51		TH 20*		570470	186,32
	M 22 S (PR-2B)	Z8	574742 R	124,51		TH 26*		570475	186,32
	M 28 S (PR-2B)	Z8	574744 R	124,51		TH 32		570480	186,32
	M 35 S (PR-2B)	Z8	574746 R	136,96		TH 16 S (PR-2B)**	Z8	574782 R	124,51
WEECON	M 15		570110	154,61		TH 20 S (PR-2B)**	Z8	574788 R	124,51
PRESS-Edelstahl	M 18		570120	154,61		TH 26 S (PR-2B)**	Z8	574794 R	124,51
	M 22		570130	154,61		TH 32 S (PR-2B)	Z8	574798 R	136,96
	M 28		570140	154,61	(DN 26)	U 16*		570765	174,33
	M 35		570150	154,61		U 20*		570775	174,33
	M 42 (PZ-4G)		570160	498,19		U 25*		570780	174,33
	M 54 (PZ-4G)		570170	498,19		U 32		570785	204,43
	M 42 (PR-3S)	Z2	572706 R	672,57		VP 16*		570910	185,75
	M 54 (PR-3S)	Z2	572708 R	672,57		VP 20*		570915	185,75
	M 76,1 XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579101 R	1 161,47		VP 32		570925	205,47
	M 88,9 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579110 R	1 355,58					
	M 108,0 G XL (PR-3S)	Z6 XL ³⁾ / Z7 XL 45 kN ⁴⁾	579111 R	1 355,58					
	M 15 S (PR-2B)	Z8	574738 R	124,51					
	M 18 S (PR-2B)	Z8	574740 R	124,51					
	M 22 S (PR-2B)	Z8	574742 R	124,51					
	M 28 S (PR-2B)	Z8	574744 R	124,51					
	M 35 S (PR-2B)	Z8	574746 R	136,96					
WEECON	V 15		570115	154,61	ZEWOTHERM	TH 12*		570452	186,32
PRESSS-Kupfer	V 18		570125	154,61	Zewo Press Premium	TH 16*		570460	186,32
	V 22		570135	154,61		TH 17*		570462	186,32
	V 28		570145	154,61		TH 18*		570465	186,32
	V 35		570155	154,61		TH 20*		570470	186,32
	V 42		570165	360,13		TH 26*		570475	186,32
	V 42 (PR-2B)	Z2	572850 R	322,77		TH 32		570480	186,32
	V 54		570175	370,51		TH 40		570485	246,99
	V 54 (PR-2B)	Z2	572851 R	348,72		TH 50 (PZ-S)		572400	645,58
	V 15 S (PR-2B)	Z8	574752 R	124,51		TH 63 (PZ-S)		572405	645,58
	V 18 S (PR-2B)	Z8	574756 R	124,51		TH 12 S (PR-2B)**	Z8	574776 R	124,51
	V 22 S (PR-2B)	Z8	574758 R	124,51		TH 16 S (PR-2B)**	Z8	574782 R	124,51
	V 28 S (PR-2B)	Z8	574760 R	124,51		TH 17 S (PR-2B)**	Z8	574784 R	124,51
	V 35 S (PR-2B)	Z8	574762 R	136,96		TH 18 S (PR-2B)**	Z8	574786 R	124,51
WEM	U 16*		570765	174,33		TH 20 S (PR-2B)**	Z8	574788 R	124,51
WIELAND-WERKE	TH 14 ²⁾		570455	186,32		TH 26 S (PR-2B)**	Z8	574790 R	124,51
cuprotherm CTX ²⁾	TH 16 ²⁾		570460	186,32		TH 32 S (PR-2B)	Z8	574794 R	124,51
WKS-Press	TH 14*		570455	186,32	ZURN	US 3/8"		571450	211,70
	TH 16*		570460	186,32		US 1/2"		571455	211,70
	TH 17*		570462	186,32	ZINDUSTRIES	US 3/4"		571460	211,70
	TH 20*		570470	186,32		US 1"		571465	211,70
	TH 26*		570475	186,32	ZURN PEX	US 1 1/4"		571470	211,70
	TH 32		570480	186,32		US 1 1/2"		571475	211,70
	TH 40		570485	246,99		US 2"		571477	285,40
WÜRTH	TH 16*		570460	186,32					
Würth	TH 20*		570470	186,32					
	TH 26*		570475	186,32					
	HE 32		571900	223,12					
	HEz 40		571904	323,80					

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

* Can also be driven by the REMS Eco-Press manual radial press, see page 185. Observe the national regulations.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Driven by REMS Power-Press XL ACC, see page 188.

⁴⁾ Driven by REMS Akku-Press XL 45 kN 22 V ACC, see page 196.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Use pressing rings labelled "M 88,9 G" or "M 108 G" on the three pressing segments for gas installations.

⁸⁾ For making press joints for operating pressure ≤ PN 10.

⁹⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

¹⁰⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

¹¹⁾ Only use pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.

¹²⁾ Previous designation: C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 238 for adapter tongs. Pressing tongs/pressing rings for additional pressfitting systems on request.

Accessories

For REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

Description	Art.-No.	€
Adapter tongs Z8 for driving REMS pressing rings S (PR-2B)	574702R	144,28
Adapter tongs Z2 for driving REMS pressing rings M 35–54 (PR-3S), V 42–54 (PR-2B), RN 40–50 (PR-3S)	572795R	144,28
Adapter tongs Z4 for driving REMS pressing rings F 75 (PR-3B), TH 63–75 (PR-3B), U 63–75 (PR-3B), RN 63 (PR-3B)	572801RX	310,36
Adapter tongs Z5 for driving REMS pressing rings VFz/VR 64–108 (PR-3B), VMPz 1½–2" (PR-3B), VUSFz 2½–4" (PR-3B), VAUFz 65–100 (PR-3B)	572802RX	310,36
Adapter tongs Z6 XL for driving REMS pressing rings 64.0–108.0 XL (PR-3S), 2½–4" XL (PR-3S) with REMS Power-Press XL ACC	579120R	373,68
Adapter tongs Z7 XL 45 kN for driving REMS pressing rings 64.0–108.0 XL (PR-3S), 2½–4" XL (PR-3S), 2½–4" XL (PR-3B) with REMS Akku-Press XL 45 kN 22V ACC	579123R	394,44
Steel case with insert for 6 pressing tongs (up to Ø 35 mm/1" and pressing tongs U 40, U 50, TH 40, F 40, F 50, G 40, VUS 1¼")/cropping tongs and compartment for pipe cutter up to 42 mm	570295R	96,53
Steel case with insert for 2 pressing tongs (M 42 (PZ-4G), M 54 (PZ-4G), V 42, V 54, H 40, H 40 A, VUS 1½", VUS 2")	570290R	96,53
Steel case with insert for adapter tongs Z2 and pressing rings M 42 (PR-3S) and M 54 (PR-3S) or pressing rings SA 42 (PR-3S) and SA 54 (PR-3S).	572810R	96,53
Steel case with insert for adapter tongs Z5 and 4 pressing rings VFz 64.0–108.0/VR 76.1–108.0/VUSFz 2½–4" (PR-3B) or for adapter tongs Z5 and 1 pressing tong VMPz 1¼ (PZ-S) and 2 pressing rings VMPz 1½–2" (PR-3B)	572809R	110,03
Steel case with insert for adapter tongs Mini Z8 and adapter tongs Z8 as well as 6 REMS pressing rings S (PR-2B)	574516R	96,53
L-Boxx system case with inlay for Mini Z8 adapter tongs and Z8 adapter tongs as well as 14 REMS S pressing rings (PR-2B)	574704R	146,36
L-Boxx system case with inserts for 8 pressing tongs (2B) and 6 pressing rings S (PR-2B)	571136R	146,36
L-Boxx system case with inserts for 3 different pressing rings VMPz 2½–4" XL (PR-3B)	571137R	146,36
XL-Boxx system case with inserts for 3 different pressing rings 64.0–108.0 XL (PR-3S) or 2½–4" XL (PR-3S)	579603R	248,08
Steel case with inserts for adapter tongs Z2 and pressing rings V 42 (PR-2B) and V 54 (PR-2B)	572813R	55,01



Confirmation of suitability

The suitability of crimping tools is determined basically by the manufacturer of crimping tools. Moreover the suitability of REMS crimping tools has been confirmed by the system manufacturer/supplier himself or approved through independent testing institutes.

Confirmation of suitability through the system manufacturer/supplier

More than 90 % of the manufacturers/suppliers of the pressfitting systems listed herein have tested REMS pressing tongs and confirmed the suitability for their pressfitting system.

Confirmation of suitability through independent testing institutes

The suitability of REMS pressing tongs for additional pressfitting systems have been confirmed through independent technical institutes:

TÜV-Certificates

Exist for Geberit Mepla, Geberit Mapress C-STAHL, Geberit Mapress EDELSTAHL, Geberit Mapress Kupfer, Nussbaum Cupress, Nussbaum Optipress, Uponor Unipipe, Viega-'profipress', Viega-'profipress G', Viega-'sanfix P', Viega-'sanpress', Viega-'Viegatherm P', Wavin Tigris. The TÜV-certificates confirm that REMS crimping tools are suitable for producing perfect and system-conformity pressing joints corresponding to these systems.

Suitability test according to DVGW W 534 (potable water)

Pressing joints produced with REMS pressing tools were tested by the state-operated material testing institute in Darmstadt/Germany or the material testing institute of the Land of North-Rhine-Westphalia, Germany according to DVGW work sheet W 534. These material testing institutes are certified by the DVGW for making these tests. A representative cross-section of press joints of pressfitting systems Geberit Mapress Edelstahl, Raccorderie Metalliche inoxPRES, Raccorderie Metalliche steelPRES, Uponor Unipipe, Viega Megapress, Viega Profipress and Viega Raxofix. was tested. The tests led to the result that all REMS pressing tools are suitable for producing perfect and system conformity pressing joints in accordance with these systems.

Suitability test according to DVGW G 5614/VP 625 or prEN 1254-7 (gas)

Pressing joints made with REMS pressing tools have been tested by the TÜV or by the Land Material Testing Institute Nordrhein-Westfalen or the DVGW Research Institute Karlsruhe according to DVGW Regulations G 5614/VP 625 or by the BSI (UK) according to prEN 1254-7. A representative cross-section of pressing joints of the pressfitting systems Geberit Mapress Edelstahl Gas, Geberit Mapress Kupfer Gas, Henco Gas, IBP >B<press Gas, Kembla KemPress Gas, Pegler Yorkshire X-Press Copper Gas, Raccorderie Metalliche inoxPRES Gas, Uponor MLC-G, Valsir PEXAL Gas, Viega Profipress G, Viega Pexfit G, Viega Sanpress INOX G, Viega ProPressG GAS System (AUS) was tested. The tests led to the result that all REMS pressing tools are suitable for producing perfect and system conformity pressing joints in accordance with these systems.



potable water



gas

Hold-Harmless and Indemnification Agreement

REMS is the first system-independent machine and tool manufacturer to sign liability acceptance agreements for pressing tools.

A hold-harmless and indemnification agreement exists with the:

Zentralverband Sanitär Heizung Klima (Central Organization for the Sanitary-, Heating- and Climatization Industries),
Rathausallee 6, D-53757 St. Augustin,
referred to in the following as "ZVSHK",

Bundesindustrieverband Technische Gebäudeausrüstung e.V.,
Hinter Hoben 149, 53129 Bonn,
referred to in the following as "BTGA",

Verband Deutscher Kälte-Klima-Fachbetriebe e. V.
(German Association for Coolant & Air-Conditioning Profession Industries),
Kaiser-Friedrich-Straße 7, D-53113 Bonn,
referred to in the following as "VDKF",

Schweizerisch-Liechtensteinischem Gebäudetechnikverband
(Swiss-Liechtenstein Technical Building Association),
Auf der Mauer 11, CH-8023 Zürich,
referred to in the following as "suisse tec",

The Zentralverband Sanitär Heizung Klima (ZVSHK), the Bundesindustrieverband Technische Gebäudeausrüstung e. V. (BTGA), the Verband Deutscher Kälte-Klima-Fachbetriebe e. V. (VDKF) and the Schweizerisch-Liechtensteinische Gebäudetechnikverband (suisse tec) have made liability acceptance agreements in the interests of trade and industry with REMS GmbH & Co KG (REMS) for the radial pressing tools.

- Manual radial press REMS Eco-Press
- Cordless radial press REMS Mini-Press 14V ACC
- Cordless radial press REMS Mini-Press 22V ACC
- Cordless radial press REMS Mini-Press S 22V ACC
- Electric radial press REMS Power-Press SE
- Electro-hydraulic radial press REMS Power-Press ACC
- Electro-hydraulic radial press REMS Power-Press XL ACC
- Cordless radial press REMS Akku-Press E 22V ACC
- Cordless radial press REMS Akku-Press 22V ACC
- Cordless radial press REMS Akku-Press 22V Connected
- Cordless radial press REMS Akku-Press XL 45kN 22V ACC
- REMS pressing tongs
- REMS pressing rings
- REMS pressing tongs Mini

This makes REMS the first system-independent machine- and tool manufacturer to have concluded a hold-harmless and indemnification agreement for pressing tools. The conclusion of the agreement was effected on the basis of a successful cooperation established on partnership between REMS, the crafts, trades and industry and their organizations.

Eligible for services and performances from this agreement are all independent professional craftsmen, and companies of such, who are enrolled in the register of artisans and craftsmen (referred to in the following as "SHK-Establishments"), in as far as they have been members of the crafts guild of the sanitary- heating- and climatization enterprises competent for their business location at the time the damage event has arisen, and this crafts guild is associated with a regional guild association, which is a member of the ZVSHK.

Entitled to the services from the agreement with the BTGA are all building technology companies (hereinafter referred to as "TGA companies") insofar as they were a member of the Land Industry Association **Technical Building Equipment** responsible at the seat of their company at the time of the damage case and therefore an indirect member of the BTGA or direct member of the BTGA.


Eligible for services and performances from this agreement with the VDKF are all coolant systems companies or professional organisations (referred to as Coolant and Air-Conditioning Profession Industries) who, at the time the damage is caused, are members of the VDKF.

Eligible for services and performances from this agreement are all building systems companies (following TGA companies) who, at the time the damaged is caused, are members of suisse tec.

In as far as the radial pressing tools mentioned show a defect with regard to construction, manufacture or material, or if the operator's manuals are faulty, thereby causing damage for the customer of the SHK-establishment, the Coolant and Air-Conditioning Profession Industries, or the TGA-companies, for which the SHK-establishment or the TGA-company is liable, then REMS shall be additionally liable - aside of the statutory prescriptions - for the consequences resulting from leakage, in accordance with the stipulations and provisions of this hold-harmless agreement.

The assumption of liability agreements apply regardless of which pressfitting system is pressed with the suitable REMS pressing tools. The current status regarding suitability of the REMS pressing tools for pressfitting systems can be viewed on the Internet: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

For further information, please contact: info@rems.de



German Quality Product

Reliable and safe: REMS was the first system-independent machine and tool manufacturer to sign liability acceptance agreements for pressing tools as early as the year 2000.



REMS cropping tongs

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

High performance cropping tongs in forged and specially hardened steel for cutting threaded rods.

Steel, stainless steel up to hardness classification 4.8 (400 N/mm²) M 6 – M 12

REMS cropping tongs – for cutting threaded rods.

Made of forged and specially hardened steel.


Reversible cropping inserts for double service life.

M cropping inserts with high precision thread contour machined on CNC machining centres for exact guiding of the threaded rod in the cutting process. Pliers parts, cropping inserts and specially machined and hardened cutting edges, made to fit exactly, for cutting without burr

Threaded rod can be screwed into a threaded connection of the pipe clip or the nut without rework after cutting

Cutting device in pliers design (Patent EP 1 459 825, patent US 7,284,330).

Driven by REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force. All cropping tongs marked with * have an optional connection for manual drive through the radial press REMS Eco-Press.




Supply format

REMS cropping tongs. Cropping tongs with 1 pair of reversible cropping inserts for steel, stainless steel, M 6 – M 12. In a carton.

Description	for threaded rods	Art.-No.	€
REMS cropping tongs M 6*	M 6	571890	241,85
REMS cropping tongs M 8*	M 8	571895	241,85
REMS cropping tongs M 10	M 10	571865	241,85
REMS cropping tongs M 12	M 12	571870	241,85

German Quality Product



Patent EP 1 459 825
Patent US 7,284,330

Accessories

Description	for threaded rods	Art.-No.	€
Cropping inserts M 6 (pair)	M 6	571891	111,07
Cropping inserts M 8 (pair)	M 8	571896	111,07
Cropping inserts M 10 (pair)	M 10	571866	111,07
Cropping inserts M 12 (pair)	M 12	571871	111,07

Steel case with insert for 6 cropping tongs/pressing tongs and compartment for pipe cutter up to 42 mm	570295R	96,53
--	---------	-------



REMS cable shear

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

High-grade cable shear in forged and specially hardened steel for cutting electric cable.

Electric cable $\leq 300 \text{ mm}^2 (\varnothing 30 \text{ mm})$

REMS cable shear – Easy cutting of electric cable.

Made of forged and specially hardened steel.

Replaceable cutting blades manufactured on CNC production centres ensure a precision blade geometry and long service life. Large cutting range.

Driven by REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.



German Quality Product



Supply format


REMS cable shear. Cable shears with 2 changeable cable cutters for electric cables $\leq 300 \text{ mm}^2 (\varnothing 30 \text{ mm})$. In a carton.

	Art.-No.	€
Cable cutters (pack of 2)	571889R02	111,07

Accessories

Description	Art.-No.	€
Cable cutters (pack of 2)	571889R02	111,07





Axial Press Jointing



**Cordless axial press 30 22V
Compression heads**

244



Manual axial press

245



**Cordless axial press 25 22V
Cordless axial press 25 L 22V**

246



Compression heads

248

REMS Ax-Press 30 22V

Compact, handy electric tool for producing compression sleeve joints with crimping sleeve. For trade and industry. For the building site and the workshop. Li-Ion 22V Technology. For battery and corded operation.

Axial compression Ø 12–32 mm

REMS Ax-Press 30 22V – up to Ø 32 mm. Ultra light, ultra small, ultra handy, ultra fast. Li-Ion 21.6 V, 2.5 Ah battery for approx. 220 pressings Georg Fischer pfci ALUPEX-EXPRESS Ø 16 mm with one battery charge*.

Compression heads for all common systems

Complete assortment of REMS compression heads for all common compression sleeve systems with crimping sleeve. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and correspond to the respective compression sleeve system. Thus perfect system-conformity, safe jointing.

Design

Compact, handy, light. Drive unit with battery only 4.6 kg. Vertically from the drive unit located pressing device for seating the compression heads. Can be used anywhere, free hand, over head, in confined spaces. Optimum weight distribution for one-hand operation. Drive unit with inserted compression heads can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Compression heads and expander heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

Drive

High pressing force for perfect pressing in seconds, e.g. Ø 26 mm in only 5 s. Thrust force 30kN. Powerful electro-hydraulic drive, eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah battery for approx. 220 pressings, 4.4 Ah for approx. 380 pressings, 5.0 Ah for approx. 430 pressings, 9.0 Ah for approx. 780 pressings Georg Fischer pfci ALUPEX-EXPRESS Ø 16 mm with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Supply format

REMS Ax-Press 30 22V Basic-Pack. Cordless axial press 30 kN for producing compression sleeve joints with crimping sleeve Ø 12–32 mm. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240V, 50–60Hz, 70W. In sturdy steel case.

	Art.-No.	€
573018R220	2 117,52	

Accessories

Description	Art.-No.	€
REMS Ax-Press 30 22V drive unit, without battery	573008R22	1 577,76
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	414,16
Steel case with insert	573282R	110,03
REMS Lumen 2800 22V, cordless LED flood light, see page 111		

REMS compression heads

Compression sleeve system	Compression head	Art.-No.	€
Brasstech Raptor/ Metalpex/ Raptor 2/ MULTitermoSAN	ME 14 (pack of 2)	573100	107,95
	ME 16 (pack of 2)	573102	107,95
	ME 20 (pack of 2)	573106	107,95
	ME 26 (pack of 2)	573108	107,95
	ME 32 (pack of 2)	573110	118,33
General Fittings Serie 5400	ME 14 (pack of 2)	573100	107,95
	ME 16 (pack of 2)	573102	107,95
	ME 20 (pack of 2)	573106	107,95
	ME 26 (pack of 2)	573108	107,95
	ME 32 (pack of 2)	573110	118,33

Cordless axial press 30 kN



German Quality Product



Info



REMS compression heads

Compression sleeve system	Compression head	Art.-No.	€
Georg Fischer pfci	ME 16 (pack of 2)	573102	107,95
	ME 20 (pack of 2)	573106	107,95
	ME 26 (pack of 2)	573108	107,95
Logstor	ME 16 (pack of 2)	573102	107,95
	LR 20 (pack of 2)	573430	107,95
	LR 22 (pack of 2)	573432	107,95
	LR 25 (pack of 2)	573434	107,95
	LR 28 (pack of 2)	573436	107,95
	LR 32 (pack of 2)	573438	118,33

*Ambient temperature approx. 20°C.

REMS Ax-Press HK / H

One-hand axial press / Manual axial press

Universal manual axial press for producing compression sleeve joints.

Axial compression

Ø 12 – 32 mm

REMS Ax-Press HK – universal up to Ø 22 mm

Ultra small, ultra light, ultra handy. Only 1.1 kg

REMS Ax-Press H – universal up to Ø 32 mm.

Handy and light. Only 1.4 kg.

**Complete assortment of REMS compression heads,
quickly interchangeable.**

System advantage

Only one type of compression heads for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22V ACC, REMS Ax-Press 25 L 22V ACC. Thus easy, economic stocking.

Compression heads

Full range of REMS compression heads for all common compression sleeve systems (page 248 – 249). Choice of REMS compression heads with spring lock for seating common compression inserts. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and meet the demands of compression sleeve systems. Thus perfect system-conformity, safe jointing.

Twin compression heads


REMS twin compression heads with two holders each which interleave, for pipe unions of different dimensions (page 248). No need to change compression heads. Extremely simple, saves time.

Design

Compact, job site proven. Handy and light. REMS Ax-Press HK drive unit only 1.1 kg. REMS Ax-Press H drive unit only 1.4 kg. Works anywhere, free-hand, also in tight spots. 66 mm stroke. Quick-acting forward and release for easy, fast operation. Selectable compression head position (**Patent DE 10 2004 018 429, Patent ES 2 273 563, Patent FR 05 03513**) for pressing compression sleeve connectors with a clamping distance of ≤ 161 mm in one action and for double pressings. Quick-change compression heads and pressing inserts without tools. Secure fit of compression heads and pressing inserts by spring catch. REMS Ax-Press H with overload protection.

Expanding

Various pipe expanders and complete range of REMS expanding heads for all common compression sleeve systems (page 253 – 257).



German Quality Product



Supply format

REMS Ax-Press HK drive unit. Axial press for single-handed operation for producing compression sleeve joints Ø 12–22 mm. 66 mm stroke. With quick-acting forward and release. For driving REMS compression heads. In a carton.

	Art.-No.	€
	574302R	206,56

Supply format

REMS Ax-Press H drive unit. Manual axial press for producing compression sleeve joints Ø 12–32 mm. 66 mm stroke. With quick-acting forward and release. For driving REMS compression heads. In a carton.

	Art.-No.	€
	574300RX	289,60

Accessories

Description	Art.-No.	€
REMS compression heads see page 248–249.		
Carrying bag for REMS Ax-Press HK/H drive unit and compression heads	574437R	45,67
Case with inlay for REMS Ax-Press HK drive unit and compression heads	574352R	64,36



REMS Ax-Press 25 22V ACC REMS Ax-Press 25 L 22V ACC

Compact, handy power tool with automatic return for manufacturing compression sleeve joints. Li-Ion 22V Technology. For battery and corded operation. For trade and industry. For the building site and the workshop.

Axial compression Ø 12–40 mm

**REMS Ax-Press 25 22V ACC – universal up to Ø 40 mm.
Super light, super handy. Fast. With automatic return.
Optimum weight distribution for single-hand operation.
Swivelling compression device. Li-Ion 21.6 V, 2.5 Ah
battery for approx. 500 pressings REHAU RAUTITAN PX
Ø 16 mm with one battery charge*.**

System advantage

Only one type of compression heads for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22V ACC, REMS Ax-Press 25 L 22V ACC. Thus easy, economic stocking.

Compression heads for all common systems

Full range of REMS compression heads for all common compression sleeve systems (page 248–249). Choice of REMS compression heads with spring lock for seating common compression inserts. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and meet the demands of compression sleeve systems. Thus perfect system-conformity, safe jointing.

Twin compression heads

REMS twin compression heads with two holders each which interleave, for pipe unions of different dimensions (page 248). No need to change compression heads. Extremely simple, saves time.

Design

Compact, handy, light. REMS Ax-Press 25 22V ACC drive machine with battery weighs only 3.0 kg, only 28 cm long REMS Ax-Press 25 L 22V ACC drive machine with battery weighs only 3.2 kg, only 31 cm long REMS Ax-Press 25 22V ACC and REMS Ax-Press 25 L 22V ACC with 40 mm stroke respectively REMS Ax-Press 25 22V ACC with preset compression head position for pressing compression sleeve connectors with a clamping distance $a \leq 82$ mm in one action REMS Ax-Press 25 L 22V ACC with selectable compression head position for pressing compression sleeve connectors with a clamping distance $a \leq 116$ mm in one action and for double pressings. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Ergonomically shaped housing with recessed grip. LED work light for illuminating the work place. Swivelling compression device for working in confined area. Compression heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

Drive

Enormous pressing force for fast and perfect jointing. Thrust force REMS Ax-Press 25 22V 20 kN, thrust force REMS Ax-Press 25 L 22V 13 kN. Powerful electro-hydraulic drive with automatic return (ACC), eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah battery for approx. 500 pressings, 4.4 Ah for approx. 880 pressings, 5.0 Ah for approx. 1000 pressings, 9.0 Ah for approx. 1800 pressings REHAU RAUTITAN PX Ø 16 mm with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. Rapid charger 100–240 V, 90 W. Rapid charger 100–240 V, 290 W, for shorter charging times, as accessory. Voltage supply 220–240 V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

Expanding

Various pipe expanders and complete range of REMS expanding heads for all common pressure sleeve systems

Cordless axial press 20 kN with automatic return
Cordless axial press 13 kN with automatic return

REMS Ax-Press 25 22V ACC



with automatic circuit control
and charging status check

e.g.
aquatherm,
General Fittings,
IVT,
REHAU,
REVEL,
Seppelfricke,
TECE,
TIEMME,
Würth


REMS Ax-Press 25 L 22V ACC



with automatic circuit control
and charging status check

e.g.
AC-FIX,
BARBI,
FERR0 systems
BRASELI,
Brass & Fittings,
EUROP'FLUIDES,
Fittings Estándar,
PLÁSTICOS FERRO,
Velta

German Quality Product



REMS Ax-Press 25 22V ACC REMS Ax-Press 25 L 22V ACC

Cordless axial press 20 kN with automatic return
Cordless axial press 13 kN with automatic return

Supply format

REMS Ax-Press 25 22V ACC Basic-Pack. Cordless axial press 20 kN for producing compression sleeve joints Ø 12–40 mm, 40 mm stroke, for pressing compression sleeve connections with a clamping distance $a \leq 82$ mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240V or 110 V, 50–60 Hz, 70 W. Without compression heads. In sturdy steel case.

	Art.-No.	€
	573022R220	1 505,10

Other voltages on request.



Info

Supply format

REMS Ax-Press 25 L 22V ACC Basic-Pack. Cordless axial press 13 kN for producing compression sleeve joints Ø 12–40 mm, 40 mm stroke, for pressing compression sleeve connections with a clamping distance $a \leq 116$ mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240V or 110 V, 50–60 Hz, 70 W. Without compression heads. In sturdy steel case.

	Art.-No.	€
	573023R220	1 505,10

Other voltages on request.



Info

Accessories

Description	Art.-No.	€
REMS compression heads see page 248–249.		
REMS Ax-Press 25 22V ACC drive unit, $a \leq 82$ mm, without battery	573020R22	1 079,52
REMS Ax-Press 25 L 22V ACC drive unit, $a \leq 116$ mm, without battery	573021R22	1 079,52
Battery Li-Ion 21.6 V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6 V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6 V, 50–60Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	414,16
Steel case with insert	578290R	110,03
REMS Lumen 2800 22V , cordless LED flood light, see page 111		



REMS compression heads

Accessories for REMS Ax-Press HK, REMS Ax-Press H,
REMS Ax-Press 25 22 V ACC, REMS Ax-Press 25 L 22 V ACC



REMS compression heads with spring lock for commercially available press inserts

Description	Use
Compression head Basic 20 (pack of 2)	for pipe fittings 20 mm and for standard press inserts outer Ø 20 mm
Compression head Basic 25 (pack of 2)	for pipe fittings 25 mm and for standard press inserts outer Ø 25 mm
Compression head Basic 32 (pack of 2)	for pipe fittings 32 mm and for standard press inserts outer Ø 32 mm

Commercially available
press inserts:

T's and
elbows



Dm 16



Dm 20



Dm 22



Dm 25




Dm 32



REMS twin compression heads

Description	Use
Twin compression head RH 16/20 (pack of 2)	for pipe fittings 16 and 20 mm



REMS compression head for T-pieces, elbows, splitters, transition pieces

Description	Use
Compression head UNI T/L (piece)	for T-pieces, elbows, splitters, in combination with an additional compression head; for transition pieces, in combination with a support bolt



REMS support bolt for transition pieces

Description	for transition pieces inch	Art.-No.	€
Support bolt 3/8"	3/8	573647R	12,98
Support bolt 1/2"	1/2	573648R	14,95
Support bolt 3/4"	3/4	573649R	16,82



REMS compression heads

Select compression heads yourself!

Search for the required compression sleeve system in the table below and select the correct compression heads.


High-grade compression heads in forged and specially hardened steel. Quickly interchangeable, without tools. The REMS compression heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, safe jointing. Drive through REMS axial presses.



Compr. heads Uni



Compr. head UNI T/L




Compr. heads Basic for press inserts

Pressure sleeves system	Compression head mm	Number of pressing heads	fits REMS Ax-Press			Art.-No.	€
			HK ¹⁾	H	25		
AC-FIX (Global Piping System)	UNI 12	2				573630	107,95
	UNI 16	2	•	•	•	573632	107,95
	UNI 20	2	•	•	•	573636	107,95
	UNI 25	2	•	•	•	573640	107,95
	UNI 32	2	•	•	•	573644	107,95
	UNI T/L**	1	•	•	•	573646 R	107,33
	Basic 20*	2	•	•	•	573624	119,37
	Basic 25*	2	•	•	•	573616	119,37
	Basic 32*	2	•	•	•	573628	119,37
aquatherm	AT 16	2	•	•	•	573120	107,95
	AT 20	2	•	•	•	573122	107,95
	AT 25	2	•	•	•	573124	107,95
	AT 32	2	•	•	•	573126	118,33
	AT 40	2	•	•	•	573128	128,71
BARBI GLADIATOR (Industrial Blasol)	UNI 18	2	•	•	•	573634	107,95
	UNI 22	2	•	•	•	573638	107,95
	UNI 26	2	•	•	•	573642	107,95
	UNI 32	2	•	•	•	573644	107,95
	UNI 40	2	•	•	•	573652	128,71
	UNI T/L**	1	•	•	•	573646 R	107,33
	Basic 20*	2	•	•	•	573624	119,37
	Basic 25*	2	•	•	•	573616	119,37
	Basic 32*	2	•	•	•	573628	119,37
BARBI RETICULADO (Industrial Blasol)	UNI 12	2	•	•	•	573630	107,95
	UNI 16	2	•	•	•	573632	107,95
	UNI 20	2	•	•	•	573636	107,95
	UNI 25	2	•	•	•	573640	107,95
	UNI 32	2	•	•	•	573644	107,95
	UNI 40	2	•	•	•	573652	128,71
	UNI T/L**	1	•	•	•	573646 R	107,33
	Basic 20*	2	•	•	•	573624	119,37
	Basic 25*	2	•	•	•	573616	119,37
	Basic 32*	2	•	•	•	573628	119,37
FERRO systems BRASELL GPF AXIAL	UNI 12	2	•	•	•	573630	107,95
	UNI 16	2	•	•	•	573632	107,95
	UNI 20	2	•	•	•	573636	107,95
	UNI 25	2	•	•	•	573640	107,95
	UNI 32	2	•	•	•	573644	107,95
	UNI 40	2	•	•	•	573652	128,71
	UNI T/L**	1	•	•	•	573646 R	107,33
	Basic 20*	2	•	•	•	573624	119,37
	Basic 25*	2	•	•	•	573616	119,37
	Basic 32*	2	•	•	•	573628	119,37
Brass & Fittings PRESSMAN PowerFit	UNI 16	2	•	•	•	573632	107,95
	UNI 20	2	•	•	•	573636	107,95
	UNI 25	2	•	•	•	573640	107,95
	UNI 32	2	•	•	•	573644	107,95
	UNI T/L**	1	•	•	•	573646 R	107,33
	Basic 20*	2	•	•	•	573624	119,37
	Basic 25*	2	•	•	•	573616	119,37
	Basic 32*	2	•	•	•	573628	119,37
COMAP PEYX	UNI 12	2	•	•	•	573630	107,95
	UNI 16	2	•	•	•	573632	107,95
	UNI 20	2	•	•	•	573636	107,95
	UNI 25	2	•	•	•	573640	107,95
	UNI 32	2	•	•	•	573644	107,95
	UNI T/L**	1	•	•	•	573646 R	107,33
	Basic 25*	2	•	•	•	573616	119,37
	Basic 32*	2	•	•	•	573628	119,37
EUROP FLUIDES HYDROFLUIDES	UNI 12	2	•	•	•	573630	107,95
	UNI 16	2	•	•	•	573632	107,95
	UNI 20	2	•	•	•	573636	107,95
	UNI 25	2	•	•	•	573640	107,95
	UNI 32	2	•	•	•	573644	107,95
	UNI T/L**	1	•	•	•	573646 R	107,33
	Basic 25*	2	•	•	•	573616	119,37
	Basic 32*	2	•	•	•	573628	119,37
Fittings Estándar	UNI 12	2	•	•	•	573630	107,95
	UNI 16	2	•	•	•	573632	107,95
	UNI 20	2	•	•	•	573636	107,95
	UNI 25	2	•	•	•	573640	107,95
	UNI 32	2	•	•	•	573644	107,95
	UNI T/L**	1	•	•	•	573646 R	107,33
	Basic 20*	2	•	•	•	573624	119,37
	Basic 25*	2	•	•	•	573616	119,37
	Basic 32*	2	•	•	•	573628	119,37
General Fittings Serie 3400 PEX Gold-Fix	RE 16	2	•	•	•	573160	107,95
	RE 20	2	•	•	•	573162	107,95
	RE 25	2	•	•	•	573172	107,95
	RE 32	2	•	•	•	573178	107,95
	RO 16	2	•	•	•	573184	107,95
	RO 20	2	•	•	•	573186	107,95
General Fittings Serie 3400 PEX/AL/PEX Gold-Fix	RE 16	2	•	•	•	573160	107,95
	RE 20	2	•	•	•	573162	107,95
	RE 25	2	•	•	•	573172	107,95
	RE 32	2	•	•	•	573178	107,95
	RO 16	2	•	•	•	573184	107,95
	RO 20	2	•	•	•	573186	107,95
General Fittings Serie 3400 PEX Gold-Therm	RH 17	2	•	•	•	573168	107,95
	RH 20	2	•	•	•	573170	107,95
HERZ QUICK FIX	HC 16	2	•	•	•	573112	107,95
	HC 20	2	•	•	•	573114	107,95
	HC 26	2	•	•	•	573116	107,95
	HC 32	2	•	•	•	573118	118,33
IVT PRINETO	IV 16/17	3	•	•	•	573320	161,93
	IV 20/21	3	•	•	•	573325	161,93
	IV 25/26	3	•	•	•	573330	161,93
	IV 32/33	3	•	•	•	573335	161,93

Accessories for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22V ACC, REMS Ax-Press 25 L 22V ACC

Pressure sleeves system	Compression head mm	Number of pressing heads	fits REMS Ax-Press			Art.-No.	€
			HK ¹⁾	H	25		
PB TUB Sertigliss	UNI 12	2	•	•	•	573630	107,95
	UNI 16	2	•	•	•	573632	107,95
	UNI 20	2	•	•	•	573636	107,95
	UNI 25	2	•	•	•	573640	107,95
	UNI 32	2	•	•	•	573644	107,95
	UNI T/L**	1	•	•	•	573646 R	107,33
	Basic 25*	2	•	•	•	573616	119,37
	Basic 32*	2	•	•	•	573628	119,37
PLÁSTICOS FERROPLAST GPF AXIAL	UNI 16	2	•	•	•	573632	107,95
	UNI 20	2	•	•	•	573636	107,95
	UNI 25	2	•	•	•	573640	107,95
	UNI 32	2	•	•	•	573644	107,95
	UNI T/L**	1	•	•	•	573646 R	107,33
	Basic 20*	2	•	•	•	573624	119,37
	Basic 25*	2	•	•	•	573616	119,37
	Basic 32*	2	•	•	•	573628	119,37
PLUMBING PLUS EZ/PEX Sleeve (AUS)	RH 16 L	2	•	•	•	573150	107,95
	RH 20 L	2	•	•	•	573152	107,95
	RH 16/20 L	2	•	•	•	573158	215,90
	RH 25	2	•	•	•	573154	107,95



Expanding Extracting

	Hand tube expander Cu	252
	Expander head Cu	252
	One-hand pipe expander	253
	Hand tube expander P	253
	Cordless pipe expander Cu	254
	Cordless pipe expander P	254
	Cordless pipe expander P-CEF	254
	Electro-hydraulic pipe expander P-CEF	256
	Expander head P Expander head P-CEF	257
	Hand tube extractor	258
	Electric tube extractor Electric tube expander	259

REMS Ex-Press Cu

Hand tube expander

Proven quality tool for expanding and calibrating pipes for pipe installation without fittings.

Soft copper tubes $s \leq 1.5$ mm	$\varnothing 8-42$ mm $\varnothing \frac{3}{8}-1\frac{1}{8}$ "
Soft aluminium tubes, soft precision steel tubes $s \leq 1.2$ mm	$\varnothing 8-42$ mm $\varnothing \frac{3}{8}-1\frac{1}{8}$ "
Soft stainless steel tubes $s \leq 1$ mm	$\varnothing 8-42$ mm $\varnothing \frac{3}{8}-1\frac{1}{8}$ "

REMS Ex-Press Cu – for making sockets yourself.

6-face mandrel for even and concentric expanding.

Extra long sockets according to DVGW. Expander heads with calibration neck, fit other makes as well.

Cost advantage

Pipe installation without fittings. No costs for fittings, storage, procurement. Savings in soldering joints, soldering material and working hours. Using up pipe pieces to provide sockets.

Design

Robust quality tool. Torsion-free, power-transmitting expander levers with ergonomically designed handles, for effortless expanding. 6-face mandrel for even and concentric expanding. Extra long sockets, spring-loaded return of mandrel release. Also for other suitable makes of expander heads.

Expander heads

Quick-change. Extra long expander heads result in extra long sockets for perfect pipe connections according to DVGW. Special neck at expander head specially for calibration of deformed pipe ends.

Supply format

REMS Ex-Press Cu Set. Hand tube expander $\varnothing 8-42$ mm, $\varnothing \frac{3}{8}-1\frac{1}{8}$ ". Soft copper tubes $\varnothing 8-42$ mm, $\varnothing \frac{3}{8}-1\frac{1}{8}$ ", $s \leq 1.5$ mm, soft aluminium tubes and soft steel precision tubes $\varnothing 8-42$ mm, $\varnothing \frac{3}{8}-1\frac{1}{8}$ ", $s \leq 1.2$ mm, soft stainless steel tubes $\varnothing 8-42$ mm, $\varnothing \frac{3}{8}-1\frac{1}{8}$ ", $s \leq 1$ mm. Expander drive. Choice of expander heads for pipes in mm or inch. In sturdy steel case.

Description	Art.-No.	€
Set 12+15+18+22	150000R	467,10
Set 12+15+22+28	150005R	482,67
Set 15+18+22+28	150006R	482,67
Set 12+15+18+22+28	150007R	544,95
Set 12+14+16+18+22+28+32	150008R	679,89
Set 12+14+16+18+22	150010R	539,76
Set $\frac{3}{8}+\frac{1}{2}+\frac{5}{8}+\frac{3}{4}+\frac{7}{8}+1\frac{1}{8}$"	150017R	643,56
Set $\frac{1}{2}+\frac{5}{8}+\frac{7}{8}+1\frac{1}{8}$"	150018R	508,62
Set $\frac{3}{8}+\frac{1}{2}+\frac{5}{8}+\frac{3}{4}"$	150019R	487,86
Set $\frac{3}{8}+\frac{1}{2}+\frac{5}{8}+\frac{3}{4}+\frac{7}{8}+1"$	150020R	643,56

Accessories

Description	Pipes Ø mm/inch	Art.-No.	€
Expander head Cu (fit expander drives of REMS Ex-Press Cu 22V ACC and other makes also)	8	150100R	64,67
	10	150105R	64,67
	12	150110R	64,67
	14	150120R	64,67
	15	150125R	64,67
	16	150130R	64,67
	18	150140R	64,67
	20	150145R	90,51
	22	150150R	64,67
	24	150155R	103,38
	25	150160R	90,51
	26	150165R	77,54
	28	150170R	77,54
	30	150175R	103,38
	32	150180R	77,54
	34	150185R	103,38
	35	150190R	103,38
	36	150195R	103,38
	40	150205R	103,38
	42	150210R	90,51
	$\frac{3}{8}"$	150220R	64,67
	$\frac{1}{2}"$	150225R	64,67
	$\frac{5}{8}"$	150230R	64,67
	$\frac{3}{4}"$	150235R	77,54
	$\frac{7}{8}"$	150240R	77,54
	1"	150245R	90,51
	$1\frac{1}{8}"$	150250R	90,51
Expander drive Cu (taper angle 18°)		150500R	180,61
Steel case with insert		150600R	55,01



German Quality Product



Info



REMS Ex-Press H

One-hand pipe expander

Robust, compact quality tool for expanding tubes.
For one-hand operation.

PEX tubes Serie S 5 according
to ISO 4065 Ø 12 – 40 mm

REMS Ex-Press H – universal up to Ø 40 mm.

Robust, compact quality tool. Super light, only 0.7 kg.
Stepped mandrels for expanding several tube dimensions, no tool change required.
Torsion-free, leveraged expander tool for effortless expanding.
For one-hand operation.

Supply format

REMS Ex-Press H. One-hand pipe expander for PEX tubes Serie S 5 according
to ISO 4065 Ø 12 – 40 mm. In a carton.

	Art.-No.	€
	150550R	196,18



German Quality Product



REMS Ex-Press P

Hand tube expander

Proven quality tool for expanding tubes.

Plastic tubes, multi-layer composite tubes Ø 12 – 32 mm

REMS Ex-Press P – for expanding tubes.

Conical mandrel for even and concentric expanding.

Design

Robust quality tool. Torsion-free, power-transmitting expander levers with ergonomically designed handles, for effortless expanding. Conical mandrel (taper angle 18°) for even and concentric expanding. Long mandrel guidance, spring-loaded mandrel release. Also for other suitable makes of expander heads.

Expander heads for all common systems

Complete assortment of REMS expander heads P for all common compression sleeve systems (page 257). Quickly interchangeable, without tools. The REMS expander heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, exact expanding.

Supply format

REMS Ex-Press P Set. Hand tube expander for plastic tubes and multi-layer composite tubes Ø 12 – 32 mm. REMS Ex-Press P. Expander heads P for tubes in mm. In sturdy steel case.

Description	Compr. sleeve system	Art.-No.	€
Set AT P 16 + 20 + 25	aquatherm SHT PB/PE-Rohre	150021R	591,66
Set AT V 16 + 20 + 25	aquatherm SHT Mehrschicht-Metall-verbundrohre IVT PRINETO, Würth	150033R	591,66
Set IV 16/17+20/21+25/26	PRINETO	150026R	591,66
Set RH HAS 17 + 20 + 25	REHAU RAUTHERM S (REHAU HAS), General Fittings Serie 3400 PEX Gold-Therm	150027R	591,66
Set RH HIS 16 + 20 + 25	REHAU RAUTITAN flex/gas flex/pink/his, General Fittings Serie 3400 PEX, REVEL, Seppelfricke SD Sistemi Italia Neroflex, TIEMME Assialplex	150028R	591,66
Set RH MKV 16 + 20 + 25	REHAU RAUTITAN stabil/gas stabil, General Fittings Serie 3400 PEX/AL/PEX, Seppelfricke SD Sistemi Italia Sylver	150022R	591,66
Set RH 16 + 20 + 25	REHAU RAUTHERM (série S 5), REHAU (GBR) EVERLOC	150029R	591,66
Set TC 16 + 18/20 + 25	TECE TECEFLEX	150025R	591,66

System-specific and/or national differences of the wall thickness (s) of tubes need to be considered selecting expander heads, see table page 257.

Accessories

Description	Art.-No.	€
Expander heads P see page 257.		
Expander drive REMS Ex-Press P (taper angle 18°)	150510R	204,49
Steel case with insert	150600R	55,01



German Quality Product



Info

e.g.
aquatherm,
General Fittings,
IVT,
REHAU,
REVEL,
Seppelfricke,
TECE,
TIEMME,
Würth



REMS Ex-Press 22V ACC

Compact, handy power tool with automatic return for fast, easy expansion of pipes/rings. Li-Ion 22V Technology. For cordless and mains operation. For trade and industry. For the building site and the workshop.

Expander Cu

for holding the REMS Cu expander heads and suitable expander heads of other makes for:

Soft copper pipes, $s \leq 1.5$ mm $\varnothing 8-42$ mm
 $\varnothing \frac{3}{8}-1\frac{3}{4}$ "

Soft aluminium pipes,
soft precision steel pipes, $s \leq 1.2$ mm $\varnothing 8-42$ mm
 $\varnothing \frac{3}{8}-1\frac{3}{4}$ "

Soft stainless steel pipes, $s \leq 1$ mm $\varnothing 8-42$ mm
 $\varnothing \frac{3}{8}-1\frac{3}{4}$ "

Expander P

for holding the REMS P expander heads and suitable expander heads of other makes for:

Plastic tubes, composite tubes $\varnothing 12-40$ mm

Expander P-CEF

for holding the REMS P-CEF expander heads and suitable expander heads of other makes for:

Cold Expansion Fittings made of plastic (P-CEF)

$\varnothing 16-40$ mm
 $\varnothing \frac{1}{2}-1\frac{1}{2}$ "
 $s \leq 4.95$ mm

REMS Ex-Press 22V ACC – fast, easy electric expanding up to $\varnothing 42$ mm. With automatic return. Conical expanding mandrel for even centric expanding. E.g. REMS Ex-Press Cu 22V ACC with Li-Ion 21.6 V, 2.5 Ah battery for approx. 600 expansions of soft copper pipe 15×1 mm with one battery charge*.

System advantage

Only one drive unit, optionally with **expander Cu** for holding the REMS Cu expander heads and suitable expander heads of other makes, **expander P** for holding the REMS P expander heads and suitable expander heads of other makes, **expander P-CEF** for holding the REMS P-CEF expander heads and suitable expander heads of other makes.

Expander heads for all common systems

Quick-change, without tools. Also for other suitable makes of expander tongs.

REMS expander heads Cu (page 252) with extra long segments provide an extra long muff for a perfect pipe joint in accordance with DVGW. Collar on the expander head for calibrating unround pipe ends.

REMS expander heads P (page 257) are system-specific and correspond to the requirements of the respective compression sleeve systems. Therefore, perfectly system-conformant, exact expanding.

REMS expander heads P-CEF (page 257) are system-specific and correspond to the requirements of the respective systems. Automatic, gradual expansion until reaching the given end position which is determined by the expander head.

Design

Ultra light, ultra small, ultra handy. Drive unit with battery pack weighs only 2.7 kg. Drive unit with expander only 26 cm long. Can therefore be used anywhere, free hand, over head, also in very confined spaces. Optimum weight distribution for one-hand operation. Ergonomically designed housing. LED work light for illuminating the work place. Expanding mandrel of the Cu and P expanders with conical angle 18°, expanding mandrel of the P-CEF expander with conical angle 20°, or even centric expanding. Long mandrel guide, spring-loaded mandrel recoil. Also for other suitable makes of expander heads.

Drive

High expanding force for perfect, split-second expanding. Thrust force 20 kN. Powerful electro-hydraulic drive with automatic return (ACC), with powerful battery motor 21.6V, 380W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety switch.

Cordless pipe expander 20 kN with automatic return



German Quality Product



Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful.

REMS Ex-Press Cu 22V ACC with Li-Ion 21.6 V, 2.5 Ah battery for approx. 600 expansions, 4.4 Ah for approx. 1050 expansions, 5.0 Ah for approx. 1200 expansions, 9.0 Ah for approx. 2160 expansions of soft copper pipe 15×1 mm with one battery charge*.

REMS Ex-Press P 22V ACC with Li-Ion 21.6 V, 2.5 Ah battery for approx. 750 expansions, 4.4 Ah for approx. 1320 expansions, 5.0 Ah for approx. 1500 expansions, 9.0 Ah for approx. 2700 expansions of REHAU RAUTITAN flex $\varnothing 16 \times 2.2$ mm with one battery charge*.

REMS Ex-Press P-CEF 22V ACC with Li-Ion 21.6 V, 2.5 Ah battery for approx. 200 expansions, 4.4 Ah for approx. 360 expansions, 5.0 Ah for approx. 410 expansions, 9.0 Ah for approx. 740 expansions of Uponor Quick & Easy $\varnothing 16 \times 1.8$ with one battery charge*.

Graduated charging status check by coloured LEDs. Operating temperature range -10 to +60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 15A output, for mains operation instead of Li-Ion xbattery 21.6 V, as accessory.

Supply format

REMS Ex-Press Cu 22V ACC Basic-Pack. Cordless pipe expander 20 kN for fast expanding of copper pipes Ø 8–42 mm. Electro-hydraulic drive with automatic return, with powerful 21.6V, 380W battery motor, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety switch. LED work light. Li-Ion 21.6V, 2.5 Ah battery, 220–240V, 50–60Hz, 70W rapid charger. Cu expander for holding the REMS Cu expander heads and suitable expander heads of other makes. Without expander heads. In sturdy steel case.

	Art.-No.	€
	575020R220	1 505,10

Other voltages on request.



Supply format

REMS Ex-Press P 22V ACC Basic-Pack. Cordless pipe expander 20 kN for fast expanding of plastic and composite tubes Ø 12–40 mm. Electro-hydraulic drive with automatic return, with powerful 21.6V, 380W battery motor, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety switch. LED work light. Li-Ion 21.6V, 2.5 Ah battery, 220–240V, 50–60Hz, 70W rapid charger. P expander for holding the REMS P expander heads and suitable expander heads of other makes. Without expander heads. In sturdy steel case.

	Art.-No.	€
	575021R220	1 505,10

Other voltages on request.



e.g.
aquatherm,
General Fittings,
IVT,
REHAU,
REVEL,
Seppelfricke,
TECE,
TIEMME,
Würth

Supply format

REMS Ex-Press P-CEF 22V ACC Basic-Pack. Cordless pipe expander 20 kN for fast expanding of plastic tubes Ø 16–40 mm. Electro-hydraulic drive with automatic return, with powerful 21.6V, 380W battery motor, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety switch. LED work light. Li-Ion 21.6V, 2.5Ah battery, 220–240V, 50–60Hz, 70W rapid charger. P-CEF expander for holding the REMS P-CEF expander heads and suitable expander heads of other makes. Without expander heads. In sturdy steel case.

	Art.-No.	€
	575022R220	1 505,10

Other voltages on request.



e.g.
Brass & Fittings,
Uponor

Accessories

Description	Art.-No.	€
REMS Ex-Press 22V ACC drive unit, without expander, without battery	575010R22	1 079,52
Expander Cu for holding the REMS Cu expander heads and suitable expander heads of other makes for: Conical angle 18°.	575252R	77,23
Expander heads Cu see page 252		
Expander P for holding the REMS P expander heads and suitable expander heads of other makes for: Conical angle 18°.	575253R	77,23
Expander heads P see page 257.		
Expander P-CEF for holding the REMS P-CEF expander heads and suitable expander heads of other makes for: Conical angle 20°.	575256R	77,23
Expander heads P-CEF see page 257.		
Expander tongs P-CEF (conical angle 20°), for accommodating the expander heads P-CEF 16–40 mm, ½–1½"	150515R	204,49
Battery Li-Ion 21.6V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W	571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 15A, for mains operation instead of battery Li-Ion 21.6 V.	571567R220	414,16
Steel case with insert	578290R	110,03
REMS Lumen 2800 22V , cordless LED flood light, see page 111		



REMS Power-Ex-Press P-CEF ACC

Compact, handy power tool for fast, easy expanding of pipes/rings. For trade and industry. For the building site and the workshop.

Cold Expansion Fittings made of plastic (P-CEF)

Ø 16 – 63 mm
Ø ½ – 2"
s ≤ 6.3 mm

REMS Power-Ex-Press P-CEF ACC – Fast, easy electric expanding up to Ø 63 mm. With automatic return.

For Uponor Quick & Easy and Giacomini GX System.

Expander heads

Large expanding capacity up to Ø 63 mm. Automatic, gradual expansion until reaching the given end position which is determined by the expander head. Use of the REMS P-CEF expander heads and suitable expander heads of other makes for: Expander 50 – 63 mm, 2", for holding the REMS P-CEF expander heads 50 – 63 mm, 2" and suitable expander heads of other makes. Expander 16 – 40 mm, ½ – 1½", for holding the REMS P-CEF expander heads 16 – 40 mm, ½ – 1½" and suitable expander heads of other makes, as an accessory.

Execution

Compact, robust, job site-proven. Small in size, slender design, drive unit only 5.6 kg. Works anywhere, free-hand, overhead, in confined areas. Ideal weight distribution for single handed operation. Ergonomically designed housing with recessed grip.

Drive

High pressing force for fast, perfect expanding. Thrust force 34 kN. Powerful electro-mechanical drive with automatic return (ACC), with proven universal motor, 450 W, maintenance-free gear with safety slipping clutch and in-feed system with machine screw spindle. Safety tip switch.

Electro-hydraulic pipe expander 34 kN with automatic return



German Quality Product



Info

Supply format

REMS Power-Ex-Press P-CEF ACC Basic-Pack. Electro-hydraulic pipe expander 34 kN for expanding tubes/coils of the Uponor Quick & Easy system Ø 16 – 63 mm, Ø ½ – 2", s ≤ 6.3 mm. Electro-hydraulic drive with automatic retraction, with proven universal motor 230 V or 110 V, 50 – 60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. Expanding device 50 – 63 mm, 2". Without expander heads. In sturdy steel case.

	Art.-No.	€
575017R220	1 462,54	

Note assembly instructions of system supplier. Battery tube expander for other systems on request. Other voltages on request.

Accessories

Description	Art.-No.	€
Expander 16 – 40 mm, ½ – 1½", for holding the P-CEF expander heads 16 – 40 mm, ½ – 1½"	575100R	122,48
Expander heads P-CEF see page 257.		
Steel case with insert	575278R	110,03



REMS expander heads P

REMS expander heads P-CEF

REMS expander heads P

Complete assortment of REMS expander heads P for all common compression sleeve systems. Quickly interchangeable, without tools. The REMS expander heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, exact expanding. Conical angle 18°. Driven by REMS Ex-Press P hand pipe expander (page 253), REMS Ex-Press P 22V ACC cordless pipe expander (page 254–255) and by suitable pipe expanders of other makes.

Compression sleeve system	Expander head P Ø × s	Art.-No.	€
aquatherm grey pipe PB/PE-RT-Rohre	AT P 14 × 2,0	150828	120,41
	AT P 16 × 2,0	150842	120,41
	AT P 18 × 2,0	150873	120,41
	AT P 20 × 2,0	150882	120,41
	AT P 25 × 2,3	150912	120,41
aquatherm grey pipe Mehrschicht-Metallverbundrohre (MVR)	AT V 16 × 2,4	150843	120,41
	AT V 20 × 2,4	150883	120,41
	AT V 25 × 2,7	150913	120,41
	AT V 32 × 3,2	150957	129,75
	AT V 40 × 3,5	150958	142,21
General Fittings Serie 3400 PEX Gold-Fix	RH HIS 16 × 2,2	150849	120,41
	RH HIS 20 × 2,8	150888	120,41
	RH HIS 25 × 3,5	150916	120,41
	RH HIS 32 × 4,4	150945	120,41
General Fittings Serie 3400 PEX/AL/PEX Gold-Fix	RH MKV 16,2 × 2,6	150858	120,41
	RH MKV 20 × 2,9	150897	120,41
	RH MKV 25 × 3,7	150926	120,41
	RH MKV 32 × 4,7	150952	120,41
General Fittings Serie 3400 PEX Gold-Therm	RH HAS 17 × 2,0	150868	120,41
	RH HAS 20 × 2,0	150887	120,41
HERZ QUICK FIX	HC P 16 × 2,0	150806	120,41
	HC P 20 × 2,0	150807	120,41
	HC P 26 × 3,0	150808	120,41
	HC P 32 × 3,0	150809	120,41
IVT PRINETO	IV 16 × 2,2/17 × 2,8	150845	120,41
	IV 20 × 2,8/21 × 3,4	150885	120,41
	IV 25 × 3,5/26 × 4,0	150914	120,41
	IV 32 × 4,4/33 × 4,9	150943	129,75
REHAU RAUTHERM (série S 5)	RH 12 × 1,1	150812	120,41
	RH 16 × 1,5	150846	120,41
	RH 20 × 1,9	150886	120,41
	RH 25 × 2,3 (RH HAS 25 × 2,3)	150915	120,41
	RH 32 × 2,9 (RH HAS 32 × 2,9)	150944	120,41
REHAU RAUTHERM S (REHAU HAS)	RH HAS 17 × 2,0	150868	120,41
	RH HAS 20 × 2,0	150887	120,41
	RH HAS 25 × 2,3	150915	120,41
	RH HAS 32 × 2,9	150944	120,41
REHAU RAUTITAN flex/RAUTITAN gas flex/RAUTITAN pink/RAUTITAN his	RH HIS 16 × 2,2	150849	120,41
	RH HIS 20 × 2,8	150888	120,41
	RH HIS 25 × 3,5	150916	120,41
	RH HIS 32 × 4,4	150945	120,41
	RH HIS 40 × 5,5	150946	129,75
REHAU RAUTITAN stabil/RAUTITAN gas stabil	RH MKV 16,2 × 2,6	150858	120,41
	RH MKV 20 × 2,9	150897	120,41
	RH MKV 25 × 3,7	150926	120,41
	RH MKV 32 × 4,7	150952	120,41
	RH MKV 40 × 6,0	150947	129,75
REHAU (GBR) EVERLOC	RH 16 × 1,5	150846	120,41
	RH 20 × 1,9	150886	120,41
	RH 25 × 2,3 (RH HAS 25 × 2,3)	150915	120,41
	RH 32 × 2,9 (RH HAS 32 × 2,9)	150944	120,41
REVEL	RH HIS 16 × 2,2	150849	120,41
	RH HIS 20 × 2,8	150888	120,41
	RH HIS 25 × 3,5	150916	120,41
	RH HIS 32 × 4,4	150945	120,41
Seppelfricke SD Sistemi Italia Neroflex	RH HIS 16 × 2,2	150849	120,41
	RH HIS 20 × 2,8	150888	120,41
	RH HIS 25 × 3,5	150916	120,41
	RH HIS 32 × 4,4	150945	120,41
Seppelfricke SD Sistemi Italia Sylver	RH MKV 16,2 × 2,6	150858	120,41
	RH MKV 20 × 2,9	150897	120,41
	RH MKV 25 × 3,7	150926	120,41
	RH MKV 32 × 4,7	150952	120,41
TECE TECEflex	TC 12/14	150826	120,41
	TC 16	150855	120,41
	TC 18/20	150894	120,41
	TC 25	150923	120,41
	TC 32	150950	120,41
TIEMME Assialpex	RH HIS 16 × 2,2	150849	120,41
	RH HIS 20 × 2,8	150888	120,41
	RH HIS 25 × 3,5	150916	120,41
	RH HIS 32 × 4,4	150945	120,41

System-specific and/or national differences of the wall thickness (s) of tubes need to be considered selecting expander heads. REMS expander heads P for additional compression sleeve systems on request.

Accessories for REMS pipe expander and other makes

Choose expander heads yourself!

Search for the required compression sleeve system in the table below and select the correct expander heads.



German Quality Product

REMS expander heads P

Complete assortment of REMS expander heads P for all common compression sleeve systems. Quickly interchangeable, without tools. The REMS expander heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, exact expanding. Conical angle 18°. Driven by REMS Ex-Press P hand pipe expander (page 253), REMS Ex-Press P 22V ACC cordless pipe expander (page 254–255) and by suitable pipe expanders of other makes.

Compression sleeve system	Expander head P Ø × s	Art.-No.	€
Würth PRINETO	IV 16 × 2,2/17 × 2,8	150845	120,41
	IV 20 × 2,8/21 × 3,4	150885	120,41
	IV 25 × 3,5/26 × 4,0	150914	120,41
	IV 32 × 4,4/33 × 4,9	150943	129,75

System-specific and/or national differences of the wall thickness (s) of tubes need to be considered selecting expander heads. REMS expander heads P for additional compression sleeve systems on request.



REMS expander heads P-CEF

Full range of REMS P-CEF expander heads for easy expanding of pipes/rings. Quick-change, without tools. The REMS P-CEF expander heads are system-specific and correspond to the requirements of the respective systems. Therefore, perfectly system-conformant, exact expanding. Conical angle 20°. Driven by REMS Ex-Press P-CEF 22V ACC cordless pipe expander (page 254–255), REMS Power-Ex-Press P-CEF ACC electro-hydraulic pipe expander (page 256) and by suitable pipe expanders of other makes.

Compression sleeve system	Expander head P-CEF Ø × s	Art.-No.	€
Uponor Quick & Easy	P-CEF 16 × 1,8	150960R	129,75
	P-CEF 20 × 1,9	150961R	129,75
	P-CEF 25 × 2,3	150962R	129,75
	P-CEF 32 × 2,9	150963R	129,75
	P-CEF 40 × 3,7	150968R	142,21

Expander drive P-CEF (taper angle 20°), for holding the P-CEF expander heads 16–40 mm, ½ – 1½"

150515R **204,49**

System-related and/or national differences of the wall thickness s of the pipes must be considered in the selection of the expander heads.

REMS Hurrican H

Hand tube extractor

Economic manual tool for efficiently making T-branches for pipe installations without fittings.

Hard and soft copper tubes

Ø 10–22 mm
Ø $\frac{3}{8}$ – $\frac{7}{8}$ "
 $s \leq 1.5$ mm

REMS Hurrican H – for making T-branches yourself.

Inexpensive. Also on tubes already installed.

System advantage

Only one type of extractor tools for REMS Hurrican H, REMS Hurrican and REMS Twist/Hurrican. Simple, inexpensive storage. No confusion possible.

Cost advantage

No costs for T-pieces, storage, procurement. Savings in soldering joints, pressing joints and working hours. Higher safety by fewer tube joints.

Design

Compact, handy, light. Can be used anywhere, free-hand, on pipes already installed. Drill head for exact drilling start without centre punching, drilling depth stop according to size of the T-outlet. Limitation of insertion depth to avoid obstruction by using the dimpling pliers. Handy gripping tongs for fixing the tool holder on the pipe, as an accessory.

Drill head drive

Drive with conventional electric drill.

Extractor tools

Special design of extractor tools facilitate even and smooth material deformation without burrs and notches. Therefore no secondary treatment required.

Tool holder drive

With standard ratchet and hexagon socket 11 mm or with spanner. Upgrade to electric pipe neck expander by buying the REMS Twist/Hurrican drive machine.



German Quality Product



Info



Supply format

REMS Hurrican H Set. Hand tube extractor for hard and soft copper tubes Ø 10–22 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", $s \leq 1.5$ mm. Tool holder, drill head, dimpling pliers, lubricant. Extractor tools for tubes in mm or inch. In sturdy case.

Description	Art.-No.	€
Set 12 + 15 + 18 + 22	151003R	550,14
Set 12 + 14 + 16 + 18 + 22	151004R	612,42
Set $\frac{3}{8}$ + $\frac{1}{2}$ + $\frac{5}{8}$ + $\frac{3}{4}$ + $\frac{7}{8}$"	151005R	633,18

Accessories

Description	Tubes Ø mm/inch	Art.-No.	€
Extractor tool			
10		151105R	67,89
12		151110R	67,89
14		151120R	67,89
15		151125R	67,89
16		151130R	67,89
18		151140R	67,89
20		151145R	67,89
22		151150R	67,89
$\frac{3}{8}"$		151155R	72,04
$\frac{1}{2}"$		151160R	69,96
$\frac{5}{8}"$		151165R	69,96
$\frac{3}{4}"$		151170R	69,96
$\frac{7}{8}"$		151175R	69,96
REMS Twist/Hurrican drive unit			
with stabiliser		151402R220	371,60
Grip wrench for clamping the tool holder		076117	109,92
Tool holder		151200R	85,32
Drill head		151210RMM	127,67
Dimpling pliers		151230R	40,48
Ratchet $\frac{1}{2}"$		074021	76,71
Hexagon socket 11 mm		074041	7,79
Lubricant (tin)		151240	9,34
Case with inlay		151618R	53,98



REMS Hurricane

Electric tube extractor

Powerful, compact electric tool for efficient machining of T-branches of hard and soft tubes for tube installations without fittings.

Hard and soft copper tubes	$\varnothing 10\text{--}22\text{ mm}$ $\varnothing \frac{3}{8}\text{--}\frac{7}{8}\text{ inch}$ $s \leq 1.5\text{ mm}$
----------------------------	--

REMS Hurricane – for making T-branches yourself.

Inexpensive. Also on tubes already installed.

System advantage

Only one type of extractor tools for REMS Hurricane H, REMS Hurricane and REMS Twist/Hurricane. Simple, inexpensive storage. No confusion possible.

Cost advantage

No costs for T-branches, storage, procurement. Savings in soldering joints, soldering material and working hours. Higher safety by fewer tube joints.

Design

Compact, handy, light. Can be used anywhere, free-hand, on pipes already installed. Drill head provides precise drilling without punching with any standard power drill. Drill depth-stop according to the size of T-branch. Tool holder for holding the extractor tools. Limitation of insertion depth to avoid obstruction by using the dimpling pliers. Handy grip wrench for clamping the tool holder onto the pipe.

Drive

Proven drive unit with hexagon mount. Enormously powerful. Handly, light, only 1.5 kg. Can be used anywhere, free-hand, also on pipes already installed. Robust, maintenance-free gear with safety slipping clutch. Universal motor, 630 W, high-torque forward and reverse at low speed. Stepless, electronic speed control. The speed can be continuously controlled electronically by variable pressure on the safety switch from 0 to 1,000 rpm (accelerator switch).

Extractor tools

Special design of extractor tools facilitate even and smooth material deformation without burrs and notches. Therefore no secondary treatment required.

REMS Twist/Hurricane

Space and weight-saving combination set for efficient production of T-branches and for efficient cold-expanding of hard and soft tubes for installations without fittings. Only one drive unit for expanding and extracting tools. Price advantage! See page 261.



German Quality Product



Info



Supply format

REMS Hurricane Set. Electric tube extractor for hard and soft copper tube Ø 10–22 mm, Ø $\frac{3}{8}\text{--}\frac{7}{8}\text{ inch}$, $s \leq .5\text{ mm}$. Drive unit with hexagon mount, maintenance-free gear, universal motor 230 V or 110 V, 50–60 Hz, 630 W. High torque at low speed, left and right-hand rotation. Safety tip switch. Continuous, electronic speed control from 0 to 1,000 rpm (accelerator switch). Drive holder. Tool holder, drill head, dimpling pliers, lubricant. Extractor tools for pipes in mm or inch. In sturdy steel case.

Description	Art.-No.	€
Set 12 + 15 + 18 + 22	151000R220	985,06
Set 12 + 14 + 16 + 18 + 22	151010R220	1 048,38
Set $\frac{3}{8}\text{--}\frac{7}{8}\text{ inch}$	151002R220	1 058,76

Other voltages on request.

Accessories

Description	Tubes Ø mm/inch	Art.-No.	€
Extractor tool	10	151105R	67,89
	12	151110R	67,89
	14	151120R	67,89
	15	151125R	67,89
	16	151130R	67,89
	18	151140R	67,89
	20	151145R	67,89
	22	151150R	67,89
	$\frac{3}{8}\text{--}\frac{7}{8}\text{ inch}$	151155R	72,04
	$\frac{1}{2}\text{--}\frac{5}{8}\text{ inch}$	151160R	69,96
	$\frac{5}{8}\text{--}\frac{3}{4}\text{ inch}$	151165R	69,96
	$\frac{3}{4}\text{--}\frac{7}{8}\text{ inch}$	151170R	69,96
	$\frac{7}{8}\text{ inch}$	151175R	69,96
REMS Twist/Hurricane drive unit with stabiliser		151402R220	371,60
Tool holder		151200R	85,32
Drill head		151210RMM	127,67
Dimpling pliers		151230R	40,48
Lubricant (tin)		151240	9,34
Case with inlay		151618R	53,98



Powerful, compact power tool for rational cold expanding of hard and soft copper pipes for pipe installation without fittings.

Hard and soft copper tubes Ø 12–22 mm
 Ø $\frac{3}{8}$ – $\frac{7}{8}$ "
 s ≤ 1 mm

REMS Twist – for making sockets yourself.

Cold-expanding of hard copper pipes.

Cost advantage

No costs for annealing hard copper tubes, for deburring and cleaning, for fittings, storage, procurement. Savings in soldering joints, soldering material and working hours. Higher safety by fewer tube joints. Using up tube pieces to make sockets.

Design

Compact, robust, job site-proven. Simple and fast working free-hand, at vice or workbench. No adjustments. Integrated clamping device provides safe support against torque in both directions.

Drive

Proven drive unit with hexagon mount. Enormously powerful. Handly, light, only 1.5 kg. Can be used anywhere, free-hand, also on pipes already installed. Robust, maintenance-free gear with safety slipping clutch. Universal motor, 630 W, high-torque forward and reverse at low speed. The speed can be continuously controlled electronically by variable pressure on the safety switch from 0 to 1,000 rpm (accelerator switch).

Expander tools

One quick-changing expander tool of each tube size with rotating mandrel for easy expanding and smooth operation. Without annealing, standard socket in just a few seconds, extra long.

REMS Twist/Hurrican

Space and weight-saving combination set for efficient production of T-branches and for efficient cold-expanding of hard and soft tubes for installations without fittings. Only one drive unit for expanding and extracting tools. Price advantage! See page 261.



German Quality Product



Info

Supply format

REMS Twist Set. Electric tube expander for hard and soft copper tubes Ø 12–22 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", s ≤ 1 mm. Drive unit with hexagon mount, maintenance-free gear, universal motor 230 V or 110 V, 50–60 Hz, 630 W. High torque at low speed, left and right-hand rotation. Safety tip switch. Continuous, electronic speed control from 0 to 1,000 rpm (accelerator switch). Drive holder. Lubricant. Expander tools for mm or inch. In sturdy steel case.

Description	Art.-No.	€
Set 12 + 15 + 18 + 22	156000R220	1 078,48
Set 12 + 14 + 16 + 18 + 22	156002R220	1 242,49
Set $\frac{3}{8}$ + $\frac{1}{2}$ + $\frac{5}{8}$ + $\frac{3}{4}$ + $\frac{7}{8}$"	156004R220	1 242,49

Other voltages on request.

Accessories

Description	Tubes Ø mm/inch	Art.-No.	€
Expander tool			
12		156150	173,35
14		156200	173,35
15		156225	173,35
16		156250	173,35
18		156300	173,35
22		156350	173,35
$\frac{3}{8}"$		156375	173,35
$\frac{1}{2}"$		156400	173,35
$\frac{5}{8}"$		156425	173,35
$\frac{3}{4}"$		156450	173,35
$\frac{7}{8}"$		156475	173,35
REMS Twist/Hurrican drive unit			
with stabiliser		151402R220	371,60
Lubricant (tin)		151240	9,34
Steel case with insert		151600R	110,03



REMS Twist/Hurrican

Electric tube extractor
Electric tube expander

Powerful, compact power tool for rational manufacture of T-joints and rational cold expanding of hard and soft copper pipes for pipe installation without fittings. Combination of REMS Twist and REMS Hurrican.

Extracting:

Hard and soft copper tubes Ø 10–22 mm
 Ø $\frac{3}{8}$ – $\frac{7}{8}$ "
 s ≤ 1.5 mm

Expanding:

Hard and soft copper tubes Ø 12–22 mm
 Ø $\frac{3}{8}$ – $\frac{7}{8}$ "
 s ≤ 1 mm

REMS Hurrican for making T-branches yourself.


Inexpensive. Also on tubes already installed.

REMS Twist for making sockets yourself.

Cold-expanding of hard copper tubes.

Space and weight saving combi set. Only one drive unit for expander and extractor tools. Price advantage!

Description see REMS Hurrican and REMS Twist (page 259–260).



German Quality Product



Supply format

REMS Twist/Hurrican Combi Set. Electric tube expander and electric tube extractor for hard and soft copper tubes. Expanding Ø 12–22 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", s ≤ 1 mm, extracting Ø 10–22 mm, Ø $\frac{3}{8}$ – $\frac{7}{8}$ ", s ≤ 1.5 mm. Drive unit with hexagon mount, maintenance-free gear, universal motor 230 V or 110 V, 50–60 Hz, 630 W. High torque at low speed, left and right-hand rotation. Stepless, electronic safety switch. Drive holder. Tool holder, drill head, dimpling pliers, lubricant. Choice of expander and extractor tools for pipes in mm or inch. In sturdy steel case.


Description	Art.-No.	€
Set 12+15+18+22	156010R220	1 542,47
Set 12+14+16+18+22	156012R220	1 782,25
Set $\frac{3}{8}$+$\frac{1}{2}$+$\frac{5}{8}$+$\frac{3}{4}$+$\frac{7}{8}$"	156014R220	1 835,18

Other voltages on request.

Accessories

Description	Tubes Ø mm/inch	Art.-No.	€
Expander tool			
12		156150	173,35
14		156200	173,35
15		156225	173,35
16		156250	173,35
18		156300	173,35
22		156350	173,35
$\frac{3}{8}$ "		156375	173,35
$\frac{1}{2}$ "		156400	173,35
$\frac{5}{8}$ "		156425	173,35
$\frac{3}{4}$ "		156450	173,35
$\frac{7}{8}$ "		156475	173,35
Extractor tool			
10		151105R	67,89
12		151110R	67,89
14		151120R	67,89
15		151125R	67,89
16		151130R	67,89
18		151140R	67,89
20		151145R	67,89
22		151150R	67,89
$\frac{3}{8}$ "		151155R	72,04
$\frac{1}{2}$ "		151160R	69,96
$\frac{5}{8}$ "		151165R	69,96
$\frac{3}{4}$ "		151170R	69,96
$\frac{7}{8}$ "		151175R	69,96
REMS Twist/Hurrican drive unit			
with stabiliser		151402R220	371,60
Tool holder		151200R	85,32
Drill head 10–22 mm		151210RMM	127,67
Drill head $\frac{3}{8}$–$\frac{7}{8}$"		151210RMM	127,67
Dimpling pliers		151230R	40,48
Lubricant (tin)		151240	9,34
Steel case with insert		151600R	110,03





Soldering




Cleaning pads

264



Electric soldering pliers

264



Electric soldering unit

265



Turbo soldering torches

266



Solder wire and solder paste

267

REMS Cu-Vlies

Cleaning pads

Metal-free, highly flexible cleaning pads for cleaning surfaces to be soldered on copper tubes and soldering fittings. Also for other materials.

REMS Cu-Vlies – clean surfaces according to DVGW.

Universal use, for many materials, highly flexible. Cleans metallic clear, dirt and oxide-free, according to DVGW work sheet GW 2. Clean finish. Multiple use, reusable by washing out, thus long service life. Can be used wet or dry.

Supply format

REMS Cu-Vlies. Metal-free, highly flexible cleaning pad for cleaning areas to be soldered on copper pipes and soldering fittings. Pack of 10.

Art.-No.	€
160300R	10,28



German Quality Product

REMS Hot Dog 2

Electric soldering pliers

Efficient, light-weight electric tool for soft soldering. Directly connected to a socket, no transformer required. For trade and industry. For the building site and the workshop.

Copper tubes	Ø 10–28 mm Ø 3/8–1 1/8"
Heating capacity	800°C

REMS Hot Dog 2 – the smallest and most powerful soldering pliers. Super fast without flame.

Super fast soldering, e.g. Ø 18 mm in only 15 s. Enormous heating capacity up to 800°C through 2 heating cartridges. For permanent use.

Super light and handy, complete only 0.7 kg. Can be used anywhere, in confined areas also.



German Quality Product



Supply format

REMS Hot Dog 2 Set. Electric soldering pliers for soft soldering copper tubes Ø 10–28 mm, Ø 3/8–1 1/8". 230 V, 50–60 Hz, 440 W. 250 g REMS Lot Cu 3 and REMS Paste Cu 3. Cleaning brush. In steel case with fire retarding insert.

Art.-No.	€
163020R220	455,68

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS soldering material see page 267.		
Steel case with fire-proof inlay	163350R	76,81



REMS Contact 2000

Electric soldering unit

Compact, powerful electric tool for soft soldering.
With safety transformer. For trade and industry.
For the building site and the workshop.

Copper tubes	Ø 6–54 mm Ø ¼–2½"
Heating capacity	900°C (1650°F)

REMS Contact 2000 – the smallest, strongest and fastest unit of its kind. 2000 W soldering power. 4 m long soldering tongs cable.

Handy, compact. Favourable weight, small in size for work and transport.
L × W × H: 210 × 150 × 140 mm.

Enormous heating capacity (900°C) ensures super-fast soldering. Rated power =
Soldering capacity = 2000 W! Soldering time, e.g. for Ø 18 mm in only 18 s.

Can be used anywhere, with rod electrodes in tight spots also. Ready to solder any
time, to be connected to a socket only. No adjustment of soldering current necessary.
Wide work radius thanks to 4 m cable length. Flexible cable protector hose.

Indifferent to temperature influences electric control of soldering current.

Prisma-electrodes for universal use, maximum use through favorable seat.
Rod-electrodes for working in tight spots. Electrode holders and bolts in
stainless steel. Electrodes can be easily replaced.



Prisma-electrodes for universal use,
maximum use through favorable seat.



German Quality Product



Info

Supply format

REMS Contact 2000. Electric soldering unit for soft soldering of copper tubes Ø 6–54 mm, Ø ¼–2½". 230 V, 50–60 Hz, 2000 W, control voltage 24 V.
Soldering pliers with 4 m cable length. Safety transformer, 2 prism electrodes.
In a carton.

	Art.-No.	€
	164011R220	799,26

Other voltages on request.

Supply format

REMS Contact 2000 Super-Pack. Electric soldering unit for soft soldering of
copper tubes Ø 6–54 mm, Ø ¼–2½". 230 V or 110 V, 50–60 Hz, 2000 W,
control voltage 24 V. Soldering pliers with 4 m cable length, safety transformer,
4 prism electrodes, 2 rod electrodes, 250 g quality soft solder REMS Lot Cu 3,
250 g quality soft solder paste REMS Paste Cu 3, 1 pipe cutter REMS RAS
Cu-INOX 3-35, pack of 10 cleaning pads REMS Cu-Vlies. In sturdy steel case.

	Art.-No.	€
	164050R220	995,44

Accessories

Description	Art.-No.	€
Prism electrodes (pack of 2)	164111R	25,43
Prism electrodes with holders (pack of 2)	164110R	42,77
Rod electrodes (pack of 2)	164115R	26,47
Steel case with insert	164250R	128,71
REMS soldering material see page 267.		



REMS Blitz

Handy self-lighting torch with turbo-flame for fast soft soldering and economic gas consumption.

Copper tubes $\leq \varnothing 35\text{ mm}$

Heating, annealing, burning, melting, thawing, shrinking and similar thermal procedures.

Flame temperature $1950^\circ\text{C} (3500^\circ\text{F})$

REMS Blitz – extremely fast soft soldering.

Piezo-electric self-lighting

Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out!

Little gas consumption, only 200 g/h!

Design

Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube. Small gas bottles can be used.

Turbo-flame

Spot-flame with turbo-twisting-booster for high heating capacity and super fast soft soldering.

Supply format

REMS Blitz. Turbo soldering torch propane for soft soldering of copper tubes $\leq \varnothing 35\text{ mm}$. Piezo-electric self-lighting. Hose connector BSPP $\frac{3}{8}\text{" LH}$. Hollow cap nut and socket BSPP $\frac{3}{8}\text{" LH}$. In blister pack.

	Art.-No.	€
	160010R	243,93

Accessories

Description	Art.-No.	€
REMS soldering material see page 267.		
High pressure hose 3 m, BSPP $\frac{3}{8}\text{" LH}$	152106	90,41
Pressure reducer for 5 or 11 kg gas bottles (2 bar)	152109	116,36

REMS Macho

Handy self-lighting torch with turbo-flame for extremely fast brazing and soft soldering. Economic gas consumption.

Copper tubes and others $\leq \varnothing 64\text{ mm}$

Heating, annealing, burning, melting, thawing, shrinking and similar thermal procedures.

Flame temperature 2500°C

REMS Macho – super fast brazing.

Piezo-electric self-lighting

Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out!

Little gas consumption, only 360 g/h!

Acetylene only

Injection torch burns atmospheric oxygen. Hence only acetylene necessary.

Design

Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube.

Turbo-flame

Spot-flame with turbo-twisting-booster for extremely high heating capacity and super fast brazing.

Supply format

REMS Macho. Turbo soldering torch acetylene for brazing and soft soldering of copper tubes and others $\leq \varnothing 64\text{ mm}$. Piezo-electric self-lighting. Hose connector BSPP $\frac{3}{8}\text{" LH}$. Hollow cap nut and socket $\frac{3}{8}\text{" LH}$. In blister pack.

	Art.-No.	€
	161010R	268,84

Accessories

REMS soldering material see page 267.

Turbo soldering torch propane



German Quality Product



Info



Turbo soldering torch acetylene



German Quality Product



Info



REMS Lot Cu 3

Soft solder Sn97Cu3, ISO 9453:2014

Soft soldering of copper tubes with copper, red copper cast and brass fittings for cold and hot water installation, heating installation $\leq 110^{\circ}\text{C}$ (230°F).

In accordance with DVGW work sheet GW 2.

Alloy (weight %)	97 % Sn, 3 % Cu
Melting temperature	230 – 250°C (450 – 480°F)



German Quality Product

REMS Lot Cu 3 – quality soft solder.

Lead-free, harmless to health and environment.
Silver-free, complies with standards. Very low price.

Supply format

REMS Lot Cu 3. 250-g spool soft solder wire Sn97Cu3, ISO 9453:2014, Ø 3 mm, for soft soldering of copper tubes with copper, red copper cast and brass fittings for cold and hot water installation, heating installation $\leq 110^{\circ}\text{C}$ (230°F).

	Art.-No.	€
	160200R	51,80

REMS Paste Cu 3

Soft solder paste of solder powder Sn97Cu3 according to ISO 9453:2014 and flux 3.1.1.C, EN 29454-1:1994

Soft soldering of copper tubes with copper, red copper cast and brass fittings for cold and hot water installation, heating installation $\leq 110^{\circ}\text{C}$ (230°F).

In accordance with DVGW work sheet GW 7 (DVGW-Reg.-Nr. DV-0101AT2244)

REMS Paste Cu 3 – quality soft solder paste.

Lead-free, harmless to health and environment.
Silver-free, complies with standards. Very low price.

No additional flux consumption, paste contains flux already.
Thus less danger of corrosion.

No overheating of tube and fitting because the melting of solder and the required temperature for soldering is clearly visible through the change of colour of paste.

High filling level of soldering joint, thereby good stability. Easy cleaning of remnants which are soluble in cold water.

Plastic bottle with brush integrated in cap which cannot get lost.

Supply format

REMS Paste Cu 3. 250-g soft solder paste of solder powder Sn97Cu3 according ISO 9453:2014 and flux 3.1.1.C, EN 29454-1:1994, for soft soldering of copper tubes with copper, red copper cast and brass fittings for cold and hot water installation, heating installation $\leq 110^{\circ}\text{C}$ (230°F). DVGW approval mark. In plastic bottle with integrated brush.

	Art.-No.	€
	160210R	39,44



German Quality Product

REMS Lot P6

Brazing solder ISO 17672-CuP 179

Brazing of copper tubes with copper, red copper cast and brass fittings in cold and hot water installation, gas installation, refrigerating and air conditioning applications.

In accordance with DVGW work sheet GW 2.

Alloy (weight %)	94 % Cu, 6 % P
Melting temperature	710 – 890°C (1310 – 1640°F)

REMS Lot P6 – quality brazing solder.

Universally applicable for almost all types of joints in copper pipe installations.

Specially useful for capillary brazing joints of copper pipe installations without fittings. Wide melting range due to low phosphor content result in higher toughness of soldering joint.

Silver-free, complies with standards. Very low price.

Supply format


REMS Lot P6. 1 kg brazing solder (rods) ISO 17672-CuP 179, Ø 2 mm, for brazing of copper tubes with copper, red copper cast and brass fittings for cold and hot water installation, gas installation, refrigerating and air conditioning applications. In a carton.

	Art.-No.	€
	160220R	61,55





Freezing



Pipe freezer CO₂

270



Electric pipe freezing unit

271

Simple, fast freezing of unemptied pipes with a carbon dioxide coolant. For repair, extensions of piping systems.

Steel, copper, plastic,
composite pipes Ø 1/8 – 2"
 Ø 10 – 60 mm

Refrigerant: carbon dioxide.

Refrigerating capacity to -79°C (-110°F).

Non toxic, non flammable.

REMS Eskimo – freezing instead of draining.

Super fast. Automatic refrigerant feed. High cooling capacity, e.g. 3/4" steel pipe in only 5 min. Very small, indestructible freeze collars.

Refrigerant

Carbon dioxide coolant with high cooling performance up to -79°C.
Non toxic. Non flammable. Easy to obtain.

Design

Tight contact between freeze collars and pipe and direct flow of the refrigerant onto the pipe ensure extremely short freezing times and economic refrigerant consumption. Freezing is possible on one or two sides, with additional T-distributors further freeze collars can also be connected.

Freeze collars


Easy. Rapid assembly, without special tools. Very small, highly flexible, indestructible freeze collars in cold-resistant thermoplastic elastomer, for operating even in the tightest spots. Clamping screws cannot get lost.

Handle piece with injector

Ergonomically designed handle pieces in plastic for comfortable operation. Unbreakable brass injector (injection nozzle). Fast and secure connection to freeze collars. No setting, the correct amount of refrigerant is automatically supplied.

High pressure hoses

Flexible, buckling-resistant and fractureproof high pressure hoses. Extra long for wide work radius. Extendable any time. Turnable hollow cap nut at bottle connector prevents high pressure hoses from tangling.



German Quality Product



Info



Supply format

REMS Eskimo Set. Pipe freezing device for carbon dioxide coolant. For steel, cast iron, lead, copper, plastic pipes Ø 1/8 – 2", Ø 10 – 60 mm. Two freezing jackets each in 10 different sizes for the whole working range, flange connection with T-junction, locking nut, 2 handles with injector, 2 high-pressure hoses. In sturdy carrying case.

	Art.-No.	€
	130002R	596,85

Accessories

Description	Size	Art.-No.	€
Freezing jacket			
1/8"	10/12 mm	130450	40,38
1/4"	15 mm	130455	40,38
3/8"	18 mm	130460	40,38
1/2"	22 mm	130465	40,38
5/8"	28 mm	130470	40,38
1"	35 mm	130475	40,38
1 1/4"	42 mm	130480	53,77
1 1/2"	54 mm	130485	53,77
	60 mm	130490	53,77
		130495	53,77
High-pressure hose 2 m		130415	115,22
T-distributor for further collar		130207	25,43
Bottle connection with T-distributor		130383	47,13
Locking nut		130209	6,23
Double nipple		130208	9,65
Handle piece with injector		130410	55,43
Case with inlay		130430R	101,72



REMS Frigo 2 F-Zero

Electric pipe freezing unit

Easy, fast freezing of pipes which are not drained.
Closed refrigerant circuit. Environmentally safe.
For repair and extension of piping systems.

Steel, copper, plastic,
composite pipes
Ø 1/8 – 2"
Ø 10 – 60 mm

REMS Frigo 2 F-Zero – electrically freezing instead of draining. Super fast up to 2". High cooling capacity, e.g. 3/8" steel pipe in only 9 min*. Particularly compact, patented deep-freezer heads, for very fast assembly. Temperature display with LCD digital thermometer.

System advantage

Only one pipe freezing unit for the complete working range up to 2". One-size freezer heads for the core working range Ø 1/4 – 1" / Ø 15 – 35 mm, no reducing inserts required. Aid the cooling process simply by spraying with water. Always clean freezer heads, no pastes/greases required.

Closed refrigerant circuit

Electric pipe freezing unit with closed refrigerant circuit. Environmentally safe. Can be used anywhere, also in closed rooms. Refrigerant R-290. High cooling capacity. Ideal also for longer repairs.

Design

Robust, compact. Very small deep-freezer heads fitted parallel to the pipe leaving refrigerant hoses for working in confined areas and niches also. Single or double freezing possible.

Cooling aggregate

Very quiet. Cooling aggregate, 430 W, in sturdy sheet metal housing with ventilating side openings for optimum air circulation. Large top compartment, easily accessible, for refrigerant hoses and accessories. Weighs only 23 kg. Easy to carry.

Deep-freezer heads

Very compact deep-freezer heads with special geometrically shaped cavities for seating different pipe diameters. Very small, only 50 mm wide. All pipe sizes from Ø 1/4 – 1" resp. Ø 15 – 35 mm can be frozen with only one deep-freezer head. Deep-freezer inserts for the rest of the capacity up to 2", 60 mm. Tightening straps for simple and quick assembly of deep-freezer heads onto the pipe, without tools.

Refrigerant hoses

Flexible, extra-long refrigerant hoses, 2.5 m long, in wear resistant, synthetic rubber for large work radius.

LCD-Digital-Thermometer

LCD digital thermometer with clip, for exact temperature display directly at the freezing points.



German Quality Product



Info



Supply format

REMS Frigo 2 F-Zero Set. Electric pipe freezing unit with closed refrigerant circuit. For steel, copper, plastic, composite pipes, Ø 1/8 – 2", Ø 10 – 60 mm. Cooling aggregate 230 V or 110 V, 50 Hz, 430 W, 2 refrigerant hoses, 2.5 m long, 2 LCD digital thermometers, 2 tightening straps, squirt bottle. Equipped for Ø 1/4 – 1 1/4", 15 – 42 mm. In sturdy sheet metal housing. In a carton.

	Art.-No.	€
	131012R220	1 858,02

Accessories

Description	Size	Art.-No.	€	
Extension kit up to 2", 60 mm	1 1/2 – 2" / 54 – 60 mm	131160R	258,46	
Deep-freeze inserts (pack of 2)	1/8"	10, 12 mm	131110R	93,63
	1 1/2"	54 mm	131156R	86,47
	2"	60 mm	131157R	86,47
Clamping band		131104R	15,26	
LCD digital thermometer		131116R	38,30	





REMS CamSys 2

Pipe and Drain inspection

Pipe and Drain cleaning

	Endoscope cameras	274
	Electronic camera inspection systems	276
	Drain cleaner for manual and electric operation	282
	Electric drain cleaning machine	283
	Cordless drain cleaning machine	284
	Electric pipe and drain cleaning machines	286

REMS MiniScope

Endoscope camera

Mobile, handy endoscope camera for low-cost inspection and damage analysis of places with difficult access such as cavities, shafts, pipes, etc. For cordless operation.

Camera head Ø 8 mm

REMS MiniScope – Brilliant pictures of cavities, shafts and pipes.

Design

Ultra light and handy. Controller unit with camera cable set only 0.4 kg. Can be used everywhere, free hand, over head, also in very confined spaces. Sturdy, impact-proof plastic housing with ergonomically shaped handle. The buttons are located directly underneath the display so that it is possible to hold the device by the handle and operate the buttons with one hand. On/Off button, button for rotating, mirroring of the image by 180° respectively, button for regulating the brightness of the LEDs in the camera head in 8 stages, button for regulating the brightness of the colour display in 8 stages. Power LED for indicating the operating state. Battery compartment for 4 commercially available 1.5V, AA, LR6 batteries. Plug-screw connections for changing the camera cable set without tools. Sturdy case for controller unit, camera cable set 8-1 and accessories.

Controller unit with TFT-LCD colour display

Controller unit with 2.3" colour display with state of the art TFT-LCD technology for brilliant pictures, 320 × 240 pixels.

Battery operation

Controller unit with four 1.5V, AA, LR6 batteries for approx. 6 hours of continuous operation.

Exchangeable camera cable set Color

Camera cable set Color 8-1, consisting of colour camera Ø 8 mm (640 × 480 pixels), with CMOS sensor, with dimmable white light LEDs for optimum setting of the brightness and fixed focus function, for automatic picture focus, protected against occasional immersion in water (IP 67), 1 m flexible push cable and add-on mirror, add-on hook, add-on magnet.



Info

Supply format

REMS MiniScope Set. Mobile, handy endoscope camera for low cost inspection and damage analysis of places with difficult access such as cavities, shafts, pipes etc. Controller unit with 2.3" TFT-LCD colour display. 4 batteries 1.5 V, AA, LR6. Camera cable set Color 8-1 with 1 m flexible push cable and add-on mirror, add-on hook, add-on magnet. In sturdy case.

Art.-No.	€
175401R6	133,90



REMS CamScope HD

Endoscope camera

Mobile, handy endoscope camera for low-cost inspection and damage analysis of places with difficult access such as cavities, shafts, pipes, etc. Documentation of photos and videos on MicroSD card. For battery and mains operation.

Camera head

Ø 8 mm

REMS CamScope HD – Brilliant pictures and videos of cavities, shafts and pipes in HD quality (1920 × 1080 pixels). MicroSD card slot.

Design

Ultra light and handy. Controller unit with pistol grip and camera cable set only 0.5 kg. Can be used everywhere, free hand, over head, also in very confined spaces. Sturdy, impact-proof plastic housing with ergonomically shaped handle. The buttons are located directly underneath the display so that it is possible to hold the device by the pistol grip and operate the buttons with one hand. Bottoms, among other things, for regulating the brightness of the LEDs in the camera head and the display in 4 stages each, for rotating, mirroring and zooming the image shown in the display, calling and navigating in the menu. Power LED for indicating the operating state integrated into the On-Off button. Li-Ion 3.7 V battery with 4.0 Ah for long service life. Different HD camera cable sets can be used. Plug-screw connections for changing the camera cable sets without tools. Sturdy case of controller unit with pistol grip, camera cable set Color 8-1 HD 180°/90°, USB cable and accessories.

Controller unit with TFT-LCD colour display

Controller unit with pistol grip with 5" colour display with state-of-the-art TFT-LCD technology and 480 × 854 pixels, for brilliant pictures and videos. Selectable menu language. MicroSD card slot. Pictures and videos in HD quality can be saved on a MicroSD card for simple documentation of the inspection result. 4x digital zoom. The date and time of the recording can be saved in the photo and video as an option. Immediate playback of saved recordings or transmission to other devices via MicroSD card. USB port for direct connection to a PC or laptop and for charging the battery.

Cordless and mains operation


Li-Ion technology. Controller unit with pistol grip with integrated 3.7 V, 4.0 Ah Li-Ion battery. Light and powerful. High energy density for approx. 5 hours continuous operation. The unit can be used in mains mode whilst charging the battery with the USB cable. No memory effect for maximum battery performance.

Exchangeable camera cable set Color

Consisting of colour camera Ø 8 mm, with CMOS sensor, with dimmable white light LEDs for optimum setting of the brightness and fixed focus function, for automatic picture focus, protected against occasional immersion in water (IP 67).

Camera cable set Color 8-1 HD 180°/90° with 180° straight and 90° angled colour camera, with 1 m flexible push cable and add-on hook, add-on magnet. Images and videos can be viewed and recorded from the selected colour camera or from both colour cameras simultaneously.

Camera cable set Color 8-5 HD with 5 m flexible push cable as an accessory.



Supply format

REMS CamScope HD Set. Mobile, handy endoscope camera for low cost inspection and damage analysis of places with difficult access such as cavities, shafts, pipes etc. Documentation of pictures and videos in HD quality on MicroSD card. Endoscope camera with 5" TFT-LCD colour display, 4x digital zoom, MicroSD card slot, USB port, integrated 3.7 V, 4.0 Ah Li-ion battery. Camera cable set Color 8-1 HD 180°/90°, 180° straight colour camera and 90° angled colour camera, with 1 m flexible push cable and add-on hook, add-on magnet. 32 GB MicroSD card. USB cable. In sturdy case.

	Art.-No.	€
	175400R4	237,70

Accessories

Description	Art.-No.	€
Camera cable set Color 8-5 HD, colour camera Ø 8 mm, 1280 × 720 pixels, with 5 m formable push cable	175440R	92,38

Mobile, handy camera inspection system for inexpensive inspection and damage analysis of pipes, drains, chimneys and other hollow cavities. With electronic metering. Also for inspection after pipe cleaning work and for acceptance of new installations or repairs. Documentation of pictures and videos on SD card. For battery and corded operation.

Camera head	Ø 25 mm
Pipe	Ø (40) 50–150 mm
Drains, chimneys, other cavities	

REMS CamSys – Brilliant pictures and videos of pipes and drains. SD card slot. Electronic metering. Cordless and mains operation.

System advantage

Only one controller unit with TFT-LCD colour display for connecting different camera cable sets for different requirements. Therefore inexpensive conversion possible.

Design

Mobile, handy, light. Can be used everywhere, even in very narrow places. Controller unit connected to the camera cable set by a 2 m connecting cable, removable for easy cleaning of the camera cable set. Various camera cable sets can be used. Plug-screw connections for changing the camera cable sets and the controller unit without tools. Sturdy case for controller unit, voltage supply/charger and accessories.

Controller unit with TFT-LCD colour display

Controller unit with 3.5" colour display with state of the art TFT-LCD technology for brilliant pictures and videos, 89 mm screen diagonal, 320×240 pixels. Very light and handy, only 0.4 kg. Sturdy, impact-proof plastic housing, spray protected. Small dimensions: 172×121×58 mm. Keys for setting the brightness of the LEDs of the colour camera head. Full screen, 2x zoom, 4x rotation options for the picture. SD card slot. Pictures and videos can be saved on an SD card for simple documentation of the inspection result. Insertion depth of the camera is stored in the picture and the video, optionally also date and time of the recording. Pictures can be taken during video recording without impairing the video recording. Immediate playback of saved recordings or transmission to other devices with SD card. Pictures can also be taken later from the video during playback of recorded videos on the controller's colour display. USB connector for direct connection to PC or laptop. Video output socket Composite-Video PAL/NTSC for connecting an external monitor. Connection for voltage supply/charger Li-Polymer 100–240 V.

Cordless and mains operation

Li-Polymer Technology. Controller unit with integrated Li-Polymer battery 3.7 V, 4.0 Ah. Light and powerful. Power supply/charger 100–240 V, 15 W, with USB port and USB cable for connecting power supply/charger, laptop or other voltage supply. No memory effect for maximum battery performance.

High resolution special colour camera


High resolution special colour camera Ø 25 mm with CMOS image sensor and 8 ultra bright, white LEDs with adjustable light intensity up to 1700 mcd and concentrated radiation angle for brilliant colour pictures with even illumination. Low light requirement due to very high light sensitivity (0.1 lux). Fixed focus and special lens with 90° wide angle, also for detecting the smallest details.

Exchangeable cable camera sets

Camera cable sets S-Color, consisting of special high-resolution colour camera with optional **30 m push cable Ø 5.4 mm**, flexible, for Ø 50–150 mm, in hasp with electronic metre counter, **20 m push cable Ø 4.5 mm**, very flexible, for small pipe diameters and narrower bends Ø (40) 50–150 mm, in the hasp with electronic metre counter or **10 m push cable Ø 4.5 mm** with length mark, very flexible, for small pipe diameters and narrower pipe bends Ø (40) 50–150 mm, in the cable reel, with connection for controller unit. Very small, rounded camera head Ø 25 mm, water-tight up to 20 m (0.2 MPa/2 bar/29 psi) and highly flexible sliding spring tapered towards the push cable for effortless feeding even through several pipe bends. Camera head with strong, quick-change protective cap with inserted mineral glass pane. Bend-maneuvring push cable in hybrid technology, with glass fibre core, data cables and plastic sheath, very stable, for long life. Robust, powder-coated, easy to clean cable cage. Hasp with rotary cage for simple unwinding and winding of the push cable and integrated sensor for electronic metering. Carrying case for camera cable set as an accessory.

Guide bodies

Various guide bodies for larger pipe diameters, firmly lockable on the camera head, as an accessory.



Info

Supply format

REMS CamSys Set S-Color. Electronic camera inspection system for low-cost inspection and damage analysis. Documentation of pictures and videos on SD card with specification of date and time. Controller unit in microprocessor technology with 3.5" TFT-LCD colour display, SD card slot, USB port, video out socket PAL/NTSC, integrated Li-Polymer battery, 3.7 V, 4.0 Ah, in sturdy, impact-proof plastic housing, spray protected. 2 m connecting cable from the controller unit to the camera cable set, voltage supply/charger 100–240V, 50–60Hz, 15 W, SD card 4 GB, USB cable, in sturdy case. Camera cable set S-Color with high resolution special colour camera Ø 25 mm with CMOS image sensor and push cable.

Description	Version	Art.-No.	€
Set S-Color 10 K	10 m push cable Ø 4.5 mm with length mark, very flexible, in cable reel. For small pipe diameters and narrower pipe bends Ø (40) 50–150 mm, drains, shafts, stacks and other cavities.	175008R220	2 491,20
Set S-Color 20 H	20 m push cable Ø 4.5 mm, very flexible, in the hasp with electronic metre counter. For small pipe diameters and narrower pipe bends Ø (40) 50–150 mm, drains, shafts, stacks and other cavities.	175007R220	3 456,54
Set S-Color 30 H	30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metre counter. For pipes Ø 50–150 mm, drains, shafts, stacks and other cavities.	175010R220	3 559,30



Accessories

Description	Art.-No.	€
REMS CamSys Basic-Pack. Controller unit in microprocessor technology with 3.5" TFT-LCD colour display, SD card slot, USB port, video out socket PAL/NTSC, integrated Li-Polymer battery, 3.7 V, 4.0 Ah, in sturdy, impact-proof plastic housing, spray protected. 2 m connecting cable from the controller unit to the camera cable set, voltage supply/charger 100–240 V, 50–60Hz, 15 W, SD card 4 GB, USB cable, in sturdy case.	175000R220	1 401,30
Camera cable set S-Color 10 K with high resolution special colour camera Ø 25 mm with CMOS image sensor, 10 m push cable Ø 4.5 mm with length marking, very flexible, with connection for controller unit, in cable reel. For small diameters and narrower pipe bends Ø (40) 50–150 mm.	175305R	1 089,90
Camera cable set S-Color 20 H with high resolution special colour camera Ø 25 mm with CMOS image sensor and 20 m push cable Ø 4.5 mm, flexible, in the hasp with electronic metering and connection for controller unit. For small diameters and narrower pipe bends Ø (40) 50–150 mm.	175306R	2 055,24
Camera cable set S-Color 30 H with high resolution special colour camera Ø 25 mm with CMOS image sensor and 30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metering and connection for controller unit. For Ø 50–150 mm.	175011R	2 158,00
Guide body Ø 62 mm S-Color/S-Color S, for camera cable set S-Color/S-Color S	175057R	107,33
Guide body Ø 100 mm S-Color/S-Color S, for camera cable set S-Color/S-Color S	175058R	124,35
Protective cap S-Color/S-Color S with mineral glass pane, sealing ring, for camera cable set S-Color/S-Color S	175026R	36,33
Carrying case for camera cable set	175123R	128,71
Case with inlay	175018R	98,61



Mobile, handy camera inspection system for inexpensive inspection and damage analysis of pipes, drains, chimneys and other hollow cavities. Self-levelling camera. Transmitter for localising camera heads. Electronic metering. Also for inspection after pipe cleaning work and for acceptance of new installations or repairs. Documentation of pictures and videos with voice recording on SD card. For battery and corded operation.

Camera head S-Color/S-Color S	Ø 25 mm
Camera head S-Color S-N	Ø 33 mm
Pipes, drains, chimneys, other cavities	
Camera head S-Color	Ø (40) 50–150 mm
Camera head S-Color S	Ø 50–150 mm
Camera head S-Color S-N	Ø 70–150 mm

REMS CamSys 2 – Brilliant pictures and videos of pipes and drains. Voice recording Self-levelling camera. Transmitter for localising camera heads. SD card slot. Electronic metering. Cordless and mains operation.

System advantage

Only one controller unit with TFT-LCD colour display for connecting different camera cable sets for different requirements. Therefore inexpensive conversion possible.

Design

Mobile, handy, light. Can be used everywhere, even in very narrow places. Controller unit connected to the camera cable set by a 2 m connecting cable, removable for easy cleaning of the camera cable set. Various camera cable sets can be used. Plug-screw connections for changing the camera cable sets and the controller unit without tools. Sturdy case for controller unit, voltage supply/charger and accessories.

Controller unit with TFT-LCD colour display




Controller unit with 7" colour display with state of the art TFT-LCD technology for brilliant pictures and videos, 178 mm screen diagonal, 720 × 480 pixels. Very light and handy, only 1.3 kg. Sturdy, impact-proof plastic housing, spray protected, glare protection. Integrated stand for different angles of inclination of the screen. Ergonomic grips with soft-grip and adjustable clamping bands, keys for picture and video, for one-hand operation by right and left handers. Small dimensions: 270 × 164 × 70 mm. Keys for setting the brightness of the LEDs of the colour camera head. Full screen, 2x zoom, 4x rotation options for the picture. Adjustable automatic switch-off. SD card slot. Pictures and videos with voice recording can be saved on an SD card for simple documentation of the inspection result. Insertion depth of the camera is stored in the picture and the video, optionally also date and time of the recording. Pictures can be taken during video recording without impairing the video recording. Immediate playback of saved recordings or transmission to other devices with SD card. Pictures can also be taken later from the video during playback of recorded videos on the controller's colour display. USB connector for direct connection to PC or laptop. Video output socket Composite-Video PAL/NTSC for connecting an external monitor. Connection for voltage supply/charger 100–240 V.

Cordless and mains operation

Li-Polymer Technology. Controller unit with integrated Li-Polymer battery 3.7 V, 7.6 Ah. Light and powerful. Power supply/charger 100–240 V, 15 W, with USB port and USB cable for connecting power supply/charger, laptop or other voltage supply. No memory effect for maximum battery performance.

High resolution special colour camera

High resolution special colour camera with CMOS image sensor and ultra bright, white light emitting diodes (LEDs) with adjustable light intensity up to 1700 mcd and concentrated radiation angle for brilliant colour pictures with evenly bright illumination. Low light requirement due to very high light sensitivity (0.1 lux). Fixed focus and special lens with 90° wide angle, also for detecting the smallest details.



Info

Exchangeable cable camera sets

Camera cable set S-Color, consisting of a special high resolution colour camera Ø 25 mm with 20 m push cable Ø 4.5 mm, very flexible, for small pipe diameters and narrower bends Ø (40) 50–150 mm, in the hasp with electronic metering or 10 m push cable Ø 4.5 mm with length mark, very flexible, for small pipe diameters and narrower pipe bends Ø (40) 50–150 mm, in the cable reel. **Camera cable set S-Color S**, consisting of a special high resolution colour camera Ø 25 mm with 30 m push cable Ø 5.4 mm, flexible, for Ø 50–150 mm, in the hasp with electronic metering and 33 kHz transmitter for localising the camera head. **Camera cable set S-Color S-N**, consisting of a special high resolution colour camera Ø 33 mm with 30 m push cable Ø 5.4 mm, flexible, for Ø 70–150 mm, in the hasp with electronic metering, 33 kHz transmitter for localising the camera head and self-levelling camera for upright pictures and videos. Connection for controller unit. Very small, rounded camera head, water-proof up to 20 m (0.2 MPa/2 bar/29 psi) and highly flexible sliding spring tapered towards the push cable for effortless feeding even through several pipe bends. Camera head with strong, quick-change protective cap with inserted mineral glass pane. Bend-manoeuvring push cable in hybrid technology, with glass fibre core, data cables and plastic sheath, very stable, for long life. Robust, powder-coated, easy to clean cable cage. Hasp with rotary cage for simple unwinding and winding of the push cable and integrated sensor for electronic metering. Carrying case for camera cable set as an accessory.

Guide bodies

Guide body S-Color/S-Color S and S-Color S-N Ø 62 mm and Ø 100 mm, for greater pipe diameters, can be locked to camera head S-Color/S-Color S or S-Color S-N, as an accessory.

Tracker

REMS Explorer for localising a camera head with a 33 kHz transmitter, for determining the position of damages or the course of a pipe, as an accessory.



Supply format

REMS CamSys 2 Set S-Color. Electronic camera inspection system for low-cost inspection and damage analysis. Documentation of pictures and videos with voice recording on SD card with specification of date and time. Controller unit in microprocessor technology with 7" TFT-LCD colour display, SD card slot, USB port, video out socket PAL/NTSC, integrated Li-Polymer battery 3.7V, 7.6 Ah, in sturdy, impact-proof plastic housing, spray protected, glare protection, stand. 2 m connecting cable from the controller unit to the camera cable set, voltage supply/charger 100–240V, 50–60 Hz, 15 W, SD card 4 GB, USB cable, video cable, in sturdy case. Camera cable set S-Color with high resolution special colour camera with CMOS image sensor and push cable.

Description	Version	Art.-No.	€
Set S-Color 10 K	High resolution special colour camera Ø 25 mm, 10 m push cable Ø 4.5 mm with length mark, very flexible, in the cable reel. For small pipe diameters and narrower pipe bends Ø (40) 50–150 mm, drains, shafts, stacks and other cavities.	175301R220	3 051,72
Set S-Color 20 H	High resolution special colour camera Ø 25 mm, 20 m push cable Ø 4.5 mm, very flexible, in the hasp with electronic metering. For small pipe diameters and narrower pipe bends Ø (40) 50–150 mm, drains, shafts, stacks and other cavities.	175302R220	4 017,06
Set S-Color S 30 H	High resolution special colour camera Ø 25 mm, 33 kHz transmitter for localising the camera head, 30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metering. For pipes Ø 50–150 mm, drains, shafts, stacks and other cavities.	175303R220	4 224,66
Set S-Color S-N 30 H	High resolution special colour camera Ø 33 mm, self-levelling, 33 kHz transmitter for localising the camera head, 30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metering. For pipes Ø 70–150 mm, drains, shafts, stacks and other cavities.	175304R220	4 587,96



Description	Art.-No.	€
REMS CamSys 2 Basic-Pack Controller unit in microprocessor technology with 7" TFT-LCD colour display, SD card slot, USB port, video out socket PAL/NTSC, integrated Li-Polymer battery, 3.7 V, 7.6 Ah, in sturdy, impact-proof plastic housing, glare protection, stand, spray protected. 2 m connecting cable from the controller unit to the camera cable set, voltage supply/charger 100–240 V, 50–60 Hz, 15 W, SD card 4 GB, USB cable, video cable, in sturdy case.	175300R220	1 961,82
Camera cable set S-Color 10 K High resolution special colour camera Ø 25 mm, 10 m push cable Ø 4.5 mm with length mark, very flexible, in the cable reel. For small diameters and narrower pipe bends Ø (40) 50–150 mm.	175305R	1 089,90
Camera cable set S-Color 20 H High resolution special colour camera Ø 25 mm, 20 m push cable Ø 4.5 mm, very flexible, in the hasp with electronic metering. For small diameters and narrower pipe bends Ø (40) 50–150 mm.	175306R	2 055,24
Camera cable set S-Color S 30 H High resolution special colour camera Ø 25 mm, 33 kHz transmitter for localising the camera head, 30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metering. For Ø 50–150 mm.	175307R	2 262,84
Camera cable set S-Color S-N 30 H High resolution special colour camera Ø 33 mm, self-levelling, 33 kHz transmitter for localising the camera head, 30 m push cable Ø 5.4 mm, flexible, in the hasp with electronic metering. For Ø 70–150 mm.	175308R	2 626,14
Guide body Ø 62 mm S-Color/S-Color S, for camera head S-Color/S-Color S	175057R	107,33
Guide body Ø 100 mm S-Color/S-Color S, for camera head S-Color/S-Color S	175058R	124,35
Guide body Ø 62 mm S-Color S-N, for camera head S-Color S-N	175343R	59,48
Guide body Ø 100 mm S-Color S-N, for camera head S-Color S-N	175339R	83,46
Protective cap S-Color/S-Color S with mineral glass pane, sealing ring, for camera head S-Color/S-Color S	175026R	36,33
Protective cap S-Color S-N with mineral glass pane, sealing ring, for camera head S-Color S-N	175330R	86,05
REMS Explorer , tracker for localising a camera head with a 33 kHz transmitter	175312R	1 987,77
Carrying case for camera cable set	175123R	128,71
Case with inlay	175323R	98,61





REMS Pull-Push

Suction and pressure cleaning device

Proven, reliable suction and pressure cleaning device for fast clearance of blockages.

REMS Pull-Push – fast clearance of blockages.

High pressing force by front, adjustable handle.

Optimum adaptation to the cleaning task by 2 sleeves:

Short sleeve for wash basins and baths, long sleeve for toilets.



Supply format

REMS Pull-Push. Suction and pressure cleaning device for fast clearance of blockages. With short and long sleeve. In a box.

Art.-No.	€
170300R	133,90

REMS Mini-Cobra

Proven, handy device for the fast unblocking of pipes, e.g. for kitchens, bathrooms and toilets.

For pipes	Ø 20–50 (75) mm
For drain cleaning cables	Ø 6, 8, 10 mm

REMS Mini-Cobra – by hand or electric.

Indispensable to remove small blockages.

Design

Simple, robust, practical design. Handy, light. Only 2.9 kg. Easy operation also in traps and tight bends. Easy insertion of cable directly through strainers in sinks and drains. Locking of cable by quick-action chuck.

Drain cleaning cables

Cables in high quality spring steel. Specially hardened. Highly flexible for effortless feed-forward in tight bends. Cable end with bulbous head (sink strainer head), thus easy to bend.

Cable drum

In hot-galvanized spring steel. Specially hardened. Highly flexible for effortless feed-forward in tight pipe bends. Cable end with bulbous head. Corrosion-resistant cable drum in shock-proof, glass-fibre reinforced plastic prevents pollution of the environment. Ventilation of the cable drum interior enables self-drying of cable. View to cable at all times.

Drive

By hand with easy action, easy grip crank handle or with suitable electric drill/with suitable electric screwdriver, speed ≤ 300 rpm. Hexagon adapter for electric drive located in the drum cover.

Drain cleaner for manual and electric operation



German Quality Product



Supply format

REMS Mini-Cobra. Pipe cleaning device for pipes Ø 20–50 (75) mm, with crank handle and hexagonal driver for electric drill/screwdriver. For drain cleaning cables Ø 6, 8 and 10 mm. Cable drum in shock-proof, glass-fibre reinforced plastic. Quick-action chuck. Cable Ø 8 mm × 7.5 m long. In a carton.

Art.-No.	€
170010R	185,80

Accessories

Description	Ø × Length	Art.-No.	€
Drain cleaning cable	8 mm × 7.5 m	170200	69,03
	10 mm × 10 m	170205	140,03
Drain cleaning cable with core	8 mm × 7.5 m	170201	98,40
L-Boxx H system case with inserts		170118R	146,36



REMS Mini-Cobra S

Electric drain cleaning machine

Electric pipe cleaning device with fast switchover.
For effortless and quick application to remove
pipe blockages in kitchen, bath, toilet.

For pipes Ø 20–50 (75) mm
For drain cleaning cables Ø 8, 10 mm

REMS Mini-Cobra S – Fast clearance of pipe blockages. Ultra fast reversal of direction of spiral feed/return by fast switchover.

Design

Compact unit of drive machine and cable drum. Handy, light. Only 5.7 kg. Combined thrust and grip handle for controlling the automatic feed-forward and reverse and for safe holding of the unit. Easy operation also in traps and tight bends.

Fast switchover

For easy operation and fast clearance of pipe blockages. Ultra fast reversal of direction of spiral feed/return by fast switchover (**Patent EP 3 059 022**) also under full load without changing the motor's direction of rotation, avoids looping of the drain cleaning cables when suddenly encountering resistance from pipe blockages, for long life of the drain cleaning cables.

Drain cleaning cables


Drain cleaning cables in high quality spring steel. Specially hardened. Highly flexible for effortless feed-forward in tight pipe bends. Cable end with bulbous head (sink strainer head), thus easy to bend. Drain cleaning cables with core in high quality spring steel prevents ingress of dirt and generation of long fibres in the cable windings.

Cable drum

Corrosion resistant cable drum in shock-proof, glass-fibre reinforced plastic prevents pollution of the environment. Ventilation of the cable drum interior enables self-drying of cable. View of the cable at any time.

Drive

Proven drive unit with hexagon mount. Enormously powerful. Robust, maintenance-free gear with safety slipping clutch. Universal motor, 630 W, high-torque forward and reverse at low speed. Stepless, electronic speed control. The speed between 0 and 950 rpm is controlled by pressing the tip switch steplessly (acceleration switch).



German Quality Product



Info



Patent EP 3 059 022

Supply format

REMS Mini-Cobra S. Electric pipe cleaning device with fast switchover, for pipes Ø 20–50 (75) mm. For drain cleaning cables Ø 8 and 10 mm. Drive unit with maintenance-free gear, universal motor 230 V or 110 V, 50–60 Hz, 630 W, high-torque forward and reverse at low speed. Safety tip switch. Stepless, electronic speed control (acceleration switch) between 0 and 950 rpm. Cable drum in shock-proof, glass-fibre reinforced plastic. Cable Ø 8 mm, with core, 7.5 m long.

Description	Art.-No.	€
REMS Mini-Cobra S, in a carton	170022R220	559,48
REMS Mini-Cobra S Set, in sturdy steel case.	170023R220	663,28



Accessories

Description	Ø × Length	Art.-No.	€
Drain cleaning cable with core	8 mm × 7.5 m	170201	98,40
Drain cleaning cable	10 mm × 10 m	170205	140,03
Steel case		185058R	110,03



REMS Mini-Cobra S 22V VE

Cordless drain cleaning machine

Mobile, handy, cordless pipe cleaning device with fast switchover. For effortless and quick application to remove pipe blockages in kitchen, bath, toilet. Li-Ion 22V Technology. For battery and corded operation.

For pipes Ø 20–50 (75) mm
For drain cleaning cables Ø 8, 10 mm

REMS Mini-Cobra S 22V VE – fast clearance of pipe blockages anywhere. Ultra fast reversal of direction of spiral feed/return by fast switchover. With powerful, brushless battery motor.

Design

Compact unit of cordless drive unit and spiral drum. Mobile, handy, light. Complete with battery pack only 5.2 kg. Combined thrust and grip handle for controlling the automatic feed-forward and reverse and for safe holding of the unit. Easy operation also in traps and tight bends. Integrated LED work light for illuminating the work place.

Fast switchover

For easy operation and fast clearance of pipe blockages. Ultra fast reversal of direction of spiral feed/return by fast switchover (**Patent EP 3 059 022**) also under full load without changing the motor's direction of rotation, avoids looping of the drain cleaning cables when suddenly encountering resistance from pipe blockages, for long life of the drain cleaning cables.

Drain cleaning cables

Drain cleaning cables in high quality spring steel. Specially hardened. Highly flexible for effortless feed-forward in tight pipe bends. Cable end with bulbous head (sink strainer head), thus easy to bend. Drain cleaning cables with core in high quality spring steel prevents ingress of dirt and generation of long fibres in the cable windings.

Cable drum

Corrosion resistant cable drum in shock-proof, glass-fibre reinforced plastic prevents pollution of the environment. Ventilation of the cable drum interior enables self-drying of cable. View of the cable at any time.

Drive

High-performance electro-mechanical drive with powerful, brushless motor 21.6V, 500W output, extra torque powerful left and right hand rotation at specially adapted speed, robust, precision ball bearing-mounted gear, maintenance-free. Safety switch, electronically controlled for jolt-free switching on and off. Continuous, electronic speed control. The speed can be continuously controlled by variable pressure on the safety switch from 0 to 560 rpm (accelerator switch /VE)).

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V battery with 1.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. 220–240V/21.6V, 15A output, voltage supply for mains operation instead of Li-Ion battery 21.6 V, as accessory.



German Quality Product



Info



Patent EP 3 059 022



Supply format

REMS Mini-Cobra S 22V VE. Cordless pipe cleaning device with fast switchover, for pipes Ø 20–50 (75) mm. For drain cleaning cables Ø 8 and 10 mm. Drive unit with powerful, brushless battery motor 21.6 V, 500 W, maintenance-free, robust gear, extra torque powerful left and right hand rotation at low speeds, safety switch. Continuous, electronic speed control (accelerator switch (VE)) from 0 to 560 rpm. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240V, 50–60 Hz, 70 W. Cable drum in shock-proof, glass-fibre reinforced plastic. Cable Ø 8 mm, with core, 7.5 m long.

Description	Art.-No.	€
REMS Mini-Cobra S 22V VE, in a carton	170025R220	767,08
REMS Mini-Cobra S 22V VE Set, in L-Boxx H system case	170027R220	922,78

Other voltages on request.

Accessories

Description	Ø × Length	Art.-No.	€
Drain cleaning cable with core	8 mm × 7.5 m	170201	98,40
Drain cleaning cable	10 mm × 10 m	170205	140,03
Battery Li-Ion 21.6 V, 2.5 Ah		571571R22	258,46
Battery Li-Ion 21.6 V, 4.4 Ah		571574R22	372,64
Battery Li-Ion 21.6 V, 5.0 Ah		571581R22	310,36
Battery Li-Ion 21.6 V, 9.0 Ah		571583R22	414,16
Rapid charger 100–240V, 50–60Hz, 90W		571585R220	175,42
Rapid charger 100–240V, 50–60Hz, 290W		571587R220	414,16
Voltage supply 220–240V/21.6V, 50–60Hz, 15A, for mains operation instead of battery Li-Ion 21.6 V.		571567R220	414,16
L-Boxx H system case with inserts		170118R	146,36

REMS Lumen 2800 22V, cordless LED flood light, see page 111



Handy, robust, compact machines for versatile use in pipe and drain cleaning. High-speed rotator with connectable cable sections. Proven technology.

For pipes Ø 20–250 mm
For pipe and drain cleaning cables Ø 8, 16, 22, 32 mm
All pipe and drain cleaning cables and tools can also be used for other makes.

REMS Cobra – clear pipe – easy and fast.

High-speed rotator with cable sections for work length up to 100 m. Effective chain knocking and milling up to 740 rpm. Closed drive spindle protects motor and drive against dirt and water.

High speed rotator with connectable cable sections

High-speed rotator, 740 rpm (REMS Cobra 22) resp. 520 rpm (REMS Cobra 32), with cable sections for effective fast operation, e.g. during chain knocking or milling. Under difficult conditions also, e.g. roots and hard incrustations. Cable sections to be connected as needed up to 70 m (REMS Cobra 22) resp. 100 m (REMS Cobra 32) work length. No unnecessary rotating of long pipe and drain cleaning cables.

Design

Robust, practical, splash-proof. Maintenance-free. Small in size. Favourable weight, drive unit REMS Cobra 22 only 19 kg, drive unit REMS Cobra 32 only 24 kg. Machine frame made of distortion-free cast aluminium with protective covers in shock-proof plastic material. REMS Cobra 22 with holders for part spirals 16 and 22 for fixing the part spirals to the machine frame when changing spirals. Chucking system which is located outside the machine housing with straight through undivided drive spindle for the pipe and drain cleaning cable. This enables a complete seal of the machine interior against dirt and water. Connecting cable with integrated personal protection switch (PRCD). Guide hose prevents excess rotation of pipe and drain cleaning cables and pollution of the environment. Legs with rubber caps guarantee a safe, floor-protecting stand.

High-performance pipe and drain cleaning cables

Specialy hardened. Highly flexible for effortless feed-forward in tight pipe bends. Rapid action coupling for fast extension and shortening. T-groove coupling with safety lock through spring-loaded thrust pin. Manual feed-forward for sensitive operation. Standard pipe and drain cleaning cable for universal pipe and drain cleaning jobs, highly flexible, specially suited for tight or several consecutive pipe bends. Pipe and drain cleaning cable S with thicker special spring steel for very difficult to remove obstructions, e.g. root cutting. Drain cleaning cables with weather-proof and temperature resistant plastic core prevents drain cleaning cable from dirt and generation of long fibres in the cable windings. Drive through REMS Cobra 22, REMS Cobra 32 or drive machines of other makes.

Clamping jaws for cable drive

Clamping jaws in high-grade hardened steel, resistant to wear and precise fit. Instant and exact clamping and opening of pipe and drain cleaning cables allow optimum control, power transmission and operating safety. REMS Cobra 22: Choice of pipe and drain cleaning cables Ø 16 mm and 22 mm, without changing the clamping jaws. Pipe and drain cleaning cable Ø 8 mm with adapter drum 22/8 and integrated clamping jaws, as accessory. REMS Cobra 32: Choice of drain cleaning cables Ø 22 and 32 mm, without changing the clamping jaws. Drain cleaning cables Ø 16 mm with clamping jaws 16, as accessory. Pipe and drain cleaning cable Ø 8 mm with adapter drum 32/8 and integrated clamping jaws, as accessory.

Drive


Powerful, quiet running capacitor motor with high torque, 750 W (REMS Cobra 22), 1050 W (REMS Cobra 32), right and left-hand rotation. Full transmission of motor power by a slipping-proof maintenance-free toothed belt drive. Straight through closed drive spindle. Permanently lubricated, maintenance-free roller bearings. Fast and secure run and stop of pipe and drain cleaning cable through strong, centrally located pressing lever provides central power input. Lever doubles as a carrying device without awkward locking.

Pipe and drain cleaning tools

Large variety of pipe and drain cleaning tools (page 288–289), also fit into pipe and drain cleaning machines of other makes.



German Quality Product



German Quality Product



Straight through closed drive spindle protects motor and drive against dirt and water.

Supply format

REMS Cobra 22 Set. Electric pipe and drain cleaning machine for pipes Ø 20–150 mm. Drive unit with maintenance-free belt drive, capacitor motor 230 V, 50 Hz, 750 W, right and left-hand rotation, guide hose. Personal protection switch (PRCD). Choice of cable and tool set 16 or/and 22. In a carton.

Description	Version	Art.-No.	€
Set 16	5 cable sections 16 × 2.3 m in cable carrier, straight auger 16, bulbous auger 16, toothed blade borer 16/25, cable joint separator, 1 pair of guide gloves, steel case for tool set	172010R220	1 806,12
Set 22	5 cable sections 22 × 4.5 m in cable carrier, straight auger 22, retrieving auger 22, funnel auger 22, toothed cross-blade borer 22/35, cable joint separator 22/32, 1 pair of guide gloves, steel case for tool set	172011R220	1 992,96
Set 16+22	5 cable sections 16 × 2.3 m in cable carrier, straight auger 16, bulbous auger 16, toothed blade borer 16/25, cable joint separator, 5 cable sections 22 × 4.5 m in cable carrier, straight auger 22, retrieving auger 22, funnel auger 22, toothed cross-blade borer 22/35, cable joint separator 22/32, 2 pairs of guide gloves, steel case for each tool set	172012R220	2 335,50



Info

Supply format

REMS Cobra 32 Set. Electric pipe and drain cleaning machine for pipes Ø 20–250 mm (½–10"). Drive unit with maintenance-free belt drive, capacitor motor 230 V, 50 Hz, 1050 W, right and left-hand rotation, guide hose. Personal protection switch (PRCD). Choice of cable and tool set 32 or cable and tool sets 22 and 32 or 16 and 22. In a carton.

Description	Version	Art.-No.	€
Set 32	4 cable sections 32 × 4.5 m in cable carrier, straight auger 32, retrieving auger 32, funnel auger 32, toothed cross-blade borer 32/45, cable joint separator 22/32, 1 pair of guide gloves, case for tool set	174010R220	3 923,64
Set 22+32	5 cable sections 22 × 4.5 m in cable carrier, straight auger 22, retrieving auger 22, funnel auger 22, toothed-cross-blade borer 22/35, cable joint separator 22/32, 4 cable sections 32 × 4.5 m in cable carrier, straight-auger 32, retrieving auger 32, funnel-auger 32, toothed cross-blade borer 32/45, cable joint separator 22/32, 2 pairs of guide gloves, steel case/case for each tool set	174011R220	4 619,10
Set 16+22	5 cable sections 16 × 2.3 m in cable carrier, 2 clamping jaws 16, straight auger 16, bulbous auger 16, toothed blade borer 16/25, cable joint separator 16, 5 cable sections 22 × 4.5 m in cable carrier, straight auger 22, retrieving auger 22, funnel auger 22, toothed cross-blade borer 22/35, cable joint separator 22/32, 2 pairs of guide gloves, steel case for each tool set	174012R220	4 224,66



Info

Accessories

Description	Art.-No.	€
REMS Cobra 22 drive unit with guide hose	172000R220	1 650,42
REMS Cobra 32 drive unit with guide hose	174000R220	3 051,72

Pipe and drain cleaning tools see page 288–289.



REMS Cobra 22/32

Accessories for REMS Cobra 22, REMS Cobra 32 and other makes

Description	Size	Art.-No.	€
Cable and tool set 16 consisting of 5 cable sections 16 × 2.3 m in cable carrier, straight auger 16, bulbous auger 16, toothed blade borer 16/25, cable joint separator, 1 pair of guide gloves, steel case for tool set		172050R	601,00
Cable and tool set 22 consisting of 5 cable sections 22 × 4.5 m in cable carrier, straight auger 22, retrieving auger 22, funnel auger 22, toothed cross-blade borer 22/35, cable joint separator, 1 pair of guide gloves, steel case for tool set		172051R	840,78
Cable and tool set 32 consisting of 4 cable sections 32 × 4.5 m in cable carrier, straight auger 32, retrieving auger 32, funnel auger 32, toothed cross-blade borer 32/45, cable joint separator 22/32, 1 pair of guide gloves, case for tool set		174050R	1 078,48
Adapter drum REMS Cobra 22/8 with cable Ø 8 mm × 7.5 m long, with bulbous head		170011	670,24
Adapter drum REMS Cobra 32/8 with cable Ø 8 mm × 7.5 m long, with bulbous head		170012	670,24
Clamping jaws 16 (pack of 2) for REMS Cobra 32 for clamping drain cleaning cables Ø 16 mm		174101	121,13
Pipe and drain cleaning cable for pipe-Ø 10–50 (75) mm for pipe-Ø 25–125 mm for pipe-Ø 50–150 mm for pipe-Ø 50–250 mm	8 × 7.5 m 16 × 2.3 m 22 × 4.5 m 32 × 4.5 m	170200 171200 172200 174200	69,03 68,72 108,99 152,59
Pipe and drain cleaning cable (5 pieces) in cable carrier for pipe-Ø 25–125 mm	16 × 2.3 m	171201	450,18
Pipe and drain cleaning cable (5 pieces) in cable carrier for pipe-Ø 50–150 mm	22 × 4.5 m	172201	576,09
Pipe and drain cleaning cable (4 pieces) in cable carrier for pipe-Ø 50–250 mm	32 × 4.5 m	174201	728,68
Pipe and drain cleaning cable S With thick special spring steel for high stability, e.g. during root cutting, milling, chain knocking for pipe-Ø 25–125 mm for pipe-Ø 50–150 mm for pipe-Ø 50–250 mm	16 × 2 m 22 × 4 m 32 × 4 m	171205 172205 174205	87,81 146,36 260,54
Pipe and drain cleaning cable with core prevents clogging of pipe and drain cleaning cable with dirt for pipe-Ø 25–125 mm for pipe-Ø 50–150 mm for pipe-Ø 50–250 mm	16 × 2.3 m 22 × 4.5 m 32 × 4.5 m	171210 172210 174210	95,18 174,38 204,49
Pipe and drain cleaning cable with core (5 pieces) in cable carrier for pipe-Ø 50–150 mm	22 × 4.5 m	172203	880,22
Pipe and drain cleaning cable with core (4 pieces) in cable carrier for pipe-Ø 50–250 mm	32 × 4.5 m	174203	936,28
Cable reduction 22/16 for connecting individual cables of different sizes	22/16	172154	124,56
Cable reduction 32/22 for connecting individual cables of different sizes	32/22	174154	144,28
Cable carrier (empty)	16 22 32	171150 172150 174150	106,60 106,91 118,33
Cable joint separator for releasing the safety lock	16 22/32	171151 172151	4,15 4,67




REMS Cobra 22/32

Accessories for REMS Cobra 22, REMS Cobra 32
and other makes

Description	Size	Art.-No.	€
Straight auger for exploring the obstruction to withdraw a sample. Clearing of solid blockages caused by e.g. textiles, paper, kitchen waste	16 22 32	171250 172250 174250	34,77 45,67 57,61
Bulbous auger for minor obstructions caused by textiles and papers. Flexible, facilitates advancement in tight bends.	16 22 32	171265 172265 174265	34,77 45,78 59,79
Funnel auger for textile and paper obstructions in particular. Especially useful for cleaning larger diameter pipes. Also be used as a recovery tool for cables left in the pipe.	16 22 32	171270 172270 174270	38,41 49,82 67,99
Retrieving auger with extended, specially angled grappling arms. Used to recover cables left in the pipe. Not suitable for boring operations.	16 22 32	171275 172275 174275	34,77 48,99 58,44
Serrated blade borer for boring out greasy or heavily silted pipes, e.g. drains of washing machines, dishwashers. Riveted to the connector (not soldered or welded), so as to prevent any deformation of the hardened spring steel blades.	16/25 22/35 22/45 32/55	171280 172280 172281 174282	31,87 46,81 58,85 76,71
Serrated cross-blade borer Universal use for obstructions of all kinds, including incrustations, e.g. limescale deposits on the inside of the pipe. Riveted to the connector (not soldered or welded), so as to prevent any deformation of the hardened spring steel blades. Operation with pipe and drain cleaning cable S recommended.	16/25 16/35 22/35 22/45 22/65 32/45 32/65 32/90 32/115	171290 171291 172290 172291 172293 174291 174293 174295 174296	61,45 69,23 82,42 92,59 88,96 93,11 112,10 138,05 148,43
Forked cutter to remove moderate to severe silting or persistent grease contamination. Made of hardened spring steel.	16	171305	40,79
Cross-forked cutter to remove moderate to severe silting or persistent grease contamination. Made of hardened spring steel. Operation with pipe and drain cleaning cable S recommended.	16	171306	60,41
Serrated forked cutter Versatile use, e.g. for removal of slurries and for mincing (crushing) of root infested pipe. Made of hardened spring steel.	22/65 32/65 32/90	172305 174305 174306	97,99 107,95 126,64
Root cutter specially designed for root infested pipe. Hardened, replaceable ring-type saw, cutting to front and rear. Operation with pipe and drain cleaning cable S recommended.	22/65 32/65 32/90	172310 174310 174311	145,32 160,89 183,73
Chain knocker, smooth rings for final pipe and drain cleaning for removal of grease deposits and incrustations, e.g. limescale deposits on the inside of the pipe. For sensitive pipes, e.g. plastic.	16 22 32	171340 172340 174340	115,53 151,55 183,93
Chain knocker, spiked links for final pipe and drain cleaning for removal of grease deposits and incrustations, e.g. limescale deposits on the inside of the pipe. For cast and concrete pipes.	16 22 32	171341 172341 174341	138,37 187,88 216,94
Guide gloves, pair for secure gripping and guiding of pipe and drain cleaning cables		172610	24,50
Riveted guide glove, left Riveted guide glove, right for secure gripping and guiding of pipe and drain cleaning cables. Fully leather, inner surface riveted.		172611 172612	51,07 51,07





Plastic Pipe Welding




Electric sleeve welding unit

292



Sleeve welding units

293



Butt welding machines

294



Butt welding units

298

REMS EMSG 160-2

Electric sleeve welding unit

Powerful, handy unit for welding plastic drain pipes with electric sleeves in PE.

Plastic pipes and electric sleeves in PE Ø 32 – 160 mm

For Geberit, Akatherm-Euro, Coes, Valsir, Waviduo

REMS EMSG 160-2 – automatic welding.

Electronic control. Acoustic and visual monitoring of welding process.

Smallest sizes. Super-handy, light, only 1.1 kg. Can be used anywhere.

Electronic control with micro controller for automatic adjustment of welding current (welding temperature) and welding time according to sleeve size.

Automatic compensation of welding time in accordance with the ambient temperature.

Acoustic and visual monitoring of welding process.

Angled electrofusion plug for use in very confined spaces.

Wide work radius through extra-long cables.

Sturdy, impact-proof plastic housing with snap hook, for hanging next to the welding point. Dust and splash water-protected.

Manual pipe scraper for treating the surface of the pipe ends to be welded.



Angled electrofusion plug for use in very confined spaces.

Supply format

REMS EMSG 160-2. Electric sleeve welding unit 230 V, 50–60 Hz, 1000 W, for welding plastic drain pipes with electric sleeves in PE made by Akatherm-Euro, Coes, Geberit, Valsir, Waviduo, Ø 32–160 mm. Electronic control, with acoustic and visual monitoring of welding process. In a sturdy, impact-proof plastic housing with snap hook. Welding lead 3.9 m. Manual pipe scraper. In sturdy case.

Art.-No.	€
261002R220	767,08



REMS SSM 160RS

Handy, easy-to-carry compact machine. Complete only 45 kg. Ideal for sanitary installations and installation of drain pipes, chimney reconstruction with PVDF pipes. For job site and workshop.

Plastic pipes and fittings

in PB, PE, PP, PVDF

Ø 40 – 160 mm

PE Ø 40 – 90 mm	SDR ≥ 6
PE Ø 40 – 110 mm	SDR ≥ 9
PE Ø 40 – 125 mm	SDR ≥ 11
PE Ø 40 – 140 mm	SDR ≥ 17
PE Ø 40 – 160 mm	SDR ≥ 21

REMS SSM 160RS – ideal for the pipe fitter.

Light and compact. Heating element according to DVS.
Electronic temperature control. High-quality PTFE coating.
Powerful facing cutter. Closed facing cutter housing.

Design

Light and compact. Low weight, complete only 60 kg.

Can be easily carried by one person.

- Base frame in cast aluminium
- Free suspension of butt welding unit REMS SSG 180 for exact alignment of the faces to be welded
- Electric facing cutter unit for plane-parallel machining of pipe ends
- Smooth sliding, roller-bearing mounting of butt welding unit and electric facing cutter unit
- Quick clamping device, also suitable for angular branches.
- Pressing device, clear scale for easy reading of jointing pressure, clamping handle for pressure holding
- Can be used on the workbench or on the tubular stand provided as standard (= sub-frame = transport device).

Heating element according to DVS

Plate-shaped, plane parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminium for indirect heat transfer. High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area. Protective cover for heating element.

Electronic temperature control

Adjustable temperature 180 – 290°C, preset for PE pipes. The electronic temperature control automatically controls the preset temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.

Facing cutter unit

Electric facing cutter unit with special, high torque universal motor, 500 W, for plane-parallel machining of one or both pipe ends according to DVS. Fast positioning of facing cutter with proven safety switch. Closed facing cutter housing. Specially hardened and specially ground planing blades guarantee easy, vibration-free planing.

Quick clamping device, also for angular branches

Sturdy quick clamping device made of nickel-plated steel, consisting of 2 vices with 2 clamping inserts each for pipes of Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140, 160 mm. Also suitable for angular branches.

Pipe supports

Multiple adjustment, easy positioning of pipe supports for pipes Ø 160 mm for supporting and easy axial alignment of pipes and fittings. 2 pipe support inserts each for pipes Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140 mm.

Supply format

REMS SSM 160RS. Butt welding machine for plastic pipes and fittings in PB, PE, PP, PVDF, PE Ø 40 – 90 mm SDR ≥ 6, PE Ø 40 – 110 mm SDR ≥ 9, PE Ø 40 – 125 mm SDR ≥ 11, PE Ø 40 – 140 mm SDR ≥ 17, PE Ø 40 – 160 mm SDR ≥ 21. Butt welding unit with PTFE-coated heating element 230 V, 50 – 60 Hz, 1200 W. Adjustable temperature 180 – 290°C, preset for PE pipes. Electronic temperature control. Protective cover for heating element. Electric planing device 230 V, 50 – 60 Hz, 500 W. Pressing device. Quick clamping device, also for angular branches, consisting of 2 vices with 2 clamping inserts each Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140, 160 mm. 2 pipe rests Ø 160 mm with pipe rest inserts Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140 mm. Work key. Steel case for pipe support inserts and clamp inserts. Tubular stand = base frame = carrying device.

	Art.-No.	€
	252026R220	4 562,01

Accessories

Description	Art.-No.	€
Planing blade (piece)	252103R	124,56

Butt welding machine



Info



REMS SSM 160KS

Butt welding machine

Powerful, proven, easy-to-transport compact machine.
Ideal for sanitary installation, drain pipe installation,
chimney reconstruction with PVDF pipes.
For job site and workshop.

Plastic pipes and fittings

in PB, PE, PP, PVDF

Ø 40 – 160 mm

PE Ø 40 – 90 mm	SDR ≥ 6
PE Ø 40 – 110 mm	SDR ≥ 9
PE Ø 40 – 125 mm	SDR ≥ 11
PE Ø 40 – 140 mm	SDR ≥ 17
PE Ø 40 – 160 mm	SDR ≥ 21

REMS SSM 160KS – ideal for the pipe fitter.
Heating element according to DVS. Electronic temperature control. High-quality PTFE coating.
Powerful facing cutter. Closed facing cutter housing.

Design

Compact, robust, job site-proven. Machine on sheet metal base weighs 101 kg.
Easy to carry.

- Base frame in aluminium cast
- Free suspension of butt welding unit REMS SSG 180 for exact alignment of the faces to be welded
- Electric facing cutter unit for plane-parallel machining of pipe ends
- Smooth sliding, roller-bearing mounting of butt welding unit and electric facing cutter unit
- Quick clamping device, also suitable for angular branches.
- Pressing device, clear scale for easy reading of jointing pressure, clamping handle for pressure holding
- Machine on sheet steel base with built-in drawer for clamping and pipe rest inserts
- Suitable for use on a work bench or on the standard supplied sheet metal cabinet (= carrying case).

Heating element according to DVS

Plate-shaped, plane-parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminium for indirect heat transfer. High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area. Protective cover for heating element.

Electronic temperature control

Adjustable temperature 180 – 290°C, preset for PE pipes. The electronic temperature control automatically controls the preset temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.

Facing cutter unit

Electric facing cutter unit with special, high torque universal motor, 500 W, for plane-parallel machining of one or both pipe ends according to DVS. Fast positioning of facing cutter with proven safety switch. Closed facing cutter housing. Specially hardened and specially ground planing blades guarantee easy, vibration-free planing.

Quick clamping device, also for angular branches

Sturdy quick clamping device made of nickel-plated steel, consisting of 2 vices with 2 clamping inserts each for pipes of Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140, 160 mm. Also suitable for angular branches.

Pipe supports

Multiple adjustment, easy positioning of pipe supports for pipes of Ø 160 mm for supporting and easy axial alignment of pipes and fittings. 2 pipe support inserts each for pipes Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140 mm.

Supply format

REMS SSM 160KS. Butt welding machine for plastic pipes and fittings in PB, PE, PP, PVDF, PE Ø 40 – 90 mm SDR ≥ 6, PE Ø 40 – 110 mm SDR ≥ 9, PE Ø 40 – 125 mm SDR ≥ 11, PE Ø 40 – 140 mm SDR ≥ 17, PE Ø 40 – 160 mm SDR ≥ 21. Butt welding unit with PTFE-coated heating element 230 V 50 – 60 Hz, 1200 W. Adjustable temperature 180 – 290°C, preset for PE pipes. Electronic temperature control. Protective cover for heating element. Electric planing device 230 V, 50 – 60 Hz, 500 W. Pressing device. Quick clamping device, also for angular branches, consisting of 2 vices with 2 clamping inserts each Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140, 160 mm. 2 pipe rests Ø 160 mm with pipe rest inserts Ø 40, 50, 56, 63, 75, 90, 110, 125, 135, 140 mm. Sheet steel base with built-in drawer. Work key. Closed sheet metal cabinet = carrying case.

	Art.-No.	€
	252046R220	6 087,87

Accessories

Description	Art.-No.	€
Planing blade (piece)	252103R	124,56



Info



REMS SSM 250KS

Butt welding machine

Powerful, proven, easy-to-transport compact machine.
Ideal for sanitary installation, drain pipe installation,
chimney reconstruction with PVDF pipes.
For job site and workshop.

Plastic pipes and fittings

in PB, PE, PP, PVDF

Ø 75 – 250 mm

PE Ø 75 – 140 mm	SDR ≥ 6
PE Ø 75 – 160 mm	SDR ≥ 9
PE Ø 75 – 180 mm	SDR ≥ 11
PE Ø 75 – 200 mm	SDR ≥ 13.6
PE Ø 75 – 225 mm	SDR ≥ 17.6
PE Ø 75 – 250 mm	SDR ≥ 22

REMS SSM 250KS – compact and robust.

Design

Compact, robust, job site-proven. Easy to carry.

Machine on sheet metal base weighs 109 kg.

- Base frame in aluminium cast
- Free suspension of butt welding unit for exact alignment of the faces to be welded
- Electric facing cutter unit for plane-parallel machining of pipe ends
- Smooth sliding, roller-bearing mounting of butt welding unit and electric facing cutter unit
- Quick clamping device, also suitable for angular branches.
- Pressing device, clear scale for easy reading of jointing pressure, clamping handle for pressure holding
- Machine on sheet steel base with built-in drawer for clamping and pipe rest inserts.
- Suitable for use on a work bench or on the standard supplied sheet metal cabinet (= carrying case).

Heating element according to DVS

Plate-shaped, plane-parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminium for indirect heat transfer.

High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area.

Electronic temperature control

Adjustable temperature 180–290°C, preset for PE pipes. The electronic temperature control automatically controls the preset temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.

Facing cutter unit

Electric facing cutter unit with special, high torque universal motor, 500 W, for plane-parallel machining of one or both pipe ends according to DVS.

Fast positioning of facing cutter with proven safety switch. Closed facing cutter housing. Specially hardened and specially ground planing blades guarantee easy, vibration-free planing.

Quick clamping device for angular branches

Sturdy quick clamping device made of nickel-plated steel which grips the pipe all round, consisting of 2 clamps Ø 250 mm with jaws Ø 250 mm, with 2 clamping jaws and 2 clamping inserts each for pipes of Ø 75, 90, 110, 125, 160, 200 mm. Also suitable for angular branches. Clamping jaws and clamping inserts available for pipes of Ø 140, 180, 225 mm.

Pipe supports

Multiple adjustment, easy positioning of pipe supports for supporting and easy axial alignment of pipes and fittings. 2 pipe support inserts each for pipes Ø 75, 90, 110, 125, 140, 160, 180, 200, 225, 250 mm. Pipe rest inserts available for pipes of Ø 140, 180, 225 mm.

Supply format

REMS SSM 250K. Butt welding machine for plastic pipes and fittings in PB, PE, PP, PVDF. PE Ø 75 – 140 mm SDR ≥ 6, PE Ø 75 – 160 mm SDR ≥ 9, PE Ø 75 – 180 mm SDR ≥ 11, PE Ø 75 – 200 mm SDR ≥ 13.6, PE Ø 75 – 225 mm SDR ≥ 17.6. PE Ø 75 – 250 mm SDR ≥ 22. Butt welding unit with PTFE-coated heating element 230 V, 50–60 Hz, 1300 W. Adjustable temperature 180–290°C, preset for PE pipes. Electronic temperature control. Electric facing cutter unit 230 V, 50–60 Hz, 500 W. Quick clamping device, also for angular branches, consisting of 2 clamps Ø 250 mm with jaws Ø 250 mm, with 2 clamping jaws and 2 clamping inserts each for pipes of Ø 75, 90, 110, 125, 160, 200 mm. 2 pipe rests with pipe rest inserts Ø 75, 90, 110, 125, 160, 200, 250 mm. Sheet steel base with built-in drawer. Work key. Closed sheet metal cabinet = carrying case.

	Art.-No.	€
	254025R220	9 881,76

Accessories

Description	Art.-No.	€
Planing blade (piece)	254103	183,73



Info



REMS SSM 315RF

Butt welding machine

Compact, easy-to-transport high-performance machine for sanitary installation, drain pipe installation, chimney reconstruction with PVDF pipes. For job site and workshop.

Plastic pipes and fittings

in PB, PE, PP, PVDF	Ø 90 – 315 mm
PE Ø 90–180 mm	SDR ≥ 6
PE Ø 90–200 mm	SDR ≥ 7.4
PE Ø 90–225 mm	SDR ≥ 9
PE Ø 90–250 mm	SDR ≥ 13.6
PE Ø 90–280 mm	SDR ≥ 17
PE Ø 90–315 mm	SDR ≥ 21

REMS SSM 315RF – convenient for job site and workshop.

Design

Compact, robust, job site-proven. Weight including tubular stand on wheels 154 kg.

- Base frame in aluminium cast
- Free suspension of butt welding unit for exact alignment of the faces to be welded
- Electric facing cutter unit for plane-parallel machining of pipe ends
- Smooth sliding, roller-bearing mounting of butt welding unit and electric facing cutter unit
- Quick clamping device
- Pressing device, clear scale for easy reading of jointing pressure, clamping handle for pressure holding
- Standard supply with tubular wheel stand for secure standing and easy transport.

Heating element according to DVS

Plate-shaped, plane-parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminium for indirect heat transfer. High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area.

Electronic temperature control

Adjustable temperature 180–290°C, preset for PE pipes. The electronic temperature control automatically controls the preset temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.

Facing cutter unit

Electric facing cutter unit with special, high torque universal motor, 500 W, for plane-parallel machining of one or both pipe ends according to DVS. Fast positioning of facing cutter with proven safety switch. Closed facing cutter housing. Specially hardened and specially ground planing blades guarantee easy, vibration-free planing.

Quick clamping device

Sturdy quick clamping devices made of nickel-plated steel which grip the pipe all round, for pipes of Ø 315 mm. 4 clamping inserts each for pipes of Ø 90, 110, 125, 160, 200, 250 mm. Clamping inserts available for pipes of Ø 140, 180, 225, 280 mm.

Pipe supports

Multiple adjustment, easy positioning of pipe supports for pipes Ø 315 mm for supporting and easy axial alignment of pipes and fittings. 2 pipe rest inserts each for pipes of Ø 90, 110, 125, 160, 200, 250 mm. Pipe rest inserts available for pipes of Ø 140, 180, 225, 280 mm.

Supply format

REMS SSM 315RF. Butt welding machine for plastic pipes and fittings in PB, PE, PP, PVDF. PE Ø 90–180 mm SDR ≥ 6, PE Ø 90–200 mm SDR ≥ 7.4, PE Ø 90–225 mm SDR ≥ 9, PE Ø 90–250 mm SDR ≥ 13.6, PE Ø 90–280 mm SDR ≥ 17, PE Ø 90–315 mm SDR ≥ 21. Butt welding unit with PTFE-coated heating element 230 V, 50–60 Hz, 3000 W. Adjustable temperature 180–290°C, preset for PE pipes. Electronic temperature control. Electric facing cutter unit 230 V, 50–60 Hz, 500 W. Pressing device. 2 quick clamping devices Ø 315 mm with 2 clamping inserts each for pipes of Ø 90, 110, 125, 160, 200, 250 mm. 2 pipe supports Ø 315 mm with pipe support inserts Ø 90, 110, 125, 160, 200, 250 mm. Ring spanner. Boxes for clamping and pipe rest inserts. Tubular stand on wheels.

	Art.-No.	€
	255020R220	13 491,92

Accessories

Description	Art.-No.	€
Planing blade (piece)	255103	196,18



Info



Powerful electric tools for efficient butt welding.
Can be used anywhere, free-hand or on the work bench.
Plastic pipes and fittings
in PB, PE, PP, PVDF

$\leq \varnothing 280 \text{ mm}$

REMS SSG – heating element according to DVS.

Electronic temperature control.

High-quality PTFE coating.

Design


Handy, light, safe. Free-hand or work bench assembly. Supplied as standard with supporting stand. Bench support available as accessory for mounting the unit in a horizontal or vertical position.

Heating element according to DVS

Plate-shaped, plane parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminum for indirect heat transfer. High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area.

Electronic temperature control

Adjustable temperature 180–290°C, preset for PE pipes. The electronic temperature control automatically controls the preset temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.



Supply format

REMS MSG. Butt welding unit for plastic pipes and fittings in PB, PE, PP, PVDF.

PTFE-coated heating element 230 V, 50–60 Hz. Adjustable temperature

180–290°C, preset for PE pipes. Electronic temperature control. Support stand.

In a carton.

Description	Heating element $\varnothing \text{ mm}$	Pipes $\leq \varnothing \text{ mm}$	Power W	Art.-No.	€
110/45° EE	125	110	500	250020R220	517,96
125 EE	145	125	700	250120R220	560,52
180 EE	200	180	1200	250220R220	643,56
280 EE	300	280	1300	250320R220	778,50

Accessories

Description	Art.-No.	€
Bench support for mounting the unit in a horizontal or vertical position		
REMS SSG 110/45°, 125, 180	250041	69,23
REMS SSG 280	250341	71,10
Steel case		
REMS SSG 110/45°	250042	107,95
REMS SSG 125	250142	107,95
REMS SSG 180	250242	107,95
REMS SSG 280	250342	153,62
Protection cover for heating element		
REMS SSG 110, 110/45°, 125	250143	42,87
REMS SSG 180	250243	44,12
REMS SSG 280	250343	50,65







Diamond core drilling

Diamond chasing and cutting machine

Wet and dry suction



**Electric diamond core
drilling machines**

302



Drill stands

310



**Universal diamond core
drilling crowns**

312



**Universal diamond core
drilling crowns LS**

314



**Electric diamond core drilling
machine with micro-pulse
technology**

316



**Dry diamond core drilling
crowns LS**

319



Tile drilling

320



**Diamond chasing
and cutting machine**

322



Diamond cutting discs

323



Dry and wet extractor

324

REMS Picus S1

Electric diamond core drilling machine

Compact, handy power tool for core drilling, e.g. in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Dry or wet drilling, hand held or with drill stand. For trade and industry.

Concrete,
steel-reinforced concrete $\leq \varnothing 102$ (132) mm

Masonry and other materials $\leq \varnothing 162$ mm

REMS Universal diamond core drilling crowns,
also suitable for drive machines of other makes,
see page 312 – 314.

REMS Picus S1 – Core drilling instead of chiselling.

Easy, fast, vibration-free, e.g. 200 mm in steel-reinforced concrete $\varnothing 62$ mm in only 3 min.

1 system – 4 applications.

Ideal for plumbers.

Universal use

Universal drive machine for dry or wet drilling, hand held or with drill stand. Can be used anywhere, in narrow angles, flush with the wall. For many materials. For pipeline and cable ducting, ventilation channels, test core drilling.

System advantage

Only one type of universal diamond core drilling crowns for all REMS Picus drive machines and other suitable makes of drive machines. Therefore simple, low cost storage. No confusion possible.

Design

Compact, handy drive machine for vibration-free core drilling, with drilling crown connecting thread UNC 1 1/4 male, BSPP 1/2 female. Robust, suitable for the building site. Extra light, only 5.2 kg. Simple, fast work, e.g. 200 mm in steel-reinforced concrete $\varnothing 62$ mm in only 3 min. Practical spade handle and stabiliser for hand held drilling. Throat $\varnothing 60$ mm for holding the drive machine in the drill stand. Water supply for wet drilling, with adjustable shut-off valve and quick-coupling with water stop and hose connection 1/2". Suction rotor for sucking off dust for dry drilling with connection for conventional vacuum cleaner, as accessory.

Drive

Robust, powerful 1850 W universal motor. Load speed drilling spindle 580 rpm. Stable, maintenance-free gear. Blocking protection by safety slip clutch. Tip switch with lock. Connecting cable with integrated personal protection switch (PRCD).

Multifunction electronics

Multifunction electronics with start-up current limiting for soft starting for delicate drilling start, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Universal diamond core drilling crowns

Universally usable for dry and wet drilling, hand held or with drill stand. Optionally REMS Universal diamond core drilling crowns, inductively soldered, resolderable or REMS Universal diamond core drilling crowns LS, laser welded, high temperature-resistant (page 312 – 314). Connecting thread UNC 1 1/4 female. Drilling depth 420 mm. Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry. Adapter for using the REMS Universal diamond core drilling crowns in drive machines of other makes, as accessory. Light loosening ring, for light loosening of the diamond core crown, as accessory.

Dust extraction in accordance with EN 60335-2-69

When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m³). Observe the national regulations.

Suction rotor for dust extraction in dry drilling with connection for REMS Pull 2 and other suitable extractors, as accessory (page 311). REMS Pull 2 M, wet and dry dust extractor, certified for extracting health hazardous dusts of dust class M (page 324).

Drilling start aid

Drilling start aid G 1/2 UDKB, with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction, with carbide masonry drill $\varnothing 8$ mm.

Water extractor unit

Water extractor unit for wet drilling up to $\varnothing 170$ mm, consisting of a water collector ring with connection for REMS Pull 2 or other suitable wet extractors, compression ring, rubber washer $\varnothing 200$ mm, adaptable to diameter of the drill crown and universal pressure pad for all REMS drill stands, as accessory.

Drill stand

REMS Simplex 2 or REMS Titan drill stands can be used optionally (page 310).



Info



REMS Simplex 2

REMS Titan



REMS Picus S1 Basic-Pack

Supply format

REMS Picus S1 Basic-Pack. Electric diamond core drilling machine for core drilling in concrete, steel-reinforced concrete $\leq \varnothing 102$ (132) mm, masonry and other materials $\leq \varnothing 162$ mm. For dry and wet drilling, hand held or with drill stand. Drive machine with drilling crown connecting thread UNC 1½ male, BSPP ½ female, maintenance-free gear with safety slip clutch, universal motor 230 V, 50–60 Hz, 1850 W. Multifunction electronics with soft starting, idle speed limiting, overload protection, blocking protection. Touch switch with lock. Personal protection switch (PRCD). Load speed drilling spindle 580 rpm. Water supply device with adjustable shut-off valve and quick coupling with water stop and ½" hose connection. Stabiliser. Drilling start aid G ½ UDKB with drill $\varnothing 8$ mm, Allen key size 3. Single open-ended wrench size 32. In sturdy steel case.

	Art.-No.	€
	180010R220	1 629,66

Other voltages on request.

Supply format

REMS Picus S1 Set Simplex 2. REMS Picus S1 Basic-Pack with REMS Simplex 2 drilling stand including tools and fastening kit for masonry and concrete.

	Art.-No.	€
	180032R220	2 646,90

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Picus S1 drive unit	180000R220	1 577,76
Steel case with inlay	180600R	128,71

REMS Universal diamond core drilling crowns, inductively soldered, resolderable, see page 312.

REMS universal diamond core drilling crowns LS, laser welded, high temperature-resistant, see page 314.

REMS Pull 2 L / M, dry and wet extractors, see page 324

Additional accessories see page 310–311.



REMS Picus S1 Set Simplex 2



REMS Picus S3

Electric diamond core drilling machine

Powerful, handy power tool for core drilling, e.g. in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Dry or wet drilling, hand held or with drill stand. For trade and industry.

Concrete,
steel-reinforced concrete $\leq \varnothing 152$ (200) mm

Masonry and other materials $\leq \varnothing 250$ mm

REMS Universal diamond core drilling crowns,
also suitable for drive machines of other makes,
see page 312 – 314.

REMS Picus S3 – Core drilling instead of chiselling.

Easy, fast, vibration-free, e.g. 200 mm in steel-reinforced concrete $\varnothing 62$ mm in only 3 min.

1 system – 4 applications.

Ideal for plumbers.

Universal use

Universal drive machine for dry or wet drilling, hand held or with drill stand. Can be used anywhere, in narrow angles, flush with the wall. Extremely versatile and efficient, e.g. drilling in steel-reinforced concrete, masonry and other materials. For pipeline and cable ducting, ventilation channels, test core drilling.

System advantage

Only one type of universal diamond core drilling crowns for all REMS Picus drive machines and other suitable makes of drive machines. Therefore simple, low cost storage. No confusion possible.

Design

Compact, handy drive machine for vibration-free core drilling, with drilling crown connecting thread UNC 1 1/4 male, BSPP 1/2 female. Robust, suitable for the building site. Only 7.4 kg. Simple, fast work, e.g. 200 mm in steel-reinforced concrete $\varnothing 62$ mm in only 3 min. Practical spade handle and stabiliser for hand held drilling. Throat $\varnothing 60$ mm for holding the drive machine in the drill stand. Water supply for wet drilling, with adjustable shut-off valve and quick-coupling with water stop and hose connection 1/2". Suction rotor for sucking off dust for dry drilling with connection for conventional vacuum cleaner, as accessory.

Drive

Robust, powerful 2200 W universal motor. Stable, maintenance-free 3-speed gear for optimum selection of load speed according to the drilling diameter. Load speed drilling spindle 530 rpm, 1280 rpm, 1780 rpm. Blocking protection by safety slip clutch. Tie switch with lock. Connecting cable with integrated personal protection switch (PRCD).

Multifunction electronics

Multifunction electronics with start-up current limiting for soft starting for delicate drilling start, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Universal diamond core drilling crowns

Universally usable for dry and wet drilling, hand held or with drill stand. Optionally REMS Universal diamond core drilling crowns, inductively soldered, resolderable or REMS Universal diamond core drilling crowns LS, laser welded, high temperature-resistant (page 312 – 314). Connecting thread UNC 1 1/4 female. Drilling depth 420 mm. Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry. Adapter for using the REMS Universal diamond core drilling crowns in drive machines of other makes, as accessory. Light loosening ring, for light loosening of the diamond core crown, as accessory.

Dust extraction in accordance with EN 60335-2-69

When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m³). Observe the national regulations.

Suction rotor for dust extraction in dry drilling with connection for REMS Pull 2 and other suitable extractors, as accessory (page 311). REMS Pull 2 M, wet and dry dust extractor, certified for extracting health hazardous dusts of dust class M (page 324).

Drilling start aid

Drilling start aid G 1/2 UDKB, with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction, with carbide masonry drill Ø 8 mm, as accessory.

Water extractor unit

Water extractor unit for wet drilling up to Ø 170 mm, consisting of a water collector ring with connection for REMS Pull 2 or other suitable wet extractors, compression ring, rubber washer Ø 200 mm, adaptable to diameter of the drill crown and universal pressure pad for all REMS drill stands, as accessory.

Drill stand

REMS Simplex 2 or REMS Titan drill stands can be used optionally (page 310).



Info



REMS Simplex 2



REMS Titan



REMS Picus S3 Basic-Pack



REMS Picus S3 Set Titan



REMS Picus S3 Set 62-82-132 Titan

Supply format

REMS Picus S3 Basic-Pack. Electric diamond core drilling machine for core drilling in concrete, steel-reinforced concrete $\leq \varnothing 152$ (200) mm, masonry and other materials ≤ 250 mm. For dry and wet drilling, hand held or with drill stand. Drive machine with drilling crown connecting thread UNC 1½ male, BSPP ½ female, maintenance-free 3-speed gear with safety slip clutch, universal motor 230 V, 50–60 Hz, 2200 W. Multifunction electronics with soft starting, idle speed limiting, overload protection, blocking protection. Touch switch with lock, personal protection switch (PRCD). Load speed drilling spindle 530 rpm, 1280 rpm, 1780 rpm. Water supply with adjustable shut-off valve and quick-coupling with water stop and hose connection ½". Stabiliser. Starting aid BSPP ½, Allen key size 3. Single open-ended wrench size 32. In sturdy steel case.

	Art.-No.	€
	180011R220	2 024,10

Other voltages on request.

Supply format

REMS Picus S3 Set Titan. REMS Picus S3 Basic-Pack with REMS Titan drilling stand including fastening kit for masonry and concrete.

	Art.-No.	€
	180029R220	3 570,72

Other voltages on request.

Supply format

REMS Picus S3 Set 62 + 82 + 132 Titan. REMS Picus S3 Basic-Pack with REMS Universal diamond core drilling crowns UDKB Ø 62 + 82 + 132 mm and REMS Titan drilling stand including fastening kit for masonry and concrete.

	Art.-No.	€
	180028R220	4 198,71

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Picus S3 drive unit	180001R220	1 972,20
Steel case with inlay	180600R	128,71

REMS Universal diamond core drilling crowns,
inductively soldered, resolderable, see page 312.

REMS universal diamond core drilling crowns LS,
laser welded, high temperature-resistant, see page 314.

REMS Pull 2 L / M, dry and wet extractors, see page 324

Additional accessories see page 310–311.



REMS Picus SR

Compact, handy power tool for core drilling, e.g. in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. With speed regulation. Dry or wet drilling, hand held or with drill stand. For trade and industry.

Concrete,
steel-reinforced concrete $\leq \varnothing 162$ (200) mm

Masonry and other materials $\leq \varnothing 250$ mm

REMS Universal diamond core drilling crowns,
also suitable for drive machines of other makes,
see page 312 – 314.

REMS Picus SR – Core drilling instead of chiselling.
Easy, fast, vibration-free, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 3 min. With speed regulation.

1 system – 4 applications.

Ideal for plumbers.

Universal use

Universal drive machine for dry or wet drilling, hand held or with drill stand. Can be used anywhere, in narrow angles, flush with the wall. Extremely versatile and efficient, e.g. drilling in steel-reinforced concrete, masonry and other materials. For pipeline and cable ducting, ventilation channels, test core drilling.

System advantage

Only one type of universal diamond core drilling crowns for all REMS Picus drive machines and other suitable makes of drive machines. Therefore simple, low cost storage. No confusion possible.

Design

Compact, handy drive machine for vibration-free core drilling, with drilling crown connecting thread UNC 1 1/4 male, BSPP 1/2 female. Robust, suitable for the building site. Extra light, only 6.4 kg. Simple, fast work, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 3 min. Practical spade handle and stabiliser for hand held drilling. Throat Ø 60 mm for holding the drive machine in the drill stand. Spacer set for additional stabilisation of the REMS Picus SR drive unit on the REMS Titan drill stand. Water supply for wet drilling, with adjustable shut-off valve and quick-coupling with water stop and hose connection 1/2".

Drive

Robust, powerful 2200 W universal motor. Overheating protection by temperature monitoring of the motor's field winding with a PTC resistor (Positive Temperature Coefficient). Stable, maintenance-free, 2-step gear. Blocking protection by safety slip clutch. Tip switch with lock. Connecting cable with integrated personal protection switch (PRCD).

Speed-Regulation

Stepless electronic speed regulation of the drive machine for selecting the speed according to the material. The speed is steplessly adjustable on the dial: 250 rpm to 500 rpm (1st gear) or 600 rpm to 1200 rpm (2nd gear). The electronic speed control that is being used keeps the selected speed constant, also under load. The speed of the drilling crown is kept at the nominal value until it meets with resistance and drops below a critical value. The drive motor stops. When the load on the drive unit is relieved again, the drill runs back up to nominal speed so that work can continue immediately at nominal speed (**Patent EP 2 085 191**). Advantage: The optimum drilling speed (load speed) selected for the respective material and the drilling crown diameter remains constant for the entire duration of the drilling. For the best drilling performance and maximum life of the drilling crowns.

Multifunction electronics

Multifunction electronics with start-up current limiting for soft starting for delicate drilling start, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Universal diamond core drilling crowns

Universally usable for dry and wet drilling, hand held or with drill stand. Optionally REMS Universal diamond core drilling crowns, inductively soldered, resolderable or REMS Universal diamond core drilling crowns LS, laser welded, high temperature-resistant (page 312 – 314). Connecting thread UNC 1 1/4 female. Drilling depth 420 mm. Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry. Adapter for using the REMS Universal diamond core drilling crowns in drive machines of other makes, as accessory. Light loosening ring, for light loosening of the diamond core crown, as accessory.


Dust extraction in accordance with EN 60335-2-69

When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/ work place limit of > 0.1 mg/m³). Observe the national regulations.

Suction rotor for dust extraction in dry drilling with connection for REMS Pull 2 and other suitable extractors, as accessory (page 311). REMS Pull 2 M, wet and dry dust extractor, certified for extracting health hazardous dusts of dust class M (page 324).

Electric diamond core drilling machine
with speed regulation

Patent EP 2 085 191



German Quality Product



Info

With speed regulation for the best drilling performance and maximum life of the drilling crowns.



REMS Simplex 2

REMS Titan

Drilling start aid

Drilling start aid G ½ UDKB, with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction, with carbide masonry drill Ø 8 mm, as accessory.

Drill stand

REMS Simplex 2 or REMS Titan drill stands can be used optionally (page 310).

Water extractor unit

Water extractor unit for wet drilling up to Ø 170 mm, consisting of a water collector ring with connection for REMS Pull 2 or other suitable wet extractors, compression ring, rubber washer Ø 200 mm, adaptable to diameter of the drill crown and universal pressure pad for all REMS drill stands, as accessory.



REMS Picus SR Basic-Pack



REMS Picus SR Set Titan



REMS Picus SR Set 62-82-132 Titan

Supply format

REMS Picus SR Basic-Pack. For core drilling in concrete, steel-reinforced concrete ≤ Ø 162 (200) mm, masonry and other materials ≤ Ø 250 mm. For dry or wet drilling, hand held or with drill stand. Drive machine with drilling crown connection thread UNC 1 ¼ male, G ½ female, maintenance-free 2-step gear with safety slip clutch, universal motor 230 V, 50–60 Hz, 2200 W. Stepless electronic speed regulation 250 rpm to 500 rpm (1st gear) or 600 rpm to 1200 rpm (2nd gear), overheating protection. Multifunction electronics with soft starting, idle speed limiting, overload protection, blocking protection. Touch switch with lock. Personal protection switch (PRCD). Water supply device with adjustable shut-off valve and quick coupling with water stop and ½" hose connection. Stabiliser. Spacer set. Single open ended wrench size 32. In sturdy steel case.

	Art.-No.	€
	183010R220	1 712,70

Other voltages on request.

Supply format

REMS Picus SR Set Titan. REMS Picus SR Basic-Pack with REMS Titan drilling stand including fastening kit for masonry and concrete.

	Art.-No.	€
	183022R220	3 093,24

Other voltages on request.

Supply format

REMS Picus SR Set 62+82+132 Titan. REMS Picus SR Basic-Pack with REMS Titan drilling stand including fastening kit for masonry and concrete and REMS Universal diamond core drilling crowns UDKB Ø 62+82+132 mm.

	Art.-No.	€
	183023R220	3 581,10

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Picus SR drive unit	183000R220	1 328,64
Spacer set for additional stabilisation of the REMS Picus SR drive unit on the REMS Titan drill stand, consisting of spacer and 2 cylinder head screws M 8 × 65	183632R	48,58
Steel case with inlay	180600R	128,71
REMS Universal diamond core drilling crowns , inductively soldered, resolderable, see page 312.		
REMS universal diamond core drilling crowns LS , laser welded, high temperature-resistant, see page 314.		
REMS Pull 2 L / M , dry and wet extractors, see page 324		
Additional accessories see page 310–311.		



REMS Picus S2/3,5

Electric diamond core drilling machine

Powerful, robust core drilling machine for core drilling, e.g. in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Dry or wet drilling with drill stand. For installation, metalwork, industry.

Concrete, steel-reinforced concrete, masonry and other materials Ø 40 – 300 mm

REMS Universal diamond core drilling crowns, also suitable for drive machines of other makes, see page 312 – 314.

REMS Picus S2/3,5 – Core drilling instead of chiselling.

Easy, fast, vibration-free, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 2 min.

Universal use

Universal drive machine for dry or wet drilling, hand held or with drill stand. Can be used anywhere, in narrow angles, flush with the wall. Extremely versatile and efficient, e.g. drilling in steel-reinforced concrete, masonry and other materials. For pipeline and cable ducting, ventilation channels, test core drilling.

System advantage

Only one type of universal diamond core drilling crowns for all REMS Picus drive machines and other suitable makes of drive machines. Therefore simple, low cost storage. No confusion possible.

Design

Compact, handy drive machine for vibration-free core drilling, with drilling crown connecting thread UNC 1 1/4 male. Light loosening ring, for light loosening of the diamond core crowns. Compact, robust, suitable for the building site. Weight just 14.4 kg. Simple, fast work, e.g. 200 mm in steel-reinforced concrete Ø 62 mm in only 2 min. Clamping plate for fast clamping to the drill stand. Water supply for wet drilling, with adjustable shut-off valve and quick coupling with water stop and hose connection 1/2".

Drive

Robust, powerful 3420 W universal motor. Stable, maintenance-free 2-speed gear for optimum selection of load speed according to the drilling diameter. Load speed drilling spindle 320 rpm, 760 rpm. Blocking protection by safety slip clutch. Rocker switch. Connecting cable with integrated personal protection switch (PRCD).

Multifunction electronics

Multifunction electronics with start-up current limiting for soft starting for delicate drilling start, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Universal diamond core drilling crowns

Universally usable for dry and wet drilling, hand held or with drill stand. Optionally REMS Universal diamond core drilling crowns, inductively soldered, resolderable or REMS Universal diamond core drilling crowns LS, laser welded, high temperature-resistant (page 312 – 314). Connecting thread UNC 1 1/4 female. Drilling depth 420 mm. Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry. Adapter for using the REMS Universal diamond core drilling crowns in drive machines of other makes, as accessory. Light loosening ring, for light loosening of the diamond core crown, as accessory.

Water extractor unit

Water extractor unit for wet drilling up to Ø 170 mm, consisting of a water collector ring with connection for REMS Pull 2 or other suitable wet extractors, compression ring, rubber washer Ø 200 mm, adaptable to diameter of the drill crown and universal pressure pad for all REMS drill stands, as accessory.

Drill stand REMS Titan

Robust, highly stable drilling stand for core drilling in steel-reinforced concrete and other materials up to Ø 300 mm. For high demands. Drill column made of rigid, unbendable square precision steel tube Ø 50 mm, with extra narrow tolerance, for low-vibration guiding of the slide. Continuously tiltable with degree scale up to 45°, with double support by adjustable, single-part steel girders, for maximum thrust pressure. Highly stable, 3-sided guidance of the drill column in the base plate and triple cross fastening for high rigidity in vertical drilling. 4 Eyebolts for levelling unevenness of the floor, for exact standing position. Drill depth scale. Slide guided on all sides by adjustable, pretensioned plastic slide bearings. Precision in-feed drive ensures easy, low-vibration drilling and precise, low-vibration drill thrust. For high thrust pressure and long life of the drilling crowns. Spirit level integrated in the slide for exact alignment of the drill stand. Locking of the slide for simple assembly of the drilling crown and safe transport. Rigid connection plate made of wear-resistant spheroidal iron. Quick-clamping device for accommodating drive units with a suitable connection plate. Highly stable clamping bracket, unbendable and rigid, for accommodating drive units with Ø 60 mm clamping throat. Rack and pinion force transmission with ergonomically designed pressing lever which can be inserted in both sides of the slide. Wide steel rack. Base plate with groove for sealing ring of the vacuum fastening. Vacuum fastening as accessory. Drill column with adjustable clamping head for clamping the drill stand between the ceiling and floor or between two walls. Mobile drill stand for easy transport. Weight 19.5 kg.

With tools, consisting of Allen key size 6, single open ended wrench size SW 19 and SW 30 and fastening kit for masonry and concrete, consisting of 2 M12 splaying anchors, 10 M12 hammer anchors for concrete, setting iron for M12 hammer anchors, cord threaded bar M12 x 52, quick clamping nut, washer, carbide masonry drill Ø 15 mm SDS-plus, in box.



Info



REMS Titan



REMS Picus S2/3,5 Basic-Pack

Supply format

REMS Picus S2/3,5 Basic-Pack. Electric diamond core drilling machine for core drilling in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed, Ø 40–300 mm. For dry and wet drilling with drill stand. Drive machine with drilling crown connecting thread UNC 11/4 male, maintenance-free 2-speed gear with safety slip clutch, universal motor 230 V, 50–60 Hz, 3420 W. Multifunction electronics with soft starting, idle speed limiting, overload protection, blocking protection. Touch switch with lock. Personal protection switch (PRCD). Load speed drilling spindle 320 rpm, 760 rpm. Water supply device with adjustable shut-off valve and quick coupling with water stop and hose connection 1/2". Light loosening ring. Single open-ended wrench size 32. In a carton.

	Art.-No.	€
	180012R220	3 176,28

Other voltages on request.

Supply format

REMS Picus S2/3,5 Set Titan. REMS Picus SR/3.5 Basic-Pack with REMS Titan drilling stand including fastening kit for masonry and concrete.

	Art.-No.	€
	180030R220	4 722,90

Other voltages on request.



REMS Picus S2/3,5 Set Titan

Accessories

Description

REMS Universal diamond core drilling crowns, inductively soldered, resolderable, see page 312.

REMS universal diamond core drilling crowns LS, laser welded, high temperature-resistant, see page 314.

REMS Pull 2 L / M, dry and wet extractors, see page 324

Additional accessories see page 310–311.



Drill stands

Accessories for REMS Picus S1, REMS Picus S3, REMS Picus SR, REMS Picus S2/3,5, REMS Picus DP and other makes

Supply format

REMS Simplex 2. Robust, handy drilling stand for core drilling up to Ø 202 mm. Drill column made of rigid, unbendable square precision steel tube Ø 50 mm, with extra narrow tolerance, for low-vibration guiding of the slide. Drilling column guided in sturdy stand and double bolted for high rigidity during drilling. Steel section stand. 4 Set screws for levelling unevenness of the floor, for exact standing position. Clamping bracket for holding drive machines with clamping throat Ø 60 mm. Slide guided on all sides by adjustable, pretensioned plastic slide bearings. Precision in-feed drive ensures easy, low-vibration drilling and precise, low-vibration drill thrust. For high thrust pressure and long life of the drilling crowns. Spirit level integrated in the slide for exact alignment of the drill stand. Locking of the slide for simple assembly of the drilling crown and safe transport. Stable clamping bracket, unbendable and rigid, for accommodating drive units with Ø 60 mm clamping throat. Rack and pinion force transmission with ergonomically designed pressing lever which can be inserted in both sides of the slide. Wide steel rack Weight 12 kg.

With tools comprising Allen key size 6, single open ended wrench size SW 19 and SW 30 and fastening kit for masonry and concrete, consisting of 2 M12 splaying anchors, 10 M12 hammer anchors for concrete, setting iron for M12 hammer anchors, cord threaded bar M12 × 52, quick clamping nut, washer, carbide masonry drill Ø 15 mm SDS-plus in box.

For REMS Picus S1, REMS Picus S3, REMS Picus SR, REMS Picus DP and other makes.

	Art.-No.	€
	183700R	1 017,24



Info

Supply format

REMS Titan. Robust, highly stable drilling stand for core drilling in steel-reinforced concrete and other materials up to Ø 300 mm. For high demands. Drill column made of rigid, unbendable square precision steel tube Ø 50 mm, with extra narrow tolerance, for low-vibration guiding of the slide. Continuously tiltable with degree scale up to 45°, with double support by adjustable, single-part steel girders, for maximum thrust pressure. Highly stable, 3-sided guidance of the drill column in the base plate and triple cross fastening for high rigidity in vertical drilling. 4 Eyebolts for levelling unevenness of the floor, for exact standing position. Drill depth scale. Slide guided on all sides by adjustable, pretensioned plastic slide bearings. Precision in-feed drive ensures easy, low-vibration drilling and precise, low-vibration drill thrust. For high thrust pressure and long life of the drilling crowns. Spirit level integrated in the slide for exact alignment of the drill stand. Locking of the slide for simple assembly of the drilling crown and safe transport. Rigid connection plate made of wear-resistant spheroidal iron. Quick-clamping device for accommodating drive units with a suitable connection plate. Highly stable clamping bracket, unbendable and rigid, for accommodating drive units with Ø 60 mm clamping throat. Rack and pinion force transmission with ergonomically designed pressing lever which can be inserted in both sides of the slide. Wide steel rack. Base plate with groove for sealing ring of the vacuum fastening. Vacuum fastening as accessory. Drill column with adjustable clamping head for clamping the drill stand between the ceiling and floor or between two walls. Mobile drill stand for easy transport Weight 19.5 kg.

With tools comprising Allen key size 6, single open ended wrench size SW 19 and SW 30 and fastening kit for masonry and concrete, consisting of 2 M12 splaying anchors, 10 M12 hammer anchors for concrete, setting iron for M12 hammer anchors, cord threaded bar M12 × 52, quick clamping nut, washer, carbide masonry drill Ø 15 mm SDS-plus in box.

System advantage: For REMS Picus S1, REMS Picus S3, REMS Picus SR, REMS Picus S2/3,5, REMS Picus DP and other makes. Use spacer set (see below) when using with REMS Picus SR.

	Art.-No.	€
	183600R	1 546,62



Info


Description	Art.-No.	€
Spacer set for additional stabilisation of the REMS Picus SR drive unit on the REMS Titan drill stand, consisting of spacer and 2 cylinder head screws M 8 × 65	183632R	48,58



Accessories

For REMS Picus S1, REMS Picus S3, REMS Picus SR,
REMS Picus S2/3,5 and other makes

Description	Art.-No.	€
Water pressure tank for 10 ltr of water, for wet drilling without water connection	182006R	205,52
Titan drilling template for easy setting of the fastening holes. For REMS Titan drilling stand.	183605R	57,61
Carbide masonry drills Ø 15 mm SDS-plus for hammer anchors M12	079018	28,13
Hammer anchor M12 (pack of 50) , for concrete	079005R50	109,82
Setting iron for hammer anchor M12	182050R	16,09
Carbide masonry drill Ø 20 mm SDS-plus for splaying anchors M12	079019	63,42
Splaying anchor M12 (pack of 10) , for masonry, reusable	079006R10	102,76
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.	079010	72,76
Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607R	54,08
Titan vacuum fastening , consisting of cover plate with nipple for $\frac{3}{8}$ " screw connection and sealing ring for base plate.	183603R	99,44
Vacuum pump , for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m ³ /h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.	183670R220	1 909,92
Laser drilling centre pointer	183604R	129,75
Drilling start aid G ½ UDKB , with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction (Art. No. 180160 R), with carbide masonry drill Ø 8 mm	180140R	91,97
Carbide masonry drill Ø 8 mm for drilling aid	079013	18,89
Single open ended wrench size 41 for loosening the universal diamond core drilling crowns	079003	38,35
Light loosening ring , for light loosening of the diamond core crown	180015	20,66
Drilling crown extension 200 mm	180155R	61,19
Sharpening stone for diamond core drilling crowns	079012	64,67
Circular spirit level , magnetic, for aligning the drill stand	182010R	75,26
Suction rotor for dust extraction with G ½ male connecting thread, UNC 1 ½ male connecting thread and with connection for REMS Pull 2 and other suitable extractors.	180160R	173,35
Water suction device , for wet drilling up to Ø 170 mm, consisting of water collection ring with pressure ring, rubber washer Ø 200 mm and universal pressure pad for all REMS drilling stands.	183606R	393,40
Rubber washer Ø 200 mm (pack of 10) , for water suction device	183675R10	74,53
REMS Pull 2 L / M , dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 324		



REMS Universal diamond core drilling crowns

For REMS Picus S1, REMS Picus SR, REMS Picus S3, REMS Picus S2/3,5 and other makes

High quality universal diamond core drilling crowns. Inductively soldered. Universally usable for dry and wet drilling, hand held or with drill stand. Ideal for universal applications in steel-reinforced concrete, masonry and many types of material. For installation, metalwork, industry.

Concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed and other Ø 32 – 300 mm

REMS Universal diamond core drilling crowns – Inductively soldered. Diamond segments with conical cut for fast, easy and quiet drilling. Versatile for many types of material. Ideal for plumbers.

Universally usable for many materials, for dry and wet drilling, hand held or with drill stand.

Single connecting thread UNC 1½ female. Drilling depth 420 mm.


Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry.

Diamond segments with conical cut ("roof shape") for fast, easy and quiet drilling. Inductively soldered on fully automatic soldering machines for constant high quality of the soldered connection. Drilling tubes with soldered diamond segments can be resoldered by simple hard soldering.

Light loosening ring, for light loosening of the diamond core crowns, as accessory.

Drive through all REMS Picus drive machines and suitable drive machines of other makes having connecting thread UNC 1½ male. Adapter for using REMS Universal diamond core drilling crowns in drive machines having other connecting threads/other tool holders, as accessory.

Suck off dusts that occur during dry drilling with REMS Pull 2 M safety vacuum cleaner, certified for extracting health hazardous dusts of dust class M (page 324).



Info

Supply format

REMS Universal diamond core drilling crown. Inductively soldered, resolderable. Universally usable for dry and wet drilling, hand held or with drill stand. For many materials, e.g. concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Connecting thread UNC 1½ female. Drilling depth 420 mm. In a carton.

Ø x drilling depth x connection	Number of segments	Art.-No.	€
UDKB 32 x 420 x UNC 1½	4	181010R	143,19
UDKB 42 x 420 x UNC 1½	4	181015R	133,85
UDKB 52 x 420 x UNC 1½	5	181020R	142,15
UDKB 62 x 420 x UNC 1½	6	181025R	154,61
UDKB 72 x 420 x UNC 1½	7	181030R	175,37
UDKB 82 x 420 x UNC 1½	7	181035R	189,90
UDKB 92 x 420 x UNC 1½	8	181040R	214,81
UDKB 102 x 420 x UNC 1½	8	181045R	220,00
UDKB 112 x 420 x UNC 1½	9	181050R	232,46
UDKB 122 x 420 x UNC 1½	10	181055R	262,56
UDKB 127 x 420 x UNC 1½	10	181059R	272,94
UDKB 132 x 420 x UNC 1½	11	181060R	284,36
UDKB 152 x 420 x UNC 1½	12	181065R	338,34
UDKB 162 x 420 x UNC 1½	12	181070R	358,06
UDKB 182 x 420 x UNC 1½	12	181075R	396,46
UDKB 200 x 420 x UNC 1½	12	181080R	419,30
UDKB 225 x 420 x UNC 1½	13	181085R	510,64
UDKB 250 x 420 x UNC 1½	14	181090R	524,14
UDKB 300 x 420 x UNC 1½	22	181095R	686,07



Accessories

Description	Art.-No.	€
Light loosening ring, for light loosening of the diamond core crown	180015	20,66
Drilling crown extension 200 mm	180155R	61,19
Adapter UNC 1½ male to G ½ male	180052	31,45
Adapter UNC 1½ male to G ½ female	180056	28,55
Adapter UNC 1½ male for Hilti BI, adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BI tool holder.	180053	48,27
Adapter UNC 1½ male for Hilti BU, adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BU tool holder.	180054	111,07
Adapter UNC 1½ male for Hilti BL, adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BL tool holder.	180057R	111,07
Sharpening stone for diamond core drilling crowns	079012	64,67
Single open ended wrench size 41 for UDKB	079003	38,35

Additional adapters for using REMS Universal diamond core drilling crowns in drive machines of other makes, on request.



REMS Universal diamond core drilling crowns LS

For REMS Picus S1, REMS Picus SR, REMS Picus S3, REMS Picus S2/3,5 and other makes

High quality universal diamond core drilling crowns. Laser welded. Universally usable for dry and wet drilling, hand held or with drill stand. Ideal for universal applications in steel-reinforced concrete, masonry and many types of material. For installation, metalwork, industry.

Concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed and other Ø 32 – 200 mm

REMS universal diamond core drilling crowns LS – laser welded. Diamond segments with conical cut for fast, easy and quiet drilling. Versatile for many types of material. Ideal for plumbers.

Universally usable for many materials, for dry and wet drilling, hand held or with drill stand.

Single connecting thread UNC 1½ female. Drilling depth 420 mm.

Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry.

Diamond segments with conical cut ("roof shape") for fast, easy and quiet drilling. Inductively soldered on fully automatic soldering machines for constant high quality of the soldered connection. Drilling tubes with soldered diamond segments can be resoldered by simple hard soldering.

Light loosening ring, for light loosening of the diamond core crowns, as accessory.

Drive through all REMS Picus drive machines and suitable drive machines of other makes having connecting thread UNC 1½ male. Adapter for using REMS Universal diamond core drilling crowns in drive machines having other connecting threads/other tool holders, as accessory.

Suck off dusts that occur during dry drilling with REMS Pull 2 M safety vacuum cleaner, certified for extracting health hazardous dusts of dust class M (page 324).




Info

Supply format

REMS Universal diamond core drilling crown. Laser welded! High temperature-resistant! Universally usable for dry and wet drilling, hand held or with drill stand. For many materials, e.g. concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Connecting thread UNC 1½ female. Drilling depth 420 mm. In a carton.

Ø x drilling depth x connection	Number of segments	Art.-No.	€
UDKB LS 32 x 420 x UNC 1½	1	181410R	157,72
UDKB LS 42 x 420 x UNC 1½	4	181415R	147,34
UDKB LS 52 x 420 x UNC 1½	5	181420R	156,69
UDKB LS 62 x 420 x UNC 1½	6	181425R	170,18
UDKB LS 72 x 420 x UNC 1½	6	181430R	193,02
UDKB LS 82 x 420 x UNC 1½	7	181435R	209,62
UDKB LS 92 x 420 x UNC 1½	8	181440R	236,61
UDKB LS 102 x 420 x UNC 1½	9	181445R	242,84
UDKB LS 112 x 420 x UNC 1½	9	181450R	256,33
UDKB LS 122 x 420 x UNC 1½	10	181455R	289,55
UDKB LS 127 x 420 x UNC 1½	10	181459R	300,97
UDKB LS 132 x 420 x UNC 1½	10	181460R	313,42
UDKB LS 152 x 420 x UNC 1½	11	181465R	372,59
UDKB LS 162 x 420 x UNC 1½	12	181470R	394,39
UDKB LS 182 x 420 x UNC 1½	13	181475R	476,39
UDKB LS 200 x 420 x UNC 1½	14	181480R	503,38



Accessories

Description	Art.-No.	€
Light loosening ring , for light loosening of the diamond core crown	180015	20,66
Drilling crown extension 200 mm	180155R	61,19
Adapter UNC 1½ male to G ½ male	180052	31,45
Adapter UNC 1½ male to G ½ female	180056	28,55
Adapter UNC 1½ male for Hilti BI , adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BI tool holder.	180053	48,27
Adapter UNC 1½ male for Hilti BU , adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BU tool holder.	180054	111,07
Adapter UNC 1½ male for Hilti BL , adapter for using the REMS universal diamond core drilling crowns in Hilti drive machines with BL tool holder.	180057R	111,07
Sharpening stone for diamond core drilling crowns	079012	64,67
Single open ended wrench size 41 for UDKB	079003	38,35

Additional adapters for using REMS Universal diamond core drilling crowns in drive machines of other makes, on request.



REMS Picus DP

Compact, handy power tool for core drilling, e.g. in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. With micro-pulse technology. Especially for dry drilling, hand held or with drill stand. For trade and industry.

Concrete, steel-reinforced concrete $\leq \varnothing 162$ (202) mm

Masonry and other materials $\leq \varnothing 202$ mm

REMS dry diamond core drilling crowns, also suitable for drive machines of other makes, see page 319.

REMS Picus DP – with micro-pulse technology

For core drilling without water. Clean, easy, fast, e.g. 200 mm in steel-reinforced concrete $\varnothing 62$ mm in only 5 min.

Especially for dry drilling

Drive machine with micro-pulse technology, specially developed for dry drilling, hand held or with drill stand. Can be used anywhere, in narrow angles, flush with the wall. Suitable for many, especially hard materials. For pipeline and cable ducting, ventilation channels, test core drilling. In combination with the REMS Pull 2 M vacuum cleaner, ideal for making core bores in finished rooms, e.g. in residential, office and industrial buildings.

Design

Compact, handy drive machine for low-vibration core drilling, with drilling crown connecting thread UNC 1 1/4 male, BSPP 1/2 female. Compact drive unit for low-vibration core drilling, with drilling crown connecting thread UNC 1 1/4 outside, G 1/2 inside. Micro-pulse technology can be switched on and off: Pulse disc with 24 teeth generates 28,800 pulses min⁻¹ in idle mode at 1,200 min⁻¹, under load at 880 min⁻¹ 21,120 pulses min⁻¹. Robust, suitable for the building site. Extra light, only 7 kg. Simple, fast work without water, e.g. 200 mm in steel-reinforced concrete $\varnothing 62$ mm in only 5 min. Practical spade handle and stabiliser for hand held drilling. Integrated suction rotor for dust extraction with connection for REMS Pull 2 M and other suitable vacuum cleaners. Throat $\varnothing 60$ mm for holding the drive machine in the drill stand.

Drive

Robust, powerful 2200 W universal motor. Load speed drilling spindle 8080 rpm. Stable, maintenance-free gear. Blocking protection by safety slip clutch. Tip switch with lock. Connecting cable with integrated personal protection switch (PRCD).

Multifunction electronics

Multifunction electronics with start-up current limiting for soft starting for delicate drilling start, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Dry diamond core drilling crowns LS

Especialy for dry drilling with core drilling machines with micro-pulse technology, laser welded, high temperature-resistant (page 319), for drilling without water, hand held or with drill stand. Connecting thread UNC 1 1/4 female. Drilling depth 320 mm. Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for dry drilling in steel-reinforced concrete and masonry. Light loosening ring, for light loosening of the dry diamond core drilling crown, as accessory.

Dust extraction in accordance with EN 60335-2-69

When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m³. Observe the national regulations.

Use REMS Pull 2 M for high-performance extraction of drilling dusts from the drilling gap during dry drilling (page 324). The REMS Pull 2 M safety vacuum cleaner is certified for extracting health hazardous dusts of dust class M.

Drilling start aid

Drilling start aid G 1/2 TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill $\varnothing 8$ mm.

Drill stand

REMS Simplex 2 or REMS Titan drill stands can be used optionally (page 318).

Electric diamond core drilling machine with micro-pulse technology



German Quality Product



Info



REMS Simplex 2

REMS Titan



REMS Picus DP Basic-Pack



REMS Picus DP Set Simplex 2



REMS Picus DP Set Titan



REMS Picus DP/Pull 2 M Set-Pack

Supply format

REMS Picus DP Basic-Pack. REMS Picus DP Basic-Pack with REMS Simplex 2 drilling stand including tools and fastening kit for masonry and concrete.

	Art.-No.	€
	180016R220	2 584,62

Other voltages on request.

Supply format

REMS Picus DP Set Titan. REMS Picus DP Basic-Pack with REMS Titan drilling stand including tools and fastening kit for masonry and concrete.

	Art.-No.	€
	180035R220	3 601,86

Other voltages on request.

Supply format

REMS Picus DP/Pull 2 M Set-Pack. REMS Picus DP Basic-Pack, Art.-No. 180016 R110G, and REMS Pull 2 M Set, Art.-No. 185601 R220G.

	Art.-No.	€
	180036R220	3 652,72

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Picus DP drive unit	180003R220	2 532,72
Steel case with inlay	180600R	128,71

REMS dry diamond core drilling crowns LS,
laser welded, high temperature-resistant, see page 319.

REMS Pull 2 M, dry and wet extractor, see page 324

Additional accessories see page 318.



Accessories

For REMS Picus DP and other makes

Description	Art.-No.	€
REMS Simplex 2. Robust, handy drilling stand for core drilling up to Ø 202 mm. Description see page 310.	183700R	1 017,24
REMS Titan. Robust, highly stable drilling stand for core drilling in steel-reinforced concrete and other materials up to Ø 300 mm. For high demands. Description see page 310.	183600R	1 546,62
Titan drilling template for easy setting of the fastening holes. For REMS Titan drilling stand.	183605R	57,61
Carbide masonry drills Ø 15 mm SDS-plus for hammer anchors M12	079018	28,13
Hammer anchor M12 (pack of 50) , for concrete	079005R50	109,82
Setting iron for hammer anchor M12	182050R	16,09
Carbide masonry drill Ø 20 mm SDS-plus for splaying anchors M12	079019	63,42
Splaying anchor M12 (pack of 10) , for masonry, reusable	079006R10	102,76
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.	079010	72,76
Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607R	54,08
Titan vacuum fastening , consisting of cover plate with nipple for $\frac{3}{8}$ " screw connection and sealing ring for base plate.	183603R	99,44
Vacuum pump , for vacuum \leq -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m ³ /h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.	183670R220	1 909,92
Laser drilling centre pointer	183604R	129,75
Drilling start aid G ½ TDKB , with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm	180145R	91,97
Carbide masonry drill Ø 8 mm for drilling aid	079013	18,89
Single open ended wrench size 41 for loosening the universal diamond core drilling crowns	079003	38,35
Light loosening ring , for light loosening of the diamond core crown	180015	20,66
Drilling crown extension 200 mm	180155R	61,19
Sharpening stone for diamond core drilling crowns	079012	64,67
Circular spirit level , magnetic, for aligning the drill stand	182010R	75,26
REMS Pull 2 M , dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 324		



REMS dry diamond core drilling crowns LS

For REMS Picus DP and other suitable makes

High quality dry diamond core drilling crowns. Laser welded. Especially for dry drilling with core drilling machines with micro-pulse technology, e.g. REMS Picus DP, hand held or with drill stand. Ideal for universal applications in steel-reinforced concrete, masonry and many types of material.

Concrete, steel-reinforced concrete, aggregate concrete, brick, clinker, all kinds of masonry, natural stone, asphalt, all kinds of screed and other Ø 32 – 202 mm

REMS dry diamond core drilling crowns LS – Laser welded, high temperature-resistant. Especially for dry drilling with core drilling machines with micro-pulse technology. Versatile for many types of material. Ideal for plumbers.

Universally usable for many materials, hand held or with drill stand.

Single connecting thread UNC 1¼ female. Drilling depth 320 mm.


Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry.

Diamond segments with diamonds positioned in the bonding agent. For fast, easy and quiet drilling. Inductively soldered on fully automatic soldering machines for constant high quality of the soldered connection. Drilling tubes with soldered diamond segments can be resoldered by simple hard soldering.

Light loosening ring, for light loosening of the diamond core crowns, as accessory.

Driven by a REMS Picus DP drive unit and suitable drive units of other makes with UNC 1¼ outer connecting thread.

Use REMS Pull 2 M for high-performance extraction of drilling dusts from the drilling gap during dry drilling (page 324). The REMS Pull 2 M safety vacuum cleaner is certified for extracting health hazardous dusts of dust class M.



Info



Supply format

REMS dry diamond core drilling crowns LS. Laser welded, high temperature-resistant. Especially for dry drilling with core drilling machines with micro-pulse technology, e.g. REMS Picus DP, hand held or with drill stand. For many materials, e.g. concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Connecting thread UNC 1¼ female. Drilling depth 320 mm. In a carton.

Ø x drilling depth x connection	Number of segments	Art.-No.	€
TDKB LS 32 x 320 x UNC 1¼	3	181500R	172,26
TDKB LS 42 x 320 x UNC 1¼	4	181502R	160,84
TDKB LS 52 x 320 x UNC 1¼	5	181504R	171,22
TDKB LS 62 x 320 x UNC 1¼	5	181506R	186,79
TDKB LS 72 x 320 x UNC 1¼	6	181508R	211,70
TDKB LS 82 x 320 x UNC 1¼	6	181510R	229,35
TDKB LS 92 x 320 x UNC 1¼	6	181512R	258,41
TDKB LS 102 x 320 x UNC 1¼	7	181514R	264,64
TDKB LS 112 x 320 x UNC 1¼	7	181516R	279,17
TDKB LS 122 x 320 x UNC 1¼	8	181532R	320,69
TDKB LS 127 x 320 x UNC 1¼	8	181518R	332,11
TDKB LS 132 x 320 x UNC 1¼	8	181520R	341,45
TDKB LS 142 x 320 x UNC 1¼	8	181522R	365,32
TDKB LS 152 x 320 x UNC 1¼	8	181524R	406,84
TDKB LS 162 x 320 x UNC 1¼	9	181526R	431,76
TDKB LS 182 x 320 x UNC 1¼	9	181528R	476,39
TDKB LS 202 x 320 x UNC 1¼	10	181530R	504,42

Accessories

Description	Art.-No.	€
Light loosening ring, for light loosening of the diamond core crown	180015	20,66
Drilling crown extension 200 mm	180155R	61,19
Sharpening stone for diamond core drilling crowns	079012	64,67
Single open ended wrench size 41 for UDKB	079003	38,35

Additional adapters for using REMS dry diamond core drilling crowns LS in drive machines of other makes, on request.



REMS tile drilling

REMS tile drilling

Diamond tipped dry drilling crowns for fast, clean drilling in all kinds of tiles. Ideal for assembly and renovation. Ceramic, fine clay, granite, marble etc.

REMS tile drilling – for dry drilling.

Can be used universally for dry drilling without hammering in ceramic, fine clay, granite, marble and other materials. No cracking of the tiles.

No water necessary.

Special wax filling inside the dry drilling crown as a cooling lubricant, becomes liquid when heated and cools the dry drilling crown.

Simple, free-hand starting by drill aid with vacuum fastening. Hexagon connection for $\frac{1}{4}$ " bit holders.

Drive by cordless REMS Helix 22V VE power drill (page 108) and other electric drills/screwdrivers (speed $\geq 1,000$ rpm).



Supply format

REMS tile drilling Set 6+8+10. Diamond-studded dry drilling crowns with special wax filling. For ceramic, fine clay, granite, marble and other materials. Tile drilling Ø 6, 8, 10 mm, drill aid with vacuum fastening. In blister pack.

	Art.-No.	€
	181700R	206,56

Accessories

Description	Art.-No.	€
REMS tile drilling Ø 5 mm	181710R	50,81
REMS tile drilling Ø 6 mm	181711R	50,81
REMS tile drilling Ø 8 mm	181712R	51,85
REMS tile drilling Ø 10 mm	181713R	52,89
REMS tile drilling Ø 12 mm	181714R	57,04
REMS tile drilling Ø 14 mm	181715R	82,99
REMS Helix 22V VE, cordless drill/screwdriver, see page 108		





REMS Krokodil 180 SR

Diamond chasing and cutting machines

Compact, handy power tool for dry chasing and cutting, e.g. of concrete, steel-reinforced concrete, all kinds of masonry, natural stone, all kinds of screed.

For trade and industry.

Chase depth	≤ 61 mm
Chase width	≤ 62 mm
Number of diamond cutting discs	1 – 3

REMS Universal diamond cutting discs, also for suitable drive machines of other makes, see page 323.

REMS Krokodil 180 SR – chasing instead of chiselling. Full contact support plate. Multi-function electronics.

Universal use

Universal drive machine for dry chasing and cutting. Ideal for producing chases/grooves for laying pipes and electric cables in heating, sanitary and electrical installation, air-conditioning and cooling technology.

Design

Compact, handy drive machine, only 8.0 kg. Robust, suitable for building site conditions. Fast, easy working, e.g. chases in masonry 500 mm long, 61 mm deep, only 34 s. Full contact support plate during the entire chasing/cutting process for guided plunge-in of the diamond cutting discs, dust-free, safe working and easy, even feed. Practical switch handle with triple force-transmitting leverage for easy plunge-in and effective feeding. Swivel handle, for optimum working position and ergonomic work. Locking of the drive shaft for easy changing of the universal diamond cutting discs. Spacer discs of different thicknesses according to desired chase width screws to the cutting discs in a stable block, ensure an even chase width. Continuously adjustable depth stop. Suction nozzle for connecting a dust extractor integrated into the housing.

Drive

Robust, powerful universal motor, 2,000 W. Load speed of the drive shaft of the cutting discs 3,300 rpm. Overheating protection by temperature monitoring of the motor's field winding with a PTC resistor (Positive Temperature Coefficient). Strong, maintenance-free gear. Connecting cable 5.7 m. Safety switch with lock. Restart protection in case of mains failure.

Speed Regulation

The electronic tachometer speed control used for regulation keeps the speed constant, also under load. The speed of the cutting disc is kept at the nominal value until it meets with resistance and drops below a critical value. The drive motor stops. When the load on the drive unit is relieved again, the drill runs back up to nominal speed so that work can continue immediately at nominal speed (**Patent EP 2 085 191**). Advantage: The chasing and cutting speed (load speed) is maintained during the entire chasing and cutting process for a high chasing and cutting performance.

Multi-function electronics

Multifunction electronics with start-up current limiting for soft starting for delicate engagement of the diamond cutting discs, automatic idle speed limiting for noise reduction and preservation of the motor, overload and blocking protection for motor and gear.

Universal diamond cutting discs

Universally usable for straight chasing and cutting. Specially developed, high quality diamond segments with high diamond content and special bonding for excellent chasing/drilling performance and very long life. Optionally REMS Universal diamond cutting discs LS Turbo, laser-welded, high temperature-resistant, for fast cuts and cuts in hard materials or REMS Universal diamond cutting discs LS H-P, high-performance, laser-welded, high temperature-resistant, for fast cuts and cuts in very hard materials, with long life (page 323), metal body in accordance with EN 13236. Mounting bore Ø 22.23 mm.

Dust extraction in accordance with EN 60335-2-69

When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m³. Observe the national regulations. REMS Pull 2 M, wet and dry dust extractor, certified for extracting health hazardous dusts of dust class M (page 324).



Full contact support plate during the entire chasing/cutting process for guided plunge-in of the diamond cutting discs, dust-free, safe working and easy, even feed.

Supply format

REMS Krokodil 180 SR Basic-Pack. Electric diamond chasing and cutting grinder with speed regulation. For chasing and cutting concrete, steel-reinforced concrete, all kinds of masonry, natural stone, all kinds of screed. Chase depth 61 mm, continuously adjustable. Chase width ≤ 62 mm, stepped with spacer discs 3, 6, 10, 20 mm. Drive machine with drive shaft Ø 22.2 mm, for 1, 2 or 3 diamond cutting discs in accordance with EN 13236, ≤ Ø 180 mm, with maintenance-free gear, 230 V, 50–60 Hz, 2,000 W universal motor. Multifunction electronics with soft start, idling speed limiting, overload protection, overheating protection. Restart protection in case of mains failure. Connecting cable 5.7 m. Safety switch with lock. Load speed 3,300 rpm. Suction nozzle for connecting an extractor/dust extractor. Pin wrench size 13. In sturdy steel case.

	Art.-No.	€
	185011R220	1 235,22

Other voltages on request.



Accessories

Description	Art.-No.	€
REMS Krokodil 180 SR drive unit	185001R220	1 183,32
REMS Universal diamond cutting disc LS-Turbo Ø 180 mm , laser-welded, high temperature-resistant, for fast cuts and cuts in very hard materials, with metal body in accordance with EN 13236	185026R	58,65
REMS Universal diamond cutting disc LS H-P Ø 180 mm , high-performance, laser-welded, high temperature-resistant, for fast cuts and cuts in very hard materials, long life, with metal body in accordance with EN 13236.	185027R	93,84
Chasing chisel for removing the ridge after chasing	185024R	25,22
Steel case	185058R	110,03

REMS Pull 2 L / M, dry and wet extractors, see page 324



REMS Pull 2 L / M

Powerful, electric dry and wet extractor with automatic filter cleaning. For commercial use in trade and industry.

For extraction of dusts, dirt and liquids.

Ideal for dust extracting when chasing, cutting, drilling, core drilling and grinding.

Certified as extractor and dust extractor for extracting health hazardous dusts.

Ideal for extracting drilling sludge during core drilling.

REMS Pull 2 L

Dust class in accordance with EN 60335-2-69 L

Exposure limit/work place limit > 1 mg/m³

Penetration level ≤ 0.1 %

REMS Pull 2 M

Dust class in accordance with EN 60335-2-69 M

Exposure limit/work place limit > 0.1 mg/m³

Penetration level ≤ 0.1 %

REMS Pull 2 – for dry and wet suction.

Constantly high suction performance

by permanent automatic filter cleaning.

Certified for extracting health hazardous dusts.

Universal use

Powerful, handy extractor for dry and wet suction. For extraction of dusts, dirt and liquids. Excellently suited for dust extracting when chasing, cutting, drilling, core drilling and grinding. Certified as an extractor and dust extractor for extracting health hazardous dusts of dust class L or M in accordance with EN 60335-2-69. For commercial use in trade and industry.

Design

Compact, handy design. REMS Pull 2 L only 13.5 kg, REMS Pull 2 M only 14.2 kg. Light and manoeuvrable by rubber wheels and steerable castors, lockable by castor with brake Large tank capacity 31 l, filling volume for liquids 17 l. On/Off switch with selection without filter cleaning or with filter cleaning with a 15 s or 60 s cycle. Adapter for connecting a power tool to the vacuum cleaner. Flexible 4 m, electrically conductive suction hose (Pull M), ergonomically angled handle, 2 pluggable, chrome-plated metal suction pipes 0.5 m for adapting the suction pipe length. Wide wet/dry surface attachment 300 mm with rubber-coated castors, optionally brush strips for extracting dusts and dirt or rubber lips for extracting liquids. Joint attachment for confined spaces. Large working radius by long 7.5 m connecting lead. Holders for connecting lead, suction hose, metal suction tubes and accessories integrated into the extractor. Practical handle for easy transport. Integrated fittings for fixing a REMS L-Boxx system case.

REMS Pull 2 M is suitable and certified for the extraction of health hazardous dusts of dust class M in accordance with EN 60335-2-69, with electronic volume flow monitoring, selector switch for adapting the suction power to different suction hose diameters (21, 27, 32, 35, 40 mm) and stopper for the suction hose connection nozzle.

Permanent automatic filter cleaning

REMS Pull 2 L and REMS Pull 2 M with innovative, patented, automatic filter cleaning, prevents clogging of the filter with dust, especially effective in fine dust applications. The flat pleated filter is cleaned automatically by targeted, powerful shots of air every 15 s or 60 s depending on the setting. The suction force remains constantly high during cleaning. Patented flat folded filter system.

Drive

Robust, powerful bypass motor, 1,200 W, with high-power turbine. High suction power, continuously adjustable up to an air rate ≤ 143 m³/h, for optimum adaptation to the suction surface and the extracted product.

Automatic switch-off

Filling level limiting with automatic switch off on reaching the maximum liquid filling level when extracting electrically conductive liquids.

Automatic power tool on/off

Appliance socket for power tools up to 2,200 W, with electronic automatic on/off integrated into the extractor. The extractor switches on/off automatically when the power tool is switched on/off. For convenient working.

Anti-static system (REMS Pull 2 M)

Static charge is dissipated to the earthed upper section of the extractor by electrically conductive metal suction pipes, electrically conductive handle E, electrically conductive suction hose E and electrically conductive suction hose connection nozzle.

Dry and wet extractor



Certified extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69.



Extraction of health hazardous dusts when chasing and cutting:
REMS Pull 2 M Set



Extraction of health hazardous dusts when dry drilling:
REMS Pull 2 M Set D

REMS Pull 2 L / M

Dry and wet extractor

Dust extraction in accordance with EN 60335-2-69

When working with mineral building materials, e.g. concrete, steel-reinforced concrete, masonry and screed, a high degree of mineral dust containing quartz is produced which is harmful to the health. Inhalation of quartz fine dust is harmful to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of dust class M for the extraction of health hazardous dusts with an exposure limit/work place limit of > 0.1 mg/m³. Observe the national regulations.

Water extraction

PES flat folded filter required for extraction of water. Use wet filter bag or polythene bag if necessary. Wet filter bags separate the water from the sucked up solids when extracting dirty water. Polythene bags simplify disposal of the dirt and prevent dirt from collecting in the tank.



Extraction of drilling sludge when wet drilling with REMS drill stands:
REMS Pull 2 L Set W

Supply format

REMS Pull 2 Set. Electric dry and wet extractor for commercial use. For extraction of dusts, dirt and liquids. Ideal for dust extracting when chasing, cutting, drilling, core drilling and grinding. Certified extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69¹⁾. Bypass motor 230 V, 50–60 Hz, 1,200 W. On/Off switch with selection for automatic filter cleaning. Suction power switch for continuous adjustment of the air flow ≤ 143 m³/h. Filling level limiting with automatic switch-off for wet suction. Automatic filter cleaning. Appliance socket for power tools up to 2,200 W, with electronic automatic on/off. Large tank capacity 31 l, filling volume for liquids 17 l. Mobile, 2 wheels, castor/caster with brake. Connecting cable 7.5 m. 1 felt filter bag, 1 flat pleated filter PES. Flat suction attachment wet/dry 300 mm with rollers, brush strips, rubber lips. Joint attachment. Pull 2 suction hose/power tool adapter. Integrated holders for connecting cable, suction hose and accessories. In a box.

Description	Version	Art.-No.	€
Pull 2 L Set	Dust class L. Exposure limit/work place limit > 1 mg/m ³ , penetration level ≤ 0.1 %, 2 metal suction pipes 0.5 m each, handle, 4 m suction hose, suction hose connection nozzle.	185600R220	798,22
Pull 2 L Set W	REMS Pull 2 L set with water suction device. Ideal for extraction of drilling sludge when wet drilling with REMS drill stands.	185603R220	1 191,62
Pull 2 M Set	Dust class M. Exposure limit/work place limit > 0.1 mg/m ³ , penetration level ≤ 0.1 %. Electronic volume flow monitor with acoustic signal. Selector switch for suction hose diameter. Stopper for the suction hose connection nozzle. Antistatic system with 2 electrically conductive metal suction pipes 0.5 m each, E handle, 4 m E suction hose, suction hose connection nozzle. 1 polythene bag.	185601R220	1 068,10
Pull 2 M Set D	REMS Pull 2 M Set including suction rotor for dust extraction. Ideal for extracting health hazardous dusts when dry drilling with REMS Picus S1, Picus SR, Picus S3 etc.	185604R220	1 241,45

Extraction of health hazardous dusts when chasing and cutting:
REMS Pull 2 L Set



REMS Pull 2 L Set



Safety extractor of dust class L



Safety extractor of dust class M



REMS Pull 2 M Set

Accessories

Description	Art.-No.	€
Felt filter bag (pack of 5), polyester felt, 3-ply, tear-proof, for wet and dry extraction, M-certified, for normal dirt, fine dusts, abrasive dusts, wet dirt	185511R05	56,26
Wet filter bag (pack of 5), paper-polyester woven felt, tear-proof, for wet and dry extraction, for abrasive dusts, wet dirt, liquids	185512R05	93,94
Polythene bag (pack of 10), for wet and dry extraction of non-health hazardous dusts, for normal dirt, fine dusts, abrasive dusts, wet dirt, liquids. Prevents soiling of the tank.	185513R10	52,83
Flat folded filter PES, polyester, nano-coated, 1 piece, water-resistant, non-rotting, washable with water. For wet and dry extraction, M-certified	185515R01	85,01
Suction rotor for dust extraction see page 311	180160R	173,35
Water suction device see page 311	183606R	393,40
Adapter suction hose/power tool , for connecting a power tool to the extractor	185654R	63,94





PRESS

Drying

Dehumidifying

Aeration and deaeration



Air dehumidifier/
building dryer

328



Construction ventilators

330

Powerful, highly efficient air dehumidifiers/building driers for drying rooms, e.g. after mains water damage, flooding, dehumidification of damp cellar rooms etc. and for fast drying of concrete, masonry, plaster and screed for example. For commercial use in trade and industry.

REMS Secco 50

Dehumidification rate	$\leq 50 \text{ l}/24 \text{ h}$
Air volume	$\leq 265 \text{ m}^3/\text{h}$

REMS Secco 80

Dehumidification rate	$\leq 80 \text{ l}/24 \text{ h}$
Air volume	$\leq 850 \text{ m}^3/\text{h}$

REMS Secco – for drying and dehumidification.

Universal use

Powerful, highly efficient air dehumidifiers/building driers for drying rooms, e.g. after mains water damage, flooding, dehumidification of damp cellar rooms etc. and for fast drying of concrete, masonry, plaster and screed for example. For commercial use in trade and industry.

Design Secco 50

Compact, handy construction in robust, plastic housing. Weight 21 kg. Large air extraction areas with washable air filter. Electronic hygostat for regulating the desired humidity: Switches off automatically on reaching the nominal humidity, switches back on automatically when humidity rises. Upward air outlet for optimum air circulation. Condensation draining into an internal 7.7 l condensation tank, hose extendible from the rear, for draining condensation into a tank to be provided or directly into the drain system. Automatic switch-off with switch-off signal when using the internal 7.7 litre condensation tank on reaching the maximum condensation filling level. Operating hours counter and electricity meter, e.g. for reporting to the damage regulator/customer, as an accessory. Sturdy plastic housing with castors for easy transport.

Design Secco 80

Compact, handy construction in robust, powder-coated sheet steel housing. Weight 51 kg. Large air extraction areas with washable air filter. Electronic hygostat for regulating the desired humidity: Switches off automatically on reaching the nominal humidity, switches back on automatically when humidity rises. Side air outlet for optimum air circulation. Hose for draining condensation into an internal 11.5 l condensation tank (accessory), extendible at the side, for draining condensation into a tank to be provided or directly into the drain system. On/Off switch for operation with and without internal 11.5 litre condensation tank. Automatic switch-off with switch-off signal when using the internal 11.5 litre condensation tank on reaching the maximum condensation filling level. Operating hours counter and electricity meter, e.g. for reporting to the damage regulator/customer. Device socket for detachable connecting cable. Practical compartment for the connecting cable during transport. Sturdy, mobile tubular steel frame with large castors for easy transport, also over steps. Easy glide down and pull-up of the machine over the back of the tubular steel frame, e.g. from and onto the loading platform of a vehicle.

Chiller unit Secco 50

High dehumidification rate by high quality chiller unit with highly efficient rotation compressor and high-performance capacitor motor 230 V, 760 W with electronic thawing system, for continuous operation. Very quiet running, also suitable for living rooms. Dehumidification rate $\leq 50 \text{ l}/24 \text{ h}$, air volume $\leq 265 \text{ m}^3/\text{h}$. High quality coolant R-290.

Chiller unit Secco 80

High dehumidification rate by high quality chiller unit with highly efficient rotation compressor and high-performance condensation motor 230 V, 680 W with automatic hot-gas thawing system, for continuous operation. Very quiet running, also suitable for living rooms. Dehumidification rate $\leq 80 \text{ l}/24 \text{ h}$, air volume $\leq 850 \text{ m}^3/\text{h}$. High quality coolant R-290.

Electronic control unit Secco 50

Large, illuminated control panel with clear display of actual and nominal humidity, operating state of the chiller unit, thawing function. Keys for setting the desired humidity in 5 % steps between 30 % and 90 % as well as for setting the continuous operation. Keys for 2 fan speeds. Key for timer. Memory function saves the settings for automatic continuation of operation after a power failure.

Electronic control unit Secco 80

Illuminated 3" display with LCD technology, 70 mm screen diagonal, with clear display of actual and nominal humidity, operating hours, operating state of the chiller unit, the thawing function, the compressor protection function and the operating position for internal 11.5 litre condensation tank. Keys for setting the desired humidity in 1 % steps between 30 % and 90 % as well as for setting the continuous operation. Memory function saves the settings for automatic continuation of operation after a power failure.

Condensation tank with pump Secco 50 and Secco 80

Condensation tank with condensation pump for pumping the condensation out of the condensation tank into a higher tank or a wash basin, as an accessory.



Exhaust air set Secco 80

Generously dimensioned exhaust air hose Ø 200 mm, 10 m long, with metal fastening eyes for hanging up on site, with connecting flange, for distribution of the exhaust air in the room, for dehumidifying cavities, e.g. above intermediate ceilings and for additional blowing of wet surfaces (accessory).

REMS Orkan

For supporting electric dehumidifiers/construction driers. For faster drying and dehumidification after floods and water mains damage, it is an advantage to improve the air exchange with electric construction ventilators REMS Orkan (page 330).



Info

Supply format

REMS Secco 50 Set. Electric air dehumidifier/building dryer for commercial use. For drying rooms, dehumidifying cellars etc. and drying concrete, masonry, plaster and screed. Chiller unit with rotation compressor and capacitor motor 230V, 50 Hz, 760W, with automatic thawing system, for continuous operation. Very quiet running. Dehumidification rate ≤ 50 l/24 h, air volume ≤ 265 m³/h. Electronic control unit with large, illuminated display and memory function. Electronic humidity switch. Air filter. Internal 7.7 l condensation tank. In sturdy plastic housing with casters. In a carton.

	Art.-No.	€
	132011R220	777,46

Other voltages on request.



Info

Supply format

REMS Secco 80 Set. Electric air dehumidifier/building dryer for commercial use. For drying rooms, dehumidifying cellars etc. and drying concrete, masonry, plaster and screed. Chiller unit with rotation compressor and capacitor motor 230V, 50 Hz, 680W, with automatic hot-gas thawing system, for continuous operation. Very quiet running. Dehumidification rate ≤ 80 l/24 h, air volume ≤ 850 m³/h. Electronic control unit with illuminated 3" display and memory function. Electronic hygrometer, operating hours counter, electricity meter. Air filter. In a sturdy sheet steel housing on a mobile tubular steel frame with large castors. In a carton.

	Art.-No.	€
	132010R220	2 169,42

Other voltages on request.

Accessories

Description	Art.-No.	€
11.5 litre condensation tank Secco 80 for discharge of condensation in the sheet steel housing. For REMS Secco 80.	132100R	53,35
Exhaust air set Secco 80 , consisting of exhaust air hose Ø 200 mm, 10 m long, with metal fastening eyes for hanging up on site, with connecting flange, for distribution of the exhaust air in the room, for dehumidifying cavities, e.g. above intermediate ceilings and for additional blowing of wet surfaces.	132104R	318,67
Condensation tank with Secco 50 pump for pumping the condensation out of the condensation tank into a higher tank or a wash basin. Pumping height ≤ 2 m. For REMS Secco 50.	132129R220	389,25
Condensation tank with Secco 80 pump for pumping the condensation out of the condensation tank into a higher tank or a wash basin. Pumping height ≤ 2 m. For REMS Secco 80.	132121R220	389,25
Operating hours counter and electricity meter , e.g. for reporting to the damage regulator/customer. For REMS Secco 50 and others.	132132R220	54,81
REMS Detect W , dielectric moisture measuring device for non-destructive moisture measurement in building materials, e.g. concrete, masonry, plaster, wood. In a case.	132115R	233,55
REMS Orkan , electric construction ventilator, see page 330.		



Powerful, highly efficient electric construction ventilator for supporting dehumidifiers/construction driers after floods and water mains damage. Ideal for aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms and for speeding up the drying of concrete, masonry, plaster and screed, for example. For commercial use in trade and industry.

REMS Orkan 1360

Air volume	1360 m ³ /h
Power	145 W

REMS Orkan 2050

Air volume stage I	1740 m ³ /h
Power stage I	355 W
Air volume stage II	2050 m ³ /h
Power stage II	450 W

REMS Orkan – for aeration.

Universal use

Powerful, highly efficient construction ventilator for supporting dehumidifiers/construction driers after floods and water mains damage. Ideal for aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms and for speeding up the drying of concrete, masonry, plaster and screed, for example. For commercial use in trade and industry.

Design Orkan 1360

Axial fan in sturdy plastic housing of rotation-moulded polyethylene for a long life. Compact, handy design, weighing only 6.8 kg, with low-noise, single-phase capacitor motor 230V, 145W, with practical handle for carrying. Generated air volume 1,360 m³/h.

Large-diameter exhaust air and suction hose, Ø 200 mm, 10 m long, e.g. for extracting air from rooms, spaces, shafts and cavities, for discharging sucked-in air or dusts to the outside and for inflating bouncy castles, hot-air balloons, for example, as an accessory. An exhaust and suction hose can be fitted to the aeration or deaeration side of the construction ventilator as the situation requires. Dust sack, Ø 200 mm, 2,980 mm long, washable, for collecting coarse and fine dusts up to dust class M, as an accessory.

Design Orkan 2050

Turbo radial fan with 2 air volume stages, in sturdy plastic housing of rotation-moulded polyethylene for a long life. Compact, handy design, weighing only 10 kg, with low-noise, single-phase capacitor motor 230V, 355/450W, with practical handle for carrying. Horizontal air outlet, adjustable to below 45° or vertical by appropriate resting surfaces on the plastic housing. Generated air volume in 2 selectable stages 1,740/2,050 m³/h. Especially suitable for speeding up drying of concrete, masonry, plaster and screed, for example.



Supply format

REMS Orkan 1360. Electric construction ventilator for commercial use. For aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms, for supporting the drying of, e.g., concrete, masonry, plaster and screed and for inflating bouncy castles, hot air balloons, for example. Capacitor motor 230V, 50Hz, 145W, for continuous operation. Very quiet running. Air volume 1,360 m³/h. In a sturdy plastic housing. In a carton.

	Art.-No.	€
	132300R220	410,01

Other voltages on request.



Info

Supply format

REMS Orkan 2050. Electric construction ventilator for commercial use. For aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms. Especially also for drying of, e.g., concrete, masonry, plaster and screed. Capacitor motor 230V, 50Hz, 355/450W, for continuous operation. Very quiet running. Air volume 1,740/2,050 m³/h. In a sturdy plastic housing. In a carton.

	Art.-No.	€
	132301R220	432,85

Other voltages on request.



Info

Accessories

Description	Art.-No.	€
Exhaust air and suction hose, Ø 200 mm, 10 m long, for extracting air from rooms, spaces, shafts and cavities, for discharging sucked-in air or dusts to the outside and for inflating bouncy castles, hot-air balloons, for example. For REMS Orkan 1360.	132307R	158,71
Dust sack, Ø 200 mm, 2,980 mm long, washable, for collecting coarse and fine dusts up to dust class M. For REMS Orkan 1360.	132308R	146,67
Operating hours counter and electricity meter, e.g. for reporting to the damage regulator/customer. For REMS Orkan and others.	132132R220	54,81
REMS Detect W, dielectric moisture measuring device for non-destructive moisture measurement in building materials, e.g. concrete, masonry, plaster, wood. In a case.	132115R	233,55

REMS Secco, electric air dehumidifiers/building driers, see page 328.



Index

A

Aeration and deaeration.....	327
Akku-Press 22V ACC.....	192–193
Akku-Press 22V Connected.....	194–195
Akku-Press E 22V ACC.....	190–191
Akku-Press XL 45 kN 22V ACC.....	196–197
Amigo.....	25
Amigo 2.....	26
Amigo 2 Compact.....	27
Amigo 22V.....	28–29
Amigo E.....	24
Aquila 3B.....	105
Aquila WB.....	105
Assembling.....	103
Attachment heads for button dies / intermediate rings / guide bushings.....	31
Axial Press Jointing.....	243
Ax-Press 25 22V ACC.....	246–247
Ax-Press 25 L 22V ACC	246–247
Ax-Press 30 22V.....	244
Ax-Press HK / H.....	245

B

Bending.....	127
Bending formers and back formers.....	143
Blitz.....	266
Brazing solder ISO 17672-CuP 179.....	267
Butt welding machine.....	294–297
Butt welding units.....	298

C

Cable shear.....	241
Calc-Push.....	116
Calibrating.....	73
Calibrating tool and outer-inner pipe deburrer.....	100
Calibrating tools and inner pipe deburrers	101
Calibrating tools and outer-inner pipe deburrers	101
CamScope HD.....	275
CamSys.....	276–277
CamSys 2.....	278–280
Cat 22V VE.....	60–61
Catch S.....	104
Catch W.....	104
Cat VE.....	59
Cento.....	84–85
Cento 22V.....	86–87
Chain pipe vice	105
Chain pipe vice for workbench.....	105
Chamfering	73
Chasers.....	44
Chasers and Holders	44
Circular pipe sawing machine.....	70
CleanH.....	119, 123
Cleaning.....	113
Cleaning and preservation unit for heating systems.....	119, 123
Cleaning pads.....	264
CleanM.....	123
Cobra 22/32	286–289
Collum.....	49
Collum 22V	50–51
Compression heads.....	248–249
Confirmation of suitability	239
Contact 2000	265
Cordless axial press 13 kN with automatic return.....	246–247
Cordless axial press 20 kN with automatic return	246–247
Cordless axial press 30 kN	244
Cordless die stock with quick-change die heads	28–29
Cordless drain cleaning machine	284–285
Cordless LED flood light	111
Cordless pipe cutter	83
Cordless pipe cutting machine.....	86
Cordless pipe expander 20 kN with automatic return	254–255
Cordless pipe reciprocating saw	66–67
Cordless power drill/screwdriver	108–109
Cordless radial press 22 kN with automatic circuit control	147–151
Cordless radial press 32 kN with automatic circuit control	190–191
Cordless radial press 32 kN with automatic circuit control, pressure monitoring and result display.....	192–193
Cordless radial press 32 kN with Connected functionality via Wi-Fi radio standard and OLED display	194–195
Cordless radial press XL 45 kN with automatic circuit control	196–197
Cordless roll grooving machine	50–51
Cordless tube bender	132–133, 140–141
Cordless universal reciprocating saw	60–61
Cropping tongs	241
Cropping tongs Mini	184
Curvo.....	136–137
Curvo 22V.....	140–141
Curvo 50.....	138–139
Cut 110 Cu-INOX.....	95
Cut 110 P.....	94
Cutter wheels	81
Cutting	73
Cu-Vlies.....	264

D

Deburring	73
Dehumidifying	327
Diamond chasing and cutting machine	301
Diamond chasing and cutting machines	322–323
Diamond core drilling	301
Dies	30, 40
Disinfecting	113
Disinfection unit for drinking water installations	119, 123
Drain cleaner for manual and electric operation	282
Drill stands	310
Dry and wet extractor	324–325
Dry diamond core drilling crowns LS	319
Drying	327
DueCento	88–89

E

Eco-Press	185
Electric air dehumidifiers/building driers	328–329, 331
Electric construction ventilator	330–331
Electric decalcifying pump	116
Electric diamond core drilling machine	302–305, 308–309
Electric diamond core drilling machine with micro-pulse technology	316–317
Electric diamond core drilling machine with speed regulation	306–307
Electric die stock with quick-change die heads	24–27
Electric drain cleaning machine	283
Electric filling and flushing unit	124–125
Electric LED flood light	110
Electric pipe and drain cleaning machines	286–287
Electric pipe and tube bender	136–139
Electric pipe cutter	82
Electric pipe freezing unit	271
Electric pressure testing pump	115
Electric radial press 32 kN	186
Electric reciprocating pipe saws	62–63
Electric sleeve welding unit	292
Electric soldering pliers	264
Electric soldering unit	265
Electric tube expander	260–261
Electric tube extractor	259, 261
Electro-hydraulic pipe expander 34 kN with automatic return	256
Electro-hydraulic radial press 32 kN with automatic retraction	187
Electro-hydraulic radial press XL 32 kN with automatic retraction	188
Electronic camera inspection system	276–279
Electronic flushing and pressure testing unit with compressor	120–123
Electronic flushing unit with compressor	117–119
EMSG 160-2	292
Endoscope camera	274–275
E-Push 2	115
Eskimo	270
Eva	22
Expander heads P	257
Expander heads P-CEF	257
Expanding	251
Ex-Press 22V ACC	254–255
Ex-Press Cu	252
Ex-Press H	253
Ex-Press P	253
Extracting	251

F

Filling	113
Flushing	113
Folding work bench	70–71
Folding work benches	106
Freezing	269
Frigo 2 F-Zero	271

H

Hand die stock with quick-change die heads	22
Hand pressure testing pump	114
Hand tube bender	142
Hand tube expander	252–253
Hand tube extractor	258
Helix 22V VE	108–109
Herkules	107
Hold-Harmless and Indemnification Agreement	240
Hog Dog 2	264
Hurrican	259
Hurrican H	258
Hydro-Swing	130–131
Hydro-Swing 22V	132–133

I

Inner pipe deburrer	97
---------------------------	----

J

Jumbo	106
-------------	-----

Index

K

KaliGrat E	100
KaliGrat H.....	101
KaliGrat R.....	101
Krokodil 180 SR	322–323

L

Lot Cu 3.....	267
Lot P6.....	267
Lumen 2800 22V.....	111
Lumen 5000/7000/10000.....	110

M

Machine cleaner.....	123
Macho.....	266
Magnum RG.....	52–53
Magnum (up to 2")	34–35
Magnum (up to 3")	36–37
Magnum (up to 4")	38–39
Manual axial press	245
Manual radial press	185
Material supports	107
Mini-Cobra.....	282
Mini-Cobra S	283
Mini-Cobra S 22V VE	284–285
Mini-Press 14V ACC	147
Mini-Press 22V ACC	148–149
Mini-Press S 22V ACC	150–151
MiniScope	274
MSG	293
Multi-Push S	117–119
Multi-Push SL/SLW	120–123

N

Nano	82
Nano 11V	83
Nippelfix	46
Nippelspanner	46
NoCor	119, 123

O

Oil-hydraulic hand pipe bender	130–131
Oil-hydraulic pipe bender	134–135
One-hand axial press	245
One-hand pipe expander	253
One-hand pipe shears	90–92
One-hand pipe shears with ratchet feed	93
Orkan 1360/2050	330–331
Outer-inner pipe deburrer	98–99
Outer-inner tube deburrer	97

P

Paste Cu 3	267
Peroxi Color	119, 123
Picus DP	316–317
Picus S1	302–303
Picus S2/3,5	308–309
Picus S3	304–305
Picus SR	306–307
Pipe and Drain cleaning	273
Pipe and Drain inspection	273
Pipe chamfering tools	96
Pipe cutter	80
Pipe cutters	74–79
Pipe cutting and pipe chamfering tool	94
Pipe cutting machine	84–85, 88
Pipe cutting tool	95
Pipe freezer	270
Pipe shears with ratchet feed	93
Pipe slitter	80
Plastic Pipe Welding	291
Pneumatic reciprocating pipe saw	64
Portable pipe workstation with chain pipe vice	105
Power-Ex-Press P-CEF ACC	256
Power-Press ACC	187–188
Power-Press SE	186
Preserving	113
Pressing rings	152–183, 198–237
Pressing tongs	198–237
Pressing tongs Mini	152–183
Pressure testing	113
Pull 2 L / M	324–325
Pull-Push	282
Puma VE	58
Push	114
Python	134–135

Q

Quick-change die heads	30
Quick-change die heads S	23

R

Radial Press Jointing	145
RAG	96
RAS Cu	77–78
RAS Cu-INOX	75–76
RAS P	78–79
RAS P/SW 45/L	80
RAS St	74
RAS W INOX	80
Reciprocating saws	56–57
REG 3–35	97
REG 8–35	98
REG 10–42	98
REG 10–54	99
REG 10–54 E	99
REG St ¼ – 2"	97
REG Universal	97
Roll Grooving	21
Roll grooving attachment	48
Roll grooving machine	49, 52–53
ROS P	92–93
ROS P 26/SW 35 S	91
ROS PEX	92
ROS P flex	90

S

Sanitol	47
Saw blades	69
Sawing	55
Secco 50/80	328–329
Single-hand tube bender	128–129
Sinus	142
Sleeve welding units	293
Soft solder paste of solder powder Sn97Cu3 according to ISO 9453:2014 and flux 3.1.1.C, EN 29454-1:1994	267
Soft solder Sn97Cu3, ISO 9453:2014	267
Solar-Push	124–125
Soldering	263
Special saw blades	68
Spezial	47
SSG	298
SSM 160KS	295
SSM 160RS	294
SSM 250KS	296
SSM 315RF	297
Suction and pressure cleaning device	282
Swedish pattern wrench 'S'	104
Swing	128–129

T

Thread-cutting oil	47
Threading	21
Threading machine	32–39, 42–43
Thread tables	45
Tiger 22V VE	66–67
Tiger pneumatic	64
Tiger/VE/SR	62–63
Tile drilling	320
Tornado	32–33
Turbo Cu-INOX	70
Turbo K	71
Turbo soldering torch acetylene	266
Turbo soldering torch propane	266
Twist	260
Twist/Hurrican	261

U

Unimat 75	42–43
Universal circular metal sawing machine with automatic cooling lubricant unit	71
Universal deburrer	97
Universal diamond core drilling crowns	312–313
Universal diamond core drilling crowns LS	314–315
Universal electric reciprocating saw	58–59
Universal saw blades	68

V

V-Jet H	119, 123
V-Jet TW	119, 123

W

Water pump pliers	104
Wet and dry suction	301

List of articles

Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page
043054	Z	119, 122, 125		114060	Z	101		140106	V	15	47	150958	Z	257	
045159	Z	119, 122		114061	Z	101		140110	V	4	47	150960	Z	257	
047069	Z	122		115000	H	114		140113	V		47	150961	Z	257	
074021	Z	258		115001	H	114		140115	V	12	47	150962	Z	257	
074041	Z	258		115045	Z	114–115, 122		140116	V	15	47	150963	Z	257	
076117	Z	258		115110	Z	114–115		140119	V	15	123	150968	Z	257	
079003	Z	311, 313, 315, 318–319		115140	Z	122		140120	V	15	137, 139, 141–142	151000	E	259	
079005	Z	311, 318		115217	Z	125		150000	H		252	151002	E	259	
079006	Z	311, 318		115220	Z	125		150005	H		252	151003	H	258	
079010	Z	311, 318		115221	Z	125		150006	H		252	151004	H	258	
079012	Z	311, 313, 315, 318–319		115311	M	125		150007	H		252	151005	H	258	
079013	Z	311, 318		115312	M	125		150008	H		252	151010	E	259	
079018	Z	311, 318		115314	Z	125		150010	H		252	151105	Z	258–259, 261	
079019	Z	311, 318		115315	Z	125		150017	H		252	151110	Z	258–259, 261	
090015	Z	119, 123		115319	Z	125		150018	H		252	151120	Z	258–259, 261	
091072	Z	119, 123		115323	Z	125		150019	H		252	151125	Z	258–259, 261	
091073	Z	119, 123		115324	Z	125		150020	H		252	151130	Z	258–259, 261	
110000	Z	46		115325	Z	125		150021	H		253	151140	Z	258–259, 261	
110100	Z	46		115326	Z	125		150022	H		253	151145	Z	258–259, 261	
110200	Z	46		115375	Z	125		150025	H		253	151150	Z	258–259, 261	
110300	Z	46		115500	M	115		150026	H		253	151155	Z	258–259, 261	
110400	Z	46		115602	Z	119, 123		150027	H		253	151160	Z	258–259, 261	
110500	Z	46		115604	Z	119, 123		150028	H		253	151165	Z	258–259, 261	
110600	Z	46		115605	Z	6	119, 123	150029	H		253	151170	Z	258–259, 261	
110620	Z	46		115607	Z	6	119, 123	150033	H		253	151175	Z	258–259, 261	
110621	Z	46		115608	Z	6	119, 123	150100	Z		252	151200	Z	258–259, 261	
111000	Z	46		115609	Z	119, 122		150105	Z		252	151210	Z	258–259, 261	
111100	Z	46		115610	M	122		150110	Z		252	151230	Z	258–259, 261	
111200	Z	46		115611	M	122		150120	Z		252	151240	Z	258–261	
111300	Z	46		115612	Z	119, 123		150125	Z		252	151402	Z	258–261	
111400	Z	46		115621	Z	119, 122		150130	Z		252	151600	Z	259–261	
111500	Z	46		115633	Z	119, 122		150140	Z		252	151618	Z	258	
111620	Z	46		115661	Z	122		150145	Z		252	152106	Z	266	
111621	Z	46		115667	Z	122		150150	Z		252	152109	Z	266	
111700	Z	46		115677	Z	119, 123		150155	Z		252	153020	H	129	
111800	Z	46		115703	Z	119, 123		150160	Z		252	153021	H	129	
111900	Z	46		115747	Z	122		150165	Z		252	153022	H	129	
113000	H	74		115810	M	118		150170	Z		252	153023	H	129	
113100	H	74		115900	M	116		150175	Z		252	153025	H	129	
113200	H	10	75	116000	H	104		150180	Z		252	153026	H	129	
113210	V	10	76, 81, 94–95	116005	H	104		150185	Z		252	153027	H	129	
113213	V	10	76, 81	116010	H	104		150190	Z		252	153028	H	129	
113220	V	10	81	116015	H	104		150195	Z		252	153029	H	129	
113225	V	10	78, 81	116020	H	104		150205	Z		252	153030	H	128	
113230	H	10	75	116050	H	104		150210	Z		252	153100	Z	129	
113240	H	10	75	116055	H	104		150220	Z		252	153115	Z	129, 131, 133	
113241	H	10	75	116060	H	104		150225	Z		252	153125	Z	129	
113250	H	10	77	120120	Z	107		150230	Z		252	153140	Z	129	
113255	H	10	77	120125	Z	107		150235	Z		252	153155	Z	129, 131, 133	
113260	H	10	77	120130	Z	107		150240	Z		252	153160	Z	129, 131, 133	
113300	H	10	76	120200	Z	106		150245	Z		252	153170	Z	129, 131, 133	
113320	H	8	77	120240	Z	106		150250	Z		252	153175	Z	129, 131, 133	
113330	H	8	75	120250	Z	105		150500	Z		252	153180	Z	129, 131, 133	
113340	H	10	77	120270	Z	105		150510	Z		253	153185	Z	129, 131, 133	
113350	H	10	75	130002	H	270		150515	Z		257, 257	153190	Z	129, 131, 133	
113351	H	10	75	130207	Z	270		150550	H		253	153195	Z	129, 131, 133	
113360	Z	10	76, 78, 97	130208	Z	270		150600	Z		252–253	153200	Z	129, 131, 133	
113370	H	78		130209	Z	270		150806	Z		257	153205	Z	129, 131, 133	
113380	H	76		130383	Z	270		150807	Z		257	153210	Z	129, 131, 133	
113385	H	76		130410	Z	270		150808	Z		257	153265	Z	128–129	
113400	H	76		130415	Z	270		150809	Z		257	153270	Z	129	
113401	H	76		130430	Z	270		150812	Z		257	153300	Z	128	
113410	H	78		130450	Z	270		150826	Z		257	153303	Z	128	
113450	H	80		130455	Z	270		150828	Z		257	153304	Z	128	
113461	V	10	80–81	130460	Z	270		150842	Z		257	153305	Z	128	
113480	H	10	80	130465	Z	270		150843	Z		257	153306	Z	128	
113481	Z	80		130470	Z	270		150845	Z		257	153307	Z	128	
113500	H	76		130475	Z	270		150846	Z		257	153400	Z	133	
113810	H	98		130480	Z	270		150849	Z		257	153401	E	133	
113815	Z	98		130485	Z	270		150855	Z		257	153410	E	133	
113825	H	10	98	130490	Z	270		150858	Z		257	153411	E	133	
113830	H	10	99	130495	Z	270		150868	Z		257	153412	E	133	
113835	H	10	99	131012	M	271		150873	Z		257	153413	E	133	
113840	Z	85, 87		131104	Z	271		150882	Z		257	153414	E	133	
113900	H	10	97	131110	Z	271		150883	Z		257	153415	E	133	
113910	H	10	97	131116	Z	271		150885	Z		257	153416	E	133	
114000	H	100		131156	Z	271		150886	Z		257	153417	E	133	
114001	H	100		131157	Z	271		150887	Z		257	153418	E	133	
114030	Z	100		131158	Z	271		150888	Z		257	153419	E	132	
114032	Z	100		131160	Z	271		150894	Z		257	153450	Z	131, 133	
114033	Z	100		132010	M	329		150897	Z		257	153455	Z	133	
114034	Z	100		132011	M	329		150912	Z		257	153500	Z	131	
114035	Z	100		132100	Z	329		150913	Z		257	153501	Z	131, 133	
114036	Z	100		132104	Z	329		150914	Z		257	153510	H	131	
114037	Z	100		132115	Z	329, 331		150915	Z		257	153520	H	131	
114038	Z	100		132121	Z	329		150916	Z		257	153521	H	131	
114039	Z	100		132129	Z	329		150923	Z		257	153522	H	131	
114040	Z	100		132132	Z	329, 331</td									

List of articles

Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page
153570	Z		131	172611	Z		289	181050	V		313	250320	E		298
154000	Z		142	172612	Z		289	181055	V		313	250341	Z		298
154001	H		142	174000	Z		287	181059	V		313	250342	Z		298
154002	H		142	174010	M		287	181060	V		313	250343	Z		298
154003	H		142	174011	M		287	181065	V		313	252026	M		294
154004	H		142	174012	M		287	181070	V		313	252046	M		295
154010	H		142	174050	Z		288	181075	V		313	252103	Z		294–295
154160	Z		142	174101	Z		288	181080	V		313	254025	M		296
156000	E		260	174150	Z		288	181085	V		313	254103	Z		296
156002	E		260	174154	Z		288	181090	V		313	255020	M		297
156004	E		260	174200	Z		288	181095	V		313	255103	Z		297
156010	E		261	174201	Z		288	181410	V		315	256020	E		293
156012	E		261	174203	Z		288	181415	V		315	256213	E		293
156014	E		261	174205	Z		288	181420	V		315	256220	E		293
156150	Z		260–261	174210	Z		288	181425	V		315	256233	E		293
156200	Z		260–261	174250	Z		289	181430	V		315	256240	E		293
156225	Z		260–261	174265	Z		289	181435	V		315	256242	Z		293
156250	Z		260–261	174270	Z		289	181440	V		315	256320	E		293
156300	Z		260–261	174275	Z		289	181445	V		315	256342	Z		293
156350	Z		260–261	174282	Z		289	181450	V		315	256400	Z		293
156375	Z		260–261	174291	Z		289	181455	V		315	256410	Z		293
156400	Z		260–261	174293	Z		289	181459	V		315	256420	Z		293
156425	Z		260–261	174295	Z		289	181460	V		315	256430	Z		293
156450	Z		260–261	174296	Z		289	181465	V		315	256440	Z		293
156475	Z		260–261	174305	Z		289	181470	V		315	256450	Z		293
160010	H		266	174306	Z		289	181475	V		315	256460	Z		293
160200	V	10	267	174310	Z		289	181480	V		315	256470	Z		293
160210	V	10	267	174311	Z		289	181500	V		319	256480	Z		293
160220	V	10	267	174340	Z		289	181502	V		319	256490	Z		293
160300	V	25	264	174341	Z		289	181504	V		319	256500	Z		293
161010	H		266	175000	Z		277	181506	V		319	256510	Z		293
163020	E		264	175007	M		277	181508	V		319	256520	Z		293
163350	Z		264	175008	M		277	181510	V		319	256530	Z		293
164011	E		265	175010	M		277	181512	V		319	261002	E		292
164050	E		265	175011	Z		277	181514	V		319	290000	H		79
164110	Z		265	175018	Z		277	181516	V		319	290001	H	10	78
164111	Z		265	175026	Z		277, 280	181518	V		319	290002	H	10	78
164115	Z		265	175057	Z		277, 280	181520	V		319	290016	V	10	79, 81
164250	Z		265	175058	Z		277, 280	181522	V		319	290023	V	10	79, 81
170010	H		282	175123	Z		277, 280	181524	V		319	290050	H		79
170011	Z		288	175210	Z		111	181526	V		319	290100	H		79
170012	Z		288	175211	Z		111	181528	V		319	290116	V	10	79, 81
170022	E		283	175220	Z		110	181530	V		319	290200	H		79
170023	E		283	175221	Z		110	181532	V		319	290216	V	10	79, 81
170025	E		285	175222	Z		110	181700	V		320	290300	H		79
170027	E		285	175230	Z		110–111	181710	V		320	290316	V	5	79, 81
170118	Z		282, 285	175300	Z		280	181711	V		320	290400	H		94
170200	Z		282, 288	175301	M		279	181712	V		320	290410	H		95
170201	Z		282–283, 285	175302	M		279	181713	V		320	290411	H		95
170205	Z		282–283, 285	175303	M		279	181714	V		320	290412	H		95
170300	H		282	175304	M		279	181715	V		320	290420	Z		94
171150	Z		288	175305	Z		277, 280	182006	Z		311	290421	Z		94
171151	Z		288	175306	Z		277, 280	182010	Z		311, 318	290422	Z		94
171200	Z		288	175307	Z		280	182050	Z		311, 318	290423	Z		94
171201	Z		288	175308	Z		280	183000	Z		307	290424	Z		94
171205	Z		288	175312	Z		280	183010	E		307	290425	Z		94
171210	Z		288	175323	Z		280	183022	E		307	290426	Z		94
171250	Z		289	175330	Z		280	183023	E		307	290427	Z		94
171265	Z		289	175339	Z		280	183600	Z		310, 318	290430	Z		94
171270	Z		289	175343	Z		280	183603	Z		311, 318	290431	Z		94
171275	Z		289	175400	E		275	183604	Z		311, 318	290432	Z		94
171280	Z		289	175401	E	6	274	183605	Z		311, 318	290433	Z		94–95
171290	Z		289	175440	Z		275	183606	Z		311, 325	290437	Z		94
171291	Z		289	180000	Z		303	183607	Z		311, 318	290440	Z		94–95
171305	Z		289	180001	Z		305	183632	Z		307, 310	290444	Z		94
171306	Z		289	180003	Z		317	183670	Z		311, 318	290445	Z		94
171340	Z		289	180010	E		303	183675	Z		311	290446	Z		94
171341	Z		289	180011	E		305	183700	Z		310, 318	290447	Z		94
172000	Z		287	180012	E		309	185001	Z		323	290448	Z		94
172010	M		287	180015	Z		311, 313, 315, 318–319	185011	E		323	290449	Z		94
172011	M		287	180016	E		317	185024	Z		323	290500	H		79
172012	M		287	180028	E		305	185026	V		323	291000	H		93
172050	Z		288	180029	E		305	185027	V		323	291010	H		93
172051	Z		288	180030	E		309	185058	Z		283, 323	291023	Z		93
172150	Z		288	180032	E		303	185511	Z		325	291036	Z		93
172151	Z		288	180033	E		317	185512	Z		325	291037	Z		93
172154	Z		288	180035	E		317	185513	Z		325	291101	H		93
172200	Z		288	180036	E		317	185515	Z		325	291112	Z		93
172201	Z		288	180052	Z		313, 315	185600	M		325	291200	H		93
172203	Z		288	180053	Z		313, 315	185601	M		325	291201	Z		93
172205	Z		288	180054	Z		313, 315	185603	M		325	291220	H		93
172210	Z		288	180056	Z		313, 315	185604	M		325	291221	Z		93
172250	Z		289	180057	Z		313, 315	185654	Z		325	291240	H	8	92
172265	Z		289	180140	Z		311	190051	Z		109	291241	Z		92
172270	Z		289	180145	Z		318	190053	Z		109	291242	H	8	91
172275	Z		289	180155	Z		311, 313, 315, 318–319	190100	Z		109	291243	Z		91
172280	Z		289	180160	Z		311, 325	190110	E		109	291244	Z		91
172281	Z		289	180600	Z		303, 305, 307, 317	250020	E		298	291250	H		93
172290	Z		289	181010	V		313	250041	Z		298	291251	Z		93
172291	Z		289	181015	V		313	250042	Z		298	291270	H		93

List of articles

Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page
291420	H	8	92	342080	S	35, 37, 39		521120	Z	30		561002	V	68	
291421	Z		92	344100	Z	33, 35, 37, 39, 53		521122	S	30		561003	V	68	
291430	H	8	90	344105	Z	33, 35, 37, 39, 53		521130	Z	30		561004	V	68	
291431	Z		90	344150	Z	33, 35, 37, 39, 53		521132	S	30		561005	V	68	
292011	Z		96	347000	M	33, 35, 37, 39, 48		521140	Z	30		561006	V	68	
292110	H		96	347001	M	48		521142	S	30		561007	V	68	
292210	H		96	347005	M	51		521150	Z	30		561008	V	68	
340100	Z		37, 39	347006	M	49		521152	S	30		561101	V	69	
340110	Z		53	347007	Z	48		521160	Z	30		561102	V	69	
340200	M		33	347008	M	49		521162	S	30		561103	V	69	
340201	M		33	347009	M	49		521170	Z	30		561104	V	69	
340202	M		33	347010	Z	49		521172	S	30		561105	V	69	
340206	M		33	347030	Z	48		521180	Z	30		561106	V	69	
340207	M		33	347034	Z	48		521182	S	30		561107	V	69	
340208	M		33	347035	Z	48		521200	Z	30		561108	V	69	
340220	M		35	347040	Z	48		521202	S	30		561109	V	69	
340221	M		35	347046	Z	48		521210	Z	30		561110	V	69	
340222	M		35	347047	Z	48		521212	S	30		561111	V	69	
340226	M		35	347053	Z	48		521220	Z	30		561112	V	69	
340227	M		35	380303	M	37		521222	S	30		561113	V	69	
340228	M		35	380304	M	37		521230	Z	30		561114	V	69	
340230	M		53	380305	M	37		521232	S	30		561115	V	69	
340231	M		53	380306	M	37		521240	Z	30		561116	V	69	
340232	M		53	380307	M	37		521242	S	30		561117	V	69	
341000	Z		33, 35, 37, 39	380308	M	37		521250	Z	30		561118	V	69	
341401	S	40		380309	M	37		521252	S	30		561119	V	69	
341402	S	40		380310	M	37		521260	Z	30		561120	V	69	
341403	S	40		380311	M	37		521262	S	30		561121	V	69	
341404	S	40		380312	M	37		521270	Z	30		561122	V	69	
341406	S	40		380313	M	37		521272	S	30		561123	V	69	
341407	S	40		380314	M	37		521280	Z	30		561124	V	69	
341408	S	40		380426	M	39		521282	S	30		561125	V	69	
341409	S	40		380427	M	39		521300	Z	30		561126	V	69	
341411	S	40		380428	M	39		521302	S	30		563000	Z	63–64, 67	
341412	S	40		380429	M	39		521310	Z	30		563008	Z	63–64	
341413	S	40		380430	M	39		521312	S	30		563100	Z	63–64	
341414	S	40		380431	M	39		521320	Z	30		563200	Z	63–64	
341416	S	40		380441	M	39		521322	S	30		563203	Z	63–64	
341417	S	40		380442	M	39		521330	Z	30		565051	Z	71	
341418	S	40		380443	M	39		521332	S	30		566030	Z	29, 61, 67, 141	
341419	S	40		380444	M	39		521340	Z	30		566051	Z	58–59, 63–64	
341426	S	40		380445	M	39		521342	S	30		570100	Z	200–201, 207–209, 212–213, 217, 220, 229–231, 234	
341427	S	40		380446	M	39		521350	Z	30		570107	Z	200–201, 207–208, 210, 212, 221, 229–231, 235–236	
341428	S	40		380447	M	39		521352	S	30		570110	Z	200–204, 206–221, 224–232, 234, 237	
341429	S	40		380448	M	39		522000	Z	22–27, 29		570112	Z	200, 207–208, 210, 230	
341430	S	40		381000	Z	37, 39		522051	Z	23		570115	Z	200–201, 206–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341431	S	40		381050	Z	37		526050	Z	22		570117	Z	200, 207–208, 210, 230	
341432	S	40		381401	S	40		526052	Z	23		570120	Z	200–204, 206–221, 224–232, 234, 237	
341433	S	40		381405	S	40		530000	Z	25		570125	Z	200–201, 206–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341434	S	40		381410	S	40		530003	Z	24		570130	Z	200–204, 206–221, 224–232, 234, 237	
341435	S	40		381415	S	40		530004	Z	29, 51		570132	Z	200, 230, 235	
341436	S	40		381430	S	40		530013	E	24		570135	Z	200–201, 206–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341437	S	40		381431	S	40		530014	E	24		570137	Z	200, 230, 235	
341438	S	40		381432	S	40		530015	E	29		570140	Z	200–204, 206–221, 224–232, 234, 237	
341439	S	40		381433	S	40		530016	E	29		570145	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341440	S	40		381622	V	5	37, 39, 74, 81	530020	E	25		570155	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341441	S	40		520003	H	22		530022	E	25		570157	Z	200–201, 206–221, 224–232, 234, 237	
341442	S	40		520004	H	22		530023	E	25		570170	Z	200, 204, 206, 209, 213, 215–216, 220, 231, 234, 237	
341443	S	40		520008	H	22		533000	Z	24–25		570175	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341444	S	40		520009	H	22		536000	Z	24–25		570280	Z	186–187	
341445	S	40		520010	H	22		540000	Z	26		570290	Z	238	
341446	S	40		520013	H	22		540001	Z	27		570295	Z	238, 241	
341466	S	40		520014	H	22		540020	E	26		570300	Z	201, 204–205, 213, 233	
341467	S	40		520015	H	22		540022	E	26		570310	Z	204–206, 210, 216, 220, 231, 234, 237	
341468	S	40		520016	H	22		540023	E	27		570315	Z	200–201, 206–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341469	S	40		520017	H	22		540024	E	27		570317	Z	200–204, 206–221, 224–232, 234, 237	
341470	S	40		520025	Z	23		540025	E	27		570318	Z	200–204, 206–221, 224–232, 234, 237	
341471	S	40		520026	Z	23		541401	Z	31		570319	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341472	S	40		520056	Z	23		541404	Z	31		570320	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341473	S	40		521000	Z	30		541406	Z	31		570321	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341474	S	40		521002	S	30		541410	Z	31		570322	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341475	S	40		521010	Z	30		541413	Z	31		570323	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341476	S	40		521012	S	30		541414	Z	31		570324	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341477	S	40		521020	Z	30		541415	Z	31		570325	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341478	S	40		521022	S	30		541416	Z	31		570326	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341479	S	40		521026	Z	23		543000	Z	26		570327	Z	200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	
341480	S	40		521030	Z	30		543010	Z	27, 29		570328	Z	235–237	
341481	S	40		521032	S	30		543100	Z	24–26, 63–64		570329	Z	235–237	
341482	S	40		521036	Z	23		546000	Z	26–27		570330	Z	200, 203, 206, 209, 213, 215–216, 220, 231, 234, 237	
341483	S	40		521040	Z	30		560000	Z	63</td					

List of articles

Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page
570315	Z		222	570780	Z		200–201, 203–204, 206–207, 209–216, 218–227, 232–234, 236–237	571583	Z		29, 51, 61, 67, 87, 109, 111, 133, 141, 149, 151, 191, 193, 195, 197, 244, 247, 255, 285	572676	Z		227
570320	Z		201–206, 208–212, 214–219, 222–223, 226–228, 232–234, 236–237	570785	Z		200–228, 232–234, 236–237	571585	Z		29, 51, 61, 67, 87, 109, 111, 133, 141, 149, 151, 191, 193, 195, 197, 244, 247, 255, 285	572678	Z		227
570330	Z		219	570790	Z		200, 202, 204–205, 207, 209–211, 214–224, 226–228, 231–234, 236	571587	Z		29, 51, 61, 67, 87, 109, 111, 133, 141, 149, 151, 191, 193, 195, 197, 244, 247, 255, 285	572680	Z		227
570340	Z		201–202, 204–206, 209–210, 214, 216, 218–219, 222–223, 226–227, 232–233	570795	Z		204–205, 207, 209–211, 214–224, 226–228, 231–234, 236	571630	Z		234	572687	Z		210–211, 221, 225, 236
570350	Z		201–206, 208–212, 214–219, 222–223, 226–228, 232–234, 236–237	570845	Z		204, 206, 218, 226–227	571635	Z		201, 235–236	572689	Z		210–211, 221, 225, 236
570360	Z		201–202, 204–206, 209, 214–216, 218–219, 222–223, 232–233, 236	570850	Z		202, 204–206, 209, 211, 214, 217–219, 223, 226–228, 234, 236	571640	Z		201, 235–236	572691	Z		210–211, 221, 225, 236
570370	Z		202–212, 214, 216–219, 222–223, 226–228, 232–234, 237	570855	Z		204, 206, 209, 214, 218, 223, 226–227	571645	Z		235–236	572693	Z		211, 221, 225, 236
570380	Z		201–206, 208–212, 214–219, 222–223, 226–228, 232–234, 236–237	570860	Z		202, 204–206, 209, 211, 214, 217–219, 223, 226–228, 234	571700	Z		206	572697	Z		211, 221, 225, 236
570390	Z		202, 205, 208–210, 214–218, 222–223, 228, 233–234, 236	570880	Z		202, 204–206, 209, 211, 214, 217–219, 223, 227–228, 234, 236	571702	Z		206	572706	Z		200–204, 206–213, 215–221, 224–232, 234, 237
570400	Z		214	570905	Z		234	571704	Z		201, 235–236	572708	Z		200–204, 206–213, 215–221, 224–232, 234, 237
570410	Z		214	570910	Z		206, 212, 226, 234, 236–237	571706	Z		206	572714	Z		227
570420	Z		214	570915	Z		206, 212, 226, 234, 236–237	571708	Z		206	572716	Z		227
570430	Z		214	570920	Z		226, 234, 236	571710	Z		206	572727	Z		206, 213, 231
570440	Z		214	570925	Z		206, 212, 236–237	571712	Z		206	572795	Z		238
570450	Z		214	570930	Z		229–231	571714	Z		206	572801	Z		238
570452	Z		213, 216, 218, 237	570932	Z		230	5717140	Z		223, 234–235	572802	Z		238
570455	Z		200, 205–206, 209–210, 213, 215–216, 218, 220, 222, 225–228, 231–233, 236–237	570935	Z		214, 228–231	5717150	Z		223, 236	572809	Z		238
570457	Z		209, 213, 218, 225	570937	Z		230	5717175	Z		223, 236	572813	Z		238
570460	Z		200–206, 208–228, 231–234, 236–237	570940	Z		214, 228–231	5717180	Z		205, 209, 214, 220–223, 235–236	572815	Z		207, 223–224, 235–236
570462	Z		209–210, 213, 216, 218, 220, 225–226, 231, 237	570945	Z		214, 228–231	5717185	Z		205, 209, 214, 220–223, 235–236	572817	Z		207, 223–224, 235–236
570465	Z		202, 204–206, 209–210, 213–216, 218, 220, 222–228, 231–233, 237	570950	Z		214, 228–231	5717188	Z		205, 209, 214, 220–223, 235–236	572829	Z		205, 215, 218, 222–223, 225–226, 233–234
570467	Z		213, 215–216, 218, 225	570955	Z		214, 228–231	5717190	Z		205, 209, 214, 220–223, 235–236	572830	Z		204, 213
570470	Z		200–206, 208–228, 231–234, 236–237	570970	Z		236	5717195	Z		205, 209, 214, 220–223, 235–236	572836	Z		227
570472	Z		218, 225	571136	Z		238	5717197	Z		223, 236	572837	Z		204–205, 207, 209–210, 214–216, 218, 220, 222–224, 226–228, 232–234, 236
570475	Z		201–220, 222–228, 231–234, 236–237	571137	Z		238	5717199	Z		232	572839	Z		211, 225
570477	Z		218, 225	571283	Z		187	5717205	Z		205, 209, 214, 220–223, 235–236	572840	Z		211, 225
570478	Z		200–206, 208–228, 231–234, 236–237	571290	Z		191, 193, 195	5717206	Z		205, 209, 214, 220–223, 235–236	572841	Z		211, 225
570479	Z		201–202, 204–205, 224, 227, 234–237	571320	Z		201–202, 204–205, 224, 227, 234–237	5717207	Z		205, 209, 214, 220–223, 235–236	572844	Z		223, 228, 234–235
570482	Z		205, 218, 234	571325	Z		227, 233	5717208	Z		205, 209, 214, 220–223, 235–236	572845	Z		223, 228, 234–235
570485	Z		200, 202–206, 209–210, 213–228, 232–234, 236–237	571327	Z		204, 206, 211, 218	5717209	Z		205, 209, 214, 220–223, 235–236	572846	Z		235
570487	Z		203, 205–206, 217–218, 232–233	571330	Z		201–202, 204–206, 210–211, 215, 218, 222–225, 227, 232–233	5717210	Z		205, 209, 214, 220–223, 235–236	572847	Z		207
570488	Z		200, 202–206, 209–210, 213–228, 232–234, 236–237	571335	Z		201–202, 204–206, 210–211, 215, 222–225, 227, 232–233	5717211	Z		205, 209, 214, 220–223, 235–237	572850	Z		200, 206–208, 210–212, 219, 223–224, 228–231, 235–237
570489	Z		203, 205–206, 217–218, 232–233	571337	Z		218, 224	5717212	Z		205, 209, 214, 220–223, 235–236	572851	Z		200, 206–208, 210–212, 219, 223–224, 228–231, 235–237
570495	Z		200–204, 206, 209–210, 213–216, 218–224, 227, 231–233, 236	571340	Z		201, 204, 206, 210–211, 215, 222–223, 225, 232–233	5717213	Z		205, 209, 214, 220–223, 235–237	573008	Z		244
570620	Z		224	571342	Z		218, 224	5717214	Z		205, 209, 214, 220–223, 235–236	573018	E		244
570650	Z		224	571360	Z		221	5717215	Z		205, 209, 214, 220–223, 235–236	573020	Z		247
570660	Z		224	571370	Z		221	5717216	E		186	573021	Z		247
570670	Z		224	571375	Z		221	5717217	Z		236	573023	E		247
570680	Z		224	571380	Z		221	5717218	Z		236	573100	Z		244
570685	Z		234	571432	Z		210	5717219	Z		204–205, 207, 209–211, 214–224, 226–228,	573102	Z		244
570690	Z		224	571434	Z		210	5717220	Z		214, 241	573106	Z		244
570717	Z		202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237	571436	Z		210	5717221	Z		210	573108	Z		244
570720	Z		206, 209, 218, 223, 226	571450	Z		203, 236–237	5717222	Z		218	573110	Z		244
570727	Z		202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237	571455	Z		203, 236–237	5717223	Z		186	573112	Z		249
570730	Z		202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237	571460	Z		203, 236–237	5717224	Z		236	573114	Z		249
570735	Z		202, 206, 209, 211–212, 214, 217–219, 223, 226, 228, 237	571465	Z		203, 236–237	5717225	Z		204, 209, 214, 220–228, 232–234, 236–237	573116	Z		249
570742	Z		204, 209, 213, 217–218, 228	571470	Z		203, 236–237	5717226	Z		205, 209, 214, 220–228, 232–234, 236–237	573118	Z		249
570747	Z		204, 209, 213, 217–218, 228	571475	Z		203, 236–237	5717227	Z		205, 209, 214, 220–228, 232–234, 236–237	573124	Z		249
570750	Z		202–205, 209, 211, 216–220, 223, 227–228, 232–234	571477	Z		203, 237	5717228	Z		205, 209, 214, 220–228, 232–234, 236–237	573126	Z		249
570760	Z		200, 205, 210, 213, 216, 220, 222–223, 226–227	571480	Z		213	5717229	Z		214	573128	Z		249
570765	Z		200–202, 202–206, 209–210, 213–214, 216, 218, 220–222, 223–234, 236–237	571485	Z		213	5717230	Z		211, 218, 225, 233	573130	Z		249
570770	Z		201–202, 204–207, 209–210, 213–214, 216, 218, 220, 222–224, 226–227, 232–233	571495	Z		147	5717231	Z		211, 218, 225, 233	573132	Z		249
570775	Z		200–205, 209, 211, 216–220, 223, 227–228, 232–234	571500	Z		147	5717232	Z		211, 218, 225, 233	573134	Z		249
570776	Z		204, 209, 213, 217–218, 228	571500	Z		83, 147	5717233	Z		211, 218, 225, 233	573136	Z		249
570777	Z		204, 209, 213, 217–218, 228	571565	Z		147	5717234	Z		211, 218, 225, 233	573156	Z		249
570778	Z		204, 209, 213, 217–218, 228	571567	Z		109, 133, 149, 151, 191, 193, 244, 247, 255, 285	5717235	Z		211, 218, 225, 233	573158	S		249
570779															

List of articles

Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page		
573325	Z	249	574754	Z	154, 177–178, 181, 200, 210, 230, 235	576015	E	195	578402	Z	169	578404	Z	154–159, 161–162, 165–166, 168–169, 171–172, 174–175, 179–180			
573330	Z	249	574756	Z	154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	576016	E	191	578406	Z	154–159, 161–169, 171–172, 174–176, 178–180, 182–183						
573335	Z	249	574758	Z	154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	576017	E	191	578408	Z	154, 156–159, 161, 165–169, 171–172, 179–180, 182						
573360	Z	249	574760	Z	154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	576345	Z	191, 193, 195	578410	Z	155–169, 171–172, 174–176, 178–180, 182–183						
573364	Z	249	574762	Z	154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210–212, 214–215, 219, 221–224, 228–231, 235–237	577000	Z	187	578412	Z	154–159, 161–169, 171–172, 174–176, 178–180, 182–183						
573367	Z	249	574764	Z	182	577010	E	187	578420	Z	172	578426	Z	172			
573370	Z	249	574766	Z	182	577013	E	187	578430	Z	172	578432	Z	172			
573400	Z	249	574768	Z	182	578001	Z	147	578434	Z	175	578436	Z	175			
573402	Z	249	574770	Z	182	578002	Z	149	578438	Z	175	578440	Z	175			
573404	Z	249	574772	Z	164, 166–168, 213, 215–216, 218	578003	Z	151	578442	Z	175	578444	Z	165			
573406	Z	249	574774	Z	168, 218, 234	578010	E	149	578446	Z	165	578448	Z	165			
573436	Z	244	574776	Z	164, 167–168, 183, 213, 216, 218, 237	578012	E	147	578450	Z	165	578452	Z	165			
573438	Z	244	574778	Z	154, 158, 161–162, 164, 166–171, 174–175, 179, 183, 200, 209–210, 213, 215–216, 218, 220, 222, 225–226, 228, 232–233	578013	E	147	578454	Z	175	578456	Z	156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183			
573439	Z	249	574780	Z	161, 164, 168, 209, 213, 218	578314	Z	154–157, 159–170, 172–179, 181–182	578458	Z	159, 161, 168, 172, 174	578460	Z	156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183			
574430	Z	185	574782	Z	154–159, 161–176, 178–183, 200–206, 208–228, 231–234, 236–237	578316	Z	154–157, 159–170, 172–179, 181–182	578462	Z	156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183	578464	Z	156, 159, 161, 163–165, 167–169, 172, 174, 176, 180, 183			
574436	Z	82–83, 185	574784	Z	161–162, 164, 167–169, 174, 183, 209–210, 213, 216, 218, 220, 225–226, 228, 234, 237	578326	Z	154, 160, 162, 177–178	578466	Z	157–158, 168, 174–175	578468	Z	155–158, 161, 163, 165, 167–169, 172, 174, 176, 180, 182			
574437	Z	245	574786	Z	155–159, 161–162, 164–166, 168–169, 171–175, 179, 183, 200, 209–210, 213, 215–216, 218, 220, 222, 225–226, 228, 232–233	578328	Z	154–155, 159–164, 166, 169–172, 176–178, 181–182	578470	Z	157–158, 161, 165, 168, 172, 174–175	578472	Z	155–158, 161, 163, 165, 167–169, 172, 174, 176, 180, 182			
574516	Z	183, 238	574788	Z	154–159, 161–176, 178–183, 200–206, 208–228, 231–234, 236–237	578330	Z	154, 160, 162, 177–178	578476	Z	155–158, 161, 163, 165, 167–169, 172, 174, 176, 180, 182	578478	Z	161, 164, 167–168, 176, 181–182			
574700	Z	147, 149, 151, 183	574790	Z	168, 218	578332	Z	154–155, 159–164, 166, 169–172, 176–178, 181–182	578478	Z	161, 164, 167–168, 176, 181–182	578480	Z	181			
574702	Z	185, 238	574792	Z	154–159, 161–176, 178–183, 200–206, 208–228, 231–234, 236–237	578334	Z	154–155, 159–164, 166, 169–172, 176–178, 181–182	578482	Z	159, 164, 174, 181–183	578484	Z	159, 164, 174, 181–183			
574704	Z	183, 238	574794	Z	154–176, 178–183, 201–220, 222–228, 231–234, 236–237	578336	Z	154–155, 160–164, 166, 169–172, 176–178, 181–182	578486	Z	181–182	578488	Z	159, 164, 174, 182–183			
574728	Z	156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183, 202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237	574796	Z	168, 218	578338	Z	154, 177–178, 181	578490	Z	154–155, 157–158, 172, 175, 179–180	578492	Z	154–155, 157–159, 162–163, 166, 171–173, 175, 179–180			
574730	Z	156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183, 202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237	574798	Z	154–159, 161–176, 178–183, 200–206, 208–228, 231–234, 236–237	578340	Z	154, 177–178, 181	578494	Z	154–155, 157–159, 162–163, 166, 171–173, 175, 179–180	578496	Z	154–155, 157–159, 162–163, 166, 171–173, 175, 179–180			
574732	Z	156, 158–159, 161, 163–165, 167–169, 172, 174, 176, 180, 183, 202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 234, 237	574800	Z	154, 160, 162, 200, 207–208, 210	578342	Z	154, 177–178, 181	578498	Z	154, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–157, 159–162, 163–165, 167–169, 172, 174–176, 179–180			
574734	Z	156, 159, 161, 163–165, 167–169, 172, 174, 176, 180, 183, 202, 205–206, 209, 211–212, 214, 217–219, 223, 226, 228, 237	574802	Z	154, 160, 162, 200, 207–208	578350	Z	161, 164, 168, 173	578498	Z	154, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–157, 159–162, 163–165, 167–169, 172, 174–176, 179–180			
574736	Z	154–155, 160, 162, 164–165, 168, 170, 177–178, 181, 200–201, 207–209, 212–213, 217, 220, 229–231, 234, 237	574804	Z	154–156, 158, 161–162, 164–172, 178–180, 182, 200–202, 206, 209–210, 213–216, 218–224, 232–233, 236	578352	Z	154–159, 161–176, 178–183	578498	Z	154–157, 159–162, 163–165, 167–169, 172, 174–176, 179–180	578498	Z	154–157, 159–162, 163–165, 167–169, 172, 174–176, 179–180			
574738	Z	154–157, 159–170, 172–179, 181–182, 200–204, 206–221, 224–232, 234, 237	574806	Z	163, 173, 182, 211, 225	578354	Z	161–162, 164, 167–169, 174, 178, 183	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180			
574740	Z	154–157, 159–170, 172–179, 181–182, 200–204, 206–221, 224–232, 234, 237	574808	Z	163, 173, 182, 211, 225	578356	Z	155–159, 161–162, 164–169, 171–175, 178–180, 183	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180			
574742	Z	154–157, 159–170, 172–179, 181–182, 200–204, 206–221, 224–232, 234, 237	574810	Z	163, 173, 182, 211, 225	578374	Z	154–176, 178–183	578510	Z	177–178	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180
574744	Z	154–157, 159–170, 172–179, 181–182, 200–204, 206–221, 224–232, 234, 237	574812	Z	168, 217	578376	Z	154–162, 164–166, 168, 170–172, 174–175, 179–180	578510	Z	177–178	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180
574746	Z	154–157, 159–170, 172–179, 181–182, 200–204, 206–221, 224–232, 234, 237	574814	Z	168, 217	578378	Z	154–176, 178–183	578512	Z	166, 176–178	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180
574748	Z	154–155, 160–164, 170–171, 177–178, 181–182, 200–201, 207–208, 210, 212, 221, 229–231, 235–236	574816	Z	168, 217	578380	Z	154, 156–157, 159–175, 178–183	578514	Z	166, 176–178	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180
574750	Z	154, 177–178, 181, 200, 230, 235	574818	Z	182	578382	Z	154–176, 178–183	578516	Z	177–178	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180
574752	Z	154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210, 212, 221, 224–232, 234, 237	574820	Z	255	578386	Z	154–155, 157–158, 161–163, 165–172, 174–176, 178–180	578518	Z	166, 176–178	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180
574754	Z	154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210, 212, 221, 224–232, 234, 237	574822	Z	255	578389	Z	154–157, 159–170, 172–179, 181–182	578524	Z	170	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180
574756	Z	154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210, 212, 221, 224–232, 234, 237	574824	Z	255	578390	Z	154–157, 159–170, 172–179, 181–182	578526	Z	170	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180
574758	Z	154–155, 160–164, 166, 169–172, 176–178, 181–182, 200–201, 207–208, 210, 212, 221, 224–232, 234, 237	574826	Z	255	578392	Z	155–158, 161, 163, 166, 167, 170–172, 174–175, 176–178, 179–180	578528	Z	170	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180	578498	Z	154–155, 157–159, 162–163, 166, 171–173, 179–180
574760	Z	154–155, 160–164, 166, 169–172, 176–17															

List of articles

Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page	Art.-No.	RG	VE	Page
578570	Z		158, 161, 166, 169–172, 182	580010	E		137	590056	Z		135	751568	S		44
578572	Z		174	580014	E		141	590057	Z		135	751569	S		44
578576	Z		180	580021	E		137	590058	Z		135	751570	S		44
578578	Z		180, 182	580022	E		137	590059	Z		135	751571	S		44
578582	Z		180, 182	580023	E		137	590060	Z		135	753240	Z		43
578584	Z		180, 182	580024	E		137	590061	Z		135	759250	S		44
578586	Z		180, 182	580025	E		137	590062	Z		135	759251	S		44
578588	Z		168, 173	580026	E		137	590063	Z		135	759252	S		44
578590	Z		168, 173	580027	E		137	590150	Z		135	759253	S		44
578592	Z		163, 168, 173, 180	580028	E		137	590153	Z		135	759254	S		44
578594	Z		163, 168, 173, 180	580029	E		137	590160	Z		135, 139	759255	S		44
578596	Z		163, 168, 173, 180	580030	E		137	731200	Z		31	759256	S		44
578598	Z		163, 168, 173, 180	580031	E		137	731205	Z		31	759257	S		44
578600	Z		163, 168, 173, 180	580033	E		137	731210	Z		31	759258	S		44
578602	Z		180	580034	E		137	731220	Z		31	759259	S		44
578604	Z		154–155, 160–164, 166, 169–172, 176–178, 181–182	580035	E		137	731230	Z		31	759260	S		44
578606	Z		158, 161, 166, 169–172, 182	580036	E		137	731240	Z		31	759261	S		44
578608	Z		154	580037	E		137	731250	Z		31	759262	S		44
578610	Z		154	580038	E		137	731301	Z		31	759263	S		44
578612	Z		154, 158	580039	E		137	731302	Z		31	759264	S		44
578614	Z		154	580040	E		137	731303	Z		31	759265	S		44
578618	Z		179	580051	E		141	731304	Z		31	759270	S		44
578620	Z		184	580052	E		141	731305	Z		31	759271	S		44
578621	Z		184	580053	E		141	731306	Z		31	759272	S		44
578622	Z		184	580054	E		141	731307	Z		31	759273	S		44
578624	Z		154–158, 161–162, 164–176, 178–183	580055	E		141	731308	Z		31	759274	S		44
578630	Z		162–163, 170, 173, 182	580056	E		141	731309	Z		31	759275	S		44
578632	Z		162–163, 170, 173, 182	580057	E		141	731310	Z		31	759276	S		44
578634	Z		162–163, 170, 173, 182	580058	E		141	731311	Z		31	759277	S		44
578636	Z		163, 170, 173, 182	580059	E		141	731312	Z		31	759278	S		44
578638	Z		157–159, 163	580060	E		141	731320	Z		31	759279	S		44
578640	Z		172, 182	580061	E		141	731321	Z		31	759280	S		44
578642	Z		172, 182	580062	E		141	731322	Z		31	759281	S		44
578644	Z		172, 182	580063	E		141	731323	Z		31	759282	S		44
578646	Z		172, 182	580064	E		141	731324	Z		31	759330	S		44
578652	Z		175	580065	E		141	731325	Z		31	759360	S		44
578654	Z		175	580066	E		141	731326	Z		31	759361	S		44
578656	Z		175	580067	E		141	731700	Z		24–27, 29, 97	759362	S		44
578659	Z		183	580068	E		141	750003	U		43	759363	S		44
578660	Z		172, 181	5801070	Z		143	750004	U		43	759364	S		44
578664	Z		172, 176, 181	581080	Z		143	751000	Z		43	759365	S		44
578666	Z		172, 176, 181	581110	Z		143	751040	Z		43	759366	S		44
578670	Z		164	581130	Z		143	751050	Z		43	759367	S		44
578700	Z		159	581150	Z		143	751096	Z		43	759373	S		44
578702	Z		159	581180	Z		143	751097	Z		43	759374	S		44
578704	Z		159	581200	Z		143	751098	Z		43	759375	S		44
578706	Z		159	581210	Z		143	751100	Z		43	759376	S		44
578708	Z		159	581220	Z		143	751102	Z		43	759377	S		44
578710	Z		159	581230	Z		143	751501	S		44	759378	S		44
578712	Z		159	581240	Z		143	751502	S		44	759379	S		44
578714	Z		159	581260	Z		143	751503	S		44	759380	S		44
578716	Z		168	581270	Z		143	751504	S		44	759381	S		44
578718	Z		168	581280	Z		143	751505	S		44	759382	S		44
578720	Z		168	581310	Z		143	751506	S		44	759383	S		44
578740	Z		173, 183	581320	Z		143	751507	S		44	759384	S		44
578742	Z		173, 183	581330	Z		143	751508	S		44	844010	E		82
578744	Z		173, 183	581350	Z		143	751509	S		44	844011	E		83
578746	Z		173, 183	581360	Z		143	751510	S		44	844045	Z		82–83
579000	Z		188	581370	Z		143	751511	S		44	844050	Z		82–83
579001	Z		197	581380	Z		143	751516	S		44	844051	Z		82–83
579010	E		188	581390	Z		143	751517	S		44	844510	Z		83
579012	E		188	581400	Z		143	751518	S		44	845001	M		85
579014	E		197	581410	Z		143	751519	S		44	845002	M		87
579100	Z		200, 207, 228, 230	581420	Z		143	751520	S		44	845003	M		85
579101	Z		200–204, 207–213, 215–221, 224–232, 234, 237	581430	Z		143	751521	S		44	845004	M		89
579104	Z		210	581440	Z		143	751522	S		44	845050	Z		85, 87, 89
579105	Z		210	581450	Z		143	751526	S		44	845053	Z		85, 87, 89
579106	Z		210	581490	Z		143	751527	S		44	845054	Z		85
579107	Z		212–213, 230–231	581500	Z		143	751528	S		44	845055	Z		85, 87, 89
579108	Z		200, 207, 220, 230–231	581510	Z		143	751544	S		44	845057	Z		89
579109	Z		200	581520	Z		143	751545	S		44	845060	Z		89
579110	Z		200–204, 207–213, 215–221, 224–232, 234, 237	581530	Z		143	751546	S		44	845085	Z		85
579111	Z		200–204, 207–213, 215–221, 224–232, 234, 237	581540	Z		143	751547	S		44	845118	Z		85, 87
579112	Z		235	582036	Z		137, 139, 141–142	751548	S		44	845131	Z		85
579113	Z		235	582110	Z		139	751549	S		44	845218	Z		85, 87
579114	Z		235	586012	Z		139	751552	S		44	845220	Z		85, 87, 89
579115	Z		235	586100	Z		137, 141	751557	S		44	845530	Z		85, 87
579120	Z		188, 238	586150	Z		137, 141	751558	S		44	849006	M		70
579123	Z		197, 238	590000	Z		135	751559	S		44	849007	M		71
579144	Z		207	590020	E		135	751560	S		44	849310	Z		49, 51, 70–71, 85, 87
579146	Z		207	590021	E		135	751561	S		44	849315	Z		49, 51, 70–71, 85, 87
579240	Z		188	590022	E		135	751562	S		44	849700	Z		71
579600	Z		119, 123	590051	Z		135	751563	S		44	849703	Z		70–71
579601	Z		188, 197	590052	Z		135	751564	S		44	849706	Z		70–71
579603	Z		238	590053	Z		135	751565	S		44				
580000	Z		137, 142	590054	Z		135	751566	S		44				
580004	Z		141	590055	Z		135	751567	S		44				

Notes

Notes



www.rems.de

Head Office



Germany: REMS GmbH & Co KG
Postfach 1631 · 71306 Waiblingen · Germany
Stuttgarter Straße 83 · 71332 Waiblingen · Germany
Tel +49 7151 17 07-0
info@rems.de

Branch Offices



Denmark: REMS Scandinavia A/S
Snedkervej 1 · 4600 Køge · Denmark
Tel +45 56 63 14 00
DNK@rems.de



France: REMS SARL
2, Rue du Stade · 67250 Hoffen · France
Tel +33 388 80 44 53
FRA@rems.de



Great Britain: REMS (U.K.) LIMITED
Unit 5 · Ash Industrial Estate
Flex Meadow · Harlow · Essex CM19 5TJ · U.K.
Tel +44 1279 413698
GBR@rems.de



Italy: REMS S.R.L.
Via Sirtori, 13/D · 20017 Passirana di Rho (Milano) · Italy
Tel +39 02 9 30 21 11
ITA@rems.de



Poland: REMS POLSKA Sp. z o.o.
Dąbrowa · Ulica Piaskowa 19 · 62-070 Dopiewo · Poland
Tel +48 61 654 09 00
POL@rems.de



Spain: REMS ESPAÑA, S.A.U.
Pol. Ind. San José de Valderas
Calle Herramientas, 28 · 28918 Leganés (Madrid) · Spain
Tel +34 916 444 833
ESP@rems.de



Czech Republic: REMS Česká republika s.r.o.
Nádražní 271 · 253 01 Hostivice · Czech Republic
Tel +420 2 20 98 28 80
CZE@rems.de

**Müük toimub ainult spetsialiseerunud
kaubandusvõrgu vahendusel.**

Tehase esindaja Eestis:

Anton Esperk

Mobil tel. + 372 5858 3943
e-mail: anton.esperk@rems.de